



### Overview

Presentation	This enclosure is designed to meet current IT market trends and applications ranging from high density computing and networking to broadcast and audio-video. The rack height is 45U, 750mm Wide x 1070mm Deep . It provides a reliable rack-mounting environment for mission-critical equipment.
Lead time	Usually in Stock

### General

Provided equipment	<ul style="list-style-type: none"> <li>Baying hardware</li> <li>Key(s)</li> <li>Keyed-alike doors and side panels</li> <li>Leveling feet</li> <li>Mounting hardware</li> <li>Pre-installed casters</li> <li>Side panels</li> </ul>
--------------------	--

### Physical

Maximum mounting depth	91.49 cm
Number of rack unit	45U
Minimum mounting depth	26.19 cm
Marking	<ul style="list-style-type: none"> <li>14 gauge EIA mounting rail</li> <li>16 gauge front door</li> <li>16 gauge post</li> <li>18 gauge rear door</li> <li>18 gauge roof</li> <li>18 gauge side panels</li> </ul>
Colour	Black
Depth	107 cm
Rack width	19"
Height	212.4 cm
Net weight	155 kg

Permanent permissible load	1020.58 kg dynamic 1700.97 kg static
Width	75 cm

### Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

### Packing Units

Package 1 Weight	172.3 kg
Package 1 Height	224 cm
Package 1 width	85 cm
Package 1 Length	132 cm
Number of Units in Package 3	1

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Take-back	Take-back program available

### Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------