

3ft/1m USB C to DisplayPort 1.2 Cable 4K 60Hz - USB-C to DisplayPort Adapter Cable HBR2 - USB Type-C DP Alt Mode to DP Monitor Video Cable - Works w/ Thunderbolt 3 - White

Product ID: CDP2DPMM1MW



This USB-C to DisplayPort cable lets you connect your Thunderbolt 3 or USB Type-C enabled device to a 4K DisplayPort monitor with just one cable, providing you with a convenient, clutter-free solution.

The USB C to DisplayPort adapter cable lets you harness the video capabilities that are built into your USB-C connection, to deliver the astonishing quality of Ultra HD to your 4K display and supporting resolutions up to 3840 x 2160.

Plus, the adapter is backward compatible with 1080p displays, which makes it a great accessory for home, office or other work environments.

At 3.3 ft. (1 m) in length, this monitor cable delivers a compact connection that eliminates excess adapters and cabling, ensuring a tidy, professional installation. For longer installations, we also offer a 6 ft. (1.8 m) (CDP2DPMM6W, CDP2DPMM6B) and a 9.8 ft. (3 m) (CDP2DPMM3MW, CDP2DPMM3MB) USB-C to DP cable, enabling you to choose the right cable length for your custom installation needs.

To ensure easy operation and installation, this USB C to DisplayPort cable works with both Windows and Mac computers and allows for plug-and-play installation, removing the need for any additional software or drivers.

CDP2DPMM1MW is backed by a 3-year StarTech.com warranty and free lifetime technical support.

Note: Your USB-C port must support DisplayPort over USB-C (DP Alt mode) in order to work with this adapter.

## **Certifications, Reports and Compatibility**







## Applications

- · Connect USB-C or Thunderbolt 3 devices to DP displays
- · Ideal for home office or hot desk environments
- Experience enhanced imaging with support for 4K 60Hz
- Deliver enriched presentations on the go

## **Features**

• HIGH PERFORMANCE: White 3.3<sup>'</sup>/1m USB-C DP Alt Mode to DisplayPort 1.2 (21.6Gbps) Cable supports 4K 60Hz UHD (3840x2160), HBR2, 5.1ch Audio, HDCP 2.2/1.4 1080p & Thunderbolt 3 Compatible

• INTEGRATED VIDEO ADAPTER CABLE: USB C to DisplayPort 1.2 cable (male/male) reduces clutter, minimizes signal loss/failure points & has slim host & display connectors that fit in tight spaces

• HOST COMPATIBILITY: Dell XPS, Precision & Latitude, Lenovo ThinkPad X1 Carbon/Extreme, Microsoft Surface & Surface Pro, MacBook Pro, iPad Pro, TB3 MacBook Air, HP EliteBook, Spectre & ZBook

• DISPLAY COMPATIBILITY: USB-C to DP cable is tested & verified w/ full range of DP monitors incl brands Dell, Samsung, Asus, Acer & LG; white cable compliments LCD/LED displays w/ white housing/backing

• EASY TO USE: DisplayPort over USB-C converter cable w/ driverless setup works w/ any USB Type-C/Thunderbolt 3 (DP Alt Mode) device; compatible w/ macOS, iPadOS, Windows 10, Chrome OS, Android & Linux

Hardware		
	Warranty	3 Years
	AV Input	USB-C
	Ports	1
	AV Output	DisplayPort - 1.2
	Chipset ID	Controller: STM32F072CBU6 or VL103
Performance		
	Maximum Digital Resolutions	3840x2160 @ 60 Hz
	Supported Resolutions	1024x768



		1280x720 (High-definition 720p)
		1920x1080 (High-definition 1080p)
		1920x1200
		2560x1440
		2560x1600
		3840x2160 (Ultra HD 4K)
	Wide Screen Supported	Yes
	Audio Specifications	DisplayPort - 5.1 Channel Audio
Connector(s)		
	Connector A	1 - USB-C (24 pin) DisplayPort Alt Mode
		1 - DisplayPort (20 pin)
Special Notes / Requirements		
	Note	Your USB-C equipped device must support video (DP Alt Mode) to work with this adapter.
Environmental		
Environmental	Operating Temperature	0C to 40C (32F to 104F)
Environmental	Operating Temperature Storage Temperature	0C to 40C (32F to 104F) -40C to 80C (-40F to 158F)
Environmental		
 Physical	Storage Temperature	-40C to 80C (-40F to 158F)
	Storage Temperature	-40C to 80C (-40F to 158F)
 Physical	Storage Temperature Humidity	-40C to 80C (-40F to 158F) 20%-70%RH
 Physical	Storage Temperature Humidity Color	-40C to 80C (-40F to 158F) 20%-70%RH White
 Physical	Storage Temperature Humidity Color Cable Length	-40C to 80C (-40F to 158F) 20%-70%RH White 3.3 ft [1.0 m]
 Physical	Storage Temperature Humidity Color Cable Length Product Length	-40C to 80C (-40F to 158F) 20%-70%RH White 3.3 ft [1.0 m] 3.3 ft [1.0 m]
 Physical	Storage Temperature Humidity Color Cable Length Product Length Product Width	-40C to 80C (-40F to 158F) 20%-70%RH White 3.3 ft [1.0 m] 3.3 ft [1.0 m] 0.8 in [2.0 cm]
 Physical	Storage Temperature Humidity Color Cable Length Product Length Product Width Product Height	-40C to 80C (-40F to 158F) 20%-70%RH White 3.3 ft [1.0 m] 3.3 ft [1.0 m] 0.8 in [2.0 cm] 0.4 in [1.0 cm]

STARTECH.COM



What's in the Box	Included in Package	1 - USB-C to DisplayPort adapter cable
	Shipping (Package) Weight	1.4 oz [40.0 g]
	Package Height	1.2 in [3.0 cm]
	Package Width	7.9 in [20.0 cm]
	Package Length	8.7 in [22.0 cm]

\*Product appearance and specifications are subject to change without notice.

