

Xerox® WorkCentre® 3655i Multifunction Printer

The WorkCentre 3655i Multifunction Printer is built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.





System Specifications	WorkCentre 3655i/S	WorkCentre 3655i/X	
Speed	Up to 47 ppm 8.5 x 11 in. Up to 45 ppm A4 / 210 x 297 mm Up to 36 ppm 8.5 x 14 in. / 216 x 356 mm		
Monthly Duty Cycle ¹	Up to 150,000 pages		
Recommended Average Monthly Print Volume ²	Up to 15,000 pages		
Hard Drive / Processor / Memory	Minimum 250 GB / 1 GHz Dual-core / 2 GB		
Connectivity	10/100/1000Base-T Ethernet, High-Speed USB 2.0 direct print, Wi-Fi Direct with	h Optional Xerox® USB Wireless Adapter	
Controller Features	Unified Address Book, Remote Control Panel, Online Support (accessed from the	user interface and print driver), Configuration Cloning	
Copy and Print			
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 1200 dpi		
First-print-out Time	As fast as 8 seconds		
First-copy-out Time	As fast as 12 seconds		
Page Description Languages	Adobe® PostScript® 3™, Adobe® PDF version 1.7, PCL® 5c / PCL 6, XML Paper Specification (XPS®)		
Print Features	Print from USB, Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs		
Mobile Printing and Apps	Standard: Apple® AirPrint™, Mopria® Certified, QR Code App, Xerox® App Gallery App, @PrintByXerox App; Free Download: Xerox® Print Service Plug-in for Android, Mopria® Print Service Plug-in for Android™, Xerox® Mobile Link App; Optional: Xerox® Mobile Print, Xerox® Mobile Print Cloud, Xerox® Easy Translator Service		
Scan			
Standard Features	Destinations : Scan to Mailbox, Scan to USB, Scan to Email, Scan to Network; File Formats : PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features : Scan to Home, Single Touch Scan, Searchable PDF, Single/Multi-page PDF/XPS/TIFF, Encrypted / Password Protected PDF, Linearized PDF / PDF/A		
Optional Features	ConnectKey® for DocuShare®, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox Business Innovation Partners		
Fax			
Standard Features	Internet Fax, Network Server Fax Enablement	Walk-up Fax³, LAN Fax, Internet Fax (includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement	
Security			
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408) (undergoing evaluation), Encrypted Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions		
Optional Features	McAfee Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET), Xerox® PrintSafe Software		
Accounting			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement		
Optional Features	Equitrac Express®, Equitrac Office®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners		
	1		

Device Specifications				
Control Panel Languages	LIS English International English 1	nternational French Italian Corm	an International Spanish Dutch Prazili	ian Portuguese Swedish Norwegian Danish
	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Arabic			
Accessories	1			
Optional Accessories	S50-sheet Feeder Stand Smart Card Enablement Kit Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit			
Electrical Requirements				
North America	Voltage : 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 11 A			
Europe	Voltage : 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 % , 6 A			
Power Consumption				
Running (Average) ⁴	110V: 525.1 watts 220V: 523.0 watts			
Standby Mode ⁴	110V: 81.7 watts 220V: 80.5 watts			
Low Power Mode ⁴	110V: 2.8 watts 220V: 3.0 watts			
Auto off / Sleep Mode ⁴	110V: 0.4 watts 220V: 0.6 watts			
Warm up	Time from power off to when serv	ices are displayed: As fast as 165 :	seconds	
Low Power Recovery ⁴	<11 seconds			
Operating Environment	1			
Required Temperature Range	41° to 90° F (5° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels	Operating 7.27 B(A), Standby: 4.8	B(A)		
Sound Pressure Levels	Operating: 55.9 dB(A), Standby: 3	1.9 dB(A)		
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
WorkCentre 3655i/S	22.0 in. / 560 mm	21.3in. / 541 mm	22.7 in. / 577 mm	56 lbs. / 25.4 kg
WorkCentre 3655i/X	22.0 in. / 560 mm	21.3in. / 541 mm	22.7 in. / 577 mm	58 lbs. / 26.3 kg
550-sheet Feeder	19.5 in. / 495 mm	18.5 in. / 469 mm	3.8 in. / 96.3 mm	9.3 lbs. / 4.2 kg
Stand	29 in. / 737 mm	27.5 in. / 699 mm	13.1 in. / 332 mm	28.4 lbs. / 12.9 kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
WorkCentre 3655i/S	25.7 in. / 653 mm	26.5 in. / 674 mm	28.5 in. / 723 mm	68.8 lbs. / 31.2 kg
WorkCentre 3655i/X	25.7 in. / 653 mm	26.5 in. / 674 mm	28.5 in. / 723 mm	70.8 lbs. / 32.1 kg
550-sheet Feeder	22.6 in. / 575 mm	23.4 in. / 601 mm	9.5 in. / 241 mm	12.8 lbs. / 5.8 kg
Stand	22 in. / 560 mm	20.9 in. / 530 mm	10.6 in. / 270 mm	36.6 lbs. / 16.6 kg
Certifications				
	FCC Part 15, Class A FCC Part 68 CE Mark applicable to Directives 20 UL 60950-1/CSA 60950-1-07, 2nd EAC ROHS Directive 2011/65/EU WEEE Directive 2012/19/EU Citrix Cerner Common Criteria (IEEE 2600.2 sta Apple® AirPrint™ 1.4 Certification Mopria™ Certified Wi-Fi Direct Certification Blue Angel ECOLOGO™ (undergoing evaluation EPEAT (United States) ENERGY STAR™ qualified To view the latest list of certification	ndard) (undergoing evaluation)		

Paper Handling	
Duplex Automatic Document Fee	eder (DADF)
Capacity ⁵	60 sheets
Speed Black-and-white	Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex) Up to 25 ipm Letter / 24 ipm A4 (duplex)
Color	Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)
Paper Sizes Sensed	5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 216 x 356 mm
Weights	Simplex: 13 lb. bond to 32 lb. bond / 50 gsm to 125 gsm Duplex: 16 lb. bond to 32 lb. bond / 60 gsm to 125 gsm
Bypass Tray	
Cαpacity⁵	150 sheets
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Cardstock, Cardstock Recycled Bond Labels Pre-printed Envelopes Custom
Trays 1	
Capacity ⁵	550 sheets
Sizes	Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Cardstock, Cardstock Recycled Bond Labels Pre-printed Custom
Up to 3 Additional Trays	
Capacity⁵	550 sheets each
Sizes	Custom Sizes from 5.5 x 8.27 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Plain Punched Letterhead Lightweight Cardstock, Cardstock Recycled Bond Labels Pre-printed Custom
Total Capacity	
Device Standard Capacity ⁵	700 sheets
Device Total Capacity ⁵	2,350 sheets
Paper Output	
Capacity	Up to 250 sheets, automatic two-sided
	ndard on WorkCentre 3655i/X, not available on WorkCentre 3655i/S)
Capacity ⁵	20-sheet stapling, single position
	Zo sinece studying single position

Сору	
Speed (cpm)	Up to 47 cpm 8.5 x 11 in.
эрсси (сріп)	Up to 45 cpm A4 / 210 x 297 mm
	Up to 36 cpm 8.5 x 14 in. / 216 x 356 mm
First-copy-out Time	As fast as 12 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1
Quantity	1 to 9,999
Resolution (max.)	Up to 600 x 600 dpi
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments
Concurrency	Program-ahead to allow job to be initiated while initial job is processed (Copy, Print, Fax and Scan)
Copy Features	Annotation and Bates™ stamping Authentication for Services Auto Paper Select Auto Reduction & Enlargement to fit selected paper size Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job: (Enables page-level programming and also lets you proof each section or delete last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Stapling
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508-compliant. For more information or to download Xerox® Copier Assistant for free, visit www.xerox.com.
Print	
First-print-out Time	As fast as 8 seconds
Print Resolution	Up to 1200 x 1200 dpi
Print Features	Application Defaults Banner Sheet Enable / Disable Bi-directional Real-time Status Booklet Printing Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Standard and High Resolution) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout / Watermark N-up (up to 16 pages per sheet) Booklet layout Finishing Fit to new paper size Hold All Jobs Paper Selection by Attribute Print Around Proof Print Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings

Print from USB			
	Supports direct printing from computer via Type B USB port		
	Supported file formats: PDF, JPEG, TXT, TIFF, PS, XPS, PCL		
Operating Systems	Microsoft® Windows® XP SP3 (32- and 64-bit)		
	Windows Server 2003 SP2 R2 (32- and 64-bit) Windows Server 2008 and R2 (32- and 64-bit)		
	Windows Server 2012 and R2 (64-bit)		
	Windows Vista SP2 (32- and 64-bit)		
	Windows 7 (32- and 64-bit)		
	Windows 8 (32- and 64-bit)		
	Windows 8.1 (32- and 64-bit)		
	Windows 10 (32- and 64-bit)		
	Mac OS 10.8, 10.9, 10.10, 10.11 Linux® Redhat® Fedora® Core 20 x86		
	Ubuntu® 14.04 x64		
	openSUSE® 13.1 x64		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,WSD		
	NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)		
	AppleTalk®: EtherTalk®		
	Microsoft Windows Networking over IP		
	Bonjour® / AirPrint™ IPv6		
	Secure FTP		
	Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, MDNS, SSDP		
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support)		
	PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express		
	Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Variation Clab at Drive Driver®			
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and		
	single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
B	Cornigate mataple arrivers. Osea in conjunction with Equitiac Office , isoft SafeQ , rilatos and others.		
Print Solutions			
Xerox® Mobile Print Cloud (Optionαl)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.		
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Xerox® Print Service Plug-in	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers.		
for Android™ (Free at Google	You can easily print photos, Web pages and documents when your mobile device is connected to ConnectKey-enabled multifunction printers using a		
Play™ Store)	wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google		
	Play [™] store.		
Xerox® Mobile Link App	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data		
(Free at Google Play Store and Apple® App Store)	to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox®		
and Apple App Store,	multifunction printer.		
Unified Address Book for Fax, Inte	ernet Fax, Email and Scan to		
Features	Services supported: Fax, Internet Fax, Email, Scan to		
	Maximum contacts: 5,000		
	Contacts: Supports 1 or more destinations		
	Favorites for quick access of fax numbers, emails, etc.		
Scan			
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing		
	concurrent jobs)		
Speed			
Black-and-white	Up to 54 images per minute (ipm) Letter / 51 ipm A4 (simplex)		
Color	Up to 25 ipm Letter / 24 ipm A4 (duplex)		
Color	Up to 29 ipm Letter / 28 ipm A4 (simplex) Up to 14 ipm Letter / 13 ipm A4 (duplex)		
Resolution	72 x 72 dpi to 600 x 600 dpi		
NESULULIOII	Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)		
Maximum Scan Area	Up to 8.5 x 14 in. / 216 x 356 mm		

Scan Template Management	Support 250 scan templates	
	Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options	
Network Protocols	sFTP, FTP, SMB, NetWare, HTTP, HTTPS	
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW)	
rile compression	Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) Encrypted / Password Protected PDF (Network Scan Templates only) Linearized PDF, PDF/A	
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input	
Scan Features	Scan Build Job Compression Quality / File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression TWAIN Support, WIA 2.0 Support Bound Originals Edge Erase Reduction / Enlargement Single Touch Scan buttons (up to 10)	
Scan to Email (Standard)		
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self	
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format)	
Scan to (Standard)		
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)	
Network Scanning – Software Solu		
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: • PaperPort Professional image viewing and file management software - Complete PDF functionality - Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) – Professional OCR software for digital archiving and document conversion • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability	
Xerox [®] ConnectKey for DocuShare [®] (Optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer.	
Xerox [®] ConnectKey [®] Apps (Found at the Xerox [®] App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.	
Security		
Features	 Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP authentication Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) / .NET Secure Data Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted / Password Protected PDF (when using Email and Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite / Securely delete jobs using approved algorithms On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, Cisco® TrustSec Identity Services Engine integration, Device Security McAFee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, McAfee Integrity Control (optional) Common Criteria Certification ISO 15408 (undergoing evaluation) 	
Xerox® PrintSafe Software	This authentication software integrates with trusted industry cards and readers and provides PIN access to nearly any printer in a customer's secured print environment. It works with both Xerox® devices and devices from other vendors. This software is open to work with a variety of industry standard secure readers and cards.	

Fax		
	(includes LAN Fax (Fax forward to Email or SMB)), Network Server Fax Enablement (Walk-up Fax and LAN Fax available on WorkCentre 3655i/X only)	
Fax Speed	Up to 33.6 Kbps (analog)	
Memory	Uses device memory	
Resolution	Up to 600 x 600 dpi (Super Fine) resolution Up to 200 x 200 dpi (Fine) resolution Up to 200 x 100 dpi (Standard) resolution	
Compression	MH, MR, MMR, JBIG	
Fax Features	Duplex Scanning Reports Auto Redial Auto Reduction Cover Page Delayed Send Fax Forward to Email Memory Receive Polling Secure Fax Speed Dials (up to 200 individual, 100 group)	
Device Management		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2	
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 8, Vista, Server 2009, Server 2012 or Windows 7 and Internet Explorer 8.x and higher. • CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®	
Novell NDPS/NEPS	Server gateway application: centralized management tool.	
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities	
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions	
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions	
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions	
CentreWare Internet Services – Int	tegrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel	
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, PRN Output feature selection (2-sided, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12	
Support	Install print / scan drivers and online support available via web page	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic	

Xerox® WorkCentre® 3655i

Remote Services			
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usag	ge, eliminating the need to manually m	anage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance Xerox, allowing for problems to be solved faster with increased uptime.	and automate the troubleshooting/rep	oair process. Diagnostic data is sent to
Accounting			
Xerox® Standard Accounting (S	Standard)		
Tracking	Copy, Print, Fax, Scan and Email usage		
Accounting	Up to 2,497 User accounts (User ID) Up to 500 General accounts (Client) Up to 498 Group accounts (Department)		
Features	Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file		
Accounting Options - Network	Accounting (Allows central server to manage all accounting)		
	 Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface 		
What Comes in the Box			
	WorkCentre 3655i Multifunction Printer Toner Cartridge (6,100 page capacity ⁶) Drum Cartridge (85,000 pages ⁷) Quick Installation Guide, Product Information Guide, Driver CD, Documentation CD (User Manual, System Admin Guide) Power Cable Fax Cord (WorkCentre 3655i/X)		
Supplies and Accessories	Description	Quantity	Part Number
Supplies	Standard Capacity Toner Cartridge High Capacity Toner Cartridge Extra-high Capacity Toner Cartridge	6,100 pages ⁶ 14,400 pages ⁶ 25,900 pages ⁶	106R02736 106R02738 106R02740
	Drum Cartridge	85,000 pages ⁷	113R00773
	Staple Cartridge	3,000 staples	108R00823
Accessories	550-sheet Feeder (Adjustable up to A4 / legal)	-	097S04625
	Stand (Adds storage capacity for supplies, device stability, mobility and 13.1 in. of height)	-	497K14670
	MC-d		497K11500
	Wireless Networking Adapter		437K11300
	Wireless Networking Adapter McAfee Integrity Kit	-	320S00665

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

Build and configure your own Xerox® WorkCentre 3655i Multifunction Printer at www.buildyourownxerox.com/connectkey.

For more information, visit us at www.xerox.com/office



² Expected regular monthly throughput.

³ Requires analog phone line.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared Yield based on letter-/A4-size 20 lb. (75 gsm) pages. Yield will vary based on media type, size, weight, orientation, and usage patterns.