

#### SPECIFICATION SHEET

# OmniLink<sup>®</sup> TM-T70II-DT2 Thermal POS Printer with Integrated PC



## High-performance front-facing all-in-one POS printer with integrated PC.

All-in-one thermal POS printer - with integrated high-powered PC

Supports the latest operating systems - built-in Windows® 10 or Linux OS

**Compact design** – takes up to 70 percent less countertop space than traditional POS systems<sup>1</sup>

**Convenient, front-facing controls** – plus front receipt printing and paper loading

**Intel® processor** — supports a variety of low- and high-powered processor options (Celeron<sup>®</sup>, i3, i5)

Storage flexibility – SSD options (32GB, 64GB, 128GB, 256GB)

**POS-peripherals future-proof connectivity** — built-in USB 3.0 (x6), HDMI<sup>®</sup> and USB Type C technology in addition to USB 2.0 (x1), Serial, VGA, Audio (x1) and cash drawer port

Fast receipt printing - speeds up to 250 mm/sec<sup>2</sup>

Advanced paper-saving functions - reduce paper usage by up to 30 percent<sup>3</sup>



### OmniLink TM-T70II-DT2 Thermal POS Printer with **Integrated PC**

#### Printing

Print Method Thermal line printing Print Speed Max. 9.84"/sec (250 mm)2 graphics and text, 180 dpi **Column Capacity** 80 mm: 42/56 columns **Character Size** Font A: 1.25 mm x 3.00 mm (W x H) Font B: 0.88 mm x 2.13 mm (W x H) Fonts Font A (default): 12 x 24 Font B: 9 x 17 (including 2-dot horizontal spacing) Character Set 95 Alphanumeric, 18 International, 128 x 43 Graphic (including user-defined page), Traditional/Simple Chinese, Thai Barcode UPC-A/E, CODE 39/93/128, EAN8/13, ITF, CODABAR 2D symbols: PDF417, QR-CODE, MaxiCode, Composite Symbology, GS1-128, GS1DataBar, Omnidirectional/Truncated/Limited/Expanded **Paper Handling** 

**Media Dimensions** 80 mm: 3.13" ± 0.02" x 3.27" diameter (79.5 mm (H) ± 0.5 mm (W) x 83 mm) Epson Tested Media Please see www.epson.com/testedmedia Thickness 55 - 80 um

#### **Retail-hardened PC**

System Memory 4.0GB DDR4-2133, SO-DIMM CPU Processor Intel Core i5-7300U 2.60 GHz Intel Core i3-7100U 2.40 GHz Intel Celeron 3965U 2.20 GHz Video Controller i3 & i5: Intel HD Graphics 610 (built into CPU), Celeron: Intel HD Graphics 620 (built into CPU) Auxiliary Storage SATAIII SSD M.2 type 2242 (32GB or more) Device Control Software ePOS-Device Backup Battery Backup RTC/CMOS by lithium primary battery Sound Capability Internal monaural speaker **Operating System** Windows 10 IoT Enterprise 2016 LTSB 64bit (Windows model) Linux General Interfaces USB 3.0 (Type A) x 6, USB 2.0 (Type A) x 1, USB 2.0 (Type C), Ethernet x 1 (10/100/1000Base-T/TX/T) VGA x 1 (D-sub 15pin female) HDMI x 1

Line out x 1 (3.5 mm stereo mini jack) for external speaker output Cash drawer x 1 (RJ12 6pin) Serial x 1 (D-sub 9pin male)

#### **Safety Approvals**

EMI standards: FCC/ICES-003 Class A Safety standards: UL 62368-1:2014, CAN/CSA C22.2 No.62368-1-14 CB certification: IEC 62368-1:2014

#### **General (continued)**

#### Reliability MTBF

Controller: 169,000 hours (excluding SSD, fan and options)<sup>4</sup> Printer: 360,000 hours<sup>4</sup> AC adapter: 150,000 hours<sup>4</sup> MCBF Printer: 65,000,000 lines<sup>4</sup>

Thermal printhead life: 120 km<sup>4</sup> Auto cutter life: 1.7 million cuts<sup>4</sup> D.K.D. Function 2 drivers

Power Consumption 9.1 W (when not printing)/ 78.9 W (when printing)

Power Specifications (dedicated AC adapter) AC100 to 240 V/50 to 60 Hz

**Options** AC adapter, Printer affixing tape: DF-10, Customer displays: DM-D110 (part numbers: A61B133113, A61B133133), DM-D30 (part number: A61CF26111) Dimensions 6.77" x 11.42" x 4.49" (172 mm x 290 mm x 114 mm) (W x D x H) inclusive of connector cover

Weight 6.17 lb (2.8 kg)

Color Epson Black (EBCK)

Warranty 3-year limited warranty in the U.S. and Canada

#### What's in the Box

OmniLink TM-T70II-DT2 printer, Start Here guide, roll paper guide, roll paper, recovery DVD (for Windows model), manual CD, power switch cover, AC cable (depending on model), AC adapter, T1

#### **Eco Features**

**RoHS** compliant Recyclable product5 Epson America, Inc. is a SmartWay® Transport Partner<sup>6</sup>

#### **Ordering Information**

Please contact your sales representative for ordering information.

1 Based on W x D x H dimensions of POS systems; Toshiba Sure POS 500 models; Toshiba TCx models 360/370/380/740/780; Dell Optiplex 9020 - (MT). | 2 Speed based on using 80 mm wide media only. | 3 Paper savings depend on the text and graphics printed on the receipt. | 4 Epson's statements about reliability levels are only estimates based on normal use of the printer using tested media only. See www.epson.com/testedmedia for more information on Tested Media. These reliability statements are not warranties of the media or Epson's printers, and the only warranties for printers are the limited warranty statements for each printer. | 5 For convenient and reasonable recycling options, visit www.epson.com/recycle | 6 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806



Epson Canada Limited 185 Renfrew Drive, Markham, Ontario L3R 6G3 www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. OmniLink is a registered trademark of Epson America, Inc. Windows is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2020 Epson America, Inc. Com-SS-Oct-13 CPD-58142R1 1/20