ZKBio CVAccess Access Control Devices List

No.	Device Type	Part Number	Firmware Version	Software Version	Remark
1	Controller	InBio160/260/360	AC Ver 5.2.4(for 19.2018 on Above	ZKBioSecurity V3.1/3.3.0	ZKAC010
		C3-100/200/400	AC Ver 3.3.4 on Above		
		C3-260	AC Ver 910.0001.0 Feb 26 2016on Above		
2	Access Standalone Devices	SC403/SC840	Ver8.0.4.3-20210617 on Above		ZAM40
		ProBA/ProBA8	Ver8.0.4.3-20200511 on Above		ZAM120
		ProBA/ProBA8	Ver8.0.4.6-20221111 on Above		ZAM120
		ProBA/ProBA8+			ZAM120
		Horus	Ver8.0.2.3-20220322		ZAM170
		MA300/ZAM400	2N-ZAM400F Ver8.0.3 on Above		ZAM40
		F18/F19	Ver 8.0.4.6-20220317 on Above		ZAM170
		F22 Lite	Ver8.0.4.3-20190804 on Above		ZAM120
		F22(AccPro2)	Ver8.0.2.3-20191231 on Above		ZAM40
		F12	Ver 8.0.4.2-20211130		ZAM40
		G1/G1Q8	Ver 8.0.1.7-20220815 S		ZAM40
		SF300/SF600	Ver 8.0.4.2-20220106		ZAM40
		TF1400/TF1700	Ver 6.0.0.0(TF).Dec 16 2019		ZAM170(Pull)
		MA600	V6.0.0.0(ZE) Dec 4 2015 and above		ZAM170 (Pull
3	Visible Light Facial Recognition Devices	FaceDepot-7A	ZAM170 MF Ver1.1.3.2 or above	ZKBioSecurity V3.1/3.3.0	
		FaceDepot-7B/7BL series			
		SpeedFace-H5(H5L),H5L(P)			
		SpeedFace-H5/H5L/H5L(P)			
		SpeedFace-H8(.PD)			
		SpeedFace-H9L(QR)	ZAM170 MF Ver1.1.3.2or above		According to the type of Firmware(Access or Attendance), visible light devices can be added to the Access Control or Attendance Module. FTD(TD) series terminals work with the Temperature Detection module to achieve users temperature and mask screening. LPD series terminals work with ZKBioAccess IVS Mobile Application.
		SpeedFace-H10	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H10(QR)	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5L(P) SpeedFace-H5L(QR)	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5L	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H8	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H8L	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H9	ZAM180 MF Ver1.1.3.2or above		
		ProFace-X	ZAM180 MF Ver1.1.3.2or above		
		ProFace-X(TD)	ZAM180 MF Ver1.1.3.2or above		
		SpeedFace-H5L(P)	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5L	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5L(P)	ZAM170 MF Ver1.1.3.2or above		
		SpeedFace-H5L	ZAM180/ZAM170(QR Ver1.1.1.4		

ZKBio CVAccess Time&Attendance Devices List

No.	Device Type	Part Number	Software Version	Remark
1	2.8" and 4.3"TFT *Platform: ZAM210D/ ZAM210J/ ZAM210Z/ ZLA8A0	**SilkBio Series:** SilkFP 120 TA, SilkBio 130TC, SilkBio 150 TC **InBody Series:**InBody H20 Pro, InBody H30, InBody270 Pro, InBody370S **BF Series:** BF160, BF160D **MB Series:** MB1 000, MB1000, MB160, MB160D, MB360, MB10, MB20, MB30, **VF Series:** VF680, VF680, VF700, VF780, VF880, VF780 **iClock Series:** iClock260, iClock360, iClock580, iClock680, iClock760, iClock880, iClock990 **IP Series:** IP-08, IP-08A **SpeedFace Series:** SF100, SF200, SF300, SF400, SF600, SF700, SF800 **K Series:** K14K-C, K18K-C, K18K-C_UHM-C, UHM-C **K Pro Series:**K7 Pro,K7 3Pro,K10Pro,K7 3Pro,K20Pro,K7 Pro,K10Pro,K20Pro,K10Pro, **Face Series:** uFace302, uFace302_C, uFace302_Pro, uFace402, uFace402_C, uFace402_Pro, uFace402_Plus, uFace802, uFace802_C, uFace802_Pro, uFace802_Plus, uFace1602 Pro	ZKBioCVSecurity 6.0.0	
2	3.5"TFT *Platform: ZAM210D/ ZAM210J/ ZAM210Z/ ZLA8A0			
3	4.3"TFT *Platform: ZAM210D/ ZAM210J/ ZAM210Z/ ZLA8A0			
4	Visible Light Facial Device	**Linux OS:** MB160/MB160_ARM/ iFace302/402/802/1602/ iFace 10 /Horus TL2 **Android OS:** Horus S7 , Horus S7 MB2, Horus S7 FP, Horus H7		

Smart Video Surveillance Devices List

2023/11/16

Brand	Model Name	Image	Firmware Version	Functions							Product
				Intelligent Intelligence Package	Video Storage	Intelligent Search and Video Tag	Face Intelligent	Vehicle Intelligent	Behavior Analysis	Video Quality Diagnosis	
					Basic						
ANTeye	ZAV-A4M1		V2.1.0_20221103 and above	√	√	√	√	√	√	√	
	ZAV-A4M2										
	ZAV-1A4M1										
	ZAV-A4M1-AP										
	ZAV-A4M2-AP										
	ZAV-1A4P4		V1.0.1_20230530 and above								
	ZAV-1A4P4										
	ZAV-1A4P4 -VP										
	ZAV-1A4P8 -VP										
	ZAV-A4M1-S		V2.1.0_20221103 and above	√	√	√	√	√	√	√	intelligent mode Evidence kit module
	ZAV-A4M1-S										
	ZAV-1A4S1-S										
	ZAV-A4M1-S-P										
	ZAV-A4M2-AP-S										
	ZAV-A4M4S-AP-S										
	ZAV-1A4P8-S		V2.1.1_20231102 and above	√	√	√	√	√	√	√	
	ZAV-1A4P8 -VP-S										
	ZAV-A4M8		V1.0.3_20231030 and above	√	√	√	√	√	√	√	
	ZAV-A4M16										
	ZAV-1A4x16										
Hikvision	NVD-1000		R3.0 and above	√	√	√	√	√	√	√	
	NVR500		R3.0 and above	√	√	√	√	√	√	√	
Tiandy	TC-R3440		R3.0 and above	√	√	√	√	√	√	√	
	TC-R3860										
	TC-R3880										

VMS Server/Client Configuration

System	Recommended Hardware				Performance and Performance			
	CPU	RAM	OS	GPU	CPU	RAM	OS	GPU
Server	Intel(R) Core(TM) i5-6500 @3.60GHz or Above	8GB	WINDOWS(WIN 10/WINDOWS SERVER2008 and SERVER2012)	NVIDIA GT610	Intel(R) Core(TM) i7-7700 @3.60GHZ or Above	16GB	WINDOWS(Windows Embedded POSReady and SERVER2012)	NVIDIA GTX1050
Client	Intel(R) Core(TM) i5-6500 @3.60GHZ or Above	8GB	WINDOWS(WIN 10/WINDOWS SERVER2008 and SERVER2012)	NVIDIA GT610	Intel(R) Core(TM) i7-7700 @3.60GHZ or Above	16GB	WINDOWS(Windows Embedded POSReady and SERVER2012)	NVIDIA GTX1050