

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
2N SIP MIC	1	15		01208-001	01208-001	2N SIP Mic allows paging to several zones with a simple push of a button. It is ideal for live or pre-recorded announcements. It has a built-in audio-management server for configuration, which means less equipment as well as flexible, easy and cost-efficient installation. The network microphone console has 12 buttons that can be configured with actions of your choice. 2N SIP Mic's 12 buttons give you a smart paging solution for up to 12 zones, and if your system grows you can easily connect the microphone console to a PBX system thanks to support for SIP. The microphone is based on open standards and connects to standard networks using PoE.	1.099
AXIS A8004 JUNCTION BOX	1	3		5801-131	5801-131	AXIS A8004 Junction box offers neat and easy recessed installations of the AXIS A8004-VE Network video door station. Multiple mounting and wiring options along with a robust steel construction makes it suitable for most situations and wall types.	69
AXIS A9801 SECURITY RELAY	1	10		5801-141	5801-141	AXIS A9801 Security relay box offer an easy and cost efficient way to improve security for doors controlled by an Axis network video door station. The product bridges the connection between door station and door lock and is placed on the secure side of the door. If an intruder attempt to tamper with the door station to access the door lock wires, AXIS A9801 Security relay will cut the connection and ensure that the door remains securely locked.	119
MOUNT KIT CODEBLUE/A8004	1	1		5507-471	5507-471	Stainless steel adapter plate for mounting AXIS A8004-VE Network Video Door Station in Code Blue emergency stanchions and call boxes, combining intelligent video surveillance with emergency communication in a single device. The adapter plate is compatible with all Code Blue help points, suitable for new deployments and retrofitting existing installations.	119
AXIS ACCESS CARD 1K, WHITE 200 pcs	1		Discontinued - contact Order dept for availability	5506-831	5506-831	AXIS Access Card is a contactless Mifare 1K smart card that uses advanced radio frequency identification (RFID) technology to deliver secure and reliable physical access to premises. It is robust and IP68-rated, comes in a pack of 200 pcs.	359
AXIS A8105-E FLUSH MOUNT	1	30		5801-481	5801-481	Nice and easy recessed mount of AXIS A8105-E Network video door station suitable for most wall types.	69
AXIS A8004-VE ACCESSIBILITY KIT	1	2		5801-671	5801-671	AXIS A8004-VE Accessibility kit is an easy way to improve access to your building and comply with regulations on barrier-free accessibility. It's designed as a new front plate that mounts on and connects directly to any AXIS A8004-E Network Video Door Station. The product includes an inductive loop for hearing aids, illuminated pictograms for user feedback and a tactile dot for the call button, all of which help to simplify interaction for people with impaired hearing or vision.	199
AXIS TA8201 RECESSED MOUNT	1	7		01762-001	01762-001	Recessed mount offering neat and easy installation of the AXIS A8207-VE Network Video Door Station. Multiple mounting and wiring options along with a robust construction makes it suitable for most situations and wall types.	119
AXIS TA8601 CONDUIT ADAPTER 3/4 NPS	1	2		01763-001	01763-001	Cable protection attachment bracket for AXIS A8207-VE Network Video Door Station Compatible with 3/4" Conduits	79
AXIS TA8501 PHYSICAL TAMPERING SW	1	6		01962-001	01962-001	AXIS TA8501 Physical Tampering Switch is an accessory to be used when the AXIS A8105-E Network Video Door Station is combined with the AXIS A9801 Security Relay. This accessory is a fix to the known issue of the integrated accelerometer showing false tampering alerts.	15

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS A1001 Network Door Controller	1	125		0540-001	0540-001	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	503
AXIS A1001 BULK 10PCS Network Door Controller	1	1		0540-021	0540-021	AXIS A1001 Network Door Controller is an open, non-proprietary platform for access management. The controller is installed by each door and data is automatically synchronized between the controllers in the system. The controller supports most Wiegand and RS 485 OSDP readers. The unit comes with a built-in software for basic access management for up to 33 controllers as well as an open API to meet the requirements for larger and more advanced installations. The plenum rated controller is designed for wall or ceiling mount indoors and supports Power over Ethernet IEEE 802.3af Class 3. It is fitted with 14 configurable input/outputs and 5 power outputs for door accessories including fault/tamper detection and support for Uninterruptible Power Supply (UPS).	5.030
AXIS A1601	1	50		01507-001	01507-001	With door controllers from Axis, you install one smart, independent device by each door to create a scalable access control system. The open platform allows you to mix and match best-of-breed software and hardware, and enables easy integration with other systems such as video surveillance, intrusion detection, and time and attendance. AXIS A1601 Network Door Controller is ideal for advanced access management in mid-sized and large, multi-site installations using third-party software (no embedded Entry Manager software). It has a powerful processor, expanded storage and memory, relays, and I/O ports. AXIS A1601 is powered by PoE+ and can also power connected equipment.	699
AXIS A8004-VE	1	30		0673-001	0673-001	AXIS A8004-VE Network Video Door Station is an open, IP-based door station for two-way communication, video and remote entry control. By combining exceptional audio capabilities, including a high performing solution for echo cancellation and noise suppression, with an integrated HDTV camera with WDR and excellent low-light performance, the unit offers reliable 24/7 identification and remote entry control also in the most demanding situations. Based on open IP standards and interfaces such as Onvif, PoE and SIP, AXIS A8004-VE Network Video Door Station offers great integration possibilities and is a perfect complement to any video surveillance system.	1.049



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS A8105-E	1	175		0871-001	0871-001	AXIS A8105-E is a small and powerful network video door station. It operates as a communication device and full-fledged security camera at the same time, providing HDTV video, audiovisual identification, two-way communication and remote entry control as an intrinsic part of video surveillance. Open standards such as ONVIF and Session Initiation Protocol (SIP) in combination with its small size, give unique opportunities for system design, integration and installation. Wide Dynamic Range (WDR) and efficient noise cancellation ensure uncompromised performance in demanding situations, such as strong backlight or surrounding noise. Axis' Digital Corridor Format easily adjusts the viewing area to the location.	799
AXIS A8207-VE	1			01436-001	01436-001	AXIS A8207-VE Network Video Door Station combines a fully featured 6MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID access control reader. By providing both surveillance, visitor management, and employee accessibility, AXIS A8207-VE increases the efficiency while keeping down the number of devices at the door. Analytics, such as motion or sound-based detection, is supported. Based on open standards and with several hardware interfaces, AXIS A8207-VE easily integrates with other systems and solutions and is prepared for future needs. Interaction is intuitive and accessible, with an inductive loop for hearing aid.	1.399
AXIS A8207-VE MKII	1	80		02026-001	02026-001	AXIS A8207-VE Network Video Door Station combines a fully featured 6MP security camera with high-quality, two-way audio communication and remote entry control. It also has an integrated RFID access control reader. By providing both surveillance, visitor management, and employee accessibility, AXIS A8207-VE increases the efficiency while keeping down the number of devices at the door. Analytics, such as motion or sound-based detection, is supported. Based on open standards and with several hardware interfaces, AXIS A8207-VE easily integrates with other systems and solutions and is prepared for future needs. Interaction is intuitive and accessible, with an inductive loop for hearing aid.	1.499
AXIS A9188 NETWORK I/O RELAY MODULE	1	30		0820-001	0820-001	AXIS A9188 Network I/O Relay Module is an intelligent module with 8 configurable I/Os and 8 form C relays and supports supervised inputs. Open API, including VAPIX, for software integration. High level of integration with AXIS A1001 Network Door Controller for elevator control for floor management etc. Supported by AXIS Video Hosting System, AXIS Camera Station and third party partner software. The module provides 12 and 24 V DC output to I/O devices and can extend the functionality of any Axis product where you need additional I/Os or relays. Powered by PoE+ or 12 and 24 V DC input	499
AXIS A9161 NETWORK I/O RELAY MODULE	1	90		0821-001	0821-001	AXIS A9161 Network I/O Relay Module has 6 configurable I/Os with supervised inputs and a relay. The module reacts on inputs, such as signals from PIR motion detectors or switches, to trigger actions. Supplying power to I/O devices, it can extend the functionality of Axis products where additional I/Os or relays are needed. Its enclosure makes installation easy and flexible. -6 I/Os and 1 form C relays -12 and 24 V DC output/input or PoE+ -Based on Axis open platforms, VAPIX and ACAP -Used with AXIS Camera station or third-party software	249

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS A9188-VE NETWORK I/O RELAY MODULE	1	5		0831-001	0831-001	<p>AXIS A9188-VE Network I/O Relay Module comes with AXIS T98A15-VE Surveillance Cabinet making it outdoor-ready, vandal-resistant, and UL294-approved. With its 8 configurable I/Os and relays, its open platform enables a high level of integration with AXIS A1001 Network Door Controller and other facility systems.</p> <p>-8 I/Os with supervised inputs and 8 form C relays -UL294-approved with cabinet AXIS T98A15-VE Surveillance Cabinet -12 and 24 V DC output/input or PoE+ -Open API, support for VAPIX, ACAP -Used with AXIS Camera station or third-party software</p>	799
AXIS A4011-E READER	1	20		0745-001	0745-001	<p>AXIS A4011-E Reader is a generic touch-free reader with keypad and illuminated symbols. It is a perfect match to the Network Door Controller A1001. The reader is intended for both indoor and outdoor use and it supports most smart card formats with 13.56 MHz. The reader is certified according to UL294</p>	310
AXIS A4010-E READER WITHOUT KEYPAD	1	30		01023-001	01023-001	<p>AXIS A4010-E Reader is a generic touch-free reader without keypad and 2 LED feedback. It is a perfect match to the Network Door Controller A1001. The reader has a small form factor, intended for both indoor and outdoor use. It uses RS485 OSDP communication and supports most smart card formats with 13.56 MHz. This reader is a Mark II for 0946-001 with same functionality but no visible differences.</p>	199
AXIS 4IN1 SECURITY SCREWDRIVER	1	10		5507-711	5507-711	<p>The AXIS 4-in-1 Security Screwdriver Kit is a great tool for installing Axis products. The kit features two double-sided insert bits type that match Axis products using tamper resistant torx and standard philips head. The kit comes with a quick-release, non-slip rubber handle, and a velcro-sealed polyester pouch with belt clip. Insert bits material in chrome vanadium (TR10+PH1) and in stainless steel (TR20+TR30).</p>	24
AXIS Q17 FRONT WINDOW KIT B	1	1		01687-001	01687-001	<p>Accessory front window assembly in polycarbonate for AXIS Q1785/86-LE, IK10 rated. Not recommended for installation that requires more than 22x optical zoom.</p>	49
GASKET A CABLE 3,5-7MM 10PCS	1	1		5503-741	5503-741	<p>M20 Gasket for cable diameter 3,5mm to 7mm. 10 pcs.</p>	16
ACC TOOL STEEL STRAP	1			21776	21776	<p>Tool for steel strap tensioning. For use with 21764 and AXIS T91A67</p>	122
AXIS GASKET M16 5-8 MM 10PCS	1	1		01785-001	01785-001	<p>IP66 cable gasket for M16 holes (max 17mm). By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Suitable for cable diameters between 5-8mm. Black color. 10 pieces (bulk pack).</p>	19
GASKET B M20 CABLE 6-13MM 10PCS	1	1		5503-751	5503-751	<p>M20 Gasket for cable diameter 6-13mm, 10 pcs.</p>	16
GASKET C M25 CABLE 8-17MM 10PCS	1	1		5503-791	5503-791	<p>M20 Gasket for cable 8-17mm, 10 pcs.</p>	16
CABLE GLAND A M20 5PCS	1	2		5503-761	5503-761	<p>M20 cable gland, 5 pcs.</p>	8
LENS TOOL KIT AXIS M311X 2MM 4PCS	1	1		5503-561	5503-561	<p>Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X cameras with 2mm lens. Content: Lens tool and Opening tool 4 pcs of each.</p>	20
GASKET C M20 10PCS	1	8		5505-941	5505-941	<p>This gasket is specially made for flexible and easy installation. By using the included CONNECTOR GUARD A over the RJ45 connector, you do not need to re-terminate the network cable which gives a much faster and more secure installation. Made for M20 holes and cables from 5 to 15mm in outer diameter. 10 pcs.</p>	16
LENS TOOL AXIS M311X 4PCS	1			5502-771	5502-771	<p>Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS M311X (except 2mm lens version). Content: Lens tool and Opening tool 4 pcs of each.</p>	20



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CABLE GASKET M20 3MM 10PCS	1	1		5506-421	5506-421	M20 gasket for small cables like I/O and audio cables. 10 pcs	16
LENS TOOLKIT P39XX-R 4 PCS	1	1		5506-441	5506-441	Tool kit for simplifying adjustment of viewing direction and focus setting. Compatible with AXIS P39xx-R cameras with the standard lens and the 2.8 mm accessory lens. Content: Lens tool, Allen key and Opening tool. 4 pcs of each.	16
CABLE GLAND A M25 5PCS	1	1		5503-831	5503-831	M25 Cable gland, 5 pcs.	16
CABLE GLAND M20x1.5 RJ45 5PCS	1	1		5503-951	5503-951	M20 cable gland for RJ45. Ease of installation, no need of cutting the cable.	16
CABLE SEALING IP65 FOR Q8108-R	1			5502-711	5502-711	Accessory cable sealing to meet IP65 rating for Q8108-R.	209
AXIS M3004-V/05-V LENS M12 6MM	1		Discontinued contact Order dept for availability	5503-651	5503-651	Optional lens, 6mm for M3004-V/M3005-V	41
AXIS M3025-VE LENS M12 6MM	1		Discontinued contact Order dept for availability	5504-551	5504-551	Optional lens for AXIS M3025-VE, 6mm. Including focus ring.	41
LENS M12 6MM F1.9 4PCS	1	10		01960-001	01960-001	Accessory lens 6 mm, F1.9 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	79
LENS M12 16MM F1.8 4PCS	1	10		01961-001	01961-001	Accessory lens 16 mm, F1.8 with M12 thread and built in IR-cut filter for AXIS F1005-E and FA1105. Tool for removing the standard lens is included. 4 Pcs.	79
LENS M12 12MM F1.6 4P	1	8		01780-001	01780-001	LENS M12 12MM F1.6 Q6100-E, Q6010-E	99
LENS M12 25MM F2.4 4P	1	8		01781-001	01781-001	LENS M12 25MM F2.4 4P Q6100-E	99
LENS M12 16MM F1.8 4P	1	8		01812-001	01812-001	LENS M12 16MM F1.8 Q6010-E Q6100-E	99
LENS M12 6MM F2.0 4P	1	15		01813-001	01813-001	LENS M12 6MM F2.0 Q6010-E Q6100-E	99
ACC LENS M12 MEGAPIXEL 16MM 10PCS	1		Discontinued contact Order dept for availability	5502-161	5502-161	Megapixel lens 16mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	125
ACC LENS M12 MEGAPIXEL 2.8MM 10PCS	1		Discontinued contact Order dept for availability	5502-101	5502-101	Megapixel lens 2.8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	167
ACC LENS M12 MEGAPIXEL 3.6MM 10PCS	1		Discontinued contact Order dept for availability	5502-151	5502-151	Megapixel lens 3.6mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	125
AXIS WEATHERSHIELD K	1	20		5507-121	5507-121	Weathershield for AXIS P14 Series designed for use in rainy and windy environments.	29
LENS M12 6MM 5PCS	1			5801-771	5801-771	Accessory M12 6mm lens for AXIS Q6000-E MklI 5pcs	99
ACC LENS M12 MEGAPIXEL 6MM 10PCS	1		Discontinued contact Order dept for availability	5502-111	5502-111	Megapixel lens 6mm lens with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter 10pcs	125
LENS M12 2.8 MM F1.2 10P	1	3		01860-001	01860-001	Megapixel lens 2.8 mm, F1.2 with M12 thread for AXIS P39-R Series that provides 110° horizontal FOV and excellent low light performance. Coated with IR-cut filter. 10 pieces bulk pack.	199
ACC LENS M12 2.8MM F2.0 10 PCS	1		Discontinued contact Order dept for availability	5504-951	5504-951	Megapixel lens 2.8 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 115° horizontal FOV with these cameras. With IR filter. 10 pieces.	167
ACC LENS M12 6MM F1.6 10 PCS	1	1		5504-961	5504-961	Megapixel lens 6 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 52° horizontal FOV with these cameras. With IR filter. 10 pieces.	167
ACC LENS M12 8MM F1.6 10 PCS	1	1		5504-971	5504-971	Megapixel lens 8 mm, F1.6 with M12 thread for AXIS P39-R Series that provides 40° horizontal FOV with these cameras. With IR filter. 10 pieces.	167
ACC LENS M12 3.6MM F2.0 10PCS	1	1		5506-011	5506-011	Megapixel lens 3.6 mm, F2.0 with M12 thread for AXIS P39-R Series that provides 87° horizontal FOV with these cameras. With IR filter. 10 pieces. Can be used as a spare part for AXIS P39-R or as a wider FOV option for P3905-RE.	199
AXIS LENS M12 2.1MM F2.2 10PCS	1	1		5901-371	5901-371	Megapixel lens 2.1mm, F2.2 with M12 thread for AXIS P39-R Series that provides 147° horizontal FOV with these cameras. With IR filter. 10 pieces. Lens tool included.	199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS LENS M12 2.1 MM F1.8 IR 10P	1	1		02006-001	02006-001	2.1 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	199
AXIS LENS M12 3.6 MM F1.8 IR 10P	1	1		02007-001	02007-001	3.6 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	199
AXIS LENS M12 6.0 MM F1.9 IR 10P	1	1		02008-001	02008-001	6.0 mm accessory lens, F1.9 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	199
AXIS LENS M12 8.0 MM F1.8 IR 10P	1	1		02009-001	02009-001	8.0 mm accessory lens, F1.8 with M12 thread, without IR-cut filter for day/night cameras with removable IR cut filter. Compatible with AXIS P3925-R and AXIS P3935-LR. 10 pcs. Lens tool included.	199
LENS M12 16MM 5PCS	1			5801-781	5801-781	Accessory M12 16mm lens for AXIS Q6000-E Mkl 5pcs	99
ACC LENS M12 MEGAPIXEL 6PCS	1	1		5506-431	5506-431	2 pieces each of 2.8 mm (F2.0), 6 mm (F1.6) and 8 mm (F1.6) Megapixel lenses with M12 thread. For use with AXIS P39-R cameras. Includes lens tools.	125
ACC LENS M12 MEGAPIXEL 8MM 10PCS	1		Discontinued contact Order dept for availability	5502-411	5502-411	Megapixel lens 8mm with M12 thread for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs	125
LENS M12 MEGAPIXEL 10PCS	1			5502-421	5502-421	Mixed pack of M12 Megapixel lenses. Focal length: 2.8mm, 3.6mm, 6mm, 8mm and 16mm for AXIS M3113-R, AXIS M3114-R, AXIS 209FD, AXIS 209MFD, AXIS M3011, AXIS 3014. With IR filter. 10pcs=2 pcs of each lens.	125
THEIA LENS CS VARIF 1.8-3MM DC-IRIS	1	10		5503-161	5503-161	Barrel distortion corrected and IR corrected wideangle lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	243
LENS CS VF 2.2-6MM F1.3 DC-I MP	1	1		5502-751	5502-751	Varifocal 2.2-6mm DC-Iris Megapixel Lens, F1.3, CS mount for AXIS M1113/4	125
LENS CS 2.4-6MM MANUAL IRIS	1	1		5503-181	5503-181	Manual iris lens, varifocal 2.4-6MM compatible with AXIS M1103 and M1104.	66
LENS FUJINON CS 2.2-6MM DC-IRIS B	1	1		5800-781	5800-781	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E, P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E.	125
LENS CS 3-10.5MM DC-IRIS	1	2		5506-961	5506-961	Standard lens for AXIS M1124/-E, M1125/-E.	99
LENS CS VARIF 9-40MM DC-IRIS D/N	1	4		5503-171	5503-171	Varifocal IR-corrected lens for cameras up to 5 mega pixel resolution. Compatible with e.g. AXIS M1114/-E, P1354/-E, P1355/-E, P1357/-E, Q1602/-E, Q1604/-E.	217
LENS CS VARIF 9-40MM P-IRIS D/N	1	1		5504-901	5504-901	Varifocal IR-corrected P-iris tele lens compatible with AXIS AXIS P1355/-E, P1357/-E, AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E.	217
LENS COMPUTAR CS 12.5-50MM DC-IRIS	1	3		5800-791	5800-791	Varifocal IR-corrected lens with DC-Iris. Compatible with e.g. AXIS P1353/-E, P1354/-E. Axis Q1602/-E, Q1604/-E.	209
LENS COMPUTAR CS 12.5-50MM P-IRIS	1	1		5800-801	5800-801	Varifocal IR-corrected lens with P-Iris. Compatible with e.g. AXIS Q1602/-E, Q1604/-E, Q1614/-E, Q1615/-E, AXIS P1355/-E, P1357/-E.	209
LENS COMPUTAR I-CS 2.8-8.5MM	1	8		5901-101	5901-101	Standard lens for AXIS Q1615 Mkl with remote zoom based on the new standard I-CS.	229
LENS CS VF 15-50MM F1.5 DC-I MP	1	1		5502-761	5502-761	Varifocal Mega Pixel DC-Iris Lens 15-50mm, F1.5, CS mount, for AXIS M1113/14	167
LENS CS 15-50MM F1.5 DC-I MP D/N	1	1		5503-421	5503-421	Varifocal Megapixel DC-Iris Lens 15-50mm, F1.5, CS mount, Day/Night for AXIS Q1602.	167
LENS FUJINON C CS 8-80MM DC	1	10		5506-991	5506-991	Varifocal IR-corrected lens with DC-Iris. For use with both C-mount and CS-mount cameras thanks to the included adapter. Compatible with e.g. AXIS Q1635.	349
RICOM 2MP LENS DC-IRIS 8-26MM F0.9	1	1		01577-001	01577-001	Lens RICOM 2 MP DC-iris CS-Mount Varifocal 8-26MM F0.9. Recommended for AXIS Q1645/-LE.	549
LENS CS 12-50 MM F1.4 P-IRIS 8MP	1	5		01690-001	01690-001	Varifocal IR-corrected 12-50 mm P-iris lens for cameras up to 8 megapixel resolution and 1/1.8" sensor . Compatible with e.g. AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1367/-E and P1368-E.	449



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
LENS I-CS 9-50 MM F1.5 8MP	1	2		01727-001	01727-001	Varifocal IR-corrected 9-50 mm i-CS lens for cameras up to 8 megapixel resolution and 1/1.8" sensor. Motorized zoom, focus and P-iris. Compatible with e.g. AXIS Q1645/-LE, AXIS Q1647/-LE, AXIS P1377/-LE and P1378/-LE.	449
LENS I-CS 3.9-10 MM F1.5 5MP	1	1		01576-001	01576-001	Spare varifocal i-CS lens for AXIS Q1645/-LE and AXIS Q1647/-LE.	299
Lens CS 2.8 - 13 mm F1.4 DC-Iris 5 MP	1	1		01775-001	01775-001	Tamron varifocal CS mount lens with DC-Iris and focal length 2.8 – 13 mm F1.4. It supports cameras up to 5 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	79
LENS CS 3-10.5 MM DC-IRIS 2 MP	1	1		01774-001	01774-001	Ricom varifocal CS mount lens with DC-Iris and focal length 3 - 10.5 mm F1.4. It supports cameras up to 2 megapixels and is compatible with selected cameras from AXIS M11 Network Camera Series.	69
AXIS LENS CLOTH 10PCS	1	1		5502-661	5502-661	Axis accessory lens cloth. 10 pack	33
AXIS LENS CLOTH 50PCS	1	1		5502-721	5502-721	Axis accessory lens cloth. 50 pack	142
SURVEILLANCE STICKER ENG 10PCS	1	1		5502-811	5502-811	Axis branded sticker showing a Camera. Text: Video surveillance in operation	7
SURVEILLANCE STICKER ENG 50PCS	1	1		5502-821	5502-821	Axis branded sticker showing a Camera. Text: Video surveillance in operation	42
RADAR DETECTION STICKER EN 10PCS	1	1		01551-001	01551-001	Axis branded sticker showing a radar detection illustration. Text: Radar detection in operation	8
AXIS WEATHERSHIELD KIT C	1	8		5504-881	5504-881	Heavy duty outdoor weathershield for wall mounted AXIS fixed dome cameras. Designed to protect the dome from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	50
AXIS PT IR ILLUMINATOR KIT C	1	1		5801-901	5801-901	850nm IR LED illuminator kit compatible with AXIS T99A Positioning Units for visual cameras. Kit includes one pair of IR illuminators, one metal mounting bracket, and three different diverging lenses. Note: this is the same illuminator kit as used in AXIS Q8685-LE PTZ Network Camera.	1.799
AXIS T99 ILLUMINATOR BRACKET KIT A	1	1		01181-001	01181-001	Bracket kit for installing a pair of compatible illuminators to Axis positioning cameras and positioning units. Designed for use with AXIS Q8685-E and AXIS T99A10. Compatible with selected T90 white-LED and IR-LED illuminators. Includes fitting brackets, illuminator connectors, screws, washers, cable glands and cable ties. Illuminators sold separately.	199
AXIS WASHER KIT B	1	2		5507-701	5507-701	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle.	999
AXIS TQ6905-E WASHER KIT	1	20	To be launched	02241-001	02241-001	Washer kit for spraying cleaning fluid on the windows of AXIS positioning cameras and positioning units. The kit contains a 23 litre tank, pump for delivery up to 11m (36ft), tube, nozzle and custom-made mounting bracket for the nozzle. This washer kit compatible with Q6215 and as well requires separate ordering of T6101 I/O since Q6215 does not have I/O.	1.099
AXIS WASHER KIT A	1		Discontinued - contact Order dept for availability	5505-921	5505-921	Washer kit for spraying cleaning fluid on the windows of AXIS Q8631-E/Q8632-E and AXIS Q8665-E/Q8665-LE. The kit contains a 23 liter tank, pump for delivery up to 11m (36ft), tube, nozzle and mounting bracket for attaching the nozzle to the PT-head.	999
AXIS BIRD CONTROL SPIKE 10P	1	10		5801-121	5801-121	Bird control spikes made of flexible UV-resistant polymer preventing birds from landing on cameras or mounts. Each module has five spikes and can be mounted on flat or curved surfaces using the pre-mounted adhesive or cable ties (not included). The modules can be connected lengthwise and/or widthwise to cover a larger area. 10 pcs.	24



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS SAFETY WIRE 3M 5P	1	8		5801-971	5801-971	Stainless steel safety wire 3 m (10 ft) long, with a fixed loop in one end and an adjustable loop with a plated brass wire lock in the other. Suitable for both indoor and outdoor use.	34
AXIS F7301 CABLE BLACK 1M 4PCS	1	3		01552-001	01552-001	Black cable with RJ12 and micro USB connectors for indoor Sensor Units. Length 1 m (39 in.) 4 pcs.	29
AXIS F7315 CABLE WHITE 15M 4PCS	1	30		5506-821	5506-821	AXIS F7315 comes in packs of four. 15-m (49 ft.) white cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit.	99
AXIS P13 WEATHERSHIELD EXTENSION A	1	3		01692-001	01692-001	AXIS P13 Weathershield Extension A for AXIS P1375-E. For mounting on AXIS P13 Series camera providing additional protection against rain, snow and sunlight.	49
M12(F)-RJ45(M) CABLE 0.5M (1.6FT)	1	4		01793-001	01793-001	M12 D-Code 4-pin (Female) to RJ45 (Male) Ethernet cable, CAT5E. Length: 0.5m (1.6ft). Cable outer diameter: 6.2mm (0.25"). Color: Black. Outdoor UV and sunlight resistant. Tested operational for shock and vibration according to requirements for rolling stock and ground vehicle installations. Compatible with all Axis network video products with female RJ45 Ethernet port 802.3af and 802.3at (up to 30W).	35
AXIS TM1803 WEATHERSHIELD EXTENSION	1	3		02061-001	02061-001	weathershield extension over M1135/37-E where entire top cover kit not wanted (TM1802)	39
AXIS T92E05 PROTECTIVE HOUSING	1	1		0344-001	0344-001	Protective camera housing for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	167
AXIS T92E20 OUTDOOR HOUSING	1	10		0433-001	0433-001	Outdoor PoE camera housing with window-/camera heaters and fan for P13XX, M11XX, Q16XX and Q1755. Die cast aluminum casing and wallbracket, polycarbonate sunshield. The housing is IP66-, Nema 4X-, Vibration 4M3 rated and IK10 impact-resistant. Sunshield, wallbracket and screwdriver included.	276
AXIS T92G20 OUTDOOR HOUSING	1	1		01085-001	01085-001	Outdoor PoE+ camera housing with IR illumination, window & camera heaters, and fan. Compatible with AXIS Q1645 and AXIS Q1647. Polycarbonate sunshield, aluminum wall mount and torx screwdriver included.	479
AXIS T93C10 OUTDOOR HOUSING	1	3		5507-681	5507-681	Outdoor camera housing for Axis cameras with EF lenses (e.g.: AXIS Q1659). Made of IK10 impact resistant thermoplastic with dual-layer UV protection. IP66, NEMA 4X rated and UL listed. Powered by 24 VDC (power supply not included). Heavy duty wall mount included.	1.299
AXIS T93C EXTENSION KIT	1	1		5901-471	5901-471	Extension kit to allow mounting of longer lenses in AXIS T93C10 Outdoor Housing (e.g.: compatible with AXIS Q1659 55-250 mm). Includes built-in sunshield and front window. The extension kit provides an extra space of 80mm in length within the housing, giving a total length of 380mm for the camera and lens. The part of the lens within the extension kit can have maximum diameter of 75mm.	99
AXIS T93F05 PROTECTIVE HOUSING	1	1		5900-261	5900-261	Fixed box protective camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Compatible with AXIS P13 Series and AXIS Q16 Series. AXIS T94Q01A Wall mount included.	134
AXIS T93F10 OUTDOOR HOUSING 24VAC/12-24VDC	1	2		5900-271	5900-271	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by 24 V AC or 12-24 V DC. Compatible with AXIS P13 Series, AXIS Q16 Series, and M11 Series. AXIS T94Q01A Wall mount included. AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F) AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F). AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F) AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F)	201



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T93F20 OUTDOOR HOUSING POE	1	2		5900-281	5900-281	Fixed box outdoor camera housing made of IK10 impact resistant and UV resistant polymer. IP66, NEMA 4X rated and UL listed. Powered by PoE IEEE802.3af. Compatible with AXIS P13 Series, AXIS Q16 Series and M11 Series. AXIS T94Q01A Wall mount included. Temperature range: AXIS P1353/P1354/P1355/P1357 and AXIS Q1604/Q1614: -40 °C to 50 °C (-40 °F to 122 °F), AXIS P1365 and AXIS Q1615/Q1635: -40 °C to 55 °C (-40 °F to 131 °F), AXIS Q1645/Q1647: -40 °C to 40 °C (-40 °F to 104 °F), AXIS M1124/M1125: -40 °C to 55 °C (-40 °F to 131 °F).	201
AXIS T93G05 PROTECTIVE HOUSING	1		Discontinued - contact Order dept for availability	5506-491	5506-491	Tailor-made light weight IP66- and IK10-rated housing for AXIS M1124/M1125. Operating temperature: -20 °C to 50 °C (-4 °F to 122 °F). Material: IK10 impact-resistant polymer. Wallmount included.	119
AXIS SUNSHIELD A	1	1		5504-941	5504-941	Accessory sunshield and weather protection for AXIS T93F Housing Series	29
AXIS T96B05 OUTDOOR HOUSING	1	10		5505-911	5505-911	Outdoor housing for selected AXIS P39 cameras. Enables the cameras to be mounted outside vehicles such as buses, trams, trucks and emergency vehicles. Includes lens tool and top cover tool.	83
AXIS T98A15-VE SURVEILLANCE CABINET	1	40		5900-151	5900-151	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included.	226
AXIS T98A16-VE SURVEILLANCE CABINET	1	3		5900-161	5900-161	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS M111X-E, P13XX-E, Q16XX-E, Q1755-E, Q191X-E Q192X-E.	226
AXIS T98A17-VE SURVEILLANCE CABINET	1	10		5900-171	5900-171	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible cameras: AXIS P33-VE/LVE.	226
AXIS T98A18-VE SURVEILLANCE CABINET	1	50		5900-181	5900-181	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS T91B61 Wall bracket for use with AXIS P55, P56, Q60 and Q61-series or fixed dome pendant kits.	226
AXIS T98A19-VE SURVEILLANCE CABINET	1	1		5900-321	5900-321	IP66, IK10 and NEMA 4X rated outdoor-ready surveillance cabinet. Protects accessory devices such as power supply, media converter, midspan and fuse from tough weather and vandalism. The camera is mounted on the door of the cabinet. Mounting bracket for wall, DIN-rail, device mounting bracket and Electrical safety cover is included. Compatible products: AXIS P5414-E/15-E.	226
AXIS T98A SUNSHIELD	1	6		5503-551	5503-551	Metal sunshield for AXIS T98A-VE Surveillance Cabinet series. Reduces the temperature inside the cabinet, caused by sun radiation, with up to 15°C (27°F).	62
AXIS CABINET LOCK A	1	5		5505-651	5505-651	Door lock for AXIS T98A surveillance cabinet. Uses a generic key but it is possible to change locking cylinder to a unique key solution (not supplied from Axis)	50



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CORRIDOR FORMAT BRACKET A	1	1		5504-931	5504-931	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F05 and AXIS T93F20 housings to enable a vertically oriented, "portrait"-shaped video stream from the camera. Includes built-in camera heater (only applicable when mounted in AXIS T93F20).	33
CORRIDOR FORMAT BRACKET B	1	1		5506-381	5506-381	The corridor format bracket makes it possible to mount a camera rotated 90 degrees inside the AXIS T93F10 housing to enable a vertically oriented, "portrait"-shaped video stream from the camera. Included with built-in camera heater.	33
AXIS T92E CAMERA HOLDER PLATE C	1	1		5505-331	5505-331	Camera holder plate for mounting an AXIS Q1614 in a AXIS T92E05 and AXIS T92E20 housing. Or change the camera unit inside an AXIS P135X-E outdoor camera.	16
AXIS T92E CAMERA CHANGE KIT A	1			5505-341	5505-341	Kit for mounting an AXIS Q1614 in a AXIS T92E05/AXIS T92E20 housing produced before 2014. Or change the camera unit inside an AXIS P134X-E outdoor camera.	33
AXIS M3004-V/05-V BLACK COVER 10PCS	1		Discontinued - contact Order dept for availability	5503-591	5503-591	Clip on black cover for AXIS M3004-V and AXIS M3005-V.	83
AXIS M3004-V/05-V WHITE COVER 10PCS	1		Discontinued - contact Order dept for availability	5503-601	5503-601	Clip on white cover for AXIS M3004-V and AXIS M3005-V.	83
AXIS M3006-V/07-PV COVER WHITE 10PCS	1		Discontinued - contact Order dept for availability	5503-621	5503-621	Clip on white cover for AXIS M3006-V and AXIS M3007-PV. 10 pcs.	83
AXIS M3044-V/45-V/46-V VIEW PROT 5P	1			5507-441	5507-441	Viewing protector that makes it harder to see where the camera is aiming. For use when the camera is used without dome. 5 pcs.	39
ACC CVER DME AXIS M301X MIX 10PCS	1		Discontinued - contact Order dept for availability	5502-341	5502-341	Mixed covers with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. Includes 3 black, 3 silver, 3 gold and 1 white cover.	125
ACC CVER DME AXIS M301X BLCK 10PCS	1		Discontinued - contact Order dept for availability	5502-181	5502-181	Black cover with clear bubble for AXIS M3011 and AXIS M3014. 10 pack	125
ACC CVER DME AXIS M301X SIL 10PCS	1		Discontinued - contact Order dept for availability	5502-191	5502-191	Silver cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	125
ACC CVER DME AXIS M301X GOLD 10PCS	1		Discontinued - contact Order dept for availability	5502-201	5502-201	Gold cover with clear bubble for AXIS M3011 and AXIS M3014 Network Cameras. 10 pack.	125
AXIS M3024/25/26/27 COVER WHT 10PCS	1	1		5504-071	5504-071	White cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	108
AXIS M3024/25/26/27 COVER BLK 10PCS	1	1		5504-061	5504-061	Black cover skins compatible with AXIS M3024/M3025/M3026/M3027 for covering screws or simplify the painting process.	108
AXIS M30 SKIN COVER A BLACK 4P	1	3		01463-001	01463-001	4-pack. Outdoor-ready skin covers compatible with AXIS M3057/58-PLVE cameras for changing the appearance of the camera, simplify re-painting and covering screws. Black color.	79
AXIS M30 CASING A BLACK 5P	1		Discontinued - contact Order dept for availability	5507-431	5507-431	Black accessory casing for AXIS M3044-V/45-V/46-V. Replaces the white original casing. 5 pcs.	79
AXIS M30 VANDAL CASING A 5P	1		Discontinued - contact Order dept for availability	5901-131	5901-131	Vandal-resistant (IK 08-rated) white casing with clear dome for M3047/48-P. 5 pcs.	99
AXIS M30 SM DETECT CASING A 5P	1		Discontinued - contact Order dept for availability	5901-151	5901-151	Highly discreet white casing with smoke-detector look for AXIS M3047/48-P. 5 pcs.	79



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M30 CASING B BLACK 5P	1		Discontinued - contact Order dept for availability	5901-121	5901-121	Black accessory casing for AXIS M3047/48-P. Replaces the white original casing. 5 pcs.	79
AXIS M30 COVER RING A BLACK 4P	1	1		01492-001	01492-001	4-pack of black accessory cover ring for AXIS M3015-V/16-V. Magnetic attachment. Replaces the original white cover ring. Dome not included.	59
AXIS M42 CASING A BLACK 4P	1	2		01245-001	01245-001	Black accessory casings for AXIS M42 series. Replaces the original white casings. 4-piece bulk pack.	59
AXIS M42 SMOKED DOME A 4P	1	2		01608-001	01608-001	Smoked dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	79
AXIS M55 SMOKED DOME A	1	4		01607-001	01607-001	Smoked dome in polycarbonate. IK09 vandal resistant. Compatible with AXISM5525-E. Single pack.	39
AXIS P32 SKIN COVER C BLACK 5P	1			5506-031	5506-031	5-pack. Skin covers compatible with AXIS P32-V cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color.	66
AXIS TP3804-E Metal Casing White 4P	1	20	To be launched	02236-001	02236-001	A white metal casing for indoor/outdoor use that is compatible with: M3205-LVE, M3206-LVE, P3245-LVE, P3245-VE, P3247-LVE, AXIS P3248-LVE. It is IK 10/IP66, has a 3/4 conduit entry and is easy to install. This casing targeted for corrections and other segments that require a tough metal casing.	199
AXIS P56 SKIN COVER D	1	1		5506-161	5506-161	Spare part skin covers for the AXIS P56 Series. Both the camera cover and the ring around the dome are included. 5 pcs.	108
AXIS P39-R SKIN COVER WHITE 10P	1	1		5505-991	5505-991	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. White color. 10 pcs.	125
AXIS P39-R SKIN COVER BLACK 10P	1	1		5506-001	5506-001	Skin covers compatible with AXIS P39-R cameras for changing the appearance of the camera, simplify re-painting or covering screws. Black color. 10 pcs.	125
AXIS F8214 DOME ACC 4PCS	1	8		5506-501	5506-501	AXIS F8214 Dome Accessory (4 pieces). Dome accessory for use with AXIS F1004 Sensor Unit. Can be mounted on walls and ceilings. Can be used with or without bubble.	50
AXIS SMOKED DOME M3004/05 5PCS	1		Discontinued - contact Order dept for availability	5504-031	5504-031	Smoked domes for AXIS M3004-V and and M3005-V. 5pcs.	192
AXIS M3006 SMOKED DOME 5PCS	1	1		5504-011	5504-011	Original white top cover with smoked dome for AXIS M3006, 5pcs.	209
AXIS M3025/26 SMOKED DOME 5PCS	1	1		5505-861	5505-861	Smoked domes for AXIS M3025-VE, M3026-VE. 5 pcs.	209
AXIS M3044-V/45-V/46-V SM DOME 5P	1	2		5507-421	5507-421	Smoked dome for AXIS M3044-V/45-V/46-V SM DOME. 5 pcs.	99
AXIS M3104/5/6-L BLACK CASING 5P	1	3		5801-401	5801-401	Black accessory casing for AXIS M3104-L/05-L/06-L. Replaces the white original casing. 5 pcs.	79
AXIS M3104/5/6-LVE BLACK CASING 5P	1	6		5801-411	5801-411	Black accessory casing for AXIS M3104-LV/5-LV/6-LV. Replaces the white original casing. 5 pcs.	89
AXIS P32 CASING A BLACK 5PCS	1			5901-461	5901-461	Black accessory casing for AXIS P32-VE and P32-LVE outdoor cameras. Replaces the white original casing. Includes anti-loss screws, conduit side covers. 5 pcs per pack.	129
AXIS P32-V SMOKED DOME A 5P	1			5506-021	5506-021	Smoked domes for AXIS P32-V Series, 5 pcs	142
AXIS P32-VE SMOKED DOME A 5P	1			5506-461	5506-461	Smoked dome for AXIS P32-VE Series, 5 pcs	169
AXIS P3346 DOME KIT CL BLACK	1			5503-151	5503-151	Black cover with clear dome for AXIS P3346.	24
AXIS P33 CASING A BLACK	1	3		01546-001	01546-001	Black accessory casing for AXIS P33-V/LV indoor cameras. Replaces the white original casing. Includes anti-loss screws, conduit side covers. Domes sold separately.	49
AXIS P33 SMOKED DOME A 4PCS	1	3		01547-001	01547-001	Smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X cameras. 4x domes per pack.	119
AXIS P37 SMOKED DOME KIT A	1	2		01715-001	01715-001	Smoked dome kit for AXIS P3717-PLE and AXIS P3719-PLE. The dome is pre-mounted in the standard white top cover casing.	99
AXIS P54 SMOKED DOME	1	1		5800-761	5800-761	Smoked dome for AXIS P54-series.	41
AXIS P5624-E/35-E SMOKED DOME	1	3		5506-151	5506-151	Smoked dome for AXIS P56 Series cameras.	41



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
TOP COVER AXIS M311X-R BL 10PCS	1		Discontinued contact Order dept for availability	5700-661	5700-661	Black top cover including dome and screws for AXIS M311X-R. 10 pcs. Approved for use in buses and trams. Not for trains.	209
AXIS P3364-LV DOME KIT BLACK	1		Discontinued contact Order dept for availability	5504-401	5504-401	Dome kit for AXIS P3364-LV. The dome is pre-mounted in a black top cover casing.	41
AXIS Q35-LV SKIN COVER A BLACK 5P	1	1		01157-001	01157-001	Skin covers in black, compatible with AXIS Q35-LV indoor cameras. Simple to repaint in other colours, and prevents unwanted access to the cameras' screws. Black in color. 5 pieces per pack.	79
AXIS Q35-LVE SKIN COVER A BLACK 2P	1	2		01529-001	01529-001	2-pack of skin covers in black, compatible with AXIS Q35-VE/LVE outdoor cameras. Simple to repaint in other colors, and prevents unwanted access to the cameras' screws. Black in color. 2 pieces per pack.	79
AXIS Q35 SMOKED DOME A 5PCS	1	1		01183-001	01183-001	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV/LVE. 5x domes per pack.	199
AXIS Q3517-SLVE NYLON DOME 2P	1	1		01585-001	01585-001	Accessory clear dome in a special nylon blend with anti-scratch hard coating. IK10+ vandal-resistant with superior chemical resistance. Compatible with AXIS Q3517-SLVE but not recommended to use with IR illumination. 2x domes per pack.	159
AXIS Q36-VE SMOKED DOME	1	1		5801-501	5801-501	Smoked dome with anti-scratch hard coating. Compatible with AXIS P38 and AXIS Q36 series.	49
AXIS Q37 SMOKED DOME A	1	1		5901-431	5901-431	Smoked dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	59
AXIS Q60-S SMOKED DOME A	1	1		5504-791	5504-791	Smoked dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	66
AXIS Q6114-E/15-E CLEAR DOME	1	2		5507-281	5507-281	Standard clear dome for AXIS Q6114-E/Q6115-E.	59
AXIS Q6114-E/15-E CLEAR DOME 5P	1	1		5506-521	5506-521	Standard clear dome for AXIS Q61 Series, 5 pcs	269
AXIS Q6128 HARD-COATED CLEAR DOME	1	2		5801-791	5801-791	Hard coated scratch resistant clear dome for AXIS Q6128-E	89
AXIS Q8414-LVS IR WINDOW B 5P	1			5506-371	5506-371	Accessory IR window without microphone hole. 5 pcs.	100
AXIS Q8414-LVS SMOKED DOME 5P	1			5506-301	5506-301	Smoked dome for hiding the direction of the camera. Compatible with AXIS Q8414-LVS. 5 pcs.	83
ACC DOME AXIS 212PTZ-V GLASS CLEAR	1			5502-091	5502-091	Vandal-resistant casing with clear transparent cover as a spare part for AXIS 212PTZ-V.	58
ACC DOME AXIS 216FD-V GLASS CLEAR	1	1		5005-051	5005-051	Vandal-resistant casing with clear transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V.	58
AXIS TM3801 BLACK CASING 4P	1	90		01854-001	01854-001	4 Pack black casing to change the appearance of the product.	59
AXIS TM3801 WHITE CASING 4P	1	1		02024-001	02024-001	4 pack white casing changing the appearance of the camera.	59
AXIS TM3803 BLACK CASING 4P	1	8		01744-001	01744-001	Cover top black casing for M3067/68 4P.	59
AXIS TM3804 SM DETECT CASING C 4P	1	4		01745-001	01745-001	SMOKE DETECTOR CASING - COVER TOP ASS SMOKE M3067/68	59
AXIS TM3805 VANDAL CASING C 4P	1	15		01746-001	01746-001	Vandal Casing COVER TOP ASS DOME M304X-PV.	79
AXIS TM3807 BLACK CASING 4P	1	8		01918-001	01918-001	4P Black casing for M3115/6 LVE. Black accessory casing that replaces the white original casing for changing the appearance of the camera.	79
AXIS TP3801 BLACK CASING 4P	1	10		01623-001	01623-001	Accessory black casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	79
AXIS TP3801-E BLACK CASING 4P	1	10		01626-001	01626-001	Accessory black casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	99
AXIS TP3802 SMOKED DOME 4P	1	20		01624-001	01624-001	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	99
AXIS TP3802-E SMOKED DOME 4P	1	6		01627-001	01627-001	Smoked dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	119
AXIS TP3806 DOME COVER BLACK 4P	1	1	Price correction	02005-001	02005-001	4 pack black dome cover for AXIS P3925-R. Replaces the standard white dome cover.	199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS TP3808 DOME COVER BLACK 4P	1	1	Price correction	02004-001	02004-001	4 pack black dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	199
AXIS TQ3801 HYDROPHILIC CLEAR DOME	1	5		01820-001	01820-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with AXIS P3807-PLE, AXIS Q3615-VE and AXIS Q3617-VE. Single pack	99
AXIS TQ6801 HYDROPHILIC CLEAR DOME	1	10		01816-001	01816-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series, e.g.: AXIS Q6124-E, AXIS Q6128-E, AXIS Q6155-E. Single pack.	149
AXIS TQ6802 HYDROPHILIC CLEAR DOME	1	3		01817-001	01817-001	Accessory clear dome with special hydrophilic coating. Helps to prevent water droplets from covering the dome in rainy conditions. The coating also provides a self-cleaning effect that helps carry away dirt and dust by rain-wash. Compatible with selected cameras from AXIS Q61 series that support IR illumination, e.g.: AXIS Q6125-L.E. Single pack.	149
AXIS TQ6807 SMOKED DOME COVER	1	6		01947-001	01947-001	Smoked dome cover including dome cover ring. Compatible with legacy AXIS Q60-E-C cameras. See axis.com for updated compatibility list.	149
ACC DOME AXIS 23XD+ SMOKED COVER	1	1		5500-201	5500-201	Smoked plastic dome for AXIS 231/232D+ dome cameras	24
ACC DOME UPGR KIT AXIS 233D CL/SM	1	1		5500-601	5500-601	Clear and Smoked plastic dome for AXIS 233D dome cameras	58
GP2 CCTV PANEL 1 PS 24V ATEX	1	1	Built to order	5507-241	5507-241	Stainless steel 316 ATEX approved power supply with Corrosion resistant epoxy paint finish. Shipped pre-mounted with (1) Transformer 115/230 VAC primary, 24VAC Secondary providing 24VAC for XF40/XP40 and washer, (2) Fuses, (3) RJ45 Coupler CAT6 The cabinet has 3 open M20 cable entries and a fourth plugged entry and is EX II 2GD, EX d IIB Gb, EX tb IIIC Db IP66 certified for temperatures between -40°C and +55°C. Weight is 85kg.	8.499
GP2 CCTV PANEL 1 PS 24V EAC	1	1	Built to order	01246-001		Stainless steel 316 EAC approved power supply with Corrosion resistant epoxy paint finish. Shipped pre-mounted with (1) Transformer 115/230 VAC primary, 24VAC Secondary providing 24VAC for XF40/XP40 and washer, (2) Fuses, (3) RJ45 Coupler CAT6 The cabinet has 3 open M20 cable entries and a fourth plugged entry and is EX d IIB T4, certified for temperatures between -40°C and +55°C. Weight is 85kg.	8.499
XWP10A-24 WASHER TANK ATEX IECEx	1	1	Built to order	5507-231	5507-231	The XWP10A-24 washer tank is designed specifically for use with explosion protected network cameras. Manually pressurized to 4 bar for a maximum head height of 20 meters. It features an ATEX/IECEx-approved solenoid release valve that can be controlled and powered through the camera and is IP65-rated. The washer tank housing is constructed from 316L stainless steel for maximum corrosion protection, optimized for use with cameras located in onshore, offshore, marine and heavy industrial environments. Free standing or wall mounted. Operating temperature of -30C to +60C and it weighs 25 kg when its full.	2.199

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XWP10R-24 WASHER TANK EAC	1		Built to order	01459-001		The XWP10R-24 washer tank is designed specifically for use with explosion protected network cameras. Manually pressurized to 4 bar for a maximum head height of 20 meters. It features an EAC-approved solenoid release valve that can be controlled and powered through the camera and is IP65-rated. The washer tank housing is constructed from 316L stainless steel for maximum corrosion protection, optimized for use with cameras located in onshore, offshore, marine and heavy industrial environments. Free standing or wall mounted. Operating temperature of -30C to +60C and it weighs 25 kg when its full.	2.599
X-TAIL CABLE 3M ATEX IECEX EAC	1	1	Built to order	5507-141	5507-141	3 meter explosion protected cable , ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	699
X-TAIL CABLE 5M ATEX IECEX EAC	1	1	Built to order	5507-151	5507-151	5 meter explosion protected cable , ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	849
X-TAIL CABLE 7M ATEX IECEX EAC	1	1	Built to order	5507-161	5507-161	7 meter explosion protected cable , ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	999
X-TAIL CABLE 10M ATEX IECEX EAC	1	1	Built to order	5507-171	5507-171	10 meter explosion protected cable, ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	1.199
X-TAIL CABLE 15M ATEX IECEX EAC	1	1	Built to order	5507-181	5507-181	15 meter explosion protected cable, ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	1.499
X-TAIL CABLE 20M ATEX IECEX EAC	1	1	Built to order	01197-001	01197-001	20 meter explosion protected cable, ATEX/IECEX/EAC-approved, for the installation of explosion protected fixed and PTZ network cameras. Multi-connector cable for power (24VAC), network and I/O port.	1.699
EX POLE BRACKET XF40	1	1	Built to order	5507-191	5507-191	The Electro-polished 316L stainless steel pole bracket is specifically designed for top mounting installations of XF40 and suitable for onshore, offshore, marine and heavy industrial applications. It features a swivel movement of pan $\pm 90^\circ$ and tilt $\pm 45^\circ$ and its weight is 1.1kg.	449
EX WALL MOUNT XF40	1	1	Built to order	5507-201	5507-201	Electro-polished 316L stainless steel wall mount for XF40, designed for onshore, offshore, marine and heavy industrial applications. Can also be used in conjunction with Bracket Pole Clamp Adaptor XF40 EX for pole mounting. It features a swivel movement of pan $\pm 90^\circ$ and tilt $\pm 45^\circ$ and its weight is 2.5 kg.	899
EX WALL MOUNT XP40	1	1	Built to order	5507-211	5507-211	Electro-polished 316L stainless steel wall mount for XP40, designed for onshore, offshore, marine and heavy industrial applications. Weight 14 kg.	799
EX POLE MOUNT XF40	1	1	Built to order	5507-221	5507-221	Pole mounting explosion protected fixed network cameras is made simple using this electro-polished 316L stainless steel Ex Pole mount XF40, accompanied by the requisite Ex Wall Mount XF40. The Ex Pole Mount XF40 is specifically designed to mount Ex Wall Mount XF40 to poles of a diameter from 90mm to 120mm. Weight 4.2 kg.	599
WALL MOUNT D201-S XPT	1	1		01521-001	01521-001	316L Stainless steel wall mount for use with D201-S AXIS Q6055 explosion-protected camera.	449
POLE MOUNT D201-S XPT	1	1		01522-001	01522-001	316L Stainless steel pole mount adapter for the D201-S AXIS Q6055 explosion-protected camera. To be used together with Wall Mount D201-S.	749
CORNER MOUNT D201-S XPT	1	1		01571-001	01571-001	316L Stainless steel corner mount adapter for the D201-S AXIS Q6055 explosion-protected camera. To be used together with Wall Mount D201-S.	999

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
SKDP03-T CABLE EXCAM 10M	1	1	Built to order	01540-001	01540-001	10m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68, M20x1.5.	749
SKDP03-T CABLE EXCAM 25M	1	1	Built to order	01541-001	01541-001	25m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68, M20x1.5.	1.199
SKDP03-T CABLE EXCAM 95M	1	1	Built to order	01542-001	01542-001	95m unarmored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 12.3mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland with compound Ex d IIC / Ex e II / Ex tD A21 IP66/67/68, M20x1.5.	3.199
EXCONNECTION RAIL 4 POE PS24	1	1	Built to order	01535-001	01535-001	Explosion-protected PoE switch and power supply for use with up to 4 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.4-D-4PoE+-100BaseFX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 4x 24VDC@30W, network uplink 1x 100BaseFX, 1x 100BaseTX, network output 4x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included. Multi mode fiber version.	7.999
EXCONNECTION RAIL 8 POE PS24	1	1	Built to order	01536-001	01536-001	Explosion-protected PoE switch and power supply for use with up to 8 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.5-D-8PoE+-1000Base-SX (multimode 850nm, LC). Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 8x 24VDC@30W, network uplink 2x 1000BaseFX, 1x 1000Base-SX, network output 8x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included.	9.999
ASKDP03-T ARM'D CABLE EXCAM 10M	1	1	Built to order	01543-001	01543-001	10m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIC Da IP66 M20x1.5.	1.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
ASKDP03-T ARM'D CABLE EXCAM 25M	1	1	Built to order	01544-001	01544-001	25m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIC Da IP66 M20x1.5.	1.899
ASKDP03-T ARM'D CABLE EXCAM 95M	1	1	Built to order	01545-001	01545-001	95m armored network and power cable for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Diameter 17.0mm, 8x AWG22 shielded, 3x 1.5mm ² , -60°C to +80°C, Ex d IIC / Ex e II / Ex tD A21 IP66, IP67, IP68, M20x1.5. Included accessories: 5ml Loctite 243 thread locker, 1x CAT6 RJ45 industrial plug (5.5mm – 10.0mm), 1x cable gland Ex d with compound Ex db eb IIC / Ex tb IIC / Ex e II / Ex tD IP66/67/68, 1x cable gland Ex e II 2 G Ex e IIC Gb / II 1 D Ex ta IIC Da IP66 M20x1.5.	4.999
WALL MOUNT EXCAM XPT	1	3	Built to order	01538-001	01538-001	Wall mount for EXCAM XPT Q6055 in stainless steel with protective hood for cable glands.	1.099
POLE MOUNT EXCAM XPT	1	1	Built to order	01539-001	01539-001	Pole mount for EXCAM XPT Q6055 in stainless steel for pole diameters 110-150mm, requires Wall Mount ExCam XPT.	1.099
EXTB-3 JUNCTION BOX EXCAM	1	1	Built to order	01537-001	01537-001	Terminal box for explosion-protected cameras in the ExCam range, certified for use in hazardous areas according to ATEX, IECEx and EAC. Ex II 2 G Ex eb IIC T5 Gb, Ex II 2 D Ex tb IIC T95°C Db, glass fiber reinforced polyester resin, 10x terminal PT 2.5, 3x terminal PT 2.5 PE. 1x M20 gland for armored cables, 2x M20 gland for unarmored cables.	699
WALL MOUNT EXCAM XF	1	1	Built to order	01569-001	01569-001	Stainless steel (1.4404 / 316L) wall bracket for fixed explosion-protected cameras in the ExCam range, includes hinge and mounting material.	1.099
POLE MOUNT EXCAM XF	1	1	Built to order	01570-001	01570-001	Stainless steel (1.4404 / 316L) pole mount, to be used with Wall Mount Excam XF. Mounting material included.	1.099
WEATHERSHIELD EXCAM XF	1			01849-001	01849-001	Weather protection shield for ExCam XF P1367 in stainless steel. 0.9kg, installation material included. Built to order.	599
WALL MOUNT F101 XF	1	3		01721-001	01721-001	Stainless steel (316L) wall mount for F101-A XF explosion-protected cameras. Compatible with Pole Mount D201-S XPT and Corder Mount D201-S XPT.	749
EX E CABLE GLAND M20 NON-ARMORED	1	1		01843-001	01843-001	Ex e cable gland in black polyamide, for non-armored cables, diameter 7-13mm, suitable for SKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex eb IIC Gb, II 2 D Ex tb IIC Db. Operating temp -60°C to +75°C. Built to order.	149
EX E CABLE GLAND M20 ARMORED	1			01844-001	01844-001	Ex e cable gland in nickel-plated brass, for armored cables, diameter 12.5-20.9mm, suitable for ASKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex eb IIC Gb, II 2 D Ex tb IIC Db. Operating temp -60°C to +130°C. Built to order.	299
EX D CABLE GLAND M20 NON-ARMORED	1	1		01845-001	01845-001	Ex d cable gland in nickel-plated brass, for non-armored cables diameter 6.5-14mm, suitable for SKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex db IIC Gb, II 1 D Ex ta IIC Da. Operating temperature -60°C to +85°C. Built to order.	299
EX D CABLE GLAND M20 ARMORED	1	2		01846-001	01846-001	Ex d cable gland in nickel-plated brass, for armored cables diameter 13.5-21mm, suitable for ASKDP03-T CABLE EXCAM. ATEX/IECEx certified II 2 G Ex db IIC, II 2 D Ex tb IIC. Operating temperature -60°C to +140°C. Built to order.	249
EXCAM XF WIPER BLADE 10 PACK	1			01930-001	01930-001	Replacement wiper blade for ExCam XF Q1785. Natural black rubber, 54mm, 10-pack.	189
WALL MOUNT D101-A XF	1	1		01969-001	01969-001	316L Stainless steel wall mount for horizontal mounting of D101-A XF P3807. Can also be used as ceiling mount for D101-A XF P3807 and D201-S XPT Q6055.	749



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
WALL MOUNT EXCAM XF M30	1	15		02028-001	02028-001	Wall bracket for ExCam XF M3016 in stainless steel, 0.5kg, pan angle 360°, tilt angle 90°. Including hinge and mounting material. Built to order.	499
WEATHERSHIELD EXCAM XF M30	1			02033-001	02033-001	Weather protection shield for ExCam XF M3016 in stainless steel. 0.15kg, installation material included. Built to order.	499
FRONT GLASS PROTECTIVE FILM F101-A	1	1		02029-001	02029-001	Plastic protective film for the front glass of the F101-A explosion-protected cameras. For use in highly corrosive atmospheres like hydrogen fluoride (HF) gas. Set of 5.	149
EX CONNECTION RAIL 4-PORT POE SM	1		Built to order	02106-001	02106-001	Explosion-protected PoE switch and power supply for use with up to 4 ExCam cameras, certified for use in hazardous areas according to ATEX and IECEx, in an Ex d copper free and sea water resistant aluminum enclosure. Model name: T04.4-D-4PoE+-100BaseFX. Ex II 2G Ex d IIC [op pr] T5 Gb, Ex II 2D Ex t IIC T95°C Db IP66, operating temperature -60°C to +50°C. Input voltage 100 VAC – 240VAC, output power 4x 24VDC@30W, network uplink 1x 100BaseFX, 1x 100BaseTX, network output 4x PoE+ (10/100BaseT(X), IEEE802.3at, max 30W/port). 2x cable glands M25x1.5 included. Single mode fiber version.	7.999
AXIS 1.5" NPS/NPT MALE COUPLER	1	15		01706-001	01706-001	1.5" NPT Male-to-Male coupler used to connect any AXIS Pendant Kit (e.g.: AXIS T94A01D) to a legacy mount with Female NPT or NPS thread (e.g.: 3rd party wall mount). Useful in retrofitting legacy cameras in existing installations. Lock nut included. Material: Aluminum with black anodizing. Note: The National Pipe Taper (NPT) is a U.S. standard for tapered threads used on threaded pipes and fittings. The National Pipe Straight (NPS) threads are straight (parallel). Both NPT and NPS have the same thread angle, shape, and pitch (threads per inch).	35
M10 STAND EXTENSION 10CM 10PCS	1	1		5502-701	5502-701	AXIS M10-series 10 cm stand extension. 10 pcs. Cable clip included.	24
ACC RACK HOLDER 2400/2401 EUR	1			19273	19273	19" Rack mount holder for up to 8 2401/2400 Video Servers.	377
AXIS T8640 WALL MOUNT BRACKET	1	6		5026-411	5026-411	Wall mount bracket for AXIS T8640 Ethernet over Coax adapter base or device unit.	21
AXIS T8640 DIN RAIL CLIP	1	10		5026-431	5026-431	DIN rail clip for AXIS 8640 Ethernet over Coax adapter.	18
AXIS T8642 MOUNTING KIT A	1	2		5506-291	5506-291	Kit for mounting an AXIS T8642 e.g. inside an AXIS Q8414-LVS. Kit contents: cable tie 432mm (17 in) long, BNC male to female angled adapter and network cable 135 mm (5.3 in) long.	12
AXIS T8640 RACK MOUNT BRACKET	1	4		5026-421	5026-421	Rack mount bracket for AXIS T8640 Ethernet over Coax adapter (8 units in 1U).	52
AXIS T91A02 DIN RAIL CLIP 77MM	1	2		5017-027	5017-027	DIN rail clip for AXIS Q7401, AXIS P8221 and AXIS 7701.	10
AXIS T91A02 DIN RAIL CLIP 86MM	1	1		5017-028	5017-028	DIN rail clip for AXIS M7014 and AXIS P7214	10
AXIS T91A03 DIN RAIL MOUNT	1	20		5503-194	5503-194	DIN rail clip for AXIS Q7424-R.	16
AXIS T91A04 CAMERA HOLDER 3/4" NPS	1	20		5017-041	5017-041	Holding device for pendant mounted cameras. For use with 3/4" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	24
AXIS T91A05 CAMERA HOLDER 1.5" NPS	1	15		5017-051	5017-051	Holding device for pendant mounted cameras. For use with 1,5" pipes with NPS or NPT threading. Compatible with all cameras with standard tripod threading.	24
AXIS T91A06 PIPE ADAPTER 3/4-1.5"	1	20		5503-091	5503-091	Pipe adapter step up from 3/4" NPT thread to 1.5" NPS thread. Compatible with all pendant kits that are made for the AXIS T91A range of brackets.	10
AXIS T91A10 MOUNTING KIT	1	60		5507-331	5507-331	Plastic mounting kit with stand and clamp for flexible mounting of Axis products with tripod thread.	19
AXIS T91A11 STAND WHITE	1	70		5017-111	5017-111	Plastic camera stand. Original stand for the AXIS M11-series.	13



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T91A13 THREADED CEIL MOUNT 10P	1	1		01464-001	01464-001	10-pack threaded ceiling mount for quick installation under ceiling tiles. Compatible with cameras with standard 1/4"-20 UNC tripod thread. Total length 80mm (3") with thread length 65mm (2.5"). Threaded rod in nylon, counter nut with friction pad. 10-piece bulk pack.	39
AXIS T91A23 TILE GRID CEIL MNT 4P	1	15		01612-001	01612-001	4-pack of ceiling mount accessory for mounting Axis cameras and stands on a variety of drop-ceiling tile grid system. Compatible with Axis Safety Wire. Color: Axis white. Bulk pack. Suitable tile grid (T-bar) dimensions: 15mm(0.6in)/24mm(0.9in)/35mm(1.4in). Suitable ceiling tiles type: square-edge, tegular edge.	79
AXIS T91A33 LIGHT TRACK MNT 4P	1	1		01467-001	01467-001	4-pack of lighting track mounts. Color: white. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	79
AXIS T91A33 LIGHT TRACK MNT BLK 4P	1	1		01474-001	01474-001	4-pack of lighting track mounts. Color: black. Compatible with universal 3-circuit lighting track systems and selected linear trunking systems. Compatible with a wide range of Axis cameras and camera stands.	79
AXIS T85 RACK MOUNT KIT A	1	10		01232-001	01232-001	Rack mount kit for AXIS T8508 PoE+ Network Switch	29
AXIS T91B21 STAND BLACK	1	4		5506-621	5506-621	Black aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	29
AXIS T91B21 STAND WHITE	1	20		5506-611	5506-611	White aluminum stand for wall or hard ceiling mount. A cable hole in the base of the stand makes it possible to hide the hole in the wall out of which the cable is routed. A snap on cover gives a clean look without visible screws. Compatible with all standard tripod thread cameras e.g. AXIS M11, P13, Q16 series.	24
AXIS T91A27 POLE MOUNT 10PCS	1	2		5503-971	5503-971	Pole mount bracket compatible with all cameras with standard tripod threading (1/4"-20 UNC)	24
AXIS T91B47 100-410MM	1	175		01164-001	01164-001	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	85
AXIS T91B47 50-150MM	1	125		01165-001	01165-001	AXIS T91B47 Pole Mount for indoor and outdoor installations, for poles with diameter between 50-150mm (2"-6"). Includes 1 pair of AXIS Stainless Steel Straps 570mm (22.5") with TX30 screw interface for ease-of-installation. AXIS T91B47 is directly compatible with a wide range of Axis cameras.	75
AXIS T91B57 POLE MOUNT 100-410MM	1	250		01470-001	01470-001	Aluminum Pole Mount for indoor and outdoor installations, for poles with diameter between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series. Color: Axis white.	115
AXIS T91B57 POLE MOUNT GREY	1	15		01446-001	01446-001	Aluminum Pole Mount in Urban Grey color. For indoor and outdoor installations. Suitable for poles diameters between 100-410 mm (4"-16"). Includes 1 pair of AXIS Stainless Steel Straps 1450mm (57") with TX30 screw interface for ease-of-installation. AXIS T91B57 is compatible with mounts such as AXIS T91G61, T91H61, and AXIS T98A Surveillance Cabinet series.	139



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T91B67 POLE MOUNT 65-165MM	1	40		01473-001	01473-001	Outdoor-ready, powder-coated aluminum pole mount with 1.5" NPS thread for fixed dome pendant kits. Includes insect-proof cable gasket and 1 pair of stainless steel straps (with TX30 screw) for pole diameter between 65-165mm (2.5"-6.5"). White in color.	95
AXIS T91M47 POLE MOUNT	1	10		01149-001	01149-001	Pole mount for our outdoor midspans and switch.	59
AXIS TD9301 OUTDOOR MIDSPAN POLE MOUNT	1	3		01951-001	01951-001	AXIS TD9301 Outdoor Midspan Pole Mount for outdoor midspans, like AXIS 30W Outdoor Midspan.	59
AXIS T91D61 WALL MOUNT	1	175		5504-821	5504-821	Chromated and powder coated aluminum wall mount with 1.5" NPS thread for fixed dome pendant kits. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal and conduit hole cover. Color: White	71
AXIS T91E61 WALL MOUNT	1	200		5506-481	5506-481	Wall mount with internal cable canal for dome cameras with 1.5" NPS thread, compatible with Axis pendant kits. IK10 and NEMA 4X rated. Powder coated aluminum for indoor and outdoor installations.	33
AXIS T91G61 WALL MOUNT	1	400		5506-951	5506-951	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Axis white color. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras, incl. AXIS M55, P56, Q37, Q60, Q61 Series.	199
AXIS T91G61 WALL MOUNT GREY	1	20		01444-001	01444-001	Aluminum wall mount with IP66 compartment to safely accommodate power and connectivity accessories (e.g. PoE midspan). IK10 and NEMA 4X rated in Urban Grey color to match AXIS Q62 series. Includes a pre-terminated IP66 rated RJ45 connector. Compatible with wide range of Axis cameras.	229
AXIS TS2901 APPLIANCE STAND	1	2		02035-001	02035-001	AXIS TS2901 Appliance Stand is a stand compatible with AXIS S2208 and AXIS S2212 Appliances which allows the unit to be mounted vertically, on a table or shelf. The appliance is secured to the stand with the 4 included screws. Mounted vertically, the appliance will take even less space than it usually does, leaving more space for other activities. The stand itself can be screwed to the table/shelf, which is a simple way to secure the appliance against light thefts and from falling. It can also lie on the table, when using the included rubber feet.	39
AXIS T91H61 WALL MOUNT	1	20		5507-641	5507-641	AXIS T91H61 Wall Mount is designed with a built-in RJ45 cable and connection, and spacious compartment for connectivity accessories such as midspans and media converters. The wall mount is impact-resistant (IK10) and weather-resistant (IP66, NEMA 4X) for indoor and outdoor use. The 1.5" NPS thread mount ensures compatibility with all pendant kits for Axis fixed dome cameras.	175
AXIS T91F61 WALL MOUNT STAINLESS STEEL	1	4		5506-681	5506-681	Wall mount for AXIS Q3505-SVE, made of stainless steel.	399
AXIS T91L61 WALL-AND-POLE MOUNT	1	300		5801-721	5801-721	Wall-and-Pole Mount for Axis PTZ and multi-sensor cameras. Built-in Ethernet cable with an IP66 RJ45 connector for quick installation with protection against dust and water. Connect PoE via either RJ45 or IDC (Insulation-displacement contact) connectors. Suitable for both indoor and outdoor environments. Separate stainless steel straps required for pole installation.	99
AXIS T91K61 WALL MOUNT	1	5		5901-401	5901-401	Marine-grade stainless steel wall mount for AXIS Q6055-S PTZ Network Camera. Compatible with stainless steel pole mount (sold separately).	399

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94J01A WALL MOUNT	1	20		5901-331	5901-331	Aluminum wall mount for Axis positioning cameras and positioning units. Robust and impact-resistant. Compatible with Axis AC1 3/4" conduit adapters, and offers multiple cable entries. Cables can be routed through the back or, by using a conduit connection, from each side or from the bottom. Suitable for indoor and outdoor use.	199
AXIS T94J01A WALL MOUNT GREY	1	20		01445-001	01445-001	Robust and impact-resistant aluminum wall mount for selected Axis PTZ and positioning cameras. Multiple cable entry points for 3/4" (M25) conduit pipes. Suitable for indoor and outdoor use. Color: Urban Grey.	229
AXIS T91D62 TELESCOPIC PARAPET MNT	1	50		5507-271	5507-271	Made for parapet and wall installations. Telescopic arm with adjustable length between 783 mm (30.1 in) to 1033 mm (40.7 in) for compensating different parapet thicknesses or obstructive elements on the facade of the building. It can Swivel round its own axis 180 degrees, allowing mounting/maintain the camera easily and safely from the rooftop. The mount is intended for outdoor fixed and PTZ dome cameras supporting 1.5" NPS thread. A retrofit mounting bracket (optional accessory) makes it possible to reuse holes drilled for Pelco's PTZ dome parapet mount.	349
AXIS T91D62 ADAPTER MOUNTING BRACKET	1	2		5507-501	5507-501	Retrofit adapter mount bracket for re-using holes drilled from Pelco's PTZ dome parapet mount, or for increasing the attachment area towards the parapet.	59
AXIS T91B62 PARAPET MOUNT	1	30		5504-631	5504-631	Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	159
AXIS T91B50 TELESCOPIC CEIL MNT	1	30		5507-451	5507-451	Indoor/outdoor telescopic ceiling mount. Expands between 1 m (39") and 2 m (79"). Features a swivel action to prevent breaking if hit by forklifts or high vehicles. Can be mounted on a sloped ceiling. Accessory extension pipes (Not included) for a maximum length of 5 m (197"). Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	199
AXIS T91B51 CEILING MOUNT	1	250		5507-461	5507-461	The indoor/outdoor ceiling mount is ideal for low ceiling installations such as parking houses, with swivel action to prevent breaking if hit. Can be mounted in a sloped ceilings/soffits to compensate angles up to 45 degrees. Available accessory extension pipes (Not included) of 30 cm (12") or 1 meter (39") to enable correct camera height for the specific environment. Compatible with all Axis pendant kits featuring a 1,5" NPS thread and the AXIS T91A05 Camera holder for fixed cameras.	119
AXIS T91B52 EXTENSION PIPE 30 CM	1	150		5507-491	5507-491	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 30 cm (12").	34
AXIS T91B52 EXTENSION PIPE 100 CM	1	100		5507-481	5507-481	Extension pipe for AXIS T91B50 and AXIS T91B51. Length 100 cm (39").	49
AXIS T91B53 TELESCOPIC CEIL MNT 2P	1	60		01189-001	01189-001	Twin-pack (bulk). Includes 2x indoor telescopic ceiling mounts, extendable between 1m to 1.8m (3.2 to 6ft) at 10cm (4") intervals. Compatible with Axis pendant kits and camera holder with 3/4" conduit interface. Suitable for vertical and horizontal mounting.	169
AXIS T91B63 CEILING MOUNT	1	150		5504-641	5504-641	Chromated and powder coated aluminum ceiling mount 75 cm / 29.5 inch compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Cable routing from behind or through 3/4" conduit hole on the side. Includes mounting plate, pipe seal, conduit hole cover and AXIS T94A01D Pendant Kit for PTZ dome cameras. Color: White	100



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T91A64 BRACKET CORNER	1	30		5017-641	5017-641	Corner Bracket. Requires AXIS T91A61 Wall Bracket. AXIS P55-series, AXIS Q60-series PTZ Dome Network Cameras, AXIS P33 Series Pendant kit, AXIS P33-VE Series Pendant kit, AXIS 225 Pendant kit and AXIS 216/P3301 Pendant kit. White.	66
AXIS T91F67 POLE MOUNT STAINLESS STEEL	1	4		5506-691	5506-691	Pole mount bracket for AXIS Q35-SLVE stainless steel cameras. Compatible with AXIS T91F61 Wall mount. Made of marine-grade stainless steel. Includes 1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Straps length 1450mm (57"), suitable for pole diameter range 100-410mm (4"-16").	139
AXIS T91A6 PIPE SEAL 1PCS	1	2		5503-781	5503-781	Pipe seal for AXIS T91A6, to protect from dust, water and bugs.	9
AXIS T93C WALL-POLE CONDUIT BACKBOX	1	1		5901-421	5901-421	Aluminum conduit back box for wall or pole mount. Space for outdoor power supply, and electrical connection boxes. Steel straps for pole mount are sold separately. Recommended to use with POWER SUPPLY PS24 240W (not included).	199
AXIS T94A01C ATTACHMENT KIT	1	20		5901-301	5901-301	For attaching AXIS Q61 PTZ network camera to AXIS Q6000-E MkII PTZ network camera.	99
AXIS T94A01D PENDANT KIT	1	350		5502-431	5502-431	Pendant kit for the AXIS Q60-series and AXIS P55-series PTZ Network Cameras, enables mount on standard '1,5" NPT threaded brackets. White.	41
AXIS T94A02D PENDANT KIT	1	1		5901-411	5901-411	Marine-grade stainless steel pendant kit for AXIS Q60-S with 1.5" NPT male thread.	129
AXIS T94A01F CEILING BRACKET	1	1		5506-181	5506-181	Bracket for mounting an AXIS P56 Series camera in a hard ceiling. For indoor and outdoor installations. 3/4" conduit hole, compatible with ACI adapters.	24
AXIS T94A02F CEILING BRACKET	1	7		5801-601	5801-601	Aluminum ceiling bracket for Axis PTZ cameras and AXIS Q37 Series for indoor or outdoor use. 3/4" conduit hole on the side.	49
AXIS T94A01L RECESSED MOUNT	1	2		5505-721	5505-721	Outdoor recessed mount for AXIS Q60-E cameras. Can be mounted in panels, wood or pre-made holes solid concrete. The mount is very sturdy and made of aluminum and stainless steel. It supports the IK10 impact rating of the camera and has two 3/4" conduit holes for a plenum rated and rodent safe installation.	209
AXIS T94A02L RECESSED MOUNT	1	15		5506-171	5506-171	Outdoor recessed mount for AXIS P56 cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	117
AXIS T94A03L RECESSED MOUNT	1		Discontinued contact Order dept for availability	5506-841	5506-841	Recessed mount for AXIS P5514-E and P5515-E cameras. Also suitable indoor for recessed camera installations in plenum as the back box is made of metal and has a 3/4" hole for cable protection conduits.	139
AXIS T94A04L RECESSED MOUNT	1	10		5801-611	5801-611	Indoor and outdoor recessed mount for AXIS Q61 Series. Suitable indoor for recessed camera installations in air handling spaces as the back box is made of metal and has a 3/4" hole for cable protection conduits.	139
AXIS T94B02D PENDANT KIT 10PCS	1	4		01159-001	01159-001	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/LVE, M30-V/WV and Companion dome cameras. 10-pack.	199
AXIS T94B02D PENDANT KIT	1	30		5507-361	5507-361	Pendant kit for wall mount or ceiling mount. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/LVE, M30-V/WV and Companion dome cameras. Single pack.	29
AXIS T94B02D PENDANT KIT BLACK	1	1		01185-001	01185-001	Pendant kit for wall mount or ceiling mount in black. Compatible with Axis mounting accessories with 1.5" NPS thread. 3/4" threaded pipes can also be used with a nut for securing. Compatible with the small form factor of AXIS M20, M31-LV/LVE, M30-V/WV and Companion dome cameras. Single pack.	29



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94B05L RECESSED MOUNT	1			01150-001	01150-001	Indoor recessed mount for drop ceiling installation. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M3044-V/M3045-V/M3046-V/M3047-V/M3048-V.	69
AXIS T94B03L RECESSED MOUNT	1	1		5801-861	5801-861	Indoor recessed mount for drop ceiling installations. The aluminum casing makes it suitable for use in air handling spaces. Compatible with AXIS M2025/26 and AXIS Companion Bullet.	69
AXIS T94B02M J-BOX/GANG BOX PLATE	1	3		5801-421	5801-421	Bracket for mounting a camera on a 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M3044-V/M3045-V/M3046-V.	24
AXIS T94B01P CONDUIT BACK BOX	1	90		5507-401	5507-401	Conduit back box for 1/2" or M20 pipes. Features the 1/2" ACI interface to enable use of ACI adapters. There is an integrated female tripod thread for use of standard camera stands or holders. Compatible with AXIS M3044-V/M3045-V/M3046-V.	19
AXIS T94B01S MNT BRACKET BLACK 10PCS	1			5504-531	5504-531	Black mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	41
AXIS T94B01S MNT BRACKET WHITE 10PCS	1			5503-911	5503-911	White mount bracket for mounting on standard tripod threading (1/4"-20 UNC) or single-gang junction box. Compatible with AXIS M3004-V/5-V.	41
AXIS T94C01L RECESSED MOUNT	1	10		01242-001	01242-001	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS M42 series and AXIS Companion Dome mini LE.	39
AXIS T94C01M J-BOX/GANG BOX PLATE	1	1		01243-001	01243-001	Bracket for mounting camera on 4" square, 4" octagon, single or double-gang junction box. Compatible with AXIS M42 Series and AXIS Companion Dome mini LE.	29
AXIS T94C01U UNIVERSAL MOUNT	1	20		01244-001	01244-001	Versatile 4-in-1 mount accessory for use as either a pendant kit with 3/4" (M25) conduit interface, conduit back box with 1/2" (M20) conduit side entry, pole mount, or standard camera thread. Compatible with AXIS M42 series and AXIS Companion Dome mini LE. Pole mounting straps available separately.	29
AXIS T94D01S MT BRACKET FL WT 10PCS	1	1		5504-911	5504-911	White plastic adapter for mounting AXIS P3904-R and AXIS P3905-R on flat surfaces. Does not fit with AXIS P3915-R. Used when the cable must enter from the side. 10 pack.	24
AXIS T94D02S MT BRACKET CU WT 10PCS	1	1		5504-921	5504-921	White plastic adapter for mounting AXIS P3904-R, AXIS P3905-R and AXIS P3915-R on curved surfaces. 10 pack.	24
AXIS T94F01D PENDANT KIT	1	8		5503-881	5503-881	Indoor pendant kit for AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE. to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes. The camera network cable fits into the product and a RJ45 network cable coupler is included.	33
AXIS T94F02D PENDANT KIT	1	2		5900-021	5900-021	Outdoor pendant kit for M3024-LVE/M3025-VE, P14 Series, to enable use of AXIS T91A Brackets or 1.5"(NPT or NPS threaded) pipes.	33
AXIS T94F01L RECESSED MOUNT	1	2		5503-901	5503-901	Indoor recessed mount for drop ceiling installations. RJ45 network cable coupler included. Compatible with AXIS M3006-V/M3007-PV,AXIS M3024-LVE/M3025-VE/M3026-VE.	75
AXIS T94F01M J-BOX/GANG BOX PLATE	1	70		5503-921	5503-921	Bracket for mounting on 4" square, 4" octagon, single or double-gang junction box. RJ45 network cable coupler included. Compatible with. Compatible with AXIS M3006/7, AXIS M3024-LVE/3025-VE/3026-VE, P14 Series.	24
AXIS T94F01P CONDUIT BACK BOX	1	40		5504-041	5504-041	Backbox for AXIS M3006-V, AXIS M3007-PV,AXIS M3024-LVE/3025-VE/3026-VE/3027-PVE, P14 Series, which enables safe cabling through 1/2" (M20) conduits.	24
AXIS T94G01P CONDUIT BACK BOX	1	20		5505-181	5505-181	Back box for 3/4" (M25) conduits/cable protection pipes. Compatible with AXIS Q1765-LE and AXIS Q1931-E.	24
AXIS T94H01P CONDUIT BACKBOX	1	50		5034-111	5034-111	Vandal resistant aluminum back box accessory for AXIS P33-IV series indoor cameras (except P3301/04) which enables safe cabling through 3/4" conduits.	33



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94K01D PENDANT KIT	1	650		5505-081	5505-081	Indoor pendant kit for AXIS P32-V Series- AXIS P33-V and AXIS Q3505-V, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	33
AXIS T94M01D PENDANT KIT	1	50		5505-091	5505-091	Outdoor pendant kit for AXIS Q3505-VE compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	50
AXIS T94M02L RECESSED MOUNT	1	30		01156-001	01156-001	Outdoor recessed mount for mid-size outdoor dome cameras such as: AXIS P32-VE/LVE, P33-VE/LVE and Q35-VE/LVE series. Suitable for outdoor installations in roof overhangs and soffits. Also suitable for indoor installations in plenum spaces.	109
AXIS T94M02D PENDANT KIT	1		Discontinued - contact Order dept for availability	5507-511	5507-511	AXIS T94M02D comprises a weather shield and a mounting adapter for AXIS P3707-PE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3707-PE to be mounted on poles, parapets and outer corners using many AXIS T91 mounting accessories.	99
AXIS T94N01D PENDANT KIT	1	300		01513-001	01513-001	AXIS T94N01D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3717-PLVE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3717-PLVE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	89
AXIS T94N02D Pendant Kit	1	40		02076-001	02076-001	AXIS T94N02D Pendant Kit comprises a weathershield and a mounting adapter for AXIS P3715-PLVE Network Camera. The mounting adapter is compatible with 1.5-inch NPS thread. The kit enables AXIS P3715-PLVE to be mounted on walls, poles, parapets and outer corners using AXIS T91 mounting accessories.	69
AXIS T94N01G POLE MOUNT	1	20		5901-341	5901-341	Stainless steel pole mount designed for use with heavier Axis products such as positioning cameras and positioning units. IK10. Includes 3pcs stainless steel straps included for pole diameter 60-400mm (2.4-15.7in) and sealing gaskets for multiple cable entries with protection against insect infestation.	199
AXIS T94N01L RECESSED MOUNT	1	10		01514-001	01514-001	Indoor and outdoor recessed mount for discreet installations in drop ceilings, roof overhangs/soffits of AXIS P37 network camera series. Also suitable for installations in plenum space, as the back box is made of metal with a 3/4" hole for cable protection conduits.	119
AXIS T94P01B CORNER BRACKET	1	15		5504-711	5504-711	Corner mount for AXIS P5414-E/15-E, AXIS Q1765-LE, AXIS Q1931-E and AXIS P33-VE series.	66
AXIS T94P01L RECESSED MOUNT	1	20		01172-001	01172-001	Indoor and outdoor recessed mount for AXIS M55 Series. Suitable for air-handling spaces in indoor installations as the enclosure is made of metal and has a 3/4" (M25) conduit hole for protected cable-routing. UL-approved.	99
AXIS T94Q01A WALL MOUNT	1	10		5505-241	5505-241	Wall mount compatible with all Axis outdoor fixed box cameras and housings. Corrosion tested according to NEMA 4X, UL listed and IK10 rated.	37
AXIS T94Q01F CEILING AND COLUMN MNT	1	30		5507-591	5507-591	The powder-coated aluminum AXIS T94Q01F for AXIS fixed box outdoor ready cameras and housings, can be used for both ceiling/soffit and column/parapet installations. This allows Axis' fixed camera housings to be mounted under hard surfaces such as ceilings, beams, soffits and canopies. It can also be mounted on pole or column tops, parapets and other horizontal building structures. Re-direction and maintenance of the camera is easy thanks to the swivel arm feature. The cable is routed through the pipe, and is never exposed to weather or potential vandalism. Cable conduits and Axis' conduit adapters (3/4" dimension) are used for cable protection when routed from the side.	109

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94R01B CORNER BRACKET	1	30		5507-601	5507-601	The powder-coated aluminum AXIS T94R01B Corner Bracket is used for attaching the wall mount of Axis' camera housing to the outer corners of a building. AXIS T94R01B Corner Bracket is compatible with AXIS T91E61 Wall Mount for fixed dome cameras. Small-size fixed dome and bullet-style cameras can also be mounted, thanks to the included and commonly used hole pattern of a single gang junction box.	59
AXIS T94R01P CONDUIT BACK BOX	1	175		5505-141	5505-141	Back box to enable external cable entry or use of cable protection equipment. Hole for 3/4 inch conduits or M25 cable protection pipes. Compatible with AXIS T94Q01A Wall mount, all AXIS M11-E/P13-E/Q16-E/Q1755-E/Q1910-E/21-E/22-E outdoor fixed box camera wall mounts and AXIS T92E Series and AXIS T93E05 Fixed camera housings.	29
AXIS T94S01L RECESSED MOUNT	1	20		5507-671	5507-671	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V-LV series.	42
AXIS T94S01L RECESSED MOUNT 10P	1	1		5901-361	5901-361	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with AXIS P32-V-LV series. 10-pack.	399
AXIS T94S02L RECESSED MOUNT	1	15		01462-001	01462-001	Indoor recessed mount for ceiling/wall installations. Compatible with AXIS M3057/58-PLVE cameras. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces.	49
AXIS T94S01P CONDUIT BACK BOX	1	600		01190-001	01190-001	Outdoor-ready, impact resistant (IK10+) back box with sealed compartment (IP66/67) for secure storage of connectivity devices. 3/4" / M25 conduit interface from both side and back. Can be mounted directly behind a wide range of Axis network cameras. Includes a network cable and extra gaskets.	119
AXIS T94T01D PENDANT KIT	1	450		5505-871	5505-871	Outdoor pendant kit for AXIS P32-VE Series, compatible with Axis ceiling-/wall mounts, AXIS T91A67 Pole mount and 1.5" NPS threaded pipes.	41
AXIS T94T02D PENDANT KIT	1	50		01461-001	01461-001	Outdoor pendant kit for AXIS M30-PLVE Series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	49
AXIS T94U01D PENDANT KIT	1	1		5506-651	5506-651	Pendant kit for AXIS Q3505-SVE, without weather shield, mainly for indoor use made of stainless steel.	379
AXIS T94U02D PENDANT KIT	1	4		5506-661	5506-661	Outdoor pendant kit with weather shield for AXIS Q3505-SVE, made of stainless steel.	419
AXIS T94V01C DUAL CAMERA MOUNT	1	20		01457-001	01457-001	AXIS T94V01C Dual Camera Mount allows back-to-back installation of two Axis cameras for panoramic coverage. Compatible with a wide range of Axis dome cameras, box cameras, and bullet cameras. Compatible with Axis mounting accessories with 1.5" NPS threaded interface, for mounting on walls, poles, and under ceilings. AXIS T94V01C is IK10 rated for impact resistance, which safeguards it against vandalism. Suitable for both indoor and outdoor use. Note: To ensure physical stability, do not use AXIS T94V01C for single camera installations.	99
AXIS T94V02D PENDANT KIT	1	40		01505-001	01505-001	Outdoor pendant kit for AXIS P38-PVE and Q36-VE series. Weathershield made from impact-, UV-, and heat-resistant polymer. Compatible with wide range of Axis mounts with 1.5" NPS threaded interface.	89
AXIS T94V01D PENDANT KIT	1	10		5801-431	5801-431	Pendant kit for indoor and outdoor use for the AXIS Q36-VE Series compatible with Axis ceiling-/wall-/pole mounts with 1.5" NPS thread.	89



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94V01L RECESSED MOUNT	1	2		5801-441	5801-441	Recessed mount for indoor and outdoor use for the AXIS Q36-VE and AXIS P38 Series. It has a metal back box with 3/4" (M25) conduit hole (for protected cable runs) and is suitable for installation in plenum (air-handling) spaces.	109
AXIS T95A64 BRACKET CORNER	1	6		5010-641	5010-641	Corner bracket for AXIS T98A-VE Surveillance Cabinet and AXIS Positioning Cameras. When used with AXIS Positioning Cameras, AXIS T94J01A Wall Mount is required.	75
AXIS T95A67 BRACKET POLE	1	10		5010-671	5010-671	Pole bracket for AXIS T98A-VE Surveillance Cabinet. No straps required.	108
ADAPTER CURV L GREY M311X 10PCS	1			5503-061	5503-061	Optional light grey adapter for mounting AXIS M311X on curved surfaces. 10 pack	24
WALL MOUNT AXIS PS24	1	1		5000-011	5000-011	Metal box to mount AXIS PS24 to a wall.	66
AXIS PS-24 Pole bracket	1	1		21764	21764	Outdoor pole mount bracket for PS-24 and AXIS T97A10. Requires the Wall Mount AXIS PS-24 (5000-011) and a mounting tool for straps (21776 or similar).	38
AXIS T91A03 DIN RAIL CLIP 5PCS	1	15		5800-511	5800-511	The clip, made of steel, enables mounting on a standard 35mm DIN rail. It includes 2 cable ties. Compatible with AXIS T8120/T8133 midspans and AXIS T8604 / T8605 converters. Weight: 17 g (0.6 oz.). 5-pack.	16
AXIS MIDSPAN DIN CLIP A	1	2		5503-931	5503-931	Din clip for AXIS midspan T8123, T8124 and T8125	16
P1214/-E MOUNT KIT INC HOUS 5-P	1	2		5800-431	5800-431	Original mounting kit for AXIS P1214/-E. Kit contents: sensor unit housing, flush wall mount bracket. 5 pack.	83
P1214/-E MOUNT KIT EXC HOUS 5-P	1	1		5800-461	5800-461	Mounting kit for AXIS P1204/E. Kit contents: Flush mount wall bracket. 5 pack.	24
STAND M10 SERIES 7CM	1		Discontinued contact Order dept for availability	5700-481	5700-481	Plastic stand for the AXIS M10-series	11
AXIS P33 MOUNTING BRACKET	1	50		5502-401	5502-401	Mounting bracket for AXIS P33-V/-LV indoor cameras. For mounting cameras on junction boxes (4" square, 4" octagon, single-gang, or double-gang), and other Axis mounting accessories. Also compatible with selected AXIS M30 and P32 cameras.	24
AXIS P33XX-VE 3/4" NPS CONDUIT ADAPTER	1	10		5503-711	5503-711	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	33
AXIS P33XX-VE 3/4" NPS COND ADPT 4P	1	2		5503-721	5503-721	Aluminum cable cover with stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection. Four complete units.	121
AXIS P33XX-VE 3/4" NPS ADAPT	1	10		5503-131	5503-131	Stainless steel adapter used for mounting 3/4" NPS or NPT pipes to AXIS P33XX-VE cameras for cable protection.	24
AXIS T94E01D PENDANT KIT 4PCS	1	1		01494-001	01494-001	Bracket for pendent mounting of AXIS Companion Eye mini L. Compatible with M25 or 3/4" pipes with NPS thread.	39
AXIS T94E01M J-BOX/GANG BOX PL 4PCS	1	1		01495-001	01495-001	Bracket for mounting AXIS Companion Eye mini L on a 4" square, 4" octagon, single or double-gang junction box.	59
AXIS RETROFIT KIT FOR T94S01L 4P	1	10		01982-001	01982-001	Cover ring and holder for installing selected AXIS P32 cameras with legacy AXIS T94S01L Recessed Mount. Bulk pack with 4 sets of rings and clips to retrofit 4 cameras.	39
AXIS RETROFIT KIT T94K01L/02L 4P	1	3		02002-001	02002-001	Retrofit into T94K01L or T94K02L. Mic hole for -LV cameras. Includes 4 sets of lid ring cover, gaskets, screws.	79
AXIS P33-VE Pendant Kit	1	60		5502-321	5502-321	Pendant kit for selected AXIS P33-VE Fixed Dome Network Cameras, compatible with mounts with 1.5" NPT/NPS threaded interface. Color: Axis white	41
ADAPTER AXIS 209 TO M31/P39 50 PCS	1	1		5503-192	5503-192	Adapter plate for mounting an AXIS M31 using the same foot print as the AXIS 209. 50 PCS	209
AXIS P33XX-VE CABLE COVER 4 PCS	1	1		5503-731	5503-731	Aluminum cable cover for AXIS P33XX-VE cameras. 4 pcs.	50



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS ACI COND ADAP 3/4" U-SHAPE 30MM 5PCS	1	3		5505-191	5505-191	Mechanical adapter that provides a U-shaped 30mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS P54-series, AXIS P32-VE Series (requires AXIS ACI Mounting Bracket A), AXIS Q3505-VE, AXIS T91B6X mounts and AXIS AXIS T94R01P Conduit Back Box. 5 pcs.	20
AXIS ACI CONDUIT BRACKET A 5P	1			5505-971	5505-971	Cable protection attachment bracket for AXIS P32-VE Series. Compatible with 3/4" Conduits, M25 pipes and AXIS ACI adapters. 5pcs.	33
AXIS ACI CONDUIT BRACKET B 5P	1			5506-041	5506-041	Cable protection attachment bracket for AXIS P32-V Series. Compatible with 1/2" Conduits, M20 pipes and AXIS ACI adapters. 5pcs.	16
AXIS ACI CONDUIT ADAPTER 1/2"-3/4" A 2P	1	1		5505-541	5505-541	Step up ACI adapter for attaching 3/4" conduits or M25 pipes to AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 2 pcs	33
AXIS ACI COND ADAP 1/2 " U-SHAPE 20MM 5P	1	2		5505-521	5505-521	Mechanical adapter that provides a U-shaped 20mm wide cable entry for use when a U-shape cable protection is required. The adapter is compatible with AXIS products with a 1/2" conduit interface such as AXIS P32-V series (requires AXIS ACI conduit bracket B) and AXIS Q3505-V. 5 pcs	16
AXIS ACI COND ADAP 1/2"-3/4" NPS 2P	1	1		5505-591	5505-591	Threaded stainless steel step up ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 1/2" conduit interface such as AXIS Q35-V series. 2 pcs	69
AXIS ACI CONDUIT ADAPTER 3/4" NPS 2P	1	7		5505-641	5505-641	Threaded stainless steel ACI adapter for attaching 3/4" NPS conduits to AXIS products with a 3/4" conduit interface such as AXIS Q35-VE series. 2 pcs	99
AXIS F8001 SURFACE MOUNT	1	8		5505-791	5505-791	Bracket to mount and secure an F Series main unit onto a surface. Withstands vibrations and secures all cables to/from the main unit.	33
ACC PL ADAPTER CURVED AXIS M311X 10PCS	1			5502-551	5502-551	Optional adapter for mounting AXIS M311X on curved surfaces. 10 pack	24
AXIS RACK SLIDE RAILS A	1	1		5504-781	5504-781	Rack slides for AXIS Q7920 Video Encoder Chassis	58
AXIS F7308 CABLE BLACK 8M 4PCS	1	1		5506-921	5506-921	AXIS F7308 comes in packs of four. 8-m (26 ft.) black cable with an RJ12 contact for connection to an AXIS F1004 Sensor Unit. Used as a spare part for the original cable that comes with AXIS F1004 Sensor Unit.	39
AXIS F8002 DIN RAIL CLIP	1	4		5505-801	5505-801	DIN clip + angled mounting bracket. Allows an AXIS F Series main unit to be mounted on a DIN rail with the short side against the rail to minimize used space. Main unit can be mounted with cables going in any of three directions (up, down or out from the rail).	33
AXIS F8401 CLEAR LENS PROTECTOR 5PCS	1	10		5505-841	5505-841	Lens protection for AXIS F1005-E. The lens protector is screwed onto the threaded front part of the sensor unit to protect the lens. Comes in pack of 5 units.	66
AXIS F8201 VARI-ANGLE MT BRACK 5PCS	1	30		5505-811	5505-811	Mounting bracket for AXIS F1005-E, AXIS F1015 and AXIS 1035-E. Allows the sensor unit to be fixed and angled into various directions to get the desired view. Comes in pack of 5 pcs.	24
AXIS F8202 STRAIGHT MT BRACKET 5PCS	1	15		5505-821	5505-821	Mounting bracket that allows the pinhole sensor unit of AXIS F1025 to be mounted onto a flat surface with the cone being flush with opposite surface. Comes in pack of 5 pcs.	24
AXIS F8203 FIXED MT BRACKET 5PCS	1	15		5505-831	5505-831	Metal bracket for stable mounting of AXIS F1005-E, F1015 and F1035-E. Variety of holes for screws for flexible mounting. Comes in pack of 5 units.	125
AXIS F8204 MOUNTING BAND 10 PCS	1	10		5506-571	5506-571	Stainless steel band for flexible mounting of AXIS F Series Sensor units and AXIS P12 sensor units. Sold in 10-pack. 10 x M20 x 1.5 nuts to lock the band to the sensor unit are included. Works with all AXIS P12 Sensor Units and all AXIS F Series Sensor units except AXIS F1015.	33



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS F8206 PINHOLE MT BRACKET 5PCS	1	1		5507-621	5507-621	Mounting bracket that allows AXIS F1004 Pinhole Sensor Unit and the sensor unit for AXIS P1264 to be mounted behind a thin metal/plastic/glass panel. Comes in pack of 5 pcs.	29
AXIS F8211 PINHOLE TRIM RING 10PCS	1	1		5507-101	5507-101	Trim ring for discreet mounting of AXIS F1025 Sensor Unit behind a thin surface. 10 PCS.	59
AXIS F8212 TRIM RING 10PCS	1	15		5507-111	5507-111	Trim ring for discreet mounting of AXIS F1005-E, F1035-E, P1214-E and P1224-E behind a surface. 10 PCS.	99
AXIS F8224 RECESSED MOUNT 4PCS	1	6		5506-511	5506-511	AXIS F8224 Recessed Mount (4 pieces). Recessed mount accessory for use with AXIS F1004 Sensor Unit. Can be mounted in a ceiling.	50
AXIS F8205 BULLET ACCESSORY	1	5		5506-211	5506-211	Bullet-style camera accessory for AXIS F1005-E. AXIS F1005-E provides 113° horizontal FOV. Comes with c-clamp and a stand.	20
AXIS F8215 VARIFOCAL BULLET ACC	1	15		5506-221	5506-221	Varifocal bullet-style camera accessory for AXIS F1015. AXIS F1015 provides 58-108° horizontal FOV. Comes with c-clamp and a stand.	20
AXIS F8225 PINHOLE ACCESSORY	1	5		5506-531	5506-531	Discreet accessory for ceiling mount of AXIS F1025 (pinhole). AXIS F1025 provides 92° horizontal FOV. Used to get overview of rooms or of a door. Can easily be repainted to fit ceiling color.	33
AXIS F8235 FISHEYE ACCESSORY	1	2		5506-541	5506-541	Discreet accessory to mount a AXIS F1035-E in a ceiling. Perfect for overview in small rooms or in parts of a larger room. Can easily be repainted to fit ceiling color.	33
AXIS F92A01 BLACK HEIGHT S. HOUSING	1	2		01630-001	01630-001	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Black aluminium housing.	99
AXIS F92A01 SILVER HEIGHT S. HOUSI-	1	3		01631-001	01631-001	Height strip housing for discrete mounting of a pin hole sensor unit, for capturing eye-level images e.g. of people leaving a store. It is compatible with AXIS F1025, FA1125, F1004 Pin hole, AXIS P1264 and P1265. Comes with both a metric and an imperial height strip. Silver aluminium housing.	99
AXIS T91R61 WALL MOUNT	1	20		01516-001	01516-001	Tiltable wall-mount for AXIS D2050-VE Network Radar Detector. Includes arm, AXIS T94R01P CONDUIT BACK BOX and conduit 260 mm (10 inch) cable kit.	129
AXIS TM3001 TILT MOUNT	1	20		01748-001	01748-001	Tilt Mount Plastic, 15deg tilt, 1/2" (M20) conduit. BRACKET MOUNT ASSEMBLY M3067.	29
AXIS TM3101 PENDANT WALL MOUNT	1	30		01742-001	01742-001	Elegant mount for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M20/M30/M31/M42, etc. Made from strengthened eco-friendly plastic.	39
AXIS TM3101 PENDANT WALL MNT BLACK	1	8		01917-001	01917-001	Elegant mount in black for indoor mounting of Axis mini dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, AXIS T8643). Compatible with wide range of cameras, incl. AXIS M30, AXIS M31, AXIS M42, etc. Made from strengthened eco-friendly plastic.	39
AXIS TM3201 RECESSED MOUNT	1	30		01856-001	01856-001	Recessed mount for selected AXIS M30 cameras. Includes covers for fixed mini dome and panoramic cameras.	39
AXIS TP1601 ADAPTER PLATE	1	20		02083-001	02083-001	Adapter plate for mounting on conduit back box TP3603 or T94S01P. Plate is for P14 series and M42 series that allows for the cameras to look aesthetically pleasing when mounted onto a conduit back box.	29

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS TP3101 PENDANT WALL MOUNT	1	50		01783-001	01783-001	Elegant mount for indoor mounting of Axis dome cameras in pendant style. Concealed mounting with no visible screws. Room for microphone and connectivity devices (e.g.: AXIS T6101, T8643) and AXIS I/O Indication LED. Compatible with AXIS M32-LVE and AXIS P32-V/LV cameras. Made from strengthened eco-friendly plastic.	49
AXIS TP3201 RECESSED MOUNT	1	200		01757-001	01757-001	Indoor recessed mount for drop ceiling installation. Supports the optional use of an internal microphone. Metal enclosure with conduit entries, suitable for installation in air handling / plenum spaces. Compatible with: AXIS M32-LVE, AXIS P32-V/LV, AXIS P33-V and AXIS Q35-V-LV series; and AXIS Device Microphone A and B.	79
AXIS TP3202 RECESSED MOUNT	1	70		01983-001	01983-001	Indoor recessed mount for drop ceiling installations. Single-screw ceiling attachment for quick and easy installation. Not suitable for air-handling (plenum) spaces. Compatible with selected AXIS M32 and AXIS P32 cameras.	42
AXIS TP3601 3/4" CONDUIT ADAPTER 4P	1	4		01804-001	01804-001	Adapters for protected cable routing in 3/4" conduit (M25 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	29
AXIS TP3603 CONDUIT BACK BOX	1	20		02025-001	02025-001	TP3603 indoor conduit back box a complement to T94S01P at a lower price point for large indoor installations (eg data centers). Compatible with P32/M32 indoor versions as well as indoor versions of Q17/19/29, P33, Q35, and P14/M42(plate needed TP1601). TP3603 has two separate conduit entries (1/2" & 3/4") and has space for connectors (e.g. T86 Media Converters & T6101 I/O interface).	49
AXIS TP3701 J-BOX & POLE ADAPTER	1	3		01743-001	01743-001	Optional accessory for mounting over junction boxes or on poles. Plastic straps (two) are included. Compatible with AXIS TM3101 and TP3101 Pendant Wall Mount.	29
AXIS TP8101 PENDANT KIT	1	8		02019-001	02019-001	An indoor metal pendant kit for mounting AXIS P8815-2 3D People Counter. Compatible AXIS ceiling mounts and 1.5" and 3/4" conduits.	39
AXIS TP8201 RECESSED MOUNT	1	4		02020-001	02020-001	A plenum rated recessed mount for P8815-2 3D People Counter	99
AXIS TP3602 1/2" CONDUIT ADAPTER 4P	1	15		01805-001	01805-001	Adapters for protected cable routing in 1/2" conduit (M20 pipe). Compatible with selected AXIS M32 and P32 cameras. 4pcs bulk pack.	29
AXIS TP3902 RETROFIT KIT 4P	1	1		01807-001	01807-001	Metal bracket with snap-on features for replacing legacy AXIS P3214/15/24/25/35-VE/-LVE outdoor fixed dome cameras with the new AXIS P324x-VE/-LVE cameras. Bulk pack for retrofitting 4 cameras.	39
AXIS TQ6501-E PARAPET MOUNT	1	20	To be launched	02110-001	02110-001	Parapet Mount is an outdoor-ready mount. The round base of the mount makes it easy to install as well as suitable for installations on poles. Cables can be routed through the bottom, or from the side by using a conduit connection. Chromated and powder coated aluminum parapet mount compatible with fixed dome pendant kits and AXIS P55-series and AXIS Q60-series PTZ dome cameras. Includes mounting plate, pipe seal, conduit hole cover. Color: White	199
AXIS TQ9601 CONDUIT TOP BOX	1	10		01818-001	01818-001	CONDUIT TOP BOX for Q9216-SLV.	99
AXIS TQ6901-E ADAPTER BRACKET 4P	1	20		02111-001	02111-001	AXIS TQ6901-E is a useful adapter for retrofitting AXIS Q6215-LE in camera installations that have 3rd party competitor mounts. AXIS TQ6901-E is made of powder coated aluminum and is sold in packs of four.	199
AXIS TS3001 Recorder Mount	1	40		02081-001	02081-001	AXIS TS3001 Recorder Mount ensures that the AXIS S3008 Recorder is in a fixed position either if it is mounted on walls, shelves, or under tables. Its design and shape allows the recorder to be mounted in two opposite directions.	19



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T99A10 24V AC/DC	1	1		01226-001	01226-001	High accuracy outdoor positioning unit with AXIS T93F10 camera housing. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. Recommended for AXIS P13 and Q16 network camera series. Optional wall mount and pole mount accessories available separately.	1.799
AXIS T99A11 24V AC/DC	1	2		01227-001	01227-001	High accuracy outdoor positioning unit to be used with PT Mount models in AXIS Q19 and Q29 series. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Optional wall mount and pole mount accessories available separately. Powered by 24 V AC/DC.	1.799
AXIS AUDIO MANAGER PRO C7050 MK II	1	3		02071-002	02071-003	AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager Pro helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	2.995
AXIS AUDIO MANAGER PRO C7050	1		Discontinued contact Order dept for availability	01519-002	01519-003	AXIS Audio Manager provides easy, remote management of large IP audio installations. Take control of your complete audio system from one single user interface which handles, for example, system setup of audio devices, zone management, audio content management, and audio scheduling. Especially useful in retail or in schools, AXIS Audio Manager helps you broadcast music, live or scheduled announcements, emergency messages, and more, either individually in separate zones or centrally to all devices. With quick installation, intuitive operation, and online device status monitoring, AXIS Audio Manager realizes the benefits of network audio.	2.995
AXIS AUDIO MANAGER PRO - E-LICENSE	1			02062-001	02062-001	AXIS Audio Manager Pro provides easy, remote management of large IP audio installations. The AXIS AUDIO MANAGER PRO - E-LICENSE is used to when installing AXIS Audio Manager Pro on your own custom hardware or virtual machine (VMWare, Microsoft Hyper-V, Microsoft Windows Datacenter)	2.495

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS C1310-E NETWORK HORN SPEAKER	1	900		01796-001	01796-001	AXIS C1310-E Network Horn Speaker is perfect for outdoor environments in most climates. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1310-E allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general voice messages. Built-in memory supports pre-recorded messages, or security personal can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP (supporting SIP). AXIS C1310-E is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design.	499
AXIS C1004-E NETW CAB SPEAKER BLACK	1	15		0923-001	0923-001	AXIS C1004-E Network Cabinet Speaker (black) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	549
AXIS C1004-E NETW CAB SPEAKER WHITE	1	80		0833-001	0833-001	AXIS C1004-E Network Cabinet Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C1004-E is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	549
AXIS C2005 NETW CEILING SPEAK WHITE	1	150		0834-001	0834-001	AXIS C2005 Network Ceiling Speaker (white) is an all-in-one speaker system connected with a single network cable. It delivers out-of-the-box-ready high-quality sound without any need for fine-tuning. Background music can be played via the preinstalled AXIS Audio Player application. You can create and schedule your own playlists from an onboard SD card or from audio streaming services. AXIS C2005 is also perfect for voice announcements (scheduled or live calls). The speakers can be zoned together thanks to built-in audio synchronization technology.	399



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS C1410 NETWORK MINI SPEAKER	1	150		01916-001	01916-001	AXIS C1410 Network Mini Speaker is a discrete and affordable speaker that fits into smaller spaces and provides wide-area audio coverage. The speaker is a complete audio system in a single unit. It connects to the standard existing network so there is no need for a separate audio network. Further it is simple to install with PoE for both power and connectivity. AXIS C1410 allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound and with remote health testing you know that it is working. Open standards support easy integration with network video, access control, analytics, and VoIP. AXIS C1410 is a standalone unit that can be placed anywhere, which supports a flexible, scalable and cost-effective approach to system design. It also has a built-in PIR sensor for motion detection.	299
AXIS C8033 NETWORK AUDIO BRIDGE	1	90		01025-001	01025-001	AXIS C8033 Network Audio Bridge is a smart solution for connecting and combining analog and digital audio systems. With this scalable and cost-efficient product, you can connect analog audio sources to Axis network speaker system, connect digital audio sources to an analog speaker system, or combine analog and digital speaker systems to act as one. Based on open standards, the audio bridge is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	199
AXIS C8210 NETWORK AUDIO AMP	1	30		01558-001	01558-001	AXIS C8210 Network Audio Amplifier is a smart migration tool for transforming any passive speaker, independent of brand or formfactor, into a network speaker. This gives you all the benefits of network audio including less components. AXIS C8210 enables scalable and cost-effective solutions and can power up to eight speakers with a total power output of 15 W. Based on open standards, the amplifier is easily integrated with other systems. It is small, easy to place, and easy to connect using Power over Ethernet.	399
XF40-Q1765 ATEX IECEX	1		Built to order	0835-001	0835-001	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C ATEX IECEX	1		Built to order	0835-011	0835-011	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q1765 INMETRO	1		Built to order	0835-021		Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to INMETRO. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C INMETRO	1		Built to order	0835-031		Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to INMETRO. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599
XF40-Q1765 CSA	1		Built to order		0835-041	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C CSA	1		Built to order		0835-051	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CSA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599
XF40-Q1765 CCOE	1		Built to order	0835-081	0835-081	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CCOE. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q1765 -60C CCOE	1		Built to order	0835-091	0835-091	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CCOE. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (- 76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599
XF40-Q1765 CNEX	1		Built to order		0835-101	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CNEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps.It supports Onvif,WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (- 40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C CNEX	1		Built to order		0835-111	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to CNEX. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps.It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (- 76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599
XF40-Q1765 IA	1		Built to order	0835-121	0835-121	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to IA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif,WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (- 40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C IA	1		Built to order	0835-131	0835-131	Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to IA. Certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (- 76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q1765 EAC	1		Built to order	01485-001		Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to EAC TR CU. Model XF40 Serie 1410, certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	6.999
XF40-Q1765 -60C EAC	1	1	Built to order	01486-001		Explosion-protected 316L stainless steel fixed network camera certified for hazardous areas according to EAC TR CU. Model XF40 Serie 1410, certification part code 1410-15-00. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	7.599
XP40-Q1765 ATEX IECEX	1		Built to order	0836-001	0836-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR-dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499
XP40-Q1765 -60C ATEX IECEX	1		Built to order	0836-011	0836-011	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1765 INMETRO	1		Built to order	0836-021		Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to INMETRO. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499
XP40-Q1765 -60C INMETRO	1		Built to order	0836-031		Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to INMETRO. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499
XP40-Q1765 CSA	1		Built to order		0836-041	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499
XP40-Q1765 -60C CSA	1		Built to order		0836-051	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CSA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1765 CCOE	1		Built to order	0836-081	0836-081	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CCOE. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499
XP40-Q1765 -60C CCOE	1		Built to order	0836-091	0836-091	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CCOE. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499
XP40-Q1765 CNEX	1		Built to order		0836-101	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CNEX. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR-dynamic contrast. Video motion detection and active tampering alarm. IP66 and IP67 rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield.	17.499
XP40-Q1765 -60C CNEX	1		Built to order		0836-111	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to CNEX. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499
XP40-Q1765 IA	1		Built to order	0836-121	0836-121	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to IA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC(Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1765 -60C IA	1		Built to order	0836-131	0836-131	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to IA. Certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499
XP40-Q1765 EAC	1		Built to order	01487-001		Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to EAC TR CU. Model XP40, Serie 2420, certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR- dynamic contrast, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	17.499
XP40-Q1765 -60C EAC	1		Built to order	01488-001		Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas according to EAC TR CU. Model XP40, Serie 2420, certification part code 1410-25/2420-01. Oxalis housing, Axis 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, AXIS Video motion detection and active tampering alarm. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.499
XF40-Q2901 ATEX IECEX 8.3FPS 19MM -40C	1	1	Built to order	01089-001	01089-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q2901 ATEX IECEX 8.3FPS 19MM -60C	1		Built to order	01090-001	01090-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19.599
XF40-Q2901 EAC 8.3FPS 19MM -40C	1		Built to order	01093-001		Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to EAC. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.999
XF40-Q2901 EAC 8.3FPS 19MM -60C	1		Built to order	01129-001		Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to EAC. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19.599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q2901 CSA 8.3FPS 19MM -40C	1		Built to order		01092-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature, 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.999
XF40-Q2901 CSA 8.3FPS 19MM -60C	1		Built to order		01128-001	Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to CSA. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature, 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19.599
XF40-Q2901 INMETRO 8.3FPS 19MM -40C	1		Built to order	01091-001		Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to INMETRO. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature, 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	18.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XF40-Q2901 INMETRO 8.3FPS 19MM -60C	1		Built to order	01127-001		Explosion-protected 316L stainless steel Temperature Alarm Camera certified for hazardous areas according to INMETRO. Certification part code 1410-TI-50. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations. Oxalis explosion-protected housing with three M20 cable entries and Axis Temperature Alarm camera inside with 336x256 resolution and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature, 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	19.599
XP40-Q1942 ATEX IECEX 8.3FPS 19MM -40C	1		Built to order	01098-001	01098-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	24.999
XP40-Q1942 ATEX IECEX 8.3FPS 19MM -60C	1		Built to order	01099-001	01099-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to ATEX and IECEX. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25.999
XP40-Q1942 EAC 8.3FPS 19MM -40C	1		Built to order	01102-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to EAC. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	24.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1942 EAC 8.3FPS 19MM -60C	1	1	Built to order	01138-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to EAC. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25.999
XP40-Q1942 CSA 8.3FPS 19MM -40C	1	1	Built to order		01101-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +60°C (-40°F to +140°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	24.999
XP40-Q1942 CSA 8.3FPS 19MM -60C	1		Built to order		01137-001	Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to CSA. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25.999
XP40-Q1942 INMETRO 8.3FPS 19MM -40C	1		Built to order	01100-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to INMETRO. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -40°C to +70°C (-40°F to +158°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	24.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1942 INMETRO 8.3FPS 19MM -60C	1		Built to order	01136-001		Explosion-protected 316L stainless steel PT Thermal Network Camera certified for hazardous areas according to INMETRO. Certification part code 1410-10-TI-50/2420-01. Oxalis explosion-protected housing with one M20 cable entry and Axis Thermal Network Camera inside with 640x480 resolution and 32° angle of view. Continuous 360° pan, ±90° tilt and 64 preset positions. At least 3 individual streams in H.264 and Motion JPEG, simultaneous, individually configured streams in maximum resolution at 8.3 fps. It supports Electronic Image Stabilization, Zipstream, ONVIF, Video motion detection and Shock detection. IP66 and IP67-rated and operating temperature in -60°C to +40°C (-76°F to +104°F). Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 64 GB.	25.999
EXCAM XPT Q6075	1		5 Built to order	01928-001	01928-001	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 40x zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T6 Gb, Ex II 2 D Ex t IIIC T80°C Db IP68, -50°C ≤ Ta ≤ +60°C. Model key:T08-TNXCD-C-005-K-LL. Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p @60 fps, Lightfinder 2.0. AXIS T8154 PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 128GB, EXTB-3 connection box, 5m armored network and power cable preinstalled. Built to order, 6 weeks lead time.	14.999
EXCAM XF Q1785	1		1 Built to order	01572-001	01572-001	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T95°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K3.BOR5-C-005-K-LL. Stainless Steel 316L housing with wiper and sunshield. Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled, Ex e connection box. Built to order, 6 weeks lead time.	9.999
EXCAM XF Q1645	1		1 Built to order	01562-001	01562-001	Explosion-protected, PoE powered, HDTV 1080p fixed network camera, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T100°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K1.BOR2-C-005-K-LL. Stainless Steel 316L housing with sunshield. 3.9 - 10mm F1.5 i-CS lens. Lightfinder, Zipstream, forensic WDR, electronic image stabilization, AXIS Motion Guard, AXIS Fence Guard. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled, Ex e connection box. Built to order, 6 weeks lead time.	8.499
EXCAM XF P1367	1		1 Built to order	01720-001	01720-001	Explosion-protected, PoE powered, 5 MP fixed network camera, ATEX/IECEX/EAC certified for hazardous locations. Ex II 2 G Ex d IIC T5 Gb, Ex II 2 D Ex t IIIC T100°C Db IP68, -60°C ≤ Ta ≤ +60°C. Model key:T08-VA2.3.K3.BOR2-C-005-K-LL. Stainless Steel 316L housing. 2.8 - 8.5mm F1.2 i-CS lens. Lightfinder, Zipstream, forensic WDR. AXIS Surveillance SD Card 64GB, 5m network and power cable preinstalled. Built to order, 6 weeks lead time.	6.999



Axis Communications				DECEMBER-2020, EUR			
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
EXCAM XF M3016	1	4	Built to order	01989-001	01989-001	Explosion-protected, PoE powered, 3 MP fixed network camera, ATEX/IECEX/EAC-Ex/IA/PESO certified for hazardous locations. Ex II 2 G Ex d IIC T6 Gb, Ex II 2 D Ex t IIC T80°C Db IP68, -5°C <= Ta <= +50°C (intermittent). Model key:T08-VA1.2.K1.BOR-N.N-005.N-P-090. Stainless steel 316L housing. 2.8mm F2.0 lens. Zipstream, WDR. AXIS Surveillance SD Card 128GB, 5m network cable preinstalled. Built to order, 6 weeks lead time.	3.999
F101-A XF P1367	1	3		01703-001	01703-001	Explosion-protected, PoE powered, 5 MP fixed network camera, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class I Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIC T6 Db, -20°C <= Ta <= +60°C. Powder coated aluminum housing (RAL 3017). i-CS mount lens, 2.8 - 8mm, F1.2. Lightfinder, Zipstream, WDR - forensic capture. AXIS Surveillance SD Card 64GB, sunshield included.	3.999
F101-A XF Q1785	1	2		01587-001	01587-001	Explosion-protected, PoE powered, HDTV 1080p 32x optical zoom, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class I Zone 1 IIB + H2 AEx d IIB+H2 T6, Class II Zone 21, AEx d IIC T6 Db, ATEX/IECEX, -40°C <= Ta <= +60°C. Powder coated aluminum housing (RAL 3017). Lightfinder, Zipstream, forensic WDR, electronic image stabilization. AXIS Surveillance SD Card 64GB.	4.999
D201-S XPT Q6055	1	1		01480-001	01480-001	Explosion-protected, top performance, PoE powered HDTV 1080p PTZ dome network camera with 32x zoom, FM listed for hazardous locations Class I Division 1, Groups B, C, D, T6; Class 1 Zone 1 IIB + H2 T6, -20°C <= Ta <= +55°C (FM17US0156). Stainless Steel 316L housing. Auto day/night functionality, Zipstream, wide dynamic range, electronic image stabilization, highlight compensation. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p@30 fps, 720@60 fps. High PoE midspan with fiber slot is included (for installation in safe area or Ex d enclosure), AXIS Surveillance SD Card 64GB. Optional accessories: Wall and pole mount.	14.999
D101-A XF P3807	1	1		01914-001	01914-001	D101-A XF P3807 is an explosion-protected multi-sensor camera, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. Enclosed in a red aluminum housing and FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T6; Class 1 Zone 1 IIB + H2 T6, -20°C <= Ta <= +55°C (FM17US0156). ATEX, IECEX II 2G Ex db IIB + H2, T6 GB, II 2 D Ex tb IIC T85°C Db IP66.	9.999
XP40-Q1785 -40C	1	1	Built to order	02115-001	02115-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIC, T4) according to ATEX, IECEX, EAC, CSA. Certification part code 1410-25/2420-01 by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated and operating temperature -40°C to +70°C. Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	17.499



Axis Communications			DECEMBER-2020, EUR				
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1785 -60C	1	1	Built to order	02116-001	02116-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature -60°C to +40°C. Powered by 24 V AC (Power supply not included). Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	18.499
XP40-Q1785 -40C 230V	1	1	Built to order	02117-001	02117-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature -40°C to +70°C. Powered by 230 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB	18.499
XP40-Q1785 -60C 230V	1	1	Built to order	02118-001	02118-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature in -60°C to +40°C). Powered by 230 V AC. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB.	19.499
XP40-Q1785 -40C 230V FO	1	1	Built to order	02119-001	02119-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature -40°C to +70°C). Powered by 230 V AC. Fiber connectivity simplex singlemode 9/125um, SC connector, 10/100Mb. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB	19.499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
XP40-Q1785 -60C 230V FO	1	1	Built to order	02120-001	02120-001	Explosion-protected 316L stainless steel PTZ network camera certified for hazardous areas (IIC, IIIC, T4) according to ATEX, IECEx, EAC, CSA. Certification part code 1410-25/2420-01, by Eaton MEDC. AXIS Q1785 1080p HDTV camera inside with 32x optical zoom, auto focus and day/night mode. Continuous 360° pan, ±90° tilt and 64 preset positions. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. It supports Onvif, WDR, EIS and active tampering alarm. IP66 and IP67-rated, operating temperature -60°C to +40°C). Powered by 230 V AC. Fiber connectivity simplex singlemode 9/125um, SC connector, 10/100Mb. Includes a removable sunshield and AXIS Surveillance microSDXC™ Card 128 GB	20.499
F101-A XF P1377	1	20	To be launched	01927-001	01927-001	Explosion-protected, PoE powered, 5 MP fixed network camera, FM listed for hazardous locations Class I/II/III Division 1, Groups B, C, D, E, F, G, T5; Class I Zone 1 IIB + H2 AEx/Ex d IIB+H2 T5, Zone 21, AEx/Ex d IIIC T85°C Db, Operating temp: -40°C (US Div)/-50°C (Zone, CAN Div) <= Ta <= +55°C. Powder coated aluminum housing (RAL 3017). I-CS mount lens, 3.9-10 mm, F1.2. Lightfinder, Zipstream, WDR - forensic capture. AXIS Surveillance SD Card 128GB, Sunshield included.	3.999
AXIS M1045-LW	1			0812-002	0812-003	Small, wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	229
AXIS M1065-L	1	175		0811-001	0811-001	Small, full-featured indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Powered over Ethernet (PoE) or by accessory power supply. Includes wall, corner bracket and table top bracket for easy mounting. Power supply not included.	279
AXIS M1065-LW	1			0810-002	0810-003	Small, full-featured wireless indoor cube camera for day & night surveillance. 2.8mm fixed lens with 110° HFOV. Automatic IR cut filter. IR illumination up to 10 meters (33 feet) . Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Built-in microphone and mini-speaker, integrated PIR motion sensor. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™ PBC compatible. Includes wall, corner bracket and table top bracket for easy mounting. Power supply included.	299



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M1124	1		Discontinued contact Order dept for availability	0747-001	0747-001	HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	293
AXIS M1124 BULK 10PCS	1		Discontinued contact Order dept for availability	0747-021	0747-021	AXIS M1124 in 10-pack. Cannot be sold separately as single packs.	2.896
AXIS M1124 BAREBONE	1		Discontinued contact Order dept for availability	0747-031	0747-031	AXIS M1124 Barebone. No lens.	276
AXIS M1124-E	1		Discontinued contact Order dept for availability	0748-001	0748-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight,HDTV 720p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan not included.	377
AXIS M1125	1		Discontinued contact Order dept for availability	0749-001	0749-001	HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Includes stand. Power supply not included.	352
AXIS M1125 BULK 10PCS	1		Discontinued contact Order dept for availability	0749-021	0749-021	AXIS M1125 in 10-pack. Cannot be sold separately as single packs.	3.484
AXIS M1125 BAREBONE	1		Discontinued contact Order dept for availability	0749-031	0749-031	AXIS M1125 Barebone. No lens.	335
AXIS M1125-E	1		Discontinued contact Order dept for availability	0750-001	0750-001	Outdoor, NEMA 4X, IP66 and IK10-rated, lightweight,HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 3-10.5 mm DC-iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps. WDR – Forensic Capture and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Power over Ethernet or 8-28 VDC input. Operation in -20°C to +50°C. Powered by IEEE 802.3af midspan. Includes a wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan not included.	436



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M1134	1	150		01979-001	01979-001	HDTV 720p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 720p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	349
AXIS M1134 BAREBONE	1	1		01979-041	01979-041	AXIS M1134 Barebone in single pack. No lens. No power supply	329
AXIS M1135	1	70		01768-001	01768-001	HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 2 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	419
AXIS M1135 BAREBONE	1	1		01768-041	01768-041	AXIS M1135 Barebone in single pack. No lens. No power supply.	399
AXIS M1135-E	1	100		01772-001	01772-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight HDTV 1080p resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 3-10.5 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 2 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	519
AXIS M1137	1	60		01769-001	01769-001	5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with either built-in microphone or optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. PoE class 3 or 8-28VDC input. Includes stand for wall and ceiling mount. Midspan or power supply not included.	499
AXIS M1135 BULK 10PCS	1	1		01768-021	01768-021	AXIS M1135 in 10-pack. Cannot be sold separately as single packs.	4.149
AXIS M1137 BAREBONE	1	10		01769-041	01769-041	AXIS M1137 Barebone in single pack. No lens. No power supply	479

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M1137-E	1	80		01773-001	01773-001	Outdoor, NEMA 4X, IP66 and IK10-rated, light weight 5MP resolution, day/night, compact fixed box camera with CS-mount providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-13 mm F1.4 DC-iris lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Audio in and audio detection with optional analog microphone. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -25°C to +50°C. PoE class 3 or 8-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66- rated cable glands. Midspan or power supply not included.	599
AXIS M1145-L	1	40		0591-001	0591-001	HDTV camera for day and night surveillance with varifocal 3-10.5mm P-iris lens. Remote 3.5 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p or 2MP resolution at 30 fps. Video motion detection and active tampering alarm and I/O ports. OptimizedIR, a power-efficient LED technology that provides an adaptable angle of IR illumination up to 15 meters (50 feet) MicroSD/SDHC memory card slot for edge storage. Includes stand for easy mounting. Power over Ethernet. Midspan not included.	419
AXIS M1145-L BULK 10PCS	1	1		0591-021	0591-021	AXIS M1145-L in 10-pack/bulk. Cannot be sold separately as single packs.	4.156
AXIS M2025-LE	1	400		0911-001	0911-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	329
AXIS M2025-LE BLACK	1	40		0988-001	0988-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	329
AXIS M2025-LE BULK 10PCS	1	1		0911-021	0911-021	AXIS M2025-LE in 10-pack/bulk. Cannot be sold separately as single packs.	3.249
AXIS M2026-LE MK II	1	70		01049-001	01049-001	Day/night, compact and outdoor-ready bullet style HDTV camera, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	399



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M2026-LE MK II BLACK	1	40		01050-001	01050-001	Day/night, compact and outdoor-ready bullet style HDTV camera in black color, IP66- and IK08-rated. Built-in IR illumination and WDR. Fixed lens with 130° HFOV. Automatic IR cut filter. Multiple, individually configurable H.264/H.265 and Motion JPEG streams; max 4 MP / QuadHD resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and corridor format. Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). Midspan not included.	399
AXIS M2026-LE MK II BULK 10PCS	1	1		01049-021	01049-021	AXIS M2026-LE Mk II in 10-pack/bulk. Cannot be sold separately as single packs.	3.949
AXIS M2026-LE MK II BLACK BULK 10PCS	1	1		01050-021	01050-021	AXIS M2026-LE Mk II Black in 10-pack/bulk. Cannot be sold separately as single packs.	3.949
AXIS P1214	1	5		0532-001	0532-001	Miniature HDTV pinhole camera for discreet surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	419
AXIS P1214 BULK 10 PCS	1	1		0532-021	0532-021	AXIS P1214 in pack of 10 units	4.156
AXIS P1214-E	1	60		0533-001	0533-001	Miniature HDTV camera for discreet outdoor surveillance. Cable from sensor unit going in the direction of the lens. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	419
AXIS P1214-E BULK 10 PCS	1	5		0533-021	0533-021	AXIS P1214-E in pack of 10 units	4.156
AXIS P1224-E	1	70		0654-001	0654-001	Miniature HDTV camera for discreet indoor/outdoor surveillance with 145° horizontal field of view. Edge storage using microSD card or NAS. ACAP support, I/O port, multiple video streams in H.264 and Motion JPEG. 25/30 fps in all resolutions up to 720p. PoE and 8-28 VDC support.	419
AXIS P1244	1	30		0896-001	0896-001	AXIS P1244 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Sensor Unit. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	299
AXIS P1245	1	125		0926-001	0926-001	AXIS P1245 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS FA1105 Sensor Unit. The camera provides HDTV 1080p resolution, 111° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance. Comes with a kit for flush mount installation in ceiling/wall.	339



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1254	1	8		0924-001	0924-001	AXIS P1254 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Bullet Sensor Unit that enables easy mounting on walls or ceilings and with the ability to tilt and rotate. The camera provides HDTV 720p resolution and 102° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance.	299
AXIS P1264	1	50		0925-001	0925-001	AXIS P1264 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and AXIS F1004 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 720p resolution and 57° horizontal FoV. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card or NAS. The main unit is powered with PoE. The sensor unit has a pigtail with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind thin metal, plastic or glass panel.	299
AXIS P1265	1	200		0927-001	0927-001	AXIS P1265 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA1125 Pinhole Sensor Unit that is designed for extremely discreet indoor installations. The camera provides HDTV 1080p resolution, 91° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector with a detachable cable (8 m/26 ft.) for easy installation and maintenance. Bracket included for mounting behind a thin metal, plastic or glass panel.	349
AXIS P1275	1	4		0928-001	0928-001	AXIS P1275 Network Camera is a modular camera based on a small-sized main unit (AXIS P12 Mk II) and an AXIS FA4115 Dome Sensor Unit with a varifocal lens that enables easy mounting on walls or ceilings. It can be manually directed with pan, tilt and rotate movements. The camera provides HDTV 1080p resolution, 53-99° horizontal FoV and WDR - Forensic Capture. Supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, and edge storage using microSD card. The main unit is powered with PoE. The sensor unit has a built in connector and a detachable cable (8 m/26 ft.) for easy installation and maintenance.	379
AXIS P1365 Mk II	1		Discontinued contact Order dept for availability	0897-001	0897-001	HDTV 1080p resolution, day/night, fixed camera with CS-mount varifocal 2.8-8 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 60 fps. WDR - Forensic Capture, Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Power over Ethernet. Includes stand with cable management. Power supply not included.	749

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1365-E Mk II	1		Discontinued contact Order dept for availability	0898-001	0898-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, lightweight, HDTV 1080p, day/night, fixed network camera with CS-mount varifocal 2.8-8 mm P-Iris lens and remote back focus (camera also supports DC-iris lenses). Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 60 fps. WDR - Forensic Capture, Lightfinder and Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. MicroSD/MicroSDHC memory card slot for optional local video storage, serial port for RS422/485 communication. Operation in -40°C to +50°C. Powered by IEEE 802.3af midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.	999
AXIS P1365 Mk II BULK 10PCS	1		Discontinued contact Order dept for availability	0897-021	0897-021	AXIS P1365 Mk II in 10-pack. Cannot be sold separately as single packs. No power supplies.	7.399
AXIS P1365 Mk II BAREB	1		Discontinued contact Order dept for availability	0897-041	0897-041	AXIS P1365 Mk II Barebone. No lens. No power supply.	649
AXIS P1365 Mk II BAREB BULK 10PCS	1		Discontinued contact Order dept for availability	0897-051	0897-051	AXIS P1365 Mk II Barebone in 10-pack. Cannot be sold separately as single packs. No lenses. No power supplies.	6.489
AXIS P1375	1	100		01532-001	01532-001	HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	649
AXIS P1375 BAREBONE	1	10		01532-031	01532-031	AXIS P1375 Barebone in single pack. No lens. No power supply.	599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1375-E	1	150		01533-001	01533-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0 technology. Includes an IR corrected varifocal 2.8-8 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Support for optional AXIS Fixed Box IR Illuminator Kit A and AXIS P13 Weathershield Extension A. Serial port for RS422/485 communication. Operation in -40°C to +60°C. Power over Ethernet or 12-28VDC input. Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	899
AXIS P1375-E BAREBONE	1	1		01533-031	01533-031	AXIS P1375-E Barebone. No lens. Midspan not included	849
AXIS P1367	1		Discontinued contact Order dept for availability	0762-001	0762-001	5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 8-28 V DC input. Includes black metal stand with hole for easy cable management. Midspan not included.	729
AXIS P1367 BAREBONE	1		Discontinued contact Order dept for availability	0762-031	0762-031	AXIS P1367 Barebone. No lens. No power supply.	647
AXIS P1367-E	1		Discontinued contact Order dept for availability	0763-001	0763-001	Outdoor, 5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions Includes an IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens and remote back focus (camera also supports i-CS and DC-iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication. Corridor format. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°C and intermittent up to +60°C. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan not included.	930



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1367-E BAREBONE	1		Discontinued - contact Order dept for availability	0763-031	0763-031	AXIS P1367-E Barebone. No lens. Midspan not included	848
AXIS P1377	1	50		01808-001	01808-001	5MP resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included	749
AXIS P1377 BAREBONE	1	5		01808-031	01808-031	AXIS P1377 Barebone in single pack. No lens. No power supply.	699
AXIS P1377-LE	1	125		01809-001	01809-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 5MP resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. OptimizedIR, a power-efficient 850nm IR LED technology covering 50 meters (130 feet).Includes an IR corrected varifocal 2.8-10 mm F1.2 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 5MP at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	999
AXIS P1377-LE BAREBONE	1	1		01809-031	01809-031	AXIS P1377-LE Barebone. No lens. Midspan not included	949



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1368-E	1		Discontinued - contact Order dept for availability	01109-001	01109-001	Outdoor, 4K Ultra HD (8MP) camera, day/night, fixed box camera providing Forensic WDR and Lightfinder for demanding light conditions. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 I-CS lens with P-Iris, remote zoom and focus for installation (camera also supports P-Iris and DC-Iris lenses with CS Mount). Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Two-way audio. I/O for alarm/event handling, Memory card slot for optional local video storage. Serial port for RS422/485 communication NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +55°. Powered by IEEE 802.3af Type 1 Class 3 midspan. Includes a removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan not included.	1.099
AXIS P1368-E BAREBONE	1		Discontinued - contact Order dept for availability	01109-031	01109-031	AXIS P1368-E Barebone. No lens. Midspan not included	999
AXIS P1378	1	20		01810-001	01810-001	4K resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and security lock slot. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. PoE class 3 or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	849
AXIS P1378 BAREBONE	1	6		01810-031	01810-031	AXIS P1378 Barebone in single pack. No lens. No power supply.	799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1378-LE	1	40		01811-001	01811-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, 4K resolution, day/night, fixed box camera providing providing Forensic WDR and Lightfinder technology. Features a 1/1.8" image sensor. OptimizedIR, a power-efficient 850nm IR LED technology covering 40 meters (130 feet).Includes an IR corrected varifocal 3.9-10 mm F1.5 P-Iris lens and remote back focus. Camera also supports CS-mount DC-iris lenses and i-CS lenses for remote installation zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4K at 25/30 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection, active tampering alarm and open casing intrusion switch. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Operation in -40°C to +60°C. PoE+ class4 or 12-28VDC input. Support for optional AXIS P13 Weathershield Extension A. Includes pre-mounted AXIS Fixed Box IR illuminator Kit A, removable sunshield, wall bracket, Torx T20 screw driver and IP66/67-rated cable glands. Midspan or power supply not included.	1.099
AXIS P1378-LE BAREBONE	1	1		01811-031	01811-031	AXIS P1378-LE Barebone. No lens. Midspan not included	1.049
AXIS P1435-LE	1	250	Discontinued contact Order dept for availability	0777-001	0777-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 3-10.5 mm P-iris lens . Remote 3.5 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 30 meters (100 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).	599
AXIS P1435-LE 22MM	1	70		0890-001	0890-001	Compact and outdoor-ready HDTV camera for day and night surveillance, IP66-rated, varifocal 10-22 mm P-iris lens . Remote 2 x optical zoom and focus. Automatic IR cut filter. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Video motion detection, active tampering alarm, corridor format, Lightfinder, Zipstream technology and WDR – Forensic Capture. I/O ports, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 50 meters (164 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -30 °C to 60 °C (-22 °F to 140 °F).	649



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1445-LE	1	60	Discontinued - contact Order dept for availability	01506-001	01506-001	Compact outdoor, HDTV, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps.. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	699
AXIS P1445-LE-3 LICENSE PLATE VERIFIER KIT	1	15		01573-001	01573-001	Please check the supported countries (https://www.axis.com/files/pods/axis_license_plate_verifier_supported_countries_1912.pdf) before ordering. Visit www.axis.com for supported products and application download. Compact outdoor, HDTV / 1080p, day/night, fixed bullet camera with built-in AXIS License Plate Verifier. application. Detect and verify vehicles in single lanes with speed up to 30 km/h (19 mph) in 2 to 7 meter distance (7 to 23 feet) to allow vehicle entry/exit into a controlled area. I/O port for direct control, built-in black and white lists of up to 1000 license plates. License plate reading time less than 1 second. OptimizedIR, Forensic WDR, Lightfinder, shock detection, IK10, IP66/67, NEMA TS-2-2003 v02.06. Operation temperature -40°C to +60°C (-40°F to 140°F), for installation any environment and license plate verification day and night. Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	999
AXIS P1455-LE	1	750		01997-001	01997-001	Compact and outdoor-ready HDTV camera for day and night surveillance. NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution fixed bullet camera providing Forensic WDR and Lightfinder 2.0. Varifocal 3-9 mm F1.6 lens with remote 3 x optical zoom and focus with automatic IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p at 50/60 fps. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm, defogging and corridor format. Audio in and I/O port, microSD/SDHC memory card slot for edge storage. OptimizedIR, a power-efficient LED technology with adaptable angle of IR illumination up to 40 meters (131 feet). Integrated bracket for easy mounting on wall and ceiling. Power over Ethernet. Operating conditions -40 °C to 60 °C (-40 °F to 140 °F). Includes removable sunshield, mounting bracket, Torx L-key, and IP66/67- rated cable glands. Midspan not included.	599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1447-LE	1	300		01054-001	01054-001	Compact outdoor, 5MP resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-8.5 mm F1.2 P-iris lens with remote 3x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 30 meters (98 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	749
AXIS P1448-LE	1	250		01055-001	01055-001	Compact outdoor, 4K Ultra HD (8MP) resolution, day/night, fixed bullet camera providing Forensic WDR and Lightfinder for demanding light conditions. IR corrected varifocal 2.8-9.8 mm F1.6 P-iris lens with remote 3.5x optical zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams; max 4K Ultra HD/8MP at 25/30 fps in 16:9 format. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm, shock detection and corridor format. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. OptimizedIR, a power-efficient IR LED technology covering 25 meters (82 feet). Integrated bracket for easy mounting on wall and ceiling. NEMA 4X, IP66/67 and IK10-rated for operation in -40°C to +60°C(-40 °F to 140 °F). Powered by IEEE 802.3af Type 1 Class 3 midspan (PoE). Midspan not included.	949
AXIS Q1615 Mk II	1		5 Discontinued - contact Order dept for availability	0883-001	0883-001	HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm I-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-Iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles.Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Power supply not included.	999
AXIS Q1615 Mk II BAREBONE	1		1 Discontinued - contact Order dept for availability	0883-041	0883-041	AXIS Q1615 Mk II Barebone in single pack. No lens. No power supply.	899



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1615-E Mk II	1	30	Discontinued - contact Order dept for availability	0884-001	0884-001	Outdoor, NEMA 4X, IP66 and IK10-rated, HDTV, Day/night fixed camera providing WDR – Forensic Capture and Lightfinder for demanding light conditions. Varifocal 2.8-8.5 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution at up to 60 fps second and 720p/1MP resolution at 120 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Scene profiles. Two-way audio and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Arctic Temperature Control, operation in -30°C to 60°C (-22 °F to 140 °F) when powered by IEEE 802.3af midspan or -40°C to 60°C (-40 °F to 140 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1.299
AXIS Q1615 Mk III	1	20		02051-001	02051-001	HDTV 1080p resolution, day/night, fixed box camera providing Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with either built-in microphone or optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Power over Ethernet or 12-28VDC input. Includes black stand for wall and ceiling mount with hole for easy cable management. Midspan or power supply not included.	999
AXIS Q1615-LE Mk III	1	80		02064-001	02064-001	Outdoor, NEMA 4X, IP66/67 and IK10-rated, light weight HDTV 1080p resolution, day/night, fixed box camera providing OptimizedIR, Forensic WDR and Lightfinder 2.0. Includes an IR corrected varifocal 2.8-8.5 mm F1.2 i-CS lens with remote zoom and focus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Axis Zipstream technology for reduced bandwidth and storage needs. Deep learning processing unit, shock detection, intrusion alarm. Barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Two-way audio, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling, MicroSD/MicroSDHC memory card slot for optional local video storage. Serial port for RS422/485 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start-up in -40°C to 60°C (-40 °F to 140 °F). Includes removable sunshield, wall bracket, Torx T20 screw driver and IP66/67- rated cable glands. Midspan or power supply not included.	1.299
AXIS Q1615 Mk III BAREBONE	1	20		02051-041	02051-041	AXIS Q1615 MK III Barebone in single pack. No lens. No power supply.	899

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1645	1	8		01222-001	01222-001	1/2" image sensor, HDTV, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	1.199
AXIS Q1645 BARE BONE	1	2		01222-041	01222-041	AXIS Q1645 Barebone in single pack. No lens. No power supply.	999
AXIS Q1645-LE	1	20		01223-001	01223-001	1/2" image sensor, outdoor, NEMA 4X, IP66 and IK10-rated HDTV, day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; full HDTV 1080p/2MP resolution up to 60 fps with Forensic WDR and up to 120 fps without. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40°F to 140°F). Includes a removable sunshield and wall bracket. Midspan not included.	1.499
AXIS Q1647	1	8		01051-001	01051-001	1/2" sensor, 5 MP, Day/night fixed camera providing Forensic WDR and Lightfinder for demanding light conditions. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus for installation. Support for P-Iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Power over Ethernet or 8-28 V DC input. Includes stand for wall and ceiling mount. Midspan or power supply not included	1.399
AXIS Q1647 BARE BONE	1	2		01051-041	01051-041	AXIS Q1647 Barebone in single pack. No lens. No power supply.	1.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1647-LE	1	40		01052-001	01052-001	1/2" sensor, outdoor, NEMA 4X, IP66 and IK10-rated, 5 MP, Day/night fixed camera providing OptimizedIR, Forensic WDR and Lightfinder. Varifocal 3.9-10 mm i-CS lens with remote zoom and focus. Support for CS-mount P-iris and DC-iris lenses, multiple, individually configurable H.264 and Motion JPEG streams; 5 MP at 30 fps with Forensic WDR, and 4 MP at up to 60 fps without Forensic WDR. Zipstream for reduced bandwidth and storage. Includes analytics AXIS Guard Suite, shock detection and active tampering alarm and shock detection. Barrel distortion correction, Defog and Electronic image stabilization. Scene profiles. Two-way audio and I/O for alarm/event handling. Memory card slot for optional local video storage. Serial port for RS485/RS422 communication. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Built-in heaters and fan, Arctic Temperature Control for start up in -40°C to 60°C (-40 °F to 140 °F). Includes a removable sunshield and wall bracket. Midspan not included.	1.699
AXIS Q1659 BAREBONE	1	1		01568-031	01568-031	<p>Note: Before the order is processed, this product requires an End User Information statement to be submitted to order@axis.com</p> <p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	4.899
AXIS Q1659 10-22MM F/3.5-4.5	1	1		0967-001	0967-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5.899

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1659 24MM F/2.8	1	1		0962-001	0962-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	4.999
AXIS Q1659 35MM F/2	1	1		0963-001	0963-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5.899
AXIS Q1659 50MM F/1.4	1	1		0964-001	0964-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5.399



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1659 85MM F/1.2	1	1		0965-001	0965-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	8.149
AXIS Q1659 100MM F/2.8	1	1		0966-001	0966-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	6.499
AXIS Q1659 70-200MM F/2.8	1	1		0968-001	0968-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	8.399



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1700-LE	1	80		01782-001	01782-001	Robust outdoor, color 2 MP/1080p HDTV license plate camera for sharp license plate images day and night. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p / 2MP resolution at up to 50/60 fps. Varifocal 18–137 mm, 8x optical zoom lens, 16°-2.3° HFOV, F2.9 with remote zoom and installation focus. License plate capture range 20-50 meter at night with built-in OptimizedIR at speeds up to 130 km/h (81 mph) Includes license plate capture assistant for easy setup, pixel counter, shock detection, active tampering alarm, defogging and electronic image stabilization. Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage. Integrated bracket for easy mounting on wall and ceiling. Dark grey (NCS S5502-B) casing, black fixed metal weather shield with anti-glare coating. NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), RJ45 or IDC punchdown connector, 20-28 V DC or 20-24 V AC. License plate recognition software, power supply or midspan not included.	1.299
AXIS Q1765-LE PTMOUNT	1		Discontinued contact Order dept for availability	0644-001	0644-001	Outdoor, IP66 and NEMA 4X-rated, 1080p HDTV camera with 18x optical zoom, auto focus and day/night mode. Integrated IR LED illumination. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 25/30 fps. WDR- dynamic contrast. Video motion detection and active tampering alarm. Serial port supporting RS422/485 communication for connection to a pan-tilt motor. MicroSD/MicroSDHC memory card slot for optional local video storage. Operation in -40°C to +50°C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes a removable sunshield. Power supply, midspan or pan-tilt motor not included.	1.175
AXIS Q1775	1		Discontinued contact Order dept for availability	0751-001	0751-001	1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB @ 30 fps and 90dB @ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SDHC/SDXC memory card slot for optional local video storage. Operation in 0 °C to +50 °C. Powered by PoE (IEEE 802-3af), 8-28 V DC or 20-24 V AC. Includes stand for wall or ceiling mount. Power supply not included.	1.259
AXIS Q1775-E	1		Discontinued contact Order dept for availability	0752-001	0752-001	Outdoor, IP66- and NEMA 4X-rated, 1080p HDTV camera with 10x zoom, auto focus and day/night mode. Multiple, individually configurable H.264 and Motion JPEG streams; max. HDTV 1080p resolution at 50/60 fps. WDR-Dynamic Capture (130dB @ 30 fps and 90dB @ 60 fps). Video motion detection, Gatekeeper functionality and active tampering alarm. Two way audio in 48KHz, I/O and serial port for RS485/RS422 communication. SD/SDHC/SDXC memory card slot for optional local video storage. Arctic Temperature Control, operation in -30°C to 50°C (-22 °F to 122 °F) when powered by IEEE 802.3af midspan or -40 °C to 50 °C (-40 °F to 122 °F) with PoE+ Midspan. Includes a removable sunshield and wall bracket. Midspan not included.	1.511



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1785-LE	1	175		01161-001	01161-001	<p>Robust outdoor, 2 MP/HDTV, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p /2MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus.</p> <p>Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield.</p> <p>Power supply or midspan not included.</p>	1.199
AXIS Q1786-LE	1	70		01162-001	01162-001	<p>Robust outdoor, 4 MP/Quad HD1440p, day/night fixed bullet camera with 32x optical zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1440p /4MP resolution at 50/60 fps. Forensic WDR and Lightfinder for demanding light conditions and Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Varifocal 4.3–137 mm, F1.4 with remote zoom and autofocus.</p> <p>Includes analytics AXIS Guard Suite, shock detection and active tampering alarm. Corridor format, Barrel distortion correction, Defog, Electronic image stabilization and Scene profiles</p> <p>Audio mic/line in, I/O for alarm/event handling and memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>NEMA 4X, IP66/67 and impact resistant in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE (IEEE 802-3af), 20-28 V DC or 20-24 V AC. Includes a removable sunshield.</p> <p>Power supply or midspan not included.</p>	1.399
AXIS Q1798-LE	1	100		01702-001	01702-001	<p>Robust outdoor, NEMA 4X, IP66/67 and IK10-rated 10 MP/ 4K, day/night, fixed bullet camera providing Forensic WDR and Lightfinder 2.0 technology. Features a 4/3" type image sensor, built-in varifocal 12–48 mm, 4 x optical Canon zoom lens, 90°-21° HFOV, F1.7 with remote zoom and autofocus. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4K at 30 fps /10MP resolution at 20 fps.</p> <p>Axis Zipstream technology for reduced bandwidth and storage needs.</p> <p>Includes analytics AXIS Guard Suite, Video motion detection, shock detection and active tampering alarm. Corridor format, barrel distortion correction, defogging and electronic image stabilization. Scene profiles. Audio mic/line in, audio detection with optional analog or digital microphone. Supervised I/O for alarm/event handling. MicroSD/MicroSDHC memory card slot for optional local video storage.</p> <p>OptimizedIR, a power-efficient IR LED technology.</p> <p>Integrated bracket for easy mounting on wall and ceiling.</p> <p>Operation in -40°C to +60°C (-40 °F to 140 °F). Powered by PoE class 4 (IEEE 802-3at), 20-28 V DC or 20-24 V AC. Includes a removable sunshield, Torx T20 allen key, IP66/67- rated cable glands and optional IDC punch connector.</p> <p>Power supply or midspan not included.</p>	1.799

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS F34 MAIN UNIT	1	40		0778-001	0778-001	AXIS F34 Main Unit. 4-channel main unit to be used with any of AXIS F Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Supports edge storage through NAS or SD cards (optional). Two SD card slots. Power over Ethernet or 8-28 V DC input. Power supply not included.	399
AXIS F41 MAIN UNIT	1	125		0658-001	0658-001	AXIS F41 Main Unit. To be used with any of AXIS F Series Sensor Units. Supports full HDTV 1080p and WDR - Forensic Capture. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD card (optional). PoE and 8-28 V DC support.	377
AXIS F44 DUAL AUDIO INPUT	1	150		0936-001	0936-001	AXIS F44 Dual Audio Input Main Unit. 4-channel main unit to be used with any of AXIS F Series Sensor Units. Supports 1080p in 15/12.5 fps or 720p in full frame rate. Two way audio, 4 configurable I/Os with 12 V output and RS232. Supports Edge Storage through NAS or SD cards (optional). Two SD card slots. PoE and 8-28 V DC support. Comes with a stereo-to-mono adapter cable that allows two audio inputs. This article replaces AXIS F44 Main Unit (0659-00x) and the US version of AXIS F44 Dual Audio Input (0936-004).	549
AXIS F1004 SENSOR UNIT	1	70		0765-001	0765-001	AXIS F1004 Sensor Unit with a fixed lens. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. A flush ceiling/wall mount kit is included.	83
AXIS F1004 BULLET SENSOR UNIT	1	6		0935-001	0935-001	AXIS F1004 Bullet Sensor Unit with a fixed lens. Bullet-style mechanics enabling easy mounting on walls or ceilings and with the ability to tilt and rotate. Provides HDTV 720p and 102° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit.	119
AXIS F1004 PINHOLE SENSOR UNIT	1	60		01003-001	01003-001	AXIS F1004 Pinhole Sensor Unit. Pinhole lens for extremely discreet surveillance. Provides HDTV 720p and 57° horizontal FOV. Pigtail for a detachable 8-m (26-ft.) cable for connecting to an AXIS F Main Unit. Comes with a mounting bracket for the sensor unit.	119
AXIS F34 SURVEILLANCE SYSTEM	1	4		0779-002	0779-003	AXIS F34 Surveillance System. Includes one AXIS F34 Main Unit, 4 x AXIS F1004 Sensor Units, 4 x AXIS F8214 Dome Accessory, 4 x AXIS F8224 Recessed Mount, 4 x AXIS F7315 Cable White 15 m (49 ft) for connecting sensor units to the main unit and 2 x AXIS Surveillance microSDXC card 64 GB. Comes with a power supply.	799
AXIS F1005-E SENSOR UNIT 3M	1	100		0675-001	0675-001	AXIS F1005-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	209
AXIS F1005-E SENSOR UNIT 12M	1	60		0676-001	0676-001	AXIS F1005-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	226
AXIS F1015 SENSOR UNIT 3M	1	10		0677-001	0677-001	AXIS F1015 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	234



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS F1015 SENSOR UNIT 12M	1	40		0678-001	0678-001	AXIS F1015 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Vari-focal lens that provides 53° - 108° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	251
AXIS F1025 SENSOR UNIT 3M	1	15		0735-001	0735-001	AXIS F1025 Sensor Unit with a 3 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	209
AXIS F1025 SENSOR UNIT 12M	1	40		0734-001	0734-001	AXIS F1025 Sensor Unit with a 12 meter cable to the main unit. To be used with AXIS F Series Main Units. Pinhole lens that provides 92° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8202 Straight Mounting Bracket.	226
AXIS F1035-E SENSOR UNIT 3M	1	50		0737-001	0737-001	AXIS F1035-E Sensor Unit with a 3 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	209
AXIS F1035-E SENSOR UNIT 12M	1	30		0736-001	0736-001	AXIS F1035-E Sensor Unit with a 12 meter cable to the main unit. IP66 rated. To be used with AXIS F Series Main Units. Fisheye lens that provides 194° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit. Includes one AXIS F8201 Vari-angle Mounting Bracket.	226
AXIS F4005-E DOME SENSOR UNIT	1	20		0775-001	0775-001	AXIS F4005-E Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Comes with a clear dome cover and damask at the back that makes it IK09 and IP66 rated. Fixed lens that provides 110° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	289
AXIS F4005 DOME SENSOR UNIT	1	6		0798-001	0798-001	AXIS F4005 Dome Sensor Unit with a 12-meter (39-feet) cable to an AXIS F Series Main Unit. Recessed dome without a clear dome cover. Fixed lens that provides 113° horizontal FOV. Full HDTV 1080p resolution and support for WDR - Forensic Capture together with AXIS F41 Main Unit.	279
AXIS FA1105 SENSOR UNIT	1	150		0913-001	0913-001	AXIS FA1105 is a discreet indoor sensor unit with 111° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a small hole visible for the lens. AXIS FA1105 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	139
AXIS FA1125 SENSOR UNIT	1	200		0914-001	0914-001	AXIS FA1125 is an extremely discreet indoor, pin hole lens, Sensor Unit with a 91° horizontal field of view, for use with an AXIS FA Main Unit. It can be installed in tight places and flush-mounted in a wall, ceiling or metal panel with only a pinhole visible for the lens. AXIS FA1125 provides a 1080p resolution and Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to a main unit.	149



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS FA3105-L EYEBALL SENSOR UNIT	1	60		01026-001	01026-001	AXIS FA3105-L is a compact eyeball sensor unit with built in IR illumination (15 m / 49 ft range of reach) for use with AXIS FA Main Unit. It has 103° horizontal field of view and 1080p HDTV resolution with Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8 m (26 ft.) cable for connection to the main unit.	149
AXIS FA4115 SENSOR UNIT	1	15		01001-001	01001-001	AXIS FA4115 is a compact varifocal dome sensor unit with 53° to 99° horizontal field of view for use with an AXIS FA Main Unit. AXIS FA4115 provides a 1080p resolution a Forensic WDR (wide dynamic range) that is optimized for low light and motion. The unit comes with a mounting bracket and an 8-m (26 ft.) cable for connection to a main unit.	179
AXIS FA54 MAIN UNIT	1	70		0878-002	0878-003	AXIS FA54 is a modular camera Main Unit and can stream full frame rate HDTV 1080p videos from four sensor units simultaneously using one IP address. It has an HDMI port for connection to a surveillance or public view monitor, Forensic WDR (wide dynamic range) that is optimized for low light and motion, Axis Zipstream, two microphone inputs and one audio out, I/O port and two micro SD card slots for local storage.	449
AXIS COMPANION CUBE L	1		Discontinued - contact Order dept for availability	0891-001	0891-001	Day/night, full HD cube camera for indoor use. Built-in IR illumination, PIR sensor, microphone, speaker and WDR. Fixed lens. HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection. Power over Ethernet. Midspan not included. For use only with AXIS Companion video management software and mobile apps.	199
AXIS COMPANION BULLET LE	1		Discontinued - contact Order dept for availability	0959-001	0959-001	Day/night, outdoor-ready, full HD bullet-style camera. Built-in IR illumination and WDR – Forensic Capture. Fixed lens with 115° HFOV. Automatic IR cut filter. HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and corridor format. Power over Ethernet. Midspan not included. Operating conditions -30 °C to 50 °C (-22 °F to 122 °F). For use only with AXIS Companion video management software and mobile apps.	229
AXIS COMPANION CUBE LW	1		Discontinued - contact Order dept for availability	0892-002	0892-003	AXIS Companion Cube LW is a wireless day/night, full HD cube camera for indoor use. Features high quality video in HDTV 1080p / 2 MP resolution and WDR. Built-in microphone for audio recording, and PIR motion sensor for detecting movement in darkness. IR illumination and day and night functionality. Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™. Axis' Zipstream technology ensures maximized recording time. Self-contained recording solution with included 64 GB high endurance microSD card optimized for surveillance. Power supply included. For use only with AXIS Companion video management software and mobile apps.	279



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1659 55-250MM F/4-5.6	1	1		01118-001	01118-001	<p>Professional photography meets video surveillance</p> <p>AXIS Q1659 Network Camera offers ultra-high image resolution for surveillance in superb detail at 8 frames per second, achieving unprecedented levels of detail for observing open spaces and across long distances.</p> <p>It features digital single-lens reflex (DSLR) imaging technology and offers a choice of Canon EF/EF-S lenses, depending on individual user needs. Equipped with an EF lens mount, the camera enables easy lens changes.</p> <p>AXIS Q1659 is compatible with a broad number of video management systems, and it supports Zipstream that significantly reduces bandwidth and storage requirements.</p> <ul style="list-style-type: none"> > 20 MP resolution > Canon EF mount and EF/EF-S lenses > Axis' Zipstream technology > PoE and SFP slot for optional fiber connectivity > Optional accessory housing 	5.199
AXIS P8815-2 3D Ppl Counter BK	1	20		01787-001	01787-001	<p>AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a black casing.</p>	799
AXIS P8815-2 3D Ppl Counter WH	1	20		01786-001	01786-001	<p>AXIS P8815-2 3D People Counter is a custom-designed stereo camera designed for people counting. The people counter functionality is included; no need to purchase and install a separately licensed product. Main features include: Accurate and reliable 3D people counting. All-in-one solution with reliable hardware. Optimized for challenging conditions. Flexible counting zones. Easy integration in AXIS Store Reporter or 3rd party reporting system. This version comes with a white casing.</p>	799
AXIS M3015	1	175		01151-001	01151-001	<p>Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.</p>	269
AXIS M3016	1	3		01152-001	01152-001	<p>Ultra-discreet, indoor fixed mini dome for recessed mounting in ceiling or wall. Fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 3 MP at 30 fps with WDR. Axis Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.</p>	369
AXIS M3044-V	1		Discontinued contact Order dept for availability	0802-001	0802-001	<p>Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.</p>	199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3044-WV	1		Discontinued - contact Order dept for availability	0803-002	0803-003	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	229
AXIS M3045-V	1		Discontinued - contact Order dept for availability	0804-001	0804-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	269
AXIS M3045-WV	1	15	Discontinued - contact Order dept for availability	0805-002	0805-003	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Connects over wireless LAN (IEEE 802.11b/g/n) or wired Ethernet. Power supply included.	299
AXIS M3046-V 1.8MM	1		Discontinued - contact Order dept for availability	01116-001	01116-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed 1.8mm lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 3 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	369
AXIS M3046-V 2.4mm	1		Discontinued - contact Order dept for availability	0806-001	0806-001	Ultra-compact, indoor fixed mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	369
AXIS M3064-V	1	350		01716-001	01716-001	AXIS M3064-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 83°/45°. D/N functionality with automatically removable IR cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 720p resolution at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	199

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3065-V	1	1600		01707-001	01707-001	AXIS M3065-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	269
AXIS M3075-V	1	175		01709-001	01709-001	AXIS M3075-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 102°/55°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Audio detection and capture with built-in microphone. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	299
AXIS M3066-V	1	700		01708-001	01708-001	AXIS M3066-V is an ultra-compact, indoor fixed mini dome with dust- and IK08 vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens, horizontal/vertical field of view 131°/97°. D/N functionality with automatically removable IR-cut filter. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP at 30 fps with WDR. HDMI output (micro). Zipstream for reduced bandwidth and storage. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet.	369
AXIS M3047-P	1			0808-001	0808-001	Ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	469
AXIS M3048-P	1			01004-001	01004-001	Ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and and tamper-resistant casing for easy mounting on wall or ceiling. Provides 360°/180° overview in up to 30 fps and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps. Multiple, individually configurable H.264 and Motion JPEG streams. Client dewarping also supported. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet. Midspan not included.	669



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3067-P	1	200		01731-001	01731-001	AXIS M3067-P is an ultra-compact, indoor fixed mini dome with 6 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Forensic WDR, Lightfinder and D/N functionality with automatically removable IR cut filter. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 30 fps with WDR, up to 60 fps without. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	469
AXIS M3068-P	1	50		01732-001	01732-001	AXIS M3068-P is an ultra-compact, indoor fixed mini dome with 12 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Forensic WDR and D/N functionality with automatically removable IR cut filter. Provides 360°/180° overview and dewarped panorama, quad, corner, corridor or digital PTZ views in up to 15 fps with WDR, up to 30 fps without. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Signed firmware and secure boot ensure firmware authenticity. Environment-friendly, PVC-free with recycled plastics. Power over Ethernet.	669
AXIS M3025-VE	1		Discontinued - contact Order dept for availability	0536-001	0536-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	461
AXIS M3026-VE	1		Discontinued - contact Order dept for availability	0547-001	0547-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation. Fixed, 106° lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps or 3 MP resolution at 20 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) network cable and is powered using Power over Ethernet. Midspan not included.	545
AXIS M3027-PVE	1		Discontinued - contact Order dept for availability	0556-001	0556-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	629



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3037-PVE	1	30		0548-001	0548-001	Compact, day/night fixed mini dome in a vandal-resistant casing for outdoor or indoor installation, offering 360°/270°/180° panoramic views as well as quad and digital PTZ views. Multiple, individually configurable H.264 and Motion JPEG streams in up to 5MP resolution at 12 fps. Two-way, echo-free audio communication with built-in microphone and speaker. SIP support for IP phone system integration. Memory card slot for optional local video storage. Video motion detection, active tampering alarm and I/O for alarm/event handling. Comes with a 2 m (6.6 ft.) cable with a male RJ-45 network connector and is powered using Power over Ethernet. Midspan not included.	799
AXIS M3057-PLVE	1	100		01177-001	01177-001	360°/180° fixed dome with 6 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 30 fps with WDR and 60 fps with WDR disabled. Distorted panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.	649
AXIS M3058-PLVE	1	100		01178-001	01178-001	360°/180° fixed dome with 12 MP sensor and support for Forensic WDR, Lightfinder and OptimizedIR illumination. Vandal-resistant casing in flat design, for outdoor or indoor installation. Provides complete 360° overview in up to 20 fps with WDR and 30 fps with WDR disabled. Distorted panorama, quad, corner, corridor and up to four digital PTZ views. Client-side dewarping also supported. Multiple, individually configurable H.264 and Motion JPEG streams, Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes. Midspan not included.	849
AXIS M3104-L	1		Discontinued - contact Order dept for availability	0865-001	0865-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	249
AXIS M3104-LVE	1		Discontinued - contact Order dept for availability	0866-001	0866-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 720p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	299

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3105-L	1		Discontinued contact Order dept for availability	0867-001	0867-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	319
AXIS M3105-LVE	1		Discontinued contact Order dept for availability	0868-001	0868-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. Multiple, individually configurable H.264 and Motion JPEG streams; max HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	369
AXIS M3106-L MK II	1		Discontinued contact Order dept for availability	01036-001	01036-001	Day/night, compact mini dome with flat-faced design for indoor use. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	419
AXIS P5654-E 50HZ	1	1		01758-001	01758-001	PTZ camera with 77° field of view, continues 360° pan for both indoor and outdoor with 21x optical zoom. HDTV 720p @ 50fps (1280x720) in H.264/265, Motion JPEG, Axis Zipstream, Lightfinder 2 and Focus Recall, WDR, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	1.599
AXIS M3106-LVE MK II	1		Discontinued contact Order dept for availability	01037-001	01037-001	Day/night, compact mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and fixed lens. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; max 4 MP resolution at 30 fps with WDR. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection and active tampering alarm. Power over Ethernet. Midspan not included.	469
AXIS M3115-LVE	1	250		01604-001	01604-001	AXIS M3115-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 105° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	319
AXIS M3116-LVE	1	90		01605-001	01605-001	AXIS M3116-LVE is a compact mini dome in a flat-faced, outdoor-ready, IK08 impact-resistant design with built-in IR illumination. Fixed lens, 130° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with Forensic WDR and Lightfinder. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet.	419

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3205-LVE	1	300		01517-001	01517-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, 100° field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; HDTV 1080p at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	499
AXIS M3206-LVE	1	90		01518-001	01518-001	Fixed dome with built-in IR illumination and IK10 vandal-resistant casing, designed for easy outdoor or indoor installation. Fixed lens, wide 105°/79° horizontal/vertical field of view. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 4 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection, tampering alarm and supervised digital input / digital output for alarm/event handling. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	599
AXIS M4206-V	1	250		01240-001	01240-001	Ultra-compact, varifocal, D/N mini dome with dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	419
AXIS M4206-LV	1	350		01241-001	01241-001	Ultra-compact, varifocal, D/N mini dome with built-in IR illumination and dust- and vandal-resistant casing for easy indoor mounting on wall or ceiling. 3-6 mm lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams; 3MP for wide 4:3 view, 1080p for 16:9, max 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. HDMI output (micro). Memory card slot for optional local video storage. Power over Ethernet. Midspan not included.	469
AXIS P3224-LV MKII	1		Discontinued contact Order dept for availability	0990-001	0990-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 2.8-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3225-V MKII	1		Discontinued - contact Order dept for availability	0952-001	0952-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	499
AXIS P3225-VE MKII	1		Discontinued - contact Order dept for availability	0953-001	0953-001	Day/night fixed dome with support for WDR – Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	619
AXIS P3225-LV MKII	1		Discontinued - contact Order dept for availability	0954-001	0954-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK08 vandal-resistant indoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	579
AXIS P3225-LVE MKII	1		Discontinued - contact Order dept for availability	0955-001	0955-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10.5 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Axis' Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and weather shield against sun, rain or snow.	699
AXIS P3227-LV	1	250		0885-001	0885-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	779



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3227-LVE	1	125		0886-001	0886-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	899
AXIS P3228-LV	1	250		0887-001	0887-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust- and IK08 vandal-resistant indoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	979
AXIS P3228-LVE	1	70		0888-001	0888-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3.5-10 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264 and Motion JPEG streams. 4K (8MP) at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1.099
AXIS P3235-LVE	1		Discontinued - contact Order dept for availability	01199-001	01199-001	Day/night fixed dome with support for WDR – Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3-10 mm P-Iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes.	749
AXIS P3245-V	1	450		01591-001	01591-001	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	499



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3245-LV	1	500		01592-001	01592-001	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant indoor casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	579
AXIS P3245-VE	1	80		01594-001	01594-001	Fixed dome with support for Forensic WDR and Lightfinder 2.0. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	619
AXIS P3245-LVE	1	600		01593-001	01593-001	Fixed dome with support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR. Zipstream for reduced bandwidth and storage. Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware and secure boot ensure firmware authenticity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	699



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3247-LV	1	1000	To be launched	01595-001	01595-001	AXIS P3247-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall/ceiling or junction boxes.	779
AXIS P3247-LVE	1	650	To be launched	01596-001	01596-001	AXIS P3247-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 3-8 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 5 MP at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	899
AXIS P3248-LV	1	200	To be launched	01597-001	01597-001	AXIS P3248-LV is a day/night fixed dome with discreet, dust- and IK10 vandal-resistant indoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	979
AXIS P3248-LVE	1	250	To be launched	01598-001	01598-001	AXIS P3248-LVE is a day/night fixed dome with IK10 vandal-resistant outdoor casing. It has support for Forensic WDR, Lightfinder 2.0, motion-adaptive exposure for minimized motion blur, and OptimizedIR illumination. Varifocal 4.3-8.6 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. 4K (8MP) at up to 30 fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Power over Ethernet.	1.099



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3255-LVE	1	20	To be launched	02099-001	02099-001	Fixed dome with Deep Learning Processing Unit. Support for Forensic WDR, Lightfinder 2.0 and OptimizedIR illumination. Discreet, dust- and IK10 vandal-resistant outdoor-ready casing. Varifocal 3.4-8.9 mm P-Iris lens with remote zoom and focus simplifying the installation. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. HDTV 1080p up to 60 fps, 30fps with WDR. Zipstream for reduced bandwidth and storage. AXIS Object Analytics, Video motion detection and tampering alarm. Two-way audio and audio detection. Supervised digital input / digital output for alarm / event handling. Signed firmware, secure boot and AXIS Edge Vault ensure firmware authenticity and device identity. Memory card slot for optional local video storage. Powered by IEEE 802.3at Type 2 Class 4 (PoE+). Includes mounting bracket for wall/ceiling or junction boxes.	799
AXIS P3367-V	1	125		0406-001	0406-001	5MP, day/night, fixed dome with discreet, vandal-resistant indoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio with built-in microphone and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers.	839
AXIS P3367-VE	1	40		0407-001	0407-001	5MP, day/night, fixed dome with vandal-resistant, IP66-rated outdoor casing. Varifocal 3-9 mm P-iris lens, remote focus and zoom. Multiple, individually configurable H.264 and Motion JPEG streams; max 5MP resolution at 12 fps or HDTV 1080p at 30 fps. WDR. Video motion detection and active tampering alarm. Two-way audio and audio detection. I/O for alarm/event handling, SD/SDHC memory card slot for optional local video storage. Operation in -40°C to +55°C powered by standard Power over Ethernet. Midspan not included. Includes smoked and clear transparent covers, weather shield against sun, rain or snow, and 5m Ethernet cable with mounted gasket.	1.007
AXIS P3374-V	1	250		01056-001	01056-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	599
AXIS P3374-LV	1	40		01058-001	01058-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 720p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	699

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3375-V	1	300		01060-001	01060-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	699
AXIS P3375-LV	1	175		01062-001	01062-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, IK10 vandal-resistant indoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Power over Ethernet, midspan not included.	799
AXIS P3375-VE	1	175		01061-001	01061-001	Day/night fixed dome with support for WDR-Forensic Capture and Lightfinder. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	899
AXIS P3375-LVE	1	90		01063-001	01063-001	Day/night fixed dome with support for WDR-Forensic Capture, Lightfinder and OptimizedIR with built-in IR illumination. IK10 vandal-resistant outdoor casing. Varifocal 3 – 10 mm P-Iris lens with remote zoom and focus. Multiple, individually configurable H.264 and Motion JPEG streams. HDTV 1080p at 30 fps with WDR, and up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection and active tampering alarm. Two-way audio and audio detection. Supervised input / digital output for alarm / event handling. Memory card slot for optional local video storage. Operation in -40 °C to 55 °C (-40 °F to 131 °F) powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	999
AXIS P3707-PE	1		Discontinued contact Order dept for availability	0815-001	0815-001	Flexible multisensor fixed camera with four 1080p sensors. The lenses can be adjusted to provide a 108° to 54° horizontal field of view for either a wide, panoramic view, or detailed, zoomed-in views. The lenses can be rotated to support vertically oriented scenes in Axis' Corridor Format. Supports individually configurable video streams from each camera head, as well as quad view streaming, enabling 4x 1080p resolution videos at 12.5/15 fps or 4x 720p resolution videos at full frame rate. Axis' Zipstream technology is supported to lower bandwidth and storage requirements. PoE Class 2.	1.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3715-PLVE	1	100		01970-001	01970-001	AXIS P3715-PLVE offers two channels with 2MP per channel, at a frame rate of 30 fps. With its unique peanut-shaped dome design, this multidirectional camera offers cost-effective installation and flexible positioning of both varifocal camera heads. Each head can be controlled individually, so you can capture scenes in two directions in wide angle or zoomed-in views. It features Axis Lightfinder and Axis Forensic WDR for true colors and great details in challenging or poor light. And, remote zoom and focus capabilities ensures fast and accurate installation. Furthermore, Zipstream with support for H.264 significantly lowers bandwidth and storage requirements.	899
AXIS P3717-PLE	1	350		01504-001	01504-001	AXIS P3717-PLE Network Camera is a compact 8-megapixel camera with four varifocal lenses enabling overview and detailed surveillance. With one IP address and one network cable, the four-camera-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, Forensic WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera comes with an integrated weathershield.	1.349
AXIS P3719-PLE	1	125		01500-001	01500-001	AXIS P3719-PLE Network Camera is a compact 15-megapixel camera with four varifocal lenses (4 x Quad HD) enabling overview and detailed surveillance. With one IP address and one network cable, the four-cameras-in-one unit provides a flexible, cost-effective solution for multidirectional surveillance. 360° IR illumination, WDR and Lightfinder technology provides excellent video quality in any light conditions. Each camera head can be individually positioned (pan, tilt, roll, and twist) along a circular track. Remote zoom and focus makes it easy to install and the clear cover, with no sharp edges, ensures undistorted views in all directions. The camera has an integrated weathershield.	1.599
AXIS P3807-PVE	1	175		01048-001	01048-001	AXIS P3807-PVE Network Camera is a fixed dome camera with multiple sensors, providing an easy, reliable and cost-efficient one-camera installation – reducing installation time, cabling and VMS license costs. Thanks to its excellent image sensors, along with Forensic WDR and Lightfinder technology, it provides great video quality in any light conditions. Its four sensors give a seamless 180° panoramic overview, at up to 30 fps in 8 MP resolution. The camera is easy to install as recessed, flush, pendant, back-to-back, and comes with adjustable pre-set camera positions. <ul style="list-style-type: none"> •Seamlessly stitched images •180° horizontal and 90° vertical coverage •8 MP resolution at full frame rate •Axis Lightfinder and Forensic WDR •Axis Zipstream for reduced bandwidth and storage needs 	1.349
AXIS P3904-R Mk II	1	10		01078-001	01078-001	720p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	377
AXIS P3904-R MK II BULK 10PCS	1	20		01078-021	01078-021	AXIS P3904-R MkII (RJ45) in bulk 10-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	3.581
AXIS P3904-R MK II BULK 50 PCS	1	5		01078-031	01078-031	AXIS P3904-R MkII (RJ45) in bulk 50-pack. 720p fixed dome onboard camera with male RJ-45 network connector.	17.885



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3904-R Mk II M12	1	30		01071-001	01071-001	720p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	377
AXIS P3904-R MK II M12 BULK 10PCS	1	30		01071-021	01071-021	AXIS P3904-R MkII (M12) in bulk 10-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	3.581
AXIS P3904-R MK II M12 BULK 50PCS	1	1		01071-031	01071-031	AXIS P3904-R MkII (M12) in bulk 50-pack. 720p fixed dome onboard camera with female M12 D-coded connector.	17.885
AXIS P3905-R Mk II	1	50		01072-001	01072-001	1080p fixed dome onboard camera with male RJ-45 network connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	461
AXIS P3905-R MK II BULK 10PCS	1	5		01072-021	01072-021	AXIS P3905-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	4.379
AXIS P3905-R MK II BULK 50 PCS	1	1		01072-031	01072-031	AXIS P3905-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector.	21.831
AXIS P3905-R Mk II M12	1	10		01073-001	01073-001	1080p fixed dome onboard camera with female M12 D-coded connector. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	461
AXIS P3905-R MK II M12 BULK 10 PCS	1	8		01073-021	01073-021	AXIS P3905-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	4.379
AXIS P3905-R MK II M12 BULK 50 PCS	1	2		01073-031	01073-031	AXIS P3905-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector.	21.831
AXIS P3905-R MK II BAREBONE 10P	1	1		01072-041	01072-041	AXIS P3905-R Mk II (RJ45) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	4.219
AXIS P3915-R Mk II	1	15	Discontinued - contact Order dept for availability	01074-001	01074-001	1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	503
AXIS P3915-R MK II BULK 10 PCS	1	1	Discontinued - contact Order dept for availability	01074-021	01074-021	AXIS P3915-R MkII (RJ45) in bulk 10-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 10-pack.	4.778
AXIS P3915-R MK II BULK 50 PCS	1	1	Discontinued - contact Order dept for availability	01074-031	01074-031	AXIS P3915-R MkII (RJ45) in bulk 50-pack. 1080p fixed dome onboard camera with male RJ-45 network connector, and support for audio and I/O. Accessory kit not included in 50-pack.	23.847
AXIS P3915-R Mk II M12	1	5	Discontinued - contact Order dept for availability	01075-001	01075-001	1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Equipped with 3.6mm, F2.0 lens in ruggedized IP66/67 casing. Includes lens tool, top cover tool, allen key, and drill template.	503
AXIS P3915-R MK II M12 BULK 10 PCS	1	1	Discontinued - contact Order dept for availability	01075-021	01075-021	AXIS P3915-R MkII (M12) in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 10-pack.	4.778
AXIS P3915-R MK II M12 BULK 50 PCS	1	1	Discontinued - contact Order dept for availability	01075-031	01075-031	AXIS P3915-R MkII (M12) in bulk 50-pack. 1080p fixed dome onboard camera with female M12 D-coded connector, and support for audio and I/O. Accessory kit not included in 50-pack.	23.847
AXIS P3905-R MK II M12 BAREBONE 10P	1	10		01073-041	01073-041	AXIS P3905-R Mk II (M12) with no lens in bulk 10-pack. 1080p fixed dome onboard camera with female M12 D-coded connector. Lenses sold separately. Note: Avoid installing lenses in dusty environments. To reduce the risk of dust falling into the sensor, hold the camera with the lens opening facing down.	4.219



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3925-R	1	50		01920-001	01920-001	Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	461
AXIS P3925-R BULK 10P	1	5		01920-021	01920-021	Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with male RJ-45 network connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage	4.379
AXIS P3925-R M12	1	10		01933-001	01933-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	461
AXIS P3925-R M12 BULK 10P	1	2		01933-021	01933-021	Bulk 10-pack of AXIS P3925-R. Full HDTV 1080p fixed dome onboard camera with female M12 D-coded connector for rolling stock and vehicles. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	4.379
AXIS P3925-LRE	1	20		02090-001	02090-001	Compact streamlined exterior onboard camera for rolling stock and vehicles with male RJ-45 network connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3925-LRE BULK 10PCS	1	20		01921-021	01921-021	Bulk 10-pack of the compact streamlined exterior onboard camera for rolling stock and vehicles with male RJ-45 network connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	9.490
AXIS P3925-LRE M12	1	20		02091-001	02091-001	Compact streamlined exterior onboard camera for rolling stock and vehicles with female M12 D-coded connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	999
AXIS P3925-LRE M12 BULK 10PCS	1	20		01934-021	01934-021	Bulk 10-pack of the compact streamlined exterior onboard camera for rolling stock and vehicles with female M12 D-coded connector. The HDTV 1080p camera is equipped with two 850 nm IR LEDs, removable IR-cut filter for day/night functionality and a 6 mm F1.9 lens in a rugged IP6K9K and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology, Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	9.490
AXIS P3935-LR	1	20		01919-001	01919-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	503
AXIS P3935-LR BULK 10P	1	4		01919-021	01919-021	Bulk 10-pack of AXIS P3935-LR. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with male RJ-45 network connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	4.778



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P3935-LR M12	1	10		01932-001	01932-001	Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage. Includes lens tool, L-key, and drill template.	503
AXIS P3935-LR M12 BULK 10P	1	1		01932-021	01932-021	Bulk 10-pack of AXIS P3935-RL. Full HDTV 1080p fixed dome onboard camera for rolling stock and vehicles with female M12 D-coded connector. Invisible 940-nm IR LEDs, I/O for alarm/event handling, built in microphone and external microphone input or line input. Equipped with 2.8mm, F1.6 lens in ruggedized IP66/IP67 and IK10 rated metal casing. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Forensic WDR, Lightfinder technology and removable IR-cut filter for day/night functionality. Axis Zipstream technology for reduced bandwidth and storage needs, microSD/microSDHC/microSDXC memory card slot for optional local video storage.	4.778
AXIS P9106-V BRUSHED STEEL	1	30		01553-001	01553-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Elegant brushed steel design with no visible screws. Dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. Color: Brushed stainless steel.	649
AXIS P9106-V WHITE	1	50		01620-001	01620-001	3MP compact and vandal-resistant (IK10) corner-mounted camera with 1.8mm lens for wide field of view without blind spots. Ligature-resistant design with dust- and waterproof (IP66) casing. WDR, Zipstream, SD card slot and support for portcast technology. Video motion detection and active tampering alarm. PoE Class 1. White in color.	599
AXIS Q3515-LV 9MM	1	175		01039-001	01039-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	849



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q3515-LV 22MM	1	100		01044-001	01044-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	899
AXIS Q3515-LVE 9MM	1	500		01041-001	01041-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 3-9 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	999
AXIS Q3515-LVE 22MM	1	100		01046-001	01046-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 9-22 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 1080p at 30 fps with WDR and Lightfinder, and up to 120 fps without. Zipstream for reduced bandwidth and storage. Fence Guard, Motion Guard, Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1.049

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q3517-LV	1	30		01021-001	01021-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. Discreet, dust and IK10 vandal-resistant indoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes.	1.099
AXIS Q3517-LVE	1	100		01022-001	01022-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1.249
AXIS Q3517-SLVE	1	40		01237-001	01237-001	Day/night fixed dome in a stainless steel (marine-grade SS 316L) outdoor casing, offering high corrosion resistance and IK10+ (50 joules) vandal resistance. Support for Forensic WDR, Lightfinder and OptimizedIR IR illumination. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall/ceiling or junction boxes.	1.349



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q3527-LVE	1	10		01565-001	01565-001	Fixed dome with enhanced security features: signed firmware and secure boot ensure firmware authenticity, and a Trusted Platform Module (TPM) secures certificates and cryptographic keys. Forensic WDR, Lightfinder and OptimizedIR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. 5 MP at 30 fps with WDR, and 4 MP at up to 60 fps with WDR disabled. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for local storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1.349
AXIS Q3518-LVE	1	30		01493-001	01493-001	Day/night fixed dome with support for Forensic WDR, Lightfinder and OptimizedIR with built-in IR illumination. IK10+ vandal-resistant outdoor casing. Varifocal 4.3 – 8.6 mm P-Iris lens with remote zoom and focus for installation or monitoring. Multiple, individually configurable H.264 and Motion JPEG streams. Up to 4K/8MP at 30 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Two-way audio and audio detection. Supervised inputs / digital outputs for alarm / event handling. Electronic image stabilization. Memory card slot for optional local video storage. Operation in -50 °C to 60 °C (-58 °F to 140 °F) powered by standard Power over Ethernet or 8-28V DC power with redundancy. Midspan and power supply not included. Includes mounting bracket for wall or junction boxes and weather shield against sun, rain or snow.	1.349
AXIS Q3615-VE	1	6		0743-001	0743-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; HDTV 1080p at up to 60 fps. Zipstream for reduced bandwidth and storage. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	1.349

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q3617-VE	1	10		0744-001	0744-001	Day/night fixed dome with 1/2" sensor, providing WDR – Forensic Capture and Lightfinder for demanding light conditions. IK10 vandal-resistant outdoor casing. Pan/tilt/roll/zoom for remote installation and readjustment. Motorized varifocal 4.1-9 mm P-Iris lens. Multiple, individually configurable H.264 and Motion JPEG streams; up to 4MP @ 30 fps with WDR, 6 MP @ 20 fps without WDR. Zipstream for reduced bandwidth and storage needs. Video motion detection, shock detection and active tampering alarm. Electronic image stabilization. Memory card slot for optional local video storage. Operation in wide temperature range powered by standard Power over Ethernet. Midspan not included. Includes mounting bracket for wall/ceiling or junction boxes and substantial weather shield against sun, rain or snow.	1.549
AXIS Q3708-PVE	1	60		0801-001	0801-001	180° multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. 3 x QHD resolution, up to 15MP total in 4:3 format. WDR Forensic Capture, Zipstream and one single IP address. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	1.999
AXIS Q3709-PVE	1	20		0664-001	0664-001	Multi-sensor, day/night fixed dome in an IK10 vandal-resistant outdoor casing. Fixed focal, multi-megapixel lenses, focused from factory. Multiple, individually configurable H.264 and Motion JPEG streams; high-quality 4K video in 30 fps from each of 3 sensors and up to 33 MP resolution in total, together providing a 180° view. Video motion detection and active tampering alarm. Operation in wide temperature range powered by standard Power over Ethernet Plus. Midspan not included. Designed for pendant or wall mount arm with same bayonet joint interface as Axis' PTZ domes. Includes weather shield against sun, rain or snow, easily repaintable to blend in with the environment.	2.014
AXIS Q9216-SLV STEEL	1	60		01766-001	01766-001	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: <ul style="list-style-type: none"> • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering 	1.149
AXIS Q9216-SLV WHITE	1	10		01767-001	01767-001	Robust stainless steel corner-mount camera replacing AXIS Q8414 (Trinity). Key features: <ul style="list-style-type: none"> • Anti-ligature, stainless steel, IK10+, IP66, • 4MP, >90° VFoV, >120° HFoV, • 940nm LEDs for invisible IR • H.264 + H.265 with Zipstream, • Built-in microphone, • I/O and optional line-in/out, • Option to further prevent screw-tampering 	1.149
AXIS COMPANION DOME V	1		Discontinued contact Order dept for availability	0894-001	0894-001	Indoor full HD mini dome with dust- and vandal-resistant casing for easy mounting on wall or ceiling. Fixed lens. max HDTV 1080p at 30 fps with WDR. HDMI output (micro). Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection. Power over Ethernet. Midspan not included. For use only with AXIS Companion video management software and mobile apps.	169

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS COMPANION DOME WV	1		Discontinued contact Order dept for availability	0895-002	0895-003	AXIS Companion Dome WV is a wireless full HD mini dome for indoor use. It features high quality video in HDTV 1080p / 2 MP resolution and WDR. Dust- and vandal-resistant casing for easy mounting on wall or ceiling. HDMI output (micro). Connects over wireless LAN (IEEE 802.11a/b/g/n) or wired Ethernet. Supports Wi-Fi Protected Setup™. Axis' Zipstream technology ensures maximized recording time. Self-contained recording solution with included 64 GB high endurance microSD card optimized for surveillance. Power supply included. For use only with AXIS Companion video management software and mobile apps.	249
AXIS COMPANION EYE L	1		Discontinued contact Order dept for availability	0881-001	0881-001	Day/night, full HD mini dome with flat-faced design for indoor use. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection. Power over Ethernet. Midspan not included. For use only with AXIS Companion video management software and mobile apps.	229
AXIS COMPANION EYE LVE	1		Discontinued contact Order dept for availability	0880-001	0880-001	Day/night, full HD mini dome in a vandal-resistant, outdoor-ready, flat-faced design. Built-in IR illumination and WDR – Forensic Capture. Fixed lens. HDTV 1080p resolution at 30 fps. Axis' Zipstream technology for reduced bandwidth and storage needs. Memory card slot for optional local video storage. Video motion detection. Power over Ethernet. Midspan not included. For use only with AXIS Companion video management software and mobile apps.	249
AXIS COMPANION 360	1		Discontinued contact Order dept for availability	01024-001	01024-001	Indoor ultra-compact, 360° panoramic mini dome with 6 MP sensor, fixed lens and tamper-resistant casing for easy mounting on wall or ceiling. Client dewarping and digital pan, tilt and zoom. Axis Zipstream technology for reduced bandwidth and storage needs. HDMI output (micro). Memory card slot for optional local video storage. Video motion detection. Power over Ethernet. Midspan not included. For use only with AXIS Companion video management software and mobile apps.	299
AXIS Q8414-LVS METAL	1		Discontinued contact Order dept for availability	0709-001	0709-001	AXIS Q8414-LVS Network Camera Metal is a brushed stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	1.091
AXIS Q8414-LVS WHITE	1		Discontinued contact Order dept for availability	0710-001	0710-001	AXIS Q8414-LVS Network Camera White is a powder coated stainless steel indoor corner camera with an anti-grip/anti-ligature design to prevent self-harm. Ideal for correctional facilities and psychiatric wards. It supports IK10+ 50 joules impact rating. It is IP66- and NEMA 4X-rated for easy and safe cleaning. Superb images day and night with Lightfinder technology and has built-in invisible IR LED (940 nm). It delivers HDTV 720p or 1.3 Megapixel video, supporting a lens with: P-Iris, varifocal 2.5–6 mm, 105°–49° horizontal angle of view, F1.2. It offers 3 masks and I/O ports. Built-in surface mounted high quality microphone.	1.091



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8685-E 24V AC/DC	1	10		0862-001	0862-001	High accuracy outdoor PTZ positioning camera. HDTV 1080p video, 30x optical zoom, focus recall, extreme light sensitivity and Axis Zipstream. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	3.599
AXIS Q8685-LE 24V AC/DC	1	6		0864-001	0864-001	High accuracy outdoor PTZ positioning camera with IR illuminators. HDTV 1080p video, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance, and integrated SFP slot for long-distance fiber connection. IK10, IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included)	5.199
AXIS M5054	1	70		01079-001	01079-001	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 720p (1280x720) 25/30fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	499
AXIS M5055	1	1		01081-001	01081-001	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 1080p (1920x1080) 30/25fps in H.264 with Zipstream and Motion JPEG. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included	599
AXIS M5065 Z-WAVE EUR	1	4		01107-002	01107-002	Ceiling-mount mini PTZ dome camera with 5x Optical zoom and autofocus, HDTV 1080p (1920x1080) 30fps in H.264 with Zipstream and Motion JPEG. 4 wireless I/O using Z-wave communication. IP51 protection against dust and water. Basic analytics are included. Only PoE, midspan not included. Surface ceiling mounting brackets included.	599
AXIS M5525-E 50HZ	1	30		01145-001	01145-001	Discreet PTZ with HDTV 1080p, 1920x1080, 10x optical zoom, automatic day/night and autofocus. Continues 360° pan. WDR- Forensic Capture, IP66, PoE and 24V. 30fps in H.264 and Motion JPEG, Zipstream, Scene profiles, two-way audio, 4 I/O. Surface mount or Axis PTZ standard mount. Midspan not included.	999
AXIS P5414-E 50HZ	1	10		0544-001	0544-001	Intelligent Direct Drive PTZ camera with HDTV 720p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	1.343
AXIS P5415-E 50HZ	1	20		0546-001	0546-001	Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	1.679
AXIS P5415-E 60HZ	1	1		0589-001		Intelligent Direct Drive PTZ camera with HDTV 1080p, day/night and 18x zoom, designed for mounting on a wall or building. No extra bracket are needed, build in junction box. Audio In/Out, full size SD card, 24 V DC, 4 configurable I/Os and Ethernet connector with PoE. Repaintable sunshield covering the entire unit. Power supply not included.	1.679



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8665-E 230V AC	1		Discontinued contact Order dept for availability	0716-001	0716-001	High speed and precision PT-head design PTZ camera with integrated wiper. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 100°/s, tilt speed: 0.02°/s to 40°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 230V AC.	4.198
AXIS Q8665-LE 24V AC	1		Discontinued contact Order dept for availability	0718-001	0718-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). Power input 24V AC.	4.366
AXIS Q8665-LE 230V AC	1		Discontinued contact Order dept for availability	0719-001	0719-001	High precision PT-head design PTZ camera with integrated wiper and IR illuminators enabling a viewing range in darkness up to 150m. HDTV 1080p resolution and 18x optical zoom. Pan speed: 0.02°/s to 40°/s, tilt speed: 0.02°/s to 30°/s. Continuous pan rotation, 360° endless and +90° to -40° tilt. IP66-rated and NEMA 4X-rated, operating temperature -40 °C to 55 °C (-40 °F to 131 °F). External power supply with power input 230V AC and integrated light sensor for IR illuminator control included.	5.457
AXIS P5624-E MK II 50HZ	1		Discontinued contact Order dept for availability	0931-001	0931-001	PTZ camera with continues 360° pan for both indoor and outdoor with 23x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264, Motion JPEG and Axis Zipstream and Focus Recall, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot, smoked and clear dome. Mounting brackets and Midspan are not included.	1.599
AXIS P5635-E MK II 50HZ	1		Discontinued contact Order dept for availability	0930-001	0930-001	PTZ camera with continues 360° pan for both indoor and outdoor with 30x optical zoom Autofocus and Focus Recall. HDTV 1080p @ 25fps (1920x1080) in H.264, Motion JPEG and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	1.999
AXIS P5655-E 50HZ	1	10		01681-001	01681-001	PTZ camera with continues 360° pan for both indoor and outdoor with 32x optical zoom, Lightfinder 2, Autofocus and Focus Recall. HDTV 1080p @ 25/50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Two-way audio, 4xI/O, 24V and PoE, Day & Night, IP66, IK10 and NEMA 4X classification. Advanced Gatekeeper, full-size SD-card slot. Mounting brackets, Midspan/Power supply and connector or cable for audio, I/O and 24V are not included.	1.999
AXIS Q6000-E 50HZ MK II	1			01005-001	01005-001	Outdoor-ready 360° situational awareness camera, comprising 4x2MP sensors @ 25fps in H.264 Zipstream and Motion JPEG. Tilttable sensors with exchangeable lenses. Designed to be integrated with any AXIS Q60-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	1.599

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q6010-E 50HZ	1	1		01980-001	01980-001	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N, Autopilot for tracking. Designed to be integrated with AXIS Q605x-E and AXIS Q607x-E series camera for large area coverage and simultaneous zoomed-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q60-E.	1.599
AXIS Q6100-E 60HZ	1	6	To be launched	01711-001		Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N. Directional Audio Detection. Designed to be integrated with any AXIS Q61-series camera for large area coverage and simultaneous zoom-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q61	1.599
AXIS Q6054 Mk III 50HZ	1		Discontinued contact Order dept for availability	01481-002	01481-002	HDTV 720p compliant, high-speed PTZ dome camera with 30x optical zoom for indoor use. HDTV 720p @ 25 fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP52. Continuous 360° rotation and 220° tilt with E-flip. Lightfinder, Focus recall, Zipstream, WDR, EIS, Automatic Defogging, shock detection. Full-size SD slot. Two-way audio, four I/Os and external power with multi-connector cable (not included). Includes High PoE midspan, smoked and clear dome covers, and mounting kits for hard and drop ceilings.	2.099
AXIS Q6054-E Mk III 50HZ	1		Discontinued contact Order dept for availability	01483-002	01483-002	HDTV 720p compliant, outdoor-ready, high-speed PTZ dome camera with 30x optical zoom. HDTV 720p @ 25fps (1280x720) in H.264 and Motion JPEG, Day & Night, IP66, IK10 and NEMA 4X classification. Continuous 360° rotation and 220° tilt with E-flip. Lightfinder, Focus recall, Zipstream, WDR, EIS, automatic defogging, shock detection, Arctic Temperature Control enables operation and start up from from -50 °C to +50 °C (-58 °F to 122 °F). Active Gatekeeper, tour recording and autotracking. Includes High PoE midspan with fiber slot and clear dome cover. Mounting brackets are not included (several different accessories available)	2.599
AXIS Q6055-C 50HZ	1			0942-001	0942-001	Actively cooled, outdoor-ready high-speed PTZ dome camera with 32x optical zoom. IP66-, MIL-, IK10 and NEMA 4X-rated. Temperature range -20 °C to +75 °C. Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. HDTV 1080p (1920x1080) @ 25 fps. 720P@50 fps. Shock detection, autotracking, tour recording and Active Gatekeeper. Highlight compensation. Basic built-in analytics: object removed, fence detector, object counter, enter/exit detection, video motion detection. Including 7m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24 V in. Power supply and brackets are not included. (several different accessories available).	4.099



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q6074 50HZ	1	1		01967-002	01967-002	Top performance PTZ camera with HDTV 720p @50fps 30x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2.099
AXIS Q6074-E 50HZ	1	80		01973-002	01973-002	Top performance PTZ camera with HDTV 720p @50fps, 30x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	2.599
AXIS Q6075 50HZ	1	30		01749-002	01749-002	Top performance PTZ camera with HDTV 1080p @50fps 40x optical zoom for indoor use. IP52 rated. Zipstream with H.264/ H.265. Auto day/night functionality. Continuous 360° rotation and 180° tilt with E-flip. Two-way audio, I/O and external power with multi-connector cable (not included). Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear and smoked transparent dome cover and High PoE midspan are included. Mounting kits for hard and drop ceilings	2.549
AXIS Q6075-E 50HZ	1	7		01751-002	01751-002	Top performance PTZ camera with HDTV 1080p @50fps, 40x optical zoom, outdoor-ready, IP66, IK10 and NEMA 4x-rated. Zipstream with H.264/ H.265, Arctic Temperature Control enables operation and start up from -40 °C to +50 °C (-58 °F to 122 °F). Auto day/night functionality. Continuous 360° rotation and 220° tilt with E-flip. Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover and High PoE midspan with fiber slot are included. No mounting bracket included (several different accessories available).	3.099

Axis Communications			DECEMBER-2020, EUR				
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q6075-S 50HZ	1	10		01755-001	01755-001	Stainless steel, (SS-316L) pressurized (5psi) Top performance HDTV 1080p compliant, outdoor-ready, IP66, IK10 and NEMA 4X-rated PTZ dome camera with 40x optical zoom. Auto day/night functionality. Continuous 360° rotation and 220° tilt. HDTV 1080p (1920x1080) @50fps. Zipstream with H.264/ H.265 Shock detection, Autotracking 2, tour recording and Active Gatekeeper. Compass ruler overlay, Privacy mask with mosaic. Highlight compensation. Build in analytics; object removed, loitering guard, fence detector, object counter, enter/exit detection, video motion detection. Clear transparent dome cover. Including 7 m cable, media converter switch with 2xSFP slots for optical fiber modules, 2xRJ-45, 2xI/O and 24V in. Brackets and power adapter are not included (several different accessories available).	4.499
AXIS Q6100-E 50HZ	1	50	To be launched	01710-001	01710-001	Outdoor-ready 360° situational awareness camera, comprising of 4x5MP sensors @ 20fps in H.264/H.265 Zipstream and Motion JPEG. Movable sensors with exchangeable lenses. Autofocus, D/N. Directional Audio Detection. Designed to be integrated with any AXIS Q61-series camera for large area coverage and simultaneous zoom-in view, using the one-click PTZ control feature. Full size SD-card slot. No extra equipment required, as it uses the same brackets, power supply and network cable as the connected AXIS Q61.	1.599
AXIS Q6124-E 50HZ	1		Discontinued contact Order dept for availability	01069-002	01069-003	Lightfinder HDTV PTZ for outdoor as well as indoor use. HDTV 720p resolution in 50fps with 30x zoom and top performance. Perfect image quality in all directions, without distortion. 130db WDR, EIS, automatic defog, Advanced gate keeper. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot included.	2.348
AXIS Q6125-LE 50HZ	1	250		01233-002	01233-003	Top of the line PTZ with IR, HDTV 1080 and 30x optical zoom, H264/265 with Zipstream and Motion JPEG. IP66 for both indoor and outdoor use, WDR . Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper analytics. With its compact size and repaintable surface, it will easily blend into the surroundings. Midspan with fiber slot and RJ45 input included.	2.999
AXIS Q6135-LE 50HZ	1	20	To be launched	01958-002	01958-003	PTZ camera with continues 360° pan and build in IR illumination (200M) with 32x optical zoom, Autofocus and Focus Recall. HDTV 1080p @ 50fps (1920x1080) in Motion JPEG, H.264, H.265, and Axis Zipstream. Day & Night, IP66, NEMA 4X and NEMA TS2 classification. Full-size SD-card slot. Perfect image quality in all directions without distortion. WDR, EIS, Speed dry. Includes Advanced gate keeper and analytics. Repaintable surface. Midspan with fiber slot and RJ45 input included.	2.499
AXIS Q6128-E 50HZ	1	50		0800-002	0800-003	Compact, top performance 4K Comparable with SMPTE 2036 3840x2160 resolution in 25fps, (8MP). With 12x optical zoom for outdoor as well as indoor use. Day/night, Automatic defog, DNR 2D/3D and EIS. IP66, Active gatekeeper, tour recording and autotracking. Perfect image quality in all directions, without distortion, repaintable surface. Mounting brackets are not included (several different accessories available). Midspan with fiber slot included	3.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q6154-E 50HZ	1	20		01510-002	01510-003	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 720p resolution in 50fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	2.418
AXIS Q6155-E 50HZ	1	1		0933-002	0933-003	Compact top performance HDTV PTZ for outdoor and indoor use with unique Laser Focus giving perfect focus. HDTV 1080p resolution in 25fps, perfect image quality in all directions without distortion due to Axis' Sharpdome technology with hard coating. Repaintable surface, will easily blend into the surroundings. 30x zoom 120dbWDR, EIS, automatic defog, Advanced gate keeper and Lightfinder. Midspan with fiber slot included	2.518
AXIS Q6215-LE 50HZ	1	175		01083-002	01083-003	PTZ for the toughest conditions. MIL specified, build in IR illumination 400M (1300i), can be mounted face up or face down. IP66/67/68, IK10, MIL 8105 521. Camera part; 1/2" sensor with HDTV 1080p, 30x optical zoom, 50fps, H264 with Zipstream and Motion JPEG, WDR. Perfect image quality in all directions without distortion, window wiper. Advanced gate keeper analytics. 90W Midspan included. Color; Urban grey.	3.499
AXIS V5925 50 Hz	1	10	New	01965-002	01965-003	Generic PTZ camera with 30x zoom, autofocus and HDTV 1080p resolution at 50fps for live streaming of video and audio. "Video conference" design, smooth pan and tilt, EIS. HDMI, 3G-SDI, XLR-3 for studio connectivity. Studio quality in stereo. Power supply and wall mount bracket are included.	1.999
AXIS Q8752-E 35 MM 30 FPS	1	20	New	01838-001	01838-001	High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	12.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8752-E 35 MM 8.3 FPS	1	20	New	01839-001	01839-001	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	12.999
AXIS Q8752-E ZOOM 30 FPS	1	20	New	01841-001	01841-001	<p>High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included).</p> <p>This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.</p>	21.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8752-E ZOOM 8.3 FPS	1	20	New	01840-001	01840-001	High accuracy outdoor PTZ positioning Bispectral camera based on AXIS ARTPEC7 platform. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 32x optical zoom, focus recall and is extremely light sensitive. EIS (Electronic Image Stabilization) on both channels ensures focused and stable video. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.265 and local storage. Included cybersecurity features are TPM-module, Axis secure boot and comes with signed FW. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	21.999
AXIS Q8641-E 35MM 30 FPS 24V	1	1		01119-001	01119-001	High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.799
AXIS Q8641-E 35MM 8.3 FPS 24V	1	1		01120-001	01120-001	High accuracy outdoor PT positioning thermal camera. 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8642-E 60MM 30 FPS 24V	1	1		01121-001	01121-001	High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 30 fps and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	9.499
AXIS Q8642-E 60MM 8.3 FPS 24V	1	1		01122-001	01122-001	High accuracy outdoor PT positioning thermal camera. 640x480 resolution, 8.3 fps and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	9.499
AXIS Q8741-E 35MM 30 FPS 24V	1	1		0824-001	0824-001	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	9.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8741-LE 35MM 30 FPS 24V	1	1		01013-001	01013-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 30 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	11.599
AXIS Q8741-E 35MM 8.3 FPS 24V	1	1		0823-001	0823-001	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	9.999
AXIS Q8741-LE 35MM 8.3 FPS 24V	1	1		01012-001	01012-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 384x288 resolution, 8.3 fps and 35 mm lens with 10.5° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	11.599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8742-E ZOOM 30 FPS 24V	1	2		0830-001	0830-001	High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	21.999
AXIS Q8742-E ZOOM 8.3 FPS 24V	1	1		0829-001	0829-001	High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	21.999
AXIS Q8742-E 35MM 30 FPS 24V	1	1		0828-001	0828-001	High accuracy outdoor PTZ positioning Bispectral camera. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	12.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8742-LE 35MM 30 FPS 24V	1	1		01017-001	01017-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 30 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	14.599
AXIS Q8742-E 35MM 8.3 FPS 24V	1	1		0827-001	0827-001	High accuracy outdoor PTZ positioning bispectral camera. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, focus recall and are extremely light sensitive. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	12.999
AXIS Q8742-LE 35MM 8.3 FPS 24V	1	1		01016-001	01016-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35 mm lens with 17° angle of view. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera only need one IP address and supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	14.599



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8742-LE ZOOM 30 FPS 24V	1	2		01019-001	01019-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 30 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	23.599
AXIS Q8742-LE ZOOM 8.3 FPS 24V	1	1		01018-001	01018-001	High accuracy outdoor PTZ positioning bispectral camera with IR illuminators. Thermal sensor features a 640x480 resolution, 8.3 fps and 35-105 mm thermal zoom lens. Visual sensor have HDTV 1080p video resolution, 30x optical zoom, built-in IR pass filter for sharper images in mixed lighting conditions. IR range up to 500m. Integrated long-life silicone wiper for remote maintenance. The bispectral camera supports Zipstream, ONVIF, H.264 and local storage. It includes Video motion detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. Responsive absolute positioning with high-speed and ultra-smooth pan and tilt capabilities. Integrated SFP slot for long-distance fiber connection. IP66, NEMA 4X rated and UL listed. Ready for column-mount. Powered by 24 V AC/DC from external power supply (not included). This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	23.599
AXIS P1280-E 2.2 MM 8.3 FPS	1	2	To be launched Description changed	02114-001	02114-001	<p>AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/39.4ft cable. The camera provides 208x156 resolution, a 2.2 mm lens with 63° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	799

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P1280-E 4MM 8.3 FPS	1	2		0940-001	0940-001	<p>AXIS P1280-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The flexible form factor allows it to be placed in locations with limited space and a wide range of mounting accessories enables wall, ceiling and recessed installations. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	799
AXIS P1290-E 4 MM 8.3 FPS	1	2		01168-001	01168-001	<p>AXIS P1290-E Thermal Network Camera is a modular thermal camera based on a small-sized main unit (AXIS P12 Thermal) and an outdoor ready thermal sensor unit with a 12 m/ 39.4ft cable and dome casing. The camera provides 208x156 resolution, a 4 mm lens with 35.4° horizontal FOV. It supports multiple streams in H.264 and Motion JPEG, Axis' Zipstream technology for lower bandwidth and storage needs, edge storage using microSD card and built-in analytics with support for AXIS Camera Application Platform, which enables the usage of a broad range of third-party applications. The main unit is powered with PoE. The sensor unit has 12 m/39.4 ft cable.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	849
AXIS Q1941-E 7MM 30 FPS	1	20		0786-001	0786-001	<p>Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed.</p> <p>This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.</p>	2.799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1941-E 7MM 8.3 FPS	1	4		0782-001	0782-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799
AXIS Q1941-E 13MM 30 FPS	1	5		0787-001	0787-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	2.799
AXIS Q1941-E 13MM 8.3 FPS	1	1		0783-001	0783-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799
AXIS Q1941-E 19MM 30 FPS	1	10		0877-001	0877-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	2.799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1941-E 19MM 8.3 FPS	1	3		0876-001	0876-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799
AXIS Q1941-E 35MM 30 FPS	1	7		0788-001	0788-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	3.799
AXIS Q1941-E 35MM 8.3 FPS	1	2		0784-001	0784-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	3.799
AXIS Q1941-E 60MM 30 FPS	1	1		0789-001	0789-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	5.299



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1941-E 60MM 8.3 FPS	1	1		0785-001	0785-001	Outdoor thermal network camera for wall and ceiling mount, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.299
AXIS Q1941-E PT MOUNT 7MM 30 FPS	1	1		0973-001	0973-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	2.799
AXIS Q1941-E PT MOUNT 7MM 8.3 FPS	1	1		0969-001	0969-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 7 mm lens with 55° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799
AXIS Q1941-E PT MOUNT 13MM 30 FPS	1	1		0974-001	0974-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	2.799
AXIS Q1941-E PT MOUNT 13MM 8.3 FPS	1	1		0970-001	0970-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 13 mm lens with 28° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1941-E PT MOUNT 19MM 30 FPS	1	1		0979-001	0979-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	2.799
AXIS Q1941-E PT MOUNT 19MM 8.3 FPS	1	1		0978-001	0978-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 19 mm lens with 19.4° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	2.799
AXIS Q1941-E PT MOUNT 35MM 30 FPS	1	1		0975-001	0975-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	3.799
AXIS Q1941-E PT MOUNT 35MM 8.3 FPS	1	1		0971-001	0971-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 35 mm lens with 10.7° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	3.799



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1941-E PT MOUNT 60MM 30 FPS	1	1		0977-001	0977-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 30 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	5.299
AXIS Q1941-E PT MOUNT 60MM 8.3 FPS	1	1		0972-001	0972-001	Outdoor Thermal Network Camera for positioning unit, 384x288 resolution, 8.3 fps, and 60 mm lens with 6.2° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.299
AXIS Q1942-E 10MM 30 FPS	1	8		0916-001	0916-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	4.999
AXIS Q1942-E 10MM 8.3 FPS	1	2		0915-001	0915-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	4.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1942-E 19MM 30 FPS	1	7		0918-001	0918-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	4.999
AXIS Q1942-E 19MM 8.3 FPS	1	2		0917-001	0917-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 19 mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	4.999
AXIS Q1942-E 35MM 30 FPS	1	6		0920-001	0920-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	5.999
AXIS Q1942-E 35MM 8.3 FPS	1	1		0919-001	0919-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 35 mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1942-E 60MM 30 FPS	1	3		0922-001	0922-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 30 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	7.499
AXIS Q1942-E 60MM 8.3 FPS	1	1		0921-001	0921-001	Outdoor thermal network camera for wall and ceiling mount, 640x480 resolution, 8.3 fps, and 60 mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, audio, I/O ports and local storage. It includes Video motion detection, audio detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, IP67, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	7.499
AXIS Q1942-E PT MOUNT 10MM 30 FPS	1	1		0981-001	0981-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	4.999
AXIS Q1942-E PT MOUNT 10MM 8.3 FPS	1	1		0980-001	0980-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 10mm lens with 63° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	4.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1942-E PT MOUNT 19MM 30 FPS	1	1		0983-001	0983-001	Q1942-E PT mount 19mm Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 19mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	4.999
AXIS Q1942-E PT MOUNT 19MM 8.3 FPS	1	1		0982-001	0982-001	Q1942-E PT mount 19mm Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 19mm lens with 32° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	4.999
AXIS Q1942-E PT MOUNT 35MM 30 FPS	1	1		0985-001	0985-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 35mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	5.999
AXIS Q1942-E PT MOUNT 35MM 8.3 FPS	1	1		0984-001	0984-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 35mm lens with 17° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	5.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q1942-E PT MOUNT 60MM 30 FPS	1	1		0987-001	0987-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 30 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is controlled for export under EU Regulation (EC) № 428/2009 and Export Control Classification Number (ECCN) 6A003.b.4.b applies. Licensing requirements may affect the lead time for delivery and/or general order status. If in doubt, please contact customs-se@axis.com for guidance on the license application procedure.	7.499
AXIS Q1942-E PT MOUNT 60MM 8.3 FPS	1	1		0986-001	0986-001	Outdoor Thermal Network Camera for positioning unit. 640x480 resolution, 8.3 fps, and 60mm lens with 10° angle of view. It supports Electronic Image Stabilization, Zipstream, ONVIF, H.264, PoE and local storage. It includes Video motion detection, shock detection and support for AXIS Camera Application Platform enabling installation of AXIS Perimeter Defender and third-party applications. IP66, NEMA 4X rated and UL listed. This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.	7.499
AXIS Q2901-E 9MM 8.3 FPS	1	15		0645-001	0645-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	4.366
AXIS Q2901-E PTMOUNT 9MM 8.3 FPS	1	1		0646-001	0646-001	AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 35° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	4.366
AXIS Q2901-E 19MM 8.3 FPS	1	2		0647-001	0647-001	AXIS Q2901-E Temperature alarm camera for wall and ceiling mount, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, audio, local storage, I/O, PoE, shock detection, AXIS Video Motion Detection 3.0, audio detection and AXIS Camera Application Platform. The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.	4.366

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q2901-E PTMOUNT 19MM 8.3 FPS	1	1		0648-001	0648-001	<p>AXIS Q2901-E PT Mount Temperature alarm camera ready for pan/tilt motor head, IP66-rated, 336x256 resolution, 8.3 fps, and 17° angle of view. Six temperature alarm zones, isothermal palettes and spot temperature. It supports ONVIF, H.264, local storage, RS422/RS485, PoE, shock detection, AXIS Video Motion Detection 3.0, and AXIS Camera Application Platform.</p> <p>The product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	4.366
AXIS FA1080-E 2.2MM 8.3 FPS	1	20	To be launched	02089-001	02089-001	<p>AXIS FA1080-E 2.2MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 2.2 mm lens with 63° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	649
AXIS FA1080-E 4MM 8.3 FPS	1	1		01728-001	01728-001	<p>AXIS FA1080-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The flexible form factor allows it to be placed in locations with limited space and can be used with a wide range of mounting accessories to enable wall, ceiling and recessed installations. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	649
AXIS FA4090-E 4MM 8.3 FPS	1	1		01729-001	01729-001	<p>AXIS FA4090-E 4MM 8.3 FPS is a modular thermal sensor unit to be used together with AXIS FA54 Main Unit. The thermal sensor unit provides 208x156 resolution and includes a 4 mm lens with 35.4° horizontal FOV. The dome housing makes it easy to install and direct the sensor unit to cover your area of interests. The sensor unit is outdoor-ready and has 12 m/39.4 ft cable.</p> <p>This product contains U.S.-origin controlled technology/component, the US Export Administration Regulations (EAR) are always applicable to the product. You should comply at all times with all applicable national and international (re-) export control regulations.</p>	699
CANON SUNSHADE COVER SC640-VB	1	1		0723C001	0723C001	<p>Sunshade cover for VB-H651LVE/VE outdoor Domes. Includes securing bolts for easy installation.</p>	76
CANON SMOKED DOME UNIT DU10-S-VB	1			0721C001	0721C001	<p>Smoked dome cover for VB-R1xVE & VB-R1x PTZ Domes</p>	74
CANON SMOKED DOME UNIT DU640-S-VB	1	1		0722C001	0722C001	<p>Smoked dome cover for VB-H651VE/V & VB-M64xVE/V domes</p>	40
CANON WALL MOUNTING KIT WM10-VB	1	1		0720C001	0720C001	<p>Wall mount bracket for VB-R1xVE outdoor PTZ Domes. Consisting of heavy duty metal hinged cable box, right angle extender and PA10-15-VE bayonet camera fitting - 215mm stand-off.</p>	415



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON PLEN REC MOUNTKIT SR640-P-VB	1	1		0717C001	0717C001	Indoor recessed ceiling mount kit for VB-H651V/M64xV domes. Comprising of in-ceiling cage and cover - Titanium White	318
CANON HEATER UNIT HU641-VB	1	1		0724C001	0724C001	Optional heater element for VB-H651VE/M641VE outdoor Domes. Requires 24V AC power.	116
CANON PLE. REC MOUNT KIT SR30-P-VB	1	1		1065C001	1065C001	Indoor plenum recessed ceiling mount kit for VB-S30D/S31D/S80xD mini-domes. Comprising of fire resistant in-ceiling cage and cover - Titanium White	110
CANON CEILIN MOUNT COV S SS40-S-VB	1	1		4962B001	4962B001	Indoor surface mount ceiling cover (Silver) for VB-H43/M42 PTZ's Comprising of a metal mounting plate and "skirt" cover - Silver	56
CANON CEILING MOUNTING KIT CM10-VB	1			0711C001	0711C001	Ceiling mount Back Box for VB-R1xVE outdoor PTZ Domes. Consisting of heavy duty metal hinged cable box and PA10-15-VE bayonet camera fitting - 342mm drop.	334
CANON 1.5 IN PIPE ADPT PA10-15-VB	1			0718C001	0718C001	1.5inch Pipe Adaptor for VB-R1xVE outdoor PTZ Domes with standard NPSM screw thread and bayonet camera fitting - 100mm long.	78
CANON REC MOUNT KIT SR640-S-VB	1			0715C001	0715C001	Indoor recessed ceiling mount kit for VB-H651V/M64xV domes. Comprising of in-ceiling cage and cover - Titanium White	251
CANON CONDUIT BOX CB740-VB	1	1		0712C001	0712C001	Conduit box for VB-H76x/H751LE/M74x outdoor bullets.	107
CANON PENDANT MOUNTING KIT PC640-VB	1	1		0719C001	0719C001	Indoor pendant mounting cap for VB-R13/11 indoor PTZ Domes, VB-H65x/M64x domes, and VB-H76x/H751LE/M74x bullets. Comprising of 1.5inch NPSM threaded pipe adaptor / cover - Titanium White.	81
CANON CONDUIT ADAPTER CA640-VB	1			0713C001	0713C001	Conduit adaptor for VB-M64xVE outdoor Domes.	94
CANON CEILIN MOUNT COV B SS40-B-VB	1	1		4962B002	4962B002	Indoor surface mount ceiling cover (Black) for VB-H43B/M42B PTZ's. Comprising of a metal mounting plate and "skirt" cover - Black	56
CANON INDOOR DOME HOUSING DR41-C-VB	1	1		6816B001	6816B001	Indoor recessed ceiling mount kit for VB-H43(B) & VB-M42(B) PTZ's. Comprising of in-ceiling cage and Clear Dome - Silver	195
CANON INDOOR DOME HOUSING DR41-S-VB	1			6816B002	6816B002	Indoor recessed ceiling mount kit for VB-H43(B) & VB-M42(B) PTZ's. Comprising of in-ceiling cage and Smoked Dome - Silver	195
CANON SURFACE MOUNT SPACER SS30-VB	1	1		9920B001	9920B001	Indoor surface mount wall/ceiling spacer for VB-S30D/S31D/S80xD mini-domes.	47
CANON A-BK3	1			0031X775	0031X775	Pole mount adaptor, Aluminum (Black) for poles 100-400mm in diameter. Compatible with A-ODW5 & A-OH15 series housings, A-SWD5ZWB600 & WM10-VB brackets	95
CANON A-CM3	1			0031X776	0031X776	Corner mount adaptor bracket (Black) Compatible with A-ODW5 & A-OH15 series housings, A-SWD5ZWB600 & WM10-VB brackets	111
CANON A-ODW5C2(OW)	1			0036X542	0036X542	Outdoor Housing with 5inch Clear Dome, AC24V Heater&Blower, Standard Bracket, Off-White Body, without Sunshade, IP66-rated, Compatible with VB-H43(B) & VB-M42(B) PTZ's	368
CANON A-ODW5C12S	1			0036X597	0036X597	Outdoor Housing with 5inch Clear Dome, DC12V Heater&Blower, Goose-Neck Bracket, Black&Silver Body, with Sunshade, IP66-rated, Compatible with VB-H43(B) & VB-M42(B) PTZ's	435
CANON A-ODW5C12S(OW)	1			0036X599	0036X599	Outdoor Housing with 5inch Clear Dome, DC12V Heater&Blower, Goose-Neck Bracket, Off-White Body, with Sunshade, IP66-rated, Compatible with VB-H43(B) & VB-M42(B) PTZ's	435
CANON A-ODW5C2S(OW)	1			0036X647	0036X647	Outdoor Housing with 5inch Clear Dome, AC24V Heater&Blower, Standard Bracket, Off-White Body, with Sunshade, IP66-rated, Compatible with VB-H43(B) & VB-M42(B) PTZ's	435
CANON A-SWD5ZWB600	1	1		0037X089	0037X089	Outdoor wall mount adaptor bracket for VB-H/M outdoor Domes. 330mm standoff to centre	225
CANON A-BK3(OW)	1	1		0037X094	0037X094	Pole mount adaptor, Aluminum (Off-White) for poles 100-400mm in diameter. Compatible with A-ODW5 & A-OH15 series housings, A-SWD5ZWB600 & WM10-VB brackets	95



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON A-CM3(OW)	1			0037X096	0037X096	Corner mount adaptor bracket (Off-White) Compatible with A-ODW5 & A-OH15 series housings, A-SWD5ZWB600 & WM10-VB brackets	111
CANON A-BK4	1			0039X883	0039X883	Pole mount adaptor (White) for poles 38-50mm in diameter. Compatible with A-ODW5 & A-OH15 series housings, A-SWD5ZWB600 & WM10-VB brackets	101
CANON A-BK5	1			0039X884	0039X884	Pole mount adaptor (Off-White) for poles 38-400mm in diameter. Compatible with VB-H652LVE/H651VE/M64xVE outdoor Domes(direct mount), and VB-H76x/H751LVE/M74x bullets (via CB740-VB)	126
CANON A-SWD5WB2	1			0040X444	0040X444	Indoor universal wall mount bracket suitable for VB-R13/R11 indoor PTZ Domes, and VB-H/M domes. 172mm standoff to centre	102
CANON A-SWD5WB3	1	1		0040X445	0040X445	Indoor universal wall mount bracket compatible with VB-S30D/S31D/S800D/S805D mini-domes, and VB-H/M PTZ's. 100mm standoff to centre	75
CANON A-ODW5C	1			0042X567	0042X567	Outdoor Housing with 5inch Clear Dome, without Heater&Blower, Standard Bracket, Black&Silver Body, without Sunshade, IP66-rated, Compatible with VB-M50B, VB-H43(B) & VB-M42(B) PTZ's	327
CANON A-ODW5CS	1			0042X901	0042X901	Outdoor Housing with 5inch Clear Dome, without Heater&Blower, Standard Bracket, Black&Silver Body, with Sunshade, IP66-rated, Compatible with VB-M50B, VB-H45(B) & VB-M44(B) PTZ's	389
CANON A-ODW5C2	1			0042X902	0042X902	Outdoor Housing with 5inch Clear Dome, AC24V Heater&Blower, Standard Bracket, Black&Silver Body, without Sunshade, IP66-rated, Compatible with VB-M50B, VB-H45(B) & VB-M44(B) PTZ's	368
CANON A-ODW5C2S	1			0042X903	0042X903	Outdoor Housing with 5inch Clear Dome, AC24V Heater&Blower, Standard Bracket, Black&Silver Body, with Sunshade, IP66-rated, Compatible with VB-M50B, VB-H45(B) & VB-M44(B) PTZ's	435
CANON HEATER UNIT HU652-VB	1			1498C001	1498C001	Optional heater element for VB-H652LVE outdoor Dome. Requires AC24V power	136
CANON SMOKED DOME UNIT DU652-S-VB	1			1497C001	1497C001	Smoked Dome Unit for VB-H652LVE outdoor dome	59
CANON PENDANT CAP PC30VE-VB	1	1		1736C001	1736C001	Indoor Pendant mounting Cap for VB-S30VE/S800VE mini-domes	61
CANON CONDUIT BOX CB30VE-VB	1	1		1735C001	1735C001	Conduit Box for VB-S30VE/S800VE mini-domes	91
CANON NETWORK CAMERA VB-S910F	1	1		1389C001	1389C001	Indoor compact fixed box network camera. 3.5x optical zoom, auto focus, digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White.	399
CANON NETWORK CAMERA VB-H761LVE (H2)	1			3749C001	3749C001	Outdoor vandal resistant fixed box network camera with IR LED illumination up to 60m. 20x optical zoom, auto focus, day/night switching, Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Enhanced Digital Zoom capabilities and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK09-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	1.350

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON NETWORK CAMERA VB-H760VE (H2)	1			3750C001	3750C001	Outdoor vandal resistant fixed box network camera. 20x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK09-rated and operating temperature in -10° C to +55° C (-14° F to +131° F). Powered by PoE(Power supply not included) and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	1.216
CANON NETWORK CAMERA VB-H751LE(H2)	1			3748C001	3748C001	Outdoor fixed box network camera with IR LED illumination up to 30m. 2.4x optical zoom, day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC	1.227
CANON NETWORK CAMERA VB-H730F MkII	1	1		2551C001	2551C001	Indoor fixed box network camera with remote Zoom configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports, and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	669
CANON NETWORK CAMERA VB-S900F MkII	1	1		2553C001	2553C001	Indoor compact fixed box network camera. Fixed 2.7mm wide angle lens (96.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	349
CANON NETWORK CAMERA VB-H651V	1	1		1385C001	1385C001	Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IK10-rated. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.	839
CANON NETWORK CAMERA VB-H651VE	1	1		1384C001	1384C001	Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with	1.119



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON NETWORK CAMERA VB-S800VE	1	1		1388C001	1388C001	Outdoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (93.8° AOV 16:9), digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. IP66, IK10-rated and operating temperature in -25° C to +50° C (-14° F to +122° F). Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. 1m pigtail cable connection. Available in Titanium White.	459
CANON NETWORK CAMERA VB-S30D MkII	1	4		2545C001	2545C001	Indoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	579
CANON NETWORK CAMERA VB-S800D MkII	1	1		2552C001	2552C001	Indoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	299
CANON NETWORK CAMERA VB-R13VE (H2)	1	1		3753C001	3753C001	Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	3.749
CANON NETWORK CAMERA VB-R12VE (H2)	1			3754C001	3754C001	Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	3.439

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON NETWORK CAMERA VB-R11VE (H2)	1			3751C001	3751C001	Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, and day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	2.889
CANON NETWORK CAMERA VB-R10VE (H2)	1			3752C001	3752C001	Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus and day/night switching. Hydrophilic Coating II for better visibility during / after rainfall and fouling resistance. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.	2.649
CANON NETWORK CAMERA VB-M50B	1	2		1064C001	1064C001	Indoor PTZ network camera with 348° rotation and large aperture lens ideal for low light applications. 5x optical zoom, auto focus, day/night switching and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Only available in Black.	3.199
CANON NETWORK CAMERA VB-H652LVE	1	1		1061C001	1061C001	Outdoor vandal resistant fixed dome network camera with IR LED illumination up to 20m, and NTSC video out for manual PT configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU652-VB sold separately.	1.279

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CANON NETWORK CAMERA VB-S30VE	1	1		1387C001	1387C001	Outdoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, digital night mode and built-in Omni-directional microphone. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSSR - Area-specific Data Size Reduction technology. 7 in-built video & audio intelligent analytic functions and linked events. IP66, IK10-rated and operating temperature in -25° C to +50° C (-14° F to + 122° F). Powered by PoE (Power supply not included). Audio output port and in-built microphone, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. 1m pigtail cable connection. Available in Titanium White.	669
CANON NETWORK CAMERA VB-M44B	1	1		2542C002	2542C002	BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (B).	1.679
CANON NETWORK CAMERA VB-M44S	1	1		2542C001	2542C001	SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	1.679
CANON NETWORK CAMERA VB-H45B	1	5		2541C002	2541C002	BLACK VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (B).	2.329
CANON NETWORK CAMERA VB-H45S	1	1		2541C001	2541C001	SILVER VERSION Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.	2.329
AXIS P7701	1	20		0319-002	0319-002	1 channel network video decoder. Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. Includes power supply.	359
AXIS P7701 VIDEO DEC BB BULK 20PCS	1			0319-051	0319-051	AXIS P7701 BARE BOARD in 20-pack. Cannot be sold separately as single packs. No power supplies.	7.180
AXIS P7701 VIDEO DECODER BARE BONE	1	1		0319-041	0319-041	Bare bone 1 channel video decoder (PCB without any mechanics). Decodes H.264 and MPEG-4 Part 2 in max. D1 resolution at 30/25 (NTSC/PAL) fps and 720p in Motion JPEG. Decodes AAC, G726 and G.711 audio streams in mono. Supports video source sequencing. Power over Ethernet enabled. No power supply.	359



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T8705 VIDEO DECODER	1	1		01186-001	01186-001	Network Video Decoder for easy display of video from IP cameras on big screens. With the 1080p HDMI output, Ethernet input and compact size, it is very easy to setup and use. It can display the video both as sequence or multimode and with the integrated VAPIX support, it automatically finds Axis cameras on the network for plug-and-play configuration.	299
AXIS M7011 Video Encoder	1	150		0764-001	0764-001	Single channel video encoder with H.264 (High, Main and Base profile) and Motion JPEG support. Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS. AVHS and ACAP support. No midspan included.	167
AXIS M7016 VIDEO ENCODER	1	40		0541-002	0541-003	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	839
AXIS M7104 VIDEO ENCODER	1	125		01679-001	01679-001	Four channel video encoder supporting PAL/NTSC cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection and active tampering alarm. Serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage.	299
AXIS P7224 Video Encoder Blade	1			0418-001	0418-001	AXIS P7224: Four-channel video encoder blade. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. PTZ support. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	335
AXIS P7216 VIDEO ENCODER	1	20		0542-002	0542-003	Sixteen-channel video encoder. Dual streaming H.264 and Motion JPEG on all channels. Max D1 resolution at 30/25 (NTSC/PAL) fps on all streams. Video motion detection. Active tampering alarm. Two-way audio with audio detection. SFP slot for optional fiber connection and/or network redundancy. Unit includes 4 x micro SD card slots for edge storage. PTZ support. Unit has 4 x ARTPEC chips and 4 x IP addresses. Includes power supply.	1.091
AXIS P7224 VID ENC BLADE BULK 10PCS	1	1		0418-021	0418-021	AXIS P7224 in 10-pack. Cannot be sold separately as single packs.	3.249
AXIS P7304 VIDEO ENCODER	1	200		01680-001	01680-001	Four channel video encoder supporting PAL/NTSC and HD analog cameras. Multiple, individually configurable H.264, H.265 and Motion JPEG streams. Frame rate 25/30 fps in all resolutions up to 1080p. Axis Zipstream technology for reduced bandwidth and storage needs. Video motion detection, active tampering alarm and audio detection. I/O for alarm/event handling, serial port for RS422/485 communication. Power over Ethernet or 12-20V DC input. MicroSD/MicroSDHC memory card slot for optional local video storage. Two-way audio with analog or digital microphone.	399
AXIS Q7411 VIDEO ENCODER	1	60		0518-002	0518-002	Video Encoder with H.264 (Main and Base profile) and Motion JPEG support. Supports 60/50 frames per second. Coax PTZ Control, video motion detection, two-way audio, configurable I/O connectors and ACAP support. 8-28 VD and Power over Ethernet (IEEE 802.3af). Edge storage using microSDHC card or NAS.	335
AXIS Q7411 VIDEO ENCODER BULK 10PCS	1	1		0518-021	0518-021	AXIS Q7411 in 10-pack. Power supply not included. Cannot be sold separately as single packs.	2.954



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q7414 VIDEO ENCODER BLADE	1	5		0354-001	0354-001	Four channel video encoder blade. Multiple, individually configurable H.264 and Motion JPEG streams; max. D1 resolution at 30/25 fps per channel. Four bi-directional audio channels with AAC encoding. Video motion detection. Active tampering alarm. COMPATIBLE WITH AXIS Q7900 RACK AND AXIS 291 1U VIDEO SERVER RACK.	839
AXIS Q7414 VIDEO ENCODER BULK 10PCS	1			0354-021	0354-021	AXIS Q7414 in 10-pack. Cannot be sold separately as single packs.	7.970
AXIS Q7424-R MKII VIDEO ENCODER	1	20		0742-001	0742-001	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps.	755
AXIS Q7424-R MKII VID ENC BULK 10P	1	1		0742-021	0742-021	Rugged Video Encoder with H.264 and Motion JPEG support. 1-4 video channels. Video motion detection. Two-way audio with audio detection. ACAP support on one channel. Ethernet port and SFP slot for fiber connection. Support for Power over Ethernet (IEEE 802.3af) and Power Supply (optional). Edge storage using SDHC card or NAS. PTZ support and configurable I/O connectors. AXIS Q7424-R MkII is an update to the original AXIS Q7424-R. The addition of 100 Mbps on the SFP slot is the only difference. The original product only has support for 1 Gbps. 10 PCS.	7.172
AXIS Q7436 VIDEO ENCODER BLADE	1	30		0584-001	0584-001	6 channel video encoder blade. Multiple, individually configurable H.264 (Base, Main and High profile) and Motion JPEG streams; max. D1 resolution at 60/50 fps per channel. Video motion detection. Active tampering alarm. Coax PTZ Control (Coaxitron). Compatible with the following video encoder chassis: AXIS Q7920, AXIS Q7900 and AXIS 291 1U	1.007
AXIS Q7436 VIDEO ENCODER BLADE BULK 10 PCS	1	1		0584-021	0584-021	AXIS Q7436 in 10-pack. Cannot be sold separately as single packs.	9.572
AXIS Q7436/Q7920 KIT	1	1		0656-002	0656-003	14 x AXIS Q7436 Video Encoder Blade mounted in an AXIS Q7920 Video Encoder Chassis. Country specific power cable.	15.617
AXIS 291 1U VIDEO SERV RACK	1	20		0267-002	0267-003	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output.	335
AXIS 291 1U VIDEO SERVER RACK < CH >	1	1		0267-010		1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output. Swiss power cable.	335
AXIS 291 1U VIDEO SERVER RACK < GENERIC >	1	1		0267-001	0267-001	1U 19" rack unit with three expansions slots, compatible with all Axis Blade video servers. Universal built-in power supply. One 10/100/1000Base-T output. No power cable.	335
AXIS Q7920 VIDEO ENCODER CHASSIS	1			0575-002	0575-003	5 U rack-mount video encoder chassis, providing an expandable solution for migrating large-scale analog installations to network video. Holds up to 14 hot-swappable video encoder blades supporting up to 84 analog cameras.	2.182
AXIS S9101	1		Discontinued - contact Order dept for availability	01173-002	01173-003	Compact Desktop Terminal with micro form factor to be used with AXIS S1032 or AXIS S1048 recording servers. The terminal is preloaded with AXIS Camera Station software and all other necessary software e.g. Windows 10IoT. Includes three year hardware warranty and on-site hardware replacement service, international keyboard and mouse.	1.399



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS S2208	1	50		01580-002	01580-003	AXIS Camera Station S2208 Appliance is an eight channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 4 TB storage, Core licenses for 8 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drive. Supports up to 4k ultra HD.	2.299
AXIS S1116 MT	1	10		01617-001	01617-003	AXIS Camera Station S1116 Recorder is an out-of-the-box ready workstation tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service, keep your hard drive and international keyboard and mouse.	3.299
AXIS S1116 RACKED	1	8		01618-001	01618-001	AXIS Camera Station S1116 Recorder is an out-of-the-box ready rack-server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 16 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	3.799
AXIS S1132	1	8		01613-001	01613-001	AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	5.499
AXIS S1148 24TB	1	10		01614-001	01614-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	8.499
AXIS S1148 64TB	1	5		01615-001	01615-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	11.499
AXIS S1148 140TB	1	3		01616-001	01616-001	AXIS Camera Station S1148 Recorder is an out-of-the-box ready rack server tested and validated with Axis products for reliable surveillance up to 4K video streams. Preconfigured and preloaded with AXIS Camera Station video management software including licenses for 48 channels plus all necessary system software. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	16.999



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS S9201 MKII	1		Discontinued - contact Order dept for availability	01691-001	01691-003	AXIS Camera Station S9201 Mk II Desktop Terminal is an all-in-one desktop terminal with a 22-inch monitor for system overview, to be used with Axis recorders. The terminal is preloaded with AXIS Camera Station software and all other necessary software. Includes 3-year hardware warranty, on-site hardware replacement service and international keyboard and mouse.	1.899
AXIS S9002 MK II	1	8		01619-001	01619-003	AXIS Camera Station S9002 Mk II Desktop Terminal is a high-performance desktop terminal to be used with Axis recorders. Optimized for surveillance purposes with four monitors and supports up to three 4K video streams. The terminal is preloaded with AXIS Camera Station software and all other necessary software. Includes 5-year limited hardware warranty, on-site hardware replacement service and international keyboard and mouse.	2.499
AXIS S2212	1	8		01581-002	01581-003	AXIS Camera Station S2212 Appliance is a twelve channel compact desktop Client/Server including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 6 TB storage, Core licenses for 12 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drive. Supports up to 4k ultra HD.	2.999
AXIS S2216	1	8		01582-002	01582-003	AXIS Camera Station S2216 Appliance is a sixteen channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 8 TB storage, Core licenses for 16 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drives. Supports up to 4k ultra HD.	3.799
AXIS S2224	1	10		01583-002	01583-003	AXIS Camera Station S2224 Appliance is a twenty four channel Client/Server for rack-mounting including an integrated managed PoE switch validated and tested with Axis products. Preloaded with AXIS Camera Station software with preconfigured AXIS Camera Station settings and all other necessary software e.g. Windows 10 IoT. Includes 12 TB storage, Core licenses for 24 devices, 5-year limited hardware warranty on the appliance and 3-year on the hard drives. Supports up to 4k ultra HD.	4.499
AXIS S9101 Mk II	1	6		01985-002	01985-003	AXIS Camera Station S9101 Mk II Desktop Terminal is a complement to Axis recorders to enable quick set-up of a surveillance workstation. The terminal is preloaded with an AXIS Camera Station client and preconfigured to minimize installation time. AXIS S9101 Mk II has validated hardware and software components for optimal surveillance experience and includes 5-year limited hardware warranty.	1.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS S1132 TOWER 32 TB	1	4		02079-002	02079-003	AXIS Camera Station S1132 Tower 32 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 32 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 32 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	7.599
AXIS S1132 TOWER 64 TB	1	2		02080-002	02080-003	AXIS Camera Station S1132 Tower 64 TB is an out-of-the-box ready server and client validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 Tower 64 TB is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower 64 TB provides high-performance and reliability for your system. Includes 5-year limited hardware warranty, on-site hardware replacement service and keep your hard drive.	9.499
AXIS S3008 4 TB	1	100		02046-002	02046-003	AXIS S3008 4 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 4 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	799
AXIS S3008 2 TB	1	100		02105-002	02105-003	AXIS S3008 2 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 2 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	599
AXIS S3008 8 TB	1	20	To be launched	02135-002	02135-003	AXIS S3008 8 TB Recorder is a compact recorder with 8 PoE ports and a gigabit uplink. Up to 8 devices can be connected to the recorder and recording is done on the internal hard drive. For an easy and intuitive surveillance, it is compatible with AXIS Companion VMS and a wide range of cameras. To increase reliability and security, the product supports disk encryption, contains a 8 TB surveillance class hard drive and includes 5-year limited hardware warranty on the recorder and 3-year on the hard drive.	1.099
ACAP AXIS PERIMETER DEFENDER 1 LICENSE	1	2		0333-606	0333-606	Single unit license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	299



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
ACAP AXIS PERIMETER DEFENDER 1 E-LICENSE	1			0333-608	0333-608	Single unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	299
ACAP AXIS PERIMETER DEFENDER 10 LICENSE	1	70		0333-607	0333-607	Ten (10) unit license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	2.989
ACAP AXIS PERIMETER DEFENDER 10 E-LICENSE	1			0333-609	0333-609	Ten (10) unit e-license for AXIS Perimeter Defender, a scalable and flexible video analytics application for perimeter surveillance and protection. Visit www.axis.com for supported products and application download.	2.989
AXIS PERIMETER DEFENDER PTZ 1P ELIC	1			01725-001	01725-001	Single unit license for AXIS Perimeter Defender PTZ Autotracking. Together with a fixed camera running AXIS Perimeter defender this enable automatic control of a PTZ camera to zoom in on and follow detected objects. Please check the supported countries (https://www.axis.com/files/pods/axis_perimeter_defender_ptz_autotracking_supported_countries.pdf) before ordering. Visit www.axis.com for supported products and application download.	299
Axis Cross Line Detection	1	2		0333-011	0333-011	Single unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	24
Axis Cross Line Detection 10-pack	1	1		0333-031	0333-031	Ten (10) unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	234
Axis Cross Line Detection 50-pack	1			0333-051	0333-051	Fifty (50) unit license for AXIS Cross Line Detection, a basic cross line video analytic. Visit www.axis.com for supported products and application download.	1.141
ACAP AXIS MOTION GUARD 10 E-LICENSE	1			0333-601	0333-601	Ten (10) unit e-license for AXIS Motion Guard, a robust, installer-friendly motion detection video analytic. As of April 2020, AXIS Guard Suite is complimentary with all compatible Axis cameras. Visit www.axis.com for application download.	0
AXIS H. 264 50-user decoder license pack	1			0160-050	0160-050	A license document that grants installation of AXIS AVC/H.264 decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 but does not have support for audio.	38
AXIS H.264 +AAC decoder 50-user decoder license pack	1	1		0160-060	0160-060	A license document that grants installation of AXIS AVC/H.264 and AAC decoder onto 50 separate computers. Applicable for all AXIS products that supports H.264 that also have support for audio.	46
AXIS STORE DATA MANAGER 10CH BASE E-LICENSE	1			01147-101	01147-101	AXIS Store Data Manager is a server side tool that is used to collect and arrange analytics data from retail analytics-enabled cameras.	499
AXIS STORE DATA MANAGER 1CH ADD-ON E-LICENSE	1			01147-111	01147-111	AXIS Store Data Manager is a server side tool that is used to collect and arrange analytics data. This article is for additional channels to be added to AXIS Store Data Mgr 10P Core	29
AXIS PEOPLE COUNTER E-LICENSE	1			01147-011	01147-011	AXIS People Counter is a cost-efficient and scalable video analytics application for people counting. This business-improving application, installed on a network camera, enables accurate monitoring and analysis of customer flows. It is ideal for e.g. quick evaluation of marketing efforts, improving staff and store planning, or evaluating conversion rate if combined with point-of-sale data.	249
AXIS QUEUE MONITOR E-LICENSE	1			01147-031	01147-031	AXIS Queue Monitor is a cost-efficient and scalable video analytics application for queue measurement and analysis. This application, installed on a network camera, provides statistics about queue duration and queue fluctuations over the course of the day, facilitating both staff planning and the comparison between store locations.	299



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS DEMOGRAPHIC IDENTIFIER E-LICE	1			01147-041	01147-041	AXIS Demographic Identifier is a cost-efficient and scalable video analytics application for detecting and analyzing faces of store visitors, displaying gender and approximate age.	459
AXIS OCCUPANCY ESTIMATOR E-LICENSE	1			01147-051	01147-051	AXIS Occupancy Estimator is a cost-efficient and scalable video analytics application for gathering and analyzing occupancy data. This application, installed on a network camera, is a valuable tool for improving service planning in places like shopping malls or entertainment venues.	249
AXIS TAILGATING DETECTOR E-LICENSE	1			01147-071	01147-071	AXIS Tailgating Detector is a cost-efficient video analytics application for ensuring that only one person at a time is entering in an automated access control system. Preventing unauthorized entering, the camera-integrated application is ideal for subways, gyms, or other places where access cards are used	249
AXIS DIRECTION DETECTOR E-LICENSE	1			01147-081	01147-081	AXIS Direction Detector is a cost-efficient and scalable video analytics application for detecting people moving in the wrong direction. This camera-integrated application reduces the need for physical barriers or extra staff in for example retail stores or airports, where it registers the number of people passing by and in what direction	249
AXIS RANDOM SELECTOR E-LICENSE	1			01147-091	01147-091	AXIS Random Selector is a camera-integrated video analytics application for randomly singling out individuals for inspection. The application eliminates any bias in the selection and inspection of, for instance, employees leaving a store, and may thereby reduce employees' discomfort.	249
AXIS LICENSE PLATE VERIFIER 1P E-LICENSE	1			01574-001	01574-001	Please check the supported countries (https://www.axis.com/files/pods/axis_license_plate_verifier_supported_countries_1912.pdf) before ordering. Single unit e-license for AXIS License Plate Verifier. AXIS License Plate Verifier is an AXIS Camera Application Platform software that can be used in selected Axis cameras (ideally with I/O ports for direct control of a vehicle access barrier and built-in IR illumination) to allow vehicle entry/exit into a controlled area such as a parking lot. Please check the supported countries before ordering. Visit www.axis.com for supported products and application download.	499
ACAP AXIS PARKING VIO DETN 1 E-LIC	1			01939-001	01939-001	Single unit e-license for AXIS Parking Violation Detection, a scalable and flexible video analytics solution to detect vehicles stopping in areas where vehicles should not park or stop.	649
AXIS LIVE PRIVACY SHIELD	1			01931-001	01931-001	When you want video surveillance but still need to protect peoples privacy.	199
AXIS LIVE PRIVACY SHIELD 10PCS	1			01931-021	01931-021	Ten (10) unit e-license for AXIS Live Privacy Shield, when you want video surveillance but still need to protect peoples privacy.	1.989
AXIS STORE REPORTER SUBSCRIPT 2021	1		0 New	02283-001	02283-001	AXIS Store Reporter is a web-based tool that is used for graphical representation and reporting of statistical data gathered from Axis retail analytics applications. It is sold on a per channel basis as e-license. A license is valid until 31 Dec 2021. After this date the license will have to be renewed. AXIS Store Data Manager is included in AXIS Store Reporter.	99
ACS CORE DEVICE E-LICENSE	1			0879-010	0879-010	One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices. AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification. Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.	79



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
ACS UNIVERSAL DEVICE E-LICENSE	1			0879-020	0879-020	<p>One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	149
ACS 4 TO UNIVERSAL UPG E-LICENSE	1			0879-040	0879-040	<p>One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	19
ACS CORE TO UNIVERSAL UPG E-LICENSE	1			0879-030	0879-030	<p>This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license and one AXIS Camera Station version 5 Core Device license upgrades to one (1) Universal Device license.</p> <p>Delivered as eLicense key. Note: eLicenses are non-cancellable, non-changeable and non-returnable.</p>	79
ACS 1 CORE DEVICE LICENSE	1		1	0879-050	0879-050	<p>One (1) AXIS Camera Station version 5.0 and up, Core Device license. Applicable for AXIS devices.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	79
ACS 4 CORE DEVICE LICENSE	1		1	0879-060	0879-060	<p>Four (4) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	316
ACS 16 CORE DEVICE LICENSE	1		150	0879-070	0879-070	<p>Sixteen (16) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	1.264



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
ACS 32 CORE DEVICE LICENSE	1	150		0879-080	0879-080	<p>Thirtytwo (32) AXIS Camera Station version 5.0 and up, Core Device licenses. Applicable for AXIS devices.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	2.528
ACS 1 UNIVERSAL DEVICE LICENSE	1	3		0879-090	0879-090	<p>One (1) Universal Device license applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	149
ACS 4 UNIVERSAL DEVICE LICENSE	1	1		0879-100	0879-100	<p>Four (4) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	596
ACS 10 UNIVERSAL DEVICE LICENSE	1	3		0879-110	0879-110	<p>Ten (10) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	1.490
ACS 20 UNIVERSAL DEVICE LICENSE	1	1		0879-120	0879-120	<p>Twenty (20) Universal Device licenses applicable for AXIS Camera Station version 5.0 and up.</p> <p>AXIS Camera Station is a monitoring and recording system mid-size installations optimized to take full advantage of Axis leading network cameras and video encoders. It combines easy setup with an intuitive user interface for efficient operation, quick investigation and high definition identification.</p> <p>Delivered as printed license code in envelope.</p>	2.980
ACS 4 TO UNIVERSAL 1 UPG.LIC	1	1		0879-170	0879-170	<p>One (1) upgrade license applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license.</p> <p>Delivered as printed license code in envelope.</p>	19

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
ACS 4 TO UNIVERSAL 5 UPG.LIC	1	1		0879-180	0879-180	Five (5) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as printed license code in envelope.	95
ACS 4 TO UNIVERSAL 10 UPG.LIC	1	1		0879-190	0879-190	Ten (10) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as printed license code in envelope.	190
ACS 4 TO UNIVERSAL 20 UPG.LIC	1	1		0879-200	0879-200	Twenty (20) upgrade licenses applicable for existing licenses of AXIS Camera Station, version 1,2,3, 4. Each existing license in combination with this upgrade license enables upgrade to a AXIS Camera Station version 5 Universal Device license. Delivered as printed license code in envelope.	380
ACS CORE TO UNIVERSAL 1 UPG.LIC	1	8		0879-130	0879-130	This license is primarily used for replacing AXIS devices with ONVIF devices. One (1) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	79
ACS CORE TO UNIVERSAL 5 UPG.LIC	1	8		0879-140	0879-140	This license is primarily used for replacing AXIS devices with ONVIF devices. Five (5) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	395
ACS CORE TO UNIVERSAL 10 UPG.LIC	1	10		0879-150	0879-150	This license is primarily used for replacing AXIS devices with ONVIF devices. Ten (10) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	790
ACS CORE TO UNIVERSAL 20 UPG.LIC	1	1		0879-160	0879-160	This license is primarily used for replacing AXIS devices with ONVIF devices. Twenty (20) Upgrade license applicable for AXIS Camera Station version 5 Core Device license upgrade to Universal Device license. Delivered as printed license code in envelope.	1.580
AXIS D20 FRONT COVER KIT A	1	1		01438-001	01438-001	Replacement front cover for AXIS D2050-VE. Includes anti-loss screws and sealing gaskets.	79
AXIS F4005-E CLEAR DOME 5PCS	1	1		5801-461	5801-461	Standard clear dome for AXIS F4005-E, 5 pcs	79
ACC TOP COVER AXIS 209FD-R 10PCS	1			5500-301	5500-301	Replaceable cover for AXIS 209FD-R, 10 pcs. Includes dry bags	209
SPR DOME CLEAR AXIS 215 PTZ-E	1		Discontinued - contact Order dept for availability	5700-291	5700-291	Spare clear dome for AXIS 215-PTZ-E. Includes mounting ring, clear bubble, rubber gasket and 4 screws.	83
ACC DOME AXIS 216FD-V GLASS SMOKED	1			5005-061	5005-061	Vandal-resistant casing with smoked transparent cover. Can also upgrade an AXIS 216FD/216MFD/P330X/M320X to an AXIS 216FD-V/216MFD-V/P330X-V/M320X-V	58
AXIS M3006 CLEAR DOME 5PCS	1	1		5800-731	5800-731	Original white top cover with clear dome for AXIS M3006, 5pcs.	209
AXIS M3007 CLEAR DOME 5PCS	1	1		5800-741	5800-741	Original white top cover with clear dome for AXIS M3007, 5pcs.	209
AXIS M3024 CLEAR DOME 5PCS	1	1		5800-711	5800-711	Standard clear domes for AXIS M3024, 5 pcs	209
AXIS M3025/26 CLEAR DOME 5PCS	1	2		5800-721	5800-721	Standard clear domes for AXIS M3025, M3026. 5 pcs	209
AXIS M3027 CLEAR DOME 5PCS	1	1		5800-751	5800-751	Standard clear domes for AXIS M3027, 5 pcs	209



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS M3044-V/45-V/46-V CL DOME 5P	1	2		5801-841	5801-841	Standard clear dome for AXIS M3044-V/45-V/46-V, 5 pcs	99
AXIS M30-PLVE CLEAR DOME A 4P	1	1		01567-001	01567-001	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXISM3057/58-PLVE. 4-piece bulk pack.	59
AXIS M30 DOME COVER CASING A 5PCS	1	1		5901-241	5901-241	Original white casing with clear dome for M3044/45/46-V-WV and AXIS Companion Dome cameras. 5 pcs.	149
AXIS M30 CASING B WHITE 5P	1	1		01153-001	01153-001	Original white casing for AXIS M3047/48-P. 5 pcs.	79
AXIS TM3803 WHITE CASING 4P	1	1		01950-001	01950-001	Spare part white casing. Cover top replacement part for M3067/68.	59
AXIS M42 CASING A WHITE 4P	1	1		01922-001	01922-001	Original white casings for AXIS M42 series. Easy to repaint. 4-piece bulk pack.	59
AXIS M42 CLEAR DOME A 4P	1	1		01923-001	01923-001	Clear dome with anti-scratch hard coating. Compatible with AXIS M42 series. 4x domes per pack.	79
TOP COVER AXIS M311X-R 10PCS	1	3	Discontinued - contact Order dept for availability	5700-641	5700-641	Original dark grey top cover including dome and screws for AXIS M311X-R. 10 pcs	209
TOP COVER M311X-VE NOCAP 10 PCS	1	1	Discontinued - contact Order dept for availability	5800-061	5800-061	Original top cover including dome and screws for AXIS M311X-VE No Cap. 10 pcs.	209
AXIS M50 CLEAR DOME COVER A	1	1		01239-001	01239-001	Spare part AXIS M50 dome casing cover in white. Included in AXIS M5054/55/65 cameras.	49
AXIS M501X DOME	1	1		5800-111	5800-111	Spare part AXIS M501X dome, pre-mounted in the white top casing. Opening tool and gasket are included.	24
AXIS M55 CLEAR DOME A	1	1		01606-001	01606-001	Spare part clear dome in polycarbonate. IK09 vandal resistant. Compatible with AXIS M5525-E. Single pack.	39
AXIS P32-V CLEAR DOME A 5P	1	3		5506-131	5506-131	Standard clear dome for AXIS P32-V Series, 5 pcs	142
AXIS P32-VE CLEAR DOME A 5P	1	3		5506-121	5506-121	Standard clear dome for AXIS P32-VE Series, 5 pcs	142
AXIS P32-LV SEMI SMOKED DOME A 5P	1	1		5504-981	5504-981	Semi smoked domes for AXIS P32-LV Series, 5 pcs	169
AXIS P32-LVE SEMI SMOKED DOME A 5P	1	1		5504-991	5504-991	Semi smoked domes for AXIS P32-LVE Series, 5 pcs	169
SPR AXIS P3343 DOME KIT	1	1		5700-321	5700-321	Dome Kit for AXIS P3343, AXIS P3344, AXIS P3353 and AXIS P3354 as spare part. Includes a clear bubble, mounted on a plastic dome cover and a separate smoked bubble.	24
SPR AXIS P3343-V DOME KIT	1	1		5700-311	5700-311	Dome kit for AXIS P3343-V, AXIS P3344-V, AXIS P3363-V and AXIS P3364-V as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	58
SPR DOME KIT AXIS P3343-VE	1	8		5700-341	5700-341	Dome Kit for AXIS P3343-VE, P3344-VE, AXIS P3363-VE and AXIS P3364-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	58
SPR AXIS P3346 DOME KIT	1	1		5700-901	5700-901	Dome Kit for AXIS P3346 as spare part. Includes a clear bubble, mounted on a plastic dome cover and a separate smoked bubble.	29
SPR AXIS P3346-V DOME KIT	1	3		5700-911	5700-911	Dome kit for AXIS P3346-V, P3367-V and AXIS P3384-V as spare part. Includes a clear bubble, mounted on a zinc alloy dome cover and a separate smoked bubble.	62
SPR AXIS P3346-VE DOME KIT	1	7		5700-921	5700-921	Dome Kit for AXIS P3346-VE, P3367-VE, AXIS P3384-VE as spare part. Includes a clear bubble, mounted on an aluminium dome cover and a separate smoked bubble.	62
AXIS P3364-LV DOME KIT	1	1		5800-691	5800-691	Dome kit for AXIS P3364-LV. The dome is pre-mounted in the standard white top cover casing.	62
AXIS P3364-LVE DOME KIT	1	2		5800-681	5800-681	Dome kit for AXIS P3364-LVE. The dome is pre-mounted in a standard white top cover casing.	62
AXIS P33 SEMI-SMOKED DOME A 4PCS	1	1		01548-001	01548-001	Semi-smoked dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-LV/-LVE cameras. 4x domes per pack.	119
AXIS P33 CLEAR DOME A 4PCS	1	1		01549-001	01549-001	Clear dome with anti-scratch hard coating for indoor and outdoor AXIS P337X-V/-VE cameras. 4x domes per pack.	119
AXIS P3707-PE CLEAR DOME KIT	1	1		5801-521	5801-521	Dome kit for AXIS P3707-PE. The dome is pre-mounted in the standard white top cover casing.	99



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P37 CLEAR DOME KIT A	1	1		01515-001	01515-001	Dome kit for AXIS P3717-PLE and AXIS P3719-PLE. The dome is pre-mounted in the standard white top cover casing.	99
SPR TOP COVER AXIS P39-R 10 PCS	1	1		5801-111	5801-111	Original top cover including dome and screws for AXIS P39-R Series. 10 pieces.	209
AXIS P54 CLEAR DOME	1	1		5800-771	5800-771	Clear dome for AXIS P54-series.	41
AXIS P5512-E DOME KIT	1	4		5800-281	5800-281	Dome kit for AXIS P5512-E, 5514-E, 5515-E. Clear-/smoked dome and dome cover included.	41
AXIS TP3809 DOME COVER WHITE 4P	1	2	Price correction	02010-001	02010-001	4 pack white dome cover for AXIS P3925-R. Replaces the standard white dome cover.	199
AXIS TQ6803 HARD-COATED CLEAR DOME	1	2		01814-001	01814-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS Q61-LE cameras. Weather-resistant and chemical-resistant. Rubber gasket included. Single pack.	89
AXIS TQ6804 SMOKED DOME	1	7		01789-001	01789-001	Accessory outdoor smoked dome compatible with selected AXIS Q60-E cameras. See axis.com for updated compatibility list.	79
AXIS TQ6804 CLEAR DOME	1	3		01790-001	01790-001	Accessory outdoor clear dome compatible with selected AXIS Q60-E cameras. See axis.com for updated compatibility list.	79
AXIS TQ6806 HARD-COATED CLEAR DOME	1	1		01771-001	01771-001	Hard coated clear dome spare part for Q6100-E.	79
AXIS TQ6807 CLEAR DOME COVER	1	20		01946-001	01946-001	Clear dome cover including dome cover ring. Compatible with legacy AXIS Q60-E/C cameras. See axis.com for updated compatibility list.	149
AXIS TQ9801 CLEAR DOME	1	2		02050-001	02050-001	TQ9801 CLEAR DOME spare part for Q9216-SLV.	75
AXIS P553X CLEAR DOME	1	4		5800-251	5800-251	Original clear dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	29
AXIS P553X SMOKED DOME	1	1		5800-191	5800-191	Original smoked dome for AXIS P5522/-E, AXIS P5532/-E, AXIS P5534/-E.	29
AXIS DOME CLEAR P5544	1	1		5800-391	5800-391	Sparepart dome for AXIS P5544. Note that this product does not contain the fisheye lens.	37
AXIS P5624-E/35-E CLEAR DOME	1	15		5506-141	5506-141	Clear dome for AXIS P56 Series cameras.	41
AXIS Q3505-V CLEAR DOME 5P	1	1		5505-611	5505-611	Standard clear domes for AXIS Q35-V Series, 5 pcs	150
AXIS Q35 CLEAR DOME A 5PCS	1	1		01180-001	01180-001	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3517-LV-LVE. 5x domes per pack.	199
AXIS Q3505-VE CLEAR DOME 5P	1	1		5505-631	5505-631	Standard clear dome for AXIS Q3505-VE. 5pcs	167
AXIS Q36-VE CLEAR DOME	1	1		5801-511	5801-511	Standard clear dome with anti-scratch hard coating. Compatible with AXIS P38 and Q36 Series.	49
AXIS Q37 CLEAR DOME A	1	1		5507-311	5507-311	Standard clear dome with anti-scratch hard coating. Compatible with AXIS Q3708-PVE and Q3709-PVE. Single pack.	49
AXIS Q6000-E CLEAR DOME	1	1		5506-641	5506-641	Clear dome for AXIS Q6000-E	79
AXIS Q603X HD DOME KIT	1	2		5700-811	5700-811	HD optimized dome kit for AXIS Q603X as spare part. Includes a clear bubble mounted on dome ring and a separate smoked bubble.	75
AXIS Q3517-SLVE CLEAR DOME 2P	1	1		01584-001	01584-001	Original clear dome in polycarbonate with anti-scratch hard coating. IK10+ vandal-resistant and high chemical resistance. Compatible with AXIS Q3517-SLVE. 2x domes per pack.	89
AXIS Q60-E/C SMOKED DOME D	1	8	Discontinued - contact Order dept for availability	5503-961	5503-961	Stand alone smoked dome for AXIS Q60XX-E/C series	66
AXIS Q60-S CLEAR DOME A	1	1		5700-751	5700-751	Original clear dome in a special nylon blend with superior stress and chemical resistance. Compatible with AXIS Q604x-S and Q6055-S cameras. Single-pack.	58
AXIS Q8414-LVS CLEAR DOME 5P	1			5506-331	5506-331	Standard clear dome for AXIS Q8414-LVS. 5 pcs.	83
AXIS Q8414-LVS IR WINDOW A 5P	1			5506-341	5506-341	Standard IR window with microphone hole and water-stop membrane for AXIS Q8414-LVS. 5 pcs.	125
AXIS A8105-E CLEAR DOME 5PCS	1	1		5801-471	5801-471	AXIS A8105-E Clear Dome is sold as spare parts to the AXIS A8105-E Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	35
AXIS COMP DOME MINI CASING A 4P	1			01784-001	01784-001	Original white casing for AXIS Companion Dome mini LE, including dome and screws. 4 pcs.	119



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS TA8801 CLEAR DOME COVER 5P	1	1		01764-001	01764-001	AXIS TA8801 Clear Dome Cover is sold as spare parts to the AXIS A8207-VE Network Video Door Station and comes in packs of five clear dome covers. It enables easy on-site replacement in case the original dome cover has been damaged or vandalized.	39
AXIS TP3801 WHITE CASING 4P	1	7		01799-001	01799-001	Original white casing for selected AXIS P32 indoor cameras. 4pcs bulk pack.	79
AXIS TP3801-E WHITE CASING 4P	1	1		01800-001	01800-001	Original white casing for selected AXIS M32 and P32 outdoor cameras. Pre-assembled with anti-loss screws. 4pcs bulk pack.	99
AXIS TP3802 CLEAR DOME 4P	1	3		01625-001	01625-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS P32 indoor cameras. 4pcs bulk pack.	99
AXIS TP3802-E CLEAR DOME 4P	1	2		01629-001	01629-001	Standard clear dome with anti-scratch hard coating. Compatible with selected AXIS M32 and P32 outdoor cameras. 4pcs bulk pack.	119
AXIS TP3807 DOME COVER WHITE 4P	1	20	Price correction	02011-001	02011-001	4 pack white dome cover for AXIS P3935-LR. Replaces the standard white dome cover.	199
ACC ALLEN-KEY M3 TAMP PROOF 10PACK	1	7		5500-491	5500-491	Allen-key for AXIS 209FD-R 10-pack	33
AXIS D20 MOUNT BRACKET KIT A	1	1		01439-001	01439-001	Original stainless steel mounting bracket for AXIS D2050-VE. Includes two pipe adapters, anti-loss screws, two gray cable gaskets, three black cable gaskets, and an M20 cable gland.	59
AXIS M10 BRACKET KIT 5P	1	1		5901-211	5901-211	Contains 5pcs wall-and-corner mount bracket and 5pcs table-top stand. Compatible with AXIS M10 Series.	39
AXIS Q604X RECESSED MOUNT	1	1		5505-161	5505-161	Spare part indoor recessed mount for mounting AXIS Q60 indoor cameras in drop ceilings.	75
AXIS F82A06 ANGLED PINHOLE MT 5PCS	1	1		01198-001	01198-001	Mounting bracket that allows AXIS FA1125 Sensor Unit to be mounted behind a thin metal/plastic/glass panel. 5 pcs.	29
P1214/P1214-E/P1224-E MOUNT BRACKET 5PCS	1	10		5503-991	5503-991	Mount bracket for AXIS P1214, P1214-E and P1224-E. Allows to mount the sensor unit in different horizontal and vertical angles.	50
AXIS M501X MOUNTING KIT	1	1		5800-121	5800-121	Original ceiling mount kit for both hard- and drop ceilings for the AXIS M501X.	13
AXIS Q8414-LVS BACK CHASSIS WHITE	1			5506-311	5506-311	Spare part powder coated white stainless steel back chassis with gaskets for AXIS Q8414-LVS.	167
AXIS Q8414-LVS BACK CHASSIS METAL	1			5506-321	5506-321	Spare part brushed stainless steel metal back chassis with gaskets for AXIS Q8414-LVS.	167
AXIS T98A MOUNTING BRACKET	1	1		5800-351	5800-351	Original stainless steel mounting bracket for AXIS T98A-VE Surveillance Cabinet series.	50
AXIS STEEL STRAPS TX30 570MM 1PAIR	1	70		01472-001	01472-001	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 570mm (22.5"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 50-150mm (2"-6") when used with AXIS T91B47 Pole Mount.	29
AXIS STEEL STRAPS TX30 1450MM 1PAIR	1	150		01471-001	01471-001	1 pair marine-grade (SS316L) stainless steel straps with TX30 screw interface for ease-of-installation. Length 1450mm (57"). Width 14.3mm (0.57"). Thickness 0.68mm (0.03"). Compatible with a wide range of Axis pole mounts. Pole diameter range 100-410mm (4"-16") when used with AXIS T91B47 Pole Mount.	39
STAINLESS STEEL STRAPS 1450MM 1 PAIR	1	40	Discontinued - contact Order dept for availability	5800-811	5800-811	Original stainless steel straps for AXIS T91A47 110-400 mm. The straps also fit the AXIS T91A67. Mounting tool (P/N 21776) is required.	27
SPR AXIS P3343-VE SCREW KIT	1	1		5700-351	5700-351	Screw Kit for AXIS P3343-VE and P3344-VE as spare part. Includes mounting screws, plugs and I/O connector.	4
SPR AXIS P3343-V SCREW KIT	1	1		5700-301	5700-301	Screw kit for AXIS P3343, P3343-V, P3344 and P3344-V as spare part. Includes mounting screws, plugs and I/O connector.	3
AXIS T94B02S MOUNTING BRACKET 5P	1	1		5901-281	5901-281	Spare part mounting brackets for AXIS M20 Series, 5-pack. Includes 5x mounting brackets with 5x Gasket C M20.	59
AXIS T94F01S MOUNTING BRACKET	1	1		5505-171	5505-171	Standard mount bracket for AXIS M3006-V, AXIS M3007-P/-PV, AXIS M3024-LVE/3025-VE/3026-VE	16



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T94G01S MOUNTING PLATE	1	2		5506-081	5506-081	Sparepart mounting bracket for AXIS Q1765-LE, Q1931-E, Q1932-E	24
AXIS T94K01S MOUNTING BRACKET 4P	1	1		5505-551	5505-551	Sparepart mounting bracket for AXIS Q3505-V. 4 pcs	100
AXIS T94M01S MOUNTING BRACKET 4P	1	1		5505-561	5505-561	Sparepart mounting bracket for AXIS Q3505-VE. 4 pcs	117
AXIS T94S01S MOUNTING BRACKET 4P	1	1		5506-061	5506-061	Sparepart mounting bracket for AXIS P32-V Series. 4 pcs	58
AXIS T94T01S MOUNTING BRACKET 4P	1			5506-071	5506-071	Sparepart mounting bracket for AXIS P32-VE Series. 4 pcs	75
AXIS T94T02S MOUNTING BRACKET	1	1		01566-001	01566-001	Spare part mounting brackets for AXIS M3057/58-PLVE, single pack. Includes spring clips for ease-of-installation.	25
MOUNTING BRACKET AXIS P33XX-VE	1	1		5700-691	5700-691	Original AXIS P33XX-VE mounting bracket for wall or hard ceiling.	24
AXIS T94V01S MOUNTING BRACKET	1	1		5801-911	5801-911	Standard mounting bracket for AXIS Q36 Series Network Cameras.	39
AXIS 3/4" CONDUIT LOCKNUT A 4P	1	1		01512-001	01512-001	4-pack of 3/4" conduit locknut. Suitable for AXIS T91B53 Telescopic Ceiling Mount.	15
AXIS T94U02S MOUNTING BRACKET	1	1		5506-671	5506-671	Standard mounting bracket for AXIS Q3505-SVE made of stainless steel. Including gasket.	169
AXIS T94F02S MOUNTING BRACKET	1	1		5507-131	5507-131	Standard plastic mounting bracket for AXIS P1405, P1425, P1427, P1428.	19
AXIS TP3001 MOUNTING BRACKET 4P	1	2		01806-001	01806-001	Spare part mounting bracket for selected AXIS M32 and P32 cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	49
AXIS TP3001-E MOUNTING BRACKET 4P	1	1		01801-001	01801-001	Spare part mounting bracket for selected AXIS P32 outdoor cameras. Suitable for mounting cameras over junction boxes (4" octagon, single-gang, or double-gang), and other Axis mounting accessories. 4-piece bulk pack.	89
AXIS P91 CLEAR DOME A 2P	1	1		01621-001	01621-001	Standard clear dome with anti-scratch hard coating. Rubber gaskets included. Compatible with AXIS P9106-V. 2-piece bulk pack.	39
AXIS P91 SKIN COVER A BRUSHED STEEL	1	1		01622-001	01622-001	Spare part skin cover for AXIS P9106-V. Brushed stainless steel finish. Easy to repaint. Magnetically attached. Suitable for both AXIS P9106-V White and Brushed Steel models.	59
AXIS P1214 SENSOR UNIT	1	1		5503-811	5503-811	Original sensor unit for AXIS P1214 with premounted cable. Flush mount bracket included.	167
AXIS P1214-E SENSOR UNIT	1	1		5503-821	5503-821	Original sensor unit for AXIS P1214-E with premounted cable. Flush mount bracket and sensor unit housing included.	167
SPR P1224-E SENSOR UNIT	1	1		5800-991	5800-991	Original sensor unit for AXIS P1224-E with premounted cable. Flush mount bracket included.	167
RJ12 PLUG SHIELDED 10 PCS	1	8		01182-001	01182-001	Shielded RJ12 connectors for use with AXIS modular cameras. 10-pack.	29
ACC MAINS ADAPTOR PS-P	1	1		5500-701	5500-711	Power supply PS-P for AXIS 215 PTZ	33
AXIS MAINS ADAPTER 12V DC 40W	1	1		01509-001	01509-001	Standard power supply for AXIS FA54. IEC-C13 mains cable is not included.	59
AXIS MAINS ADAPTER 48V DC 90W	1	1		01508-001	01508-001	Standard power supply for AXIS Companion Recorder. IEC-C13 mains cable is not included.	99
ACC PS-RACK	1	1		22512	22512	Power supply for the Axis Video Server Rack	419
ACC MALE RJ45 AXIS 209FD-R	1	1		5502-061	5502-061	Vibration resistant male RJ-45 connector suitable for RJ-45 version of AXIS M31XX-R and AXIS 209FD-R/MFD-R Network Cameras.	13
MAINS CABLE IEC-C13	1			5800-161	5800-171	Mains cable for AXIS One-Port Midspan, AXIS T8123/24, AXIS 291, AXIS Q7900, AXIS Video Server Rack, AXIS PoE Midspan 8-Port/16-Port, Power Supply AXIS T8412.	13
AXIS PATCH CABLE A 200MM 6PCS	1	1		5506-451	5506-451	Set of patch cables for AXIS T8085 PS57 RACK MOUNT 500W 1U to connect AXIS T8646 POE+ OVER COAX BLADE	66
ACC MALE RJ45 AXIS 209FD-R 10PCS	1	1		5502-051	5502-051	Vibration resistant male RJ-45 connector suitable for AXIS 209FD-R/MFD-R Network Camera. 10 pack	125
CABLE GLAND A M16 5PCS	1	1		5800-961	5800-961	M16 cable gland for cable diameter of 4.5 to 10mm. IP68. 5 pcs.	16
AXIS P3367-VE CASING KIT	1	3		5800-601	5800-601	The kit contains a complete AXIS P3367-VE enclosure, heater and cable cover. The kit could also be used for converting an indoor version of AXIS P3346, P3367, P3384 and P3365 to an outdoor VE version.	181
AXIS P54-SERIES WEATHER COVER	1	1		5505-151	5505-151	Sparepart weather cover for Axis P54-Series.	33



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
CONN KIT AXIS P1311	1	300		5500-851	5500-851	Kit for the AXIS P13XX-series. Content: one terminal connector 4P str 250mm BP LF and one 2P STR 3.81MM BP LF.	8
CONN KIT AXIS Q7404	1			5700-161	5700-161	Terminal connectors for AXIS Q7404. Includes 8 pcs 2P 2.50MM, 4 pcs 4P 2.50MM and one 2P 3.81MM. In total 13 connectors.	29
AXIS TM3807 WHITE CASING 4P	1	1		02074-001	02074-001	AXIS M3115/16-LVE WHITE CASING 4P sold as a spare part and comes in pack of four. It enables easy on-site replacement in case the original case has been damaged.	79
LENS M12 2.8-6MM 5PCS	1	1		5801-651	5801-651	Varifocal lens 2.8-6MM, F2.0, M12 thread. Standard lens for AXIS F1015.	249
LENS M12 2.8MM F2.0 10PCS	1	1		5801-921	5801-921	Standard lens for AXIS F4005-E, AXIS F1005-E and AXIS P1214-E.	199
LENS PINHOLE M12 3.7MM 10PCS	1	1		5801-661	5801-661	Pinhole lens 3.7MM, F2.5, M12 thread. Standard lens for AXIS F1025. 10pcs	249
AXIS T93F TOP COVER	1	1		5505-891	5505-891	Spare part top part of the housing including window.	59
ACC LENS CS VARIF 3-8MM DC-IR D/N	1			5500-061	5500-061	CS mount Varifocal 3-8 mm DC-Iris for 221	105
ACC LENS CS VARIF 3-8MM DC-IR	1	1		5500-051	5500-051	CS mount Varifocal 3-8 mm DC-Iris for 211	83
LENS CS 2.8-8MM F1.2 DC-I MP	1		Discontinued contact Order dept for availability	5700-881	5700-881	CS mounted Varifocal 2.8-8 mm DC-iris megapixel lens. Original lens for AXIS M1114.	125
POWER SUPPLY AXIS Q872X-E 230V	1			5503-451	5503-451	IP66 rated power supply for AXIS Q872X-E with 230 V AC input.	318
LENS CS VF 2.8-8MM F1.2 P-IRIS	1	1		5800-671	5800-671	Original CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1604/14 and AXIS P1355/57	125
LENS CS VF 2.8-8MM F1.2 DC-IR	1	1		5800-661	5800-661	Original CS mounted varifocal DC-Iris lens 2.8-8mm for AXIS Q1602/04 and AXIS P1354/55	125
AXIS LENS FUJINON CS 2.8-8MM P-IRIS	1	1		5506-721	5506-721	Standard CS mounted varifocal P-Iris lens 2.8-8mm for AXIS Q1615.	125
LENS CS 2.8-8.5MM P-IRIS	1	1		5801-491	5801-491	Standard CS mounted varifocal P-Iris lens 2.8-8.5mm for AXIS P1364.	159
LENS CS 2.9-8.2MM F1.4 DC SVGA	1	1		5700-871	5700-871	Varifocal 2.9-8.2mm CS mounted SVGA DC-iris lens. Original lens for AXIS M1113	58
LENS CS 4-10MM P-IRIS	1			5801-011	5801-011	Standard lens for AXIS Q1635-E.	249
LENS CS 6.0MM F1.8 MP	1		Discontinued contact Order dept for availability	5700-861	5700-861	CS mounted 6.0 mm megapixel lens. Original lens for AXIS M1103/4	41
AXIS LENS TAMRON C 4-13MM DC-IRIS	1	1		5506-731	5506-731	Standard C mounted varifocal DC-Iris lens 4-13mm for AXIS Q1635.	335
TAMRON 5MP LENS P-IRIS 8-50 MM F1.6	1	10		01469-001	01469-001	Varifocal 8-50 MM, 5 MP telephoto IR-corrected lens with P-Iris. Recommended for AXIS P1367 and AXIS P1367-E.	249
LENS CS 2.8 - 10 MM F1.2 P-IRIS 2MP	1	1		01949-001	01949-001	Lens CS-mount 2.8 - 10 mm. F1.2 P-IRIS 2MP resolution Computer. Spare part for AXIS P1375 / -E	149
LENS M12 2.9MM F2.0 1P	1	1		02065-001	02065-001	LENS M12 2.9MM F2.0 for Q6010-E and Q6100-E.	39
AXIS Q872x-E SUNSHIELD KIT	1		Discontinued contact Order dept for availability	5800-321	5800-321	Sunshield for AXIS Q872x-E as sparepart. Including screws and washer	251
SPR BRACKET KIT AXIS Q60XX/P55XX	1	1		5700-851	5700-851	Bracket kit for surface mounting a camera on a hard ceiling. Compatible with Q603X and P553X. Content: Bracket, screws with washers and wave springs.	20
CONN KIT AXIS M7014	1	1		5800-621	5800-621	Terminal connectors for AXIS M7014. Includes 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	8
SPR CONN KIT AXIS Q7401	1	350		5500-831	5500-831	Connectors for AXIS Q7410 as spare parts. Includes two 2pin STR 2.50MM, one 6pin STR 2.50MM and one 2pin STR 3.81MM. In total 4 connectors.	16
CONN KIT AXIS P7214/Q7411	1	1		5800-611	5800-611	Terminal connectors for AXIS P7214 and AXIS Q7411. Includes 1 pcs TERMINAL CONN 6P STR 2.50MM, 2 pcs TERMINAL CONN 2P STR 2.50MM, rubber feet and mounting screws for the encoder.	8
SPR CONN PUSH PULL PLUG IDC-8 IP67	1	40		5700-371	5700-371	Spare RJ45 connector plug for AXIS Q603X-E & AXIS P55XX-E. IP67 rated.	41
NETWORK CABLE WITH GASKET 5M	1	60		5700-331	5700-331	Shielded outdoor network cable 5 meter. Pre mounted rubber gasket and male RJ45 connectors. For use with AXIS M11-E series, AXIS P13-E series, AXIS Q16-E series, AXIS Q1755-E, AXIS Q19-E series, AXIS P33-VE series and AXIS T92/3-E housings.	8



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q60XX-C MULTI CONNECT CABLE 7M	1	1		5800-821	5800-821	Cable between AXIS Q60XX-C and connection box AXIS T8605	150
AXIS T91G61/T91L61 SCREW KIT	1	6		5901-391	5901-391	Screw kit for installing AXIS P55-E Series with either AXIS T91L61 or AXIS T91G61 Wall Mounts. Single-pack includes 3x bayonet screws, 3x securing screws, 3x springs and an installation guide.	10
AXIS P5544 LENS KIT	1			5800-401	5800-401	Spare part lens kit for AXIS P5544	335
AXIS Q6000-E SOLO KIT	1	15		5801-321	5801-321	Kit for making a stand-alone AXIS Q6000-E MkII installation without PTZ camera inside. Includes a metal cover lid, an internal adapter plate, and IP66-rated RJ45 push-pull connector. Use this kit together with an AXIS Q6000-E MkII network camera (not included) and the AXIS T8133 Midspan 30 W 1-port (not included).	119
AXIS Q603X-E DOME COVER RING	1			5800-101	5800-101	Dome cover ring for AXIS Q603X-E including screws.	15
AXIS T96B05 FRONT KIT 5 PCS	1	1		5506-851	5506-851	Spare part window and window holder for AXIS T96B05 Outdoor Housing and AXIS P3905-RE. 5 Pcs. Includes screws.	169
AXIS Q60XX-C COOLING MODULE	1			5800-501	5800-501	Peltier element, inside and outside fan for AXIS Q60XX-C	839
SPR ELECTRONIC KIT T95A00	1			5700-081	5700-081	Electronic boards for replacement in AXIS T95A00 110-230 VAC. Includes 4 boards.	181
SPR HEATER/FAN KIT T95A10	1			5700-111	5700-111	Replacement kit with 3 heaters and fans for AXIS T95A10	83
SPR SCREW AND GLAND KIT T95A	1			5700-151	5700-151	Replacement cable gland plate, cable glands and screws for AXIS T95A	20
SPR MAINS ADAPTOR PS-V EUR	1			5700-201	5700-211	Power supply PS-V for AXIS M10 series. White Sparepart	33
AXIS T8005 POWER SUPPLY 5V 5W USB	1	5		5901-191	5901-191	Switching power supply, 5W with microUSB connector. Including interchangeable regional power plugs for world wide use.	39
SPR POWER SUPPLY 1U 310W FRONT	1	1		5700-071	5700-071	Replacement power supply for AXIS Q7900 encoder rack	276
SPR POWER SUPPLY 1U 300W BL. FRONT	1	1		5800-861	5800-861	Replacement power supply for AXIS Q7920 Video Encoder Chassis	276
AXIS T93G TOP COVER	1	1		5506-971	5506-971	Spare part top part of the AXIS T93G housing including window.	49
AXIS T92G FRONT WINDOW KIT A	1	1		01578-001	01578-001	Replacement front window assembly for AXIS T92G Outdoor Housing and AXIS Q16-LE Fixed Box Cameras. Includes front window, adjacent IR windows, mounting screws and sealing gasket.	99
AXIS T92G WEATHERSHIELD KIT A	1	1		01579-001	01579-001	Original outdoor weathershield for AXIS T92G Outdoor Housing and AXIS Q16-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light source. Mounting screws included.	59
AXIS T92G20 CAMERA HOLDER	1	1		01954-001	01954-001	Spare Camera Holder for AXIS T92G20 Outdoor Housing and for AXIS Q1645/7-LE Network Cameras. The holder makes it possible to mount AXIS P13 Network Camera Series into AXIS T92G20 Outdoor Housing.	29
AXIS SUNSHIELD B	1	1		5800-971	5800-971	Sunshield compatible with AXIS Q1765-LE, Q1931-E/32-E/41-E and Q2901-E	24
AXIS SUNSHIELD C	1	1		5800-981	5800-981	Sunshield compatible with AXIS Q1765-LE PT Mount	24
AXIS P5512-E SUNSHIELD	1	1		5800-151	5800-151	Sunshield for AXIS P5512-E.	20
SUNSHIELD KIT AXIS P553X-E	1	1		5700-961	5700-961	Sunshield for AXIS P553X-E including mounting screws.	24
SUNSHIELD AXIS Q603X-E	1	2		5700-951	5700-951	Sunshield for AXIS Q603X-E.	24
AXIS Q60XX-C SUNSHIELD	1	1		5800-471	5800-471	Sunshield for AXIS Q60xx-C series	33
AXIS Q604X-S SUNSHIELD	1		Discontinued - contact Order dept for availability	5504-671	5504-671	Stainless steel sunshield for AXIS Q604X-S	246
AXIS Q62 IMPACT PROTECTION BRACKET	1			01600-001	01600-001	Protection of front window on AXIS Q62-LE camera. Provides IK10 rating on product. Includes bracket and mounting screws.	19
AXIS Q62 FRONT WINDOW KIT A	1			01601-001	01601-001	Original front window assembly for AXIS Q62-LE, IK09 rated. Includes a complete front window glass assembly with mounting screws and sealing gasket; and a wiper arm (long-life, UV-resistant silicone rubber included). Note: IR window available separately.	149
AXIS Q62 WIPER KIT A 4P	1	1		01602-001	01602-001	Bulk pack (4 pcs) of replacement wiper arms (rubber included) for AXIS Q62-LE. Made from long-life, UV-resistant silicone rubber.	49

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q62 IR WINDOW KIT A	1			01603-001	01603-001	Original IR window assembly for AXIS Q62-LE. Includes a complete IR Window assembly with mounting screws and sealing gasket. Note: clear front window available separately.	49
SUNSHIELD KIT T92E	1	2		5700-941	5700-941	Sunshield for AXIS P134X-E, AXIS Q1755-E and AXIS Q192X-E. Includes mounting screws and Torx key.	29
AXIS P33 WEATHERSHIELD KIT A	1	3		01701-001	01701-001	Original weathershield with anti-loss screws for protecting AXIS P33 outdoor cameras from rain, snow and sun when wall mounted. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from IR LEDs and other light sources. This part is included with AXIS P3375-VE/LVE Cameras.	25
AXIS P38 WEATHERSHIELD KIT A	1	8		01499-001	01499-001	Original weathershield with anti-loss screws for protecting AXIS P3807-PVE from rain, snow and sun when wall mounted.	25
AXIS Q35 WEATHERSHIELD KIT A	1	1		01179-001	01179-001	Original weathershield for AXIS Q35-LVE network camera series. Screws and gasket included.	24
AXIS WEATHERSHIELD KIT D	1	1		5506-761	5506-761	Weathershield with screws for protecting the dome of an AXIS Q35-VE camera from rain, snow and sun.	17
AXIS WEATHERSHIELD KIT E	1	1		5506-751	5506-751	Weathershield with screws for protecting the dome of an AXIS P32-VE camera from rain, snow and sun.	15
AXIS WEATHERSHIELD KIT M	1	2		5507-321	5507-321	Standard weathershield for AXIS Q3709	34
AXIS WEATHERSHIELD KIT N	1	1		5801-851	5801-851	Standard weather shield for AXIS M2025/26 and AXIS Companion Bullet	24
AXIS WEATHERSHIELD KIT Q	1	1		5801-451	5801-451	Standard weather shield for Axis Q36 Series, protecting the dome from rain, snow and sun.	24
AXIS WEATHERSHIELD KIT R	1	10		01238-001	01238-001	Weathershield for protecting wall mounted fixed dome cameras against rain, snow and sun. UV-resistant plastics and matte black anti-reflective coating on the underside to prevent reflection from IR illumination. Equipped with anti-loss screws for ease of installation. Compatible with AXIS P32-VE/LVE fixed dome cameras.	39
WEATHERSHIELD KIT P3343/44-VE	1	1		5800-011	5800-011	Original weathershield for AXIS P3343, AXIS P3344-VE, AXIS P3363-VE and AXIS P3364-VE. Screws included.	17
WEATHERSHIELD KIT P3346/67-VE	1	3		5800-021	5800-021	Original weathershield for AXIS P3346, AXIS P3367-VE and AXIS P3384-VE. Screws included.	17
AXIS TP3805 WEATHERSHIELD 2P	1	8		01628-001	01628-001	Outdoor weathershield for selected AXIS M32 and P32 cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Anti-loss screws included. Bulk 2 pack.	69
FRONT GLASS KIT AXIS T92E20/21	1	10		5700-831	5700-831	Complete Front Kit for AXIS T92E20/21. Content: Front Cover, Front Glass, Gasket & Screws.	17
ELECTRONIC KIT AXIS T92E20	1	20		5700-971	5700-971	Sparepart including the electronics module of the AXIS T92E20 housing including fan and screws.	150
AXIS T92E EXTENSION KIT	1	1		5506-101	5506-101	Extension front for AXIS T92E20 outdoor housing, allowing longer lenses than the standard housing. The kit includes aluminum front and extension part, window, gasket and screws.	39
AXIS M20 FRONT KIT A	1	1		5901-291	5901-291	Replacement front window assembly for AXIS M2025-LE, M2026-LE. The kit comes with both a black and a white front cover ring. Includes one window and sealing gasket.	29
AXIS P13 WEATHERSHIELD KIT A	1	1		01693-001	01693-001	Standard weather shield for selected AXIS P13 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use near IR LEDs.	39
AXIS P13-E TOP COVER A	1	1		01694-001	01694-001	Replacement top cover with front window for selected AXIS P13-E cameras. Original weathershield is not included but available separately.	79
AXIS P14 FRONT KIT A	1	1		5801-151	5801-151	Standard front for AXIS P1405-E, P1405-LE, P1405-LE MKII, P1425-E, P1425-LE, P1425-LE MKII, P1427-E, P1427-LE, P1435-LE. Includes front ring, window and gasket.	29

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS P14 FRONT KIT B	1			5801-891	5801-891	Standard front for AXIS P1428-E and AXIS P1435-E. Includes front ring, window and gasket.	29
AXIS P14 FRONT KIT C	1	1		01761-001	01761-001	Standard front window kit for selected AXIS P14 series. Abrasion and UV resistant for long service life. Includes cover ring, front window, and rubber gasket.	29
AXIS P14 WEATHERSHIELD A	1	6		01717-001	01717-001	Standard weather shield for selected AXIS P14 series. For protection from rain, snow and sun. The underside of the cover is coated with matte black anti-reflective coating, for suitable use with camera's built-in IR LEDs.	25
AXIS Q17 FRONT WINDOW KIT A	1	1		01686-001	01686-001	Original front glass window assembly for AXIS Q1785/86-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	79
AXIS Q17 FRONT WINDOW KIT C	1			01971-001	01971-001	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	99
AXIS Q1798-LE WEATHERSHIELD	1	2		01972-001	01972-001	Original outdoor weathershield for AXIS Q1700-LE camera. Color: Black	49
AXIS Q1765-LE FRONT KIT	1	1		5801-101	5801-101	Spare part front window for AXIS Q1765-LE	50
SPR FAN CASSETTE AXIS Q7900 E2	1			5800-271	5800-271	Original spare part fan cassette for AXIS Q7900 E2.	167
SPR FAN CASSETTE AXIS Q7920	1	1		5800-851	5800-851	Original spare part fan cassette for AXIS Q7920.	83
AXIS T98A05 CABINET DOOR	1	2		5800-521	5800-521	Cabinet door for AXIS T98A Surveillance Cabinet. Stand alone. Used in T98A15-VE Cabinets.	108
AXIS T98A06 CABINET DOOR	1	1		5800-531	5800-531	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS M111X-E, AXIS P13XX-E, AXIS Q16XX-E, AXIS Q17XX-E, AXIS Q191X-E, AXIS Q192X-E. Used in T98A16-VE Cabinets.	108
AXIS T98A07 CABINET DOOR	1	1		5800-541	5800-541	Cabinet door for AXIS T98A Surveillance Cabinet. Compatible cameras: AXIS P33-VE/LVE and the outdoor bullet-style Q1765 and Q1931 cameras. Used in T98A17-VE Cabinets.	108
AXIS T98A08 CABINET DOOR	1	1		5800-551	5800-551	Cabinet door for T98A. Compatible products: AXIS T91A61 Wall bracket for use with AXIS P55 and Q60-series or fixed dome pendant kits. Used in T98A18-VE Cabinets.	108
AXIS T98A09 CABINET DOOR	1	1		5800-871	5800-871	Cabinet door for AXIS T98A. Compatible products: AXIS P54-Series. Used in T98A19-VE Cabinets.	108
AXIS P135X CONN KIT	1			5800-381	5800-381	Terminal connectors for AXIS P135X-series. Includes 1 pcs TERMINAL CONNECTOR 4P STR 2.50MM, 1 pcs TERMINAL CONNECTOR 2P STR 3.81MM, 2 pcs TERMINAL CONNECTOR 2P STR 2.50MM	8
AXIS T8123/4-E MIDSPAN SPARE KIT	1	1		5800-371	5800-371	2pcs RJ-45 waterproof plugs and 1pcs grounding wire for outdoor midspan T8123/4-E	23
FRONT KIT 60MM AXIS Q872X-E	1		Discontinued - contact Order dept for availability	5800-311	5800-311	Frontkit for AXIS Q872X-E with 60mm lens as spare part.	1.259
FRONT KIT 35MM AXIS Q872X-E	1		Discontinued - contact Order dept for availability	5800-301	5800-301	Frontkit for AXIS Q872X-E with 30mm lens as spare part	587
PT IR ILLUMINATOR KIT B	1			5800-921	5800-921	Spare part illuminator kit for AXIS Q8665-LE. NOTE: it is not possible to upgrade a Q8665-E to become LE version	1.299
AXIS Q86 FRONT KIT A	1	1		01440-001	01440-001	Replacement front window assembly for AXIS Q8685-E/-LE. Window in clear tempered glass. Includes built-in heater, wiper mechanism, and heat sink.	349
AXIS Q86 WIPER KIT A 5P	1	1		01441-001	01441-001	Replacement wiper blades for selected AXIS Q86 and Q87 cameras. Made from long-life, UV-resistant silicone rubber. 5pcs per pack.	49
AXIS Q86-E LIGHT SENSOR BOX 230 V	1			5505-761	5505-761	Light sensor box with integrated power supply for controlling IR illuminators and power AXIS Q8665-LE. Input power 230V AC.	649
AXIS Q8665-E BASE UNIT 24 V AC	1			5801-171	5801-171	Spare part base unit for AXIS Q86-E 24 V AC.	1.199
AXIS Q8665-LE BASE UNIT 24V AC	1			5801-191	5801-191	Spare part base unit for AXIS Q86-LE 24 V AC.	1.199



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS Q8665-E BASE UNIT 230V	1			5801-161	5801-161	AXIS Q8665-E BASE UNIT 230 V AC	1.199
AXIS Q8631-E/32-E HOUSING TOP	1			5801-291	5801-291	Spare part top housing with germanium window for AXIS Q8631-E/32-E.	599
AXIS Q8665 HOUSING TOP	1			5801-281	5801-281	Spare part top housing with glass window for AXIS Q8665-E/-LE.	399
AXIS Q8665-LE ILLUMINATOR	1		Discontinued contact Order dept for availability	5801-261	5801-261	Spare part IR illuminator for AXIS Q8665-LE. Note. This is a single pack.	799
AXIS Q8665-LE ILLUMINATOR BRACKET	1		Discontinued contact Order dept for availability	5801-271	5801-271	Spare part IR illuminator bracket for AXIS Q8665-LE	299
AXIS Q8631/32/65 SUNSHIELD	1			5801-311	5801-311	Spare parte sunshield for AXIS Q8631-E/32-E/65-E/65-LE	59
AXIS Q8665 WIPER	1			5801-201	5801-201	Spare part wiper blade for AXIS Q8665-E/-LE including the stainless steel holder	59
AXIS Q8631/32/65 SEAL AND GASKET KIT	1		Discontinued contact Order dept for availability	5801-231	5801-231	Spare part kit for AXIS Q8631/32/65 consisting of mount bracket gasket, base unit cable glands, IR glands and housing gasket	79
AXIS Q8631/32/65 SCREW KIT	1		Discontinued contact Order dept for availability	5801-211	5801-211	Spare part screw kit for AXIS Q8631/32/65 consisting of all external screws and washers of the cameras	69
AXIS Q8721-E/22-E BASE	1		Discontinued contact Order dept for availability	5800-951	5800-951	Base assembly for the AXIS Q8721-E/22-E.	587
AXIS BISPECTRAL TOP COVER A	1			01497-001	01497-001	Top cover for Axis bi-spectral cameras. Includes top housing, 38mm Germanium front window for thermal and glass window for visual camera, wiper etc.	1.199
AXIS BISPECTRAL TOP COVER B	1			01498-001	01498-001	Top cover for Axis bi-spectral cameras. Includes top housing, 60mm Germanium front window for thermal and glass window for visual camera, wiper etc.	1.999
AXIS TM1802 TOP COVER KIT	1			01779-001	01779-001	Replacement top cover with front window for selected AXIS M11-E cameras. Original weathershield included.	119
AXIS WEATHERSHIELD S	1			01496-001	01496-001	Weathershield from UV-resistant plastics for protecting camera against rain, snow and sun.	59
AXIS WIPER KIT B	1	2		01688-001	01688-001	Wiper arm with blade for easy replacement. Spare part.	59
AXIS CONNECTOR A 2P2.5 STR 10PCS	1	1		5505-261	5505-261	Axis male connector for legacy IO port . Pitch: 2.50 mm. 2pos terminal block. 10pack.	16
AXIS CONNECTOR A 4P2.5 STR 10PCS	1	7		5800-891	5800-891	Axis male connector for limited and full IO port . Pitch: 2.50 mm. 4pos terminal block. 10pack.	16
AXIS CONNECTOR A 6P2.5 STR 10PCS	1	1		5505-271	5505-271	Axis male connector for extended IO port . Pitch: 2.50 mm. 6pos terminal block. 10pack	50
AXIS CONNECTOR A 2P3.81 STR 10PCS	1	7		5800-901	5800-901	Axis male connector for low voltage power. Pitch: 3.81 mm. 2pos terminal block. 10pack	16
AXIS CONNECTOR A 3P3.81 STR 10PCS	1	1		5505-281	5505-281	Axis male connector for low voltage power. Pitch: 3.81 mm. 3pos terminal block. 10pack	24
AXIS CONN A 4P3.81 STR IN/OUT 10P	1	1		5505-291	5505-291	Axis male connector for audio. Pitch: 3.81 mm. 2+2pos terminal block. 10pack	33
AXIS CONNECTOR A 4P3.81 STR 10PCS	1	1		5505-251	5505-251	Axis male connector for low voltage power. Pitch: 3.81 mm. 4pos terminal block. 10pack	24
AXIS CONNECTOR A 2P5.08 STR 10PCS	1	1		5505-301	5505-301	Axis male connector for low voltage power. Pitch: 5.08 mm. 2pos terminal block. 10pack	24
SPR 5 PORT GB ETHERNET SWITCH KIT	1			5800-881	5800-881	Spare part internal switch for the AXIS Q8721-E/22-E Dual cameras,including brackets.	503
AXIS Q1765 FOOT CHASSIS	1	1		5506-091	5506-091	Sparepart foot chassis for AXIS Q1765-LE and AXIS Q193X-E. Note. This sales part does not include the mounting bracket (5506-081 AXIS T94G01S Mounting plate)	33
AXIS ADAPTER RJ45 MALE TO MALE	1	1		5506-891	5506-891	Adapter for connecting Q6000-E to PTZ camera	15
AXIS ACI CONDUIT COVER A 10PCS	1	1		01175-001	01175-001	Spare part plastic side covers for compatible AXIS T91- and AXIS T94- series of mounting accessories. 10 pcs per pack.	19
AXIS Q60-E PCB POWER REPAIR BOARD A	1	1		01195-001	01195-001	Replacement part PCB power board for AXIS Q60-E Outdoor Cameras (not applicable to AXIS Q6000-E)	99



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS TQ1801 WEATHERSHIELD	1	1		01760-001	01760-001	Original outdoor weathershield for AXIS Q1785/86-LE cameras. The underside of the cover is specially coated with matte black anti-reflective coating to prevent reflections from external light sources. Includes weathershield slider and anti-loss screw.	49
AXIS TQ1802 WEATHERSHIELD	1			02014-001	02014-001	KIT WEATHER SHIELD spare part Q1700-LE E1.	99
AXIS TQ1803 FRONT WINDOW KIT	1			02015-001	02015-001	Original front glass window assembly for AXIS Q1700-LE, IK08 rated. Provides the clarity required for maximum utilization of the camera's zoom capacity.	149
AXIS DEVICE MICROPHONE A	1	20		01575-001	01575-001	AXIS Device Microphone A is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product is compatible with devices that support 3.5 mm audio input, like AXIS indoor Q35 series or P33 series together with AXIS TP3201 Recessed Mount.	29
AXIS T8351 MK II MICROPHONE 3.5MM	1	175		01560-001	01560-001	AXIS T8351 Mk II Microphone 3.5mm is an omnidirectional microphone with a 3.5mm connector, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. Flexible to install, AXIS T8351 adapts to different installation scenarios thanks to a vast range of included accessories and to its dust-and-water proof casing.	99
AXIS T8355 DIGITAL MICROPHONE	1	15		01561-001	01561-001	AXIS T8355 Digital Microphone is an omnidirectional microphone compatible with Axis network product with digital in and ring power supporting both a 3.5mm jack and audio terminal block for microphone input. Axis T8355 could be placed up to 100m (328 ft) away from Axis network products, generating flexibility for installation without deterioration of the audio signal.	129
AXIS TP3901 MICROPHONE KIT	1	6		01798-001	01798-001	Casing with built-in microphone for selected AXIS P32-LV cameras. Color: Axis white.	49
AXIS DEVICE MICROPHONE B	1	7		01963-001	01963-001	AXIS Device Microphone B is an omnidirectional microphone to enable audio recording and/or audio analytics with AXIS devices that support audio but do not include a microphone. The product includes a Terminal Block to 3.5 mm Audio Extension allowing it to be installed together with our latest AXIS P32 series.	35
POE SPLITTER 5V	1	20		02044-001	02044-001	PoE Splitter 5 V can be used together with a network device that has no built-in support for Power over Ethernet (PoE). The product splits PoE into separate 5 V DC and data outputs. The product is IEEE 802.3af compliant.	59
AXIS POE MIDSPAN 8-PORT	1	3		5012-002	5012-003	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to eight Axis Network cameras/video servers. Metal casing.	503
AXIS POE MIDSPAN 16-PORT	1	5		5012-012	5012-013	802.3af compliant power injector for standard Cat 5 network cables. Maximum cable length is 328ft/100m. Supporting up to sixteen Axis Network cameras/video servers. Metal casing.	671
AXIS T8120 15W MIDSPAN 1-PORT	1	3		5026-202	5026-203	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf.	46
AXIS T8120 15W MIDSPAN 10PCS	1	20		5026-222	5026-223	Provides power over Ethernet to Axis network video products with built-in PoE support. AXIS T8120 is IEEE 802.3af compliant, ensuring compatibility with all Axis PoE Class 1-3 products. The midspan can be installed on a wall or shelf. 10 pcs.	414
AXIS T8607 MEDIA CONV SWITCH 24VDC	1	2		5901-271	5901-271	Media converter switch . 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Two I/O ports and a combined communication and powering port for the camera. Temp spec. -40 °C to 75 °C (-40 °F to 167 °F). 12 V DC power input. Shelf or DIN-rail mount. 24 V DC power in.	449



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T8123-E OUTDOOR MIDSPAN 30w	1		Discontinued - contact Order dept for availability	5030-231	5030-231	Outdoor ready IP66-rated midspan compliant with IEEE802.3af and 802.3at. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 30W. Temperature specification: -40°C to 55°C (-40° to 131°F) for 30W and -40°C to 65°C (-40°F to 149°F) for 15.4W.	195
AXIS T8611 SFP MODULE LC.LX	1	70		5801-801	5801-801	Small Form Factor Pluggable (SFP) transceiver module. Single mode 1310nm, 10km. Industrial grade.	99
AXIS 30W OUTDOOR MIDSPAN	1	30		01944-001	01944-001	AXIS 30 W Outdoor Midspan is an outdoor ready IP66-/IP67-rated midspan compliant with IEEE802.3af and 802.3at. With built in 6kV surge protection. Delivers up to 30W. Temperature specification: 40°C to 65°C (-40°F to 149°F) for 30W.	249
AXIS T8612 SFP MODULE LC.SX	1	50		5801-811	5801-811	Small Form Factor Pluggable (SFP) transceiver module. Multi mode 850nm, 550m. Industrial grade.	79
AXIS T8613 SFP MODULE 1000BASE-T	1	2		5801-821	5801-821	Small Form Factor Pluggable (SFP) transceiver module. Ethernet RJ-45 . Industrial grade	99
AXIS T8133 30W MIDSPAN	1	5		5900-292	5900-293	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4. Replaces AXIS T8123.	66
AXIS T8134 MIDSPAN 60W	1	1		5900-332	5900-333	High PoE 1-port midspan 60W. Compliant with 802.3.at and PoE 802.3af.	125
AXIS T8144 60W INDUSTRIAL MIDSPAN	1	40		01154-001	01154-001	Industrial midspan with extended temperature range, PoE 60W and dual DC 12/24 V DC power input for redundancy. Operating temperature - 40 to +75 degC or -40 to +167 °F. DIN and wall mount included.	249
AXIS T8154 60W SFP MIDSPAN	1	125		5901-002	5901-003	AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers High PoE 60 W. It works with all Axis network products supporting Power over Ethernet	199
AXIS T8124-E OUTDOOR MIDSPAN 60W	1	15		5031-241	5031-241	Outdoor ready IP66-rated midspan for AXIS Q60-E. Built in surge protection and IP66-rated male RJ45 connector is included. Delivers up to 60W. Temperature specification: -40°C to 50°C (-40° to 122°F).	250
AXIS T8125 AC 24V MIDSPAN 60W	1	15		5900-251	5900-251	60W PoE midspan for 24V AC input.	134
POWER SUPPLY DIN CP-D 12/2.1 25W	1	4		5505-731	5505-731	DIN power supply. 12V DC, 2.1 A. For use in T98A to power cameras, media converters etc.	83
POWER SUPPLY DIN CP-D 24/4.2 100 W	1	3		01169-001	01169-001	DIN power supply. 24V DC, 4.2 A. For use in AXIS Surveillance Cabinets to power cameras, media converters etc.	149
POWER SUPPLY PS24 240 W	1	6		01170-001	01170-001	24V DC power supply with 240 W output power.	229
SPR Q62 MIDSPAN 90W 1-PORT	1	6		01938-001	01938-001	Spare part: 90W Midspan for devices like AXIS Q62 Series.	199
AXIS T8127 60 W SPLITTER 12/24 V DC	1	10		5500-001	5500-001	PoE splitter. Can deliver both 12 and 24 V DC (user selectable) from High PoE 60W midspan. Useful to power and connect non-PoE devices like IP cameras, magnetic locks for access control systems, WiFi AP, thin clients etc.	89
POWER SUPPLY DIN PS24 480W	1	10		01677-001	01677-001	Power supply for AXIS Q86, Q87 & T99A product lines. 480W 24V 20A for DIN rail mounting.	299
AXIS POWER SUPPLY DIN PS56 240W	1	15		01726-001	01726-001	Power supply for AXIS T8504-R Industrial PoE Switch. 240W 56V 5A for DIN rail mounting.	249
AXIS T8129 PoE EXTENDER	1	175		5025-281	5025-281	Power over Ethernet extender repeats the data signal and forward the PoE to the camera, PoE+ compliant it is compatible with all Axis cameras. No additional power supply is required. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	156



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T8129-E OUTDOOR POE EXTENDER	1	70		01148-001	01148-001	AXIS T8129-E Outdoor PoE Extender repeats the data signal and PoE to the camera. AXIS T8129-E is PoE+ compliant with all Axis cameras and does not require an additional power supply. The maximum total distance between switch and camera depends on the power input and the power required by the camera, but all cameras can be at least extended to 200 meter connection.	299
ACC CABLE I/O AUDIO 5M P3343-VE	1	1		5502-331	5502-331	Audio and I/O extension cable for AXIS P33 Series. Includes 4 pin terminal connector 2.5mm Female to Male, 2 x stereo plug 3.5mm Male to Female. 5 meter.	33
AXIS LONG RANGE POE EXTENDER KIT	1	30		01857-001	01857-001	AXIS Long range PoE Extender kit offers a smart and easy-to-install solution for extending the range of your network and PoE up to 1000m (3280ft.). Connect the product in-line with the CAT5e or CAT6 cable and power and data are forwarded to your Axis network devices. AXIS Long range PoE Extender kit supports both IEEE 802.3af and IEEE 802.3at compliant devices and can withstand challenging temperatures. The product is NEMA TS2 compatible.	499
AXIS DIGITAL AUDIO EXTENSION KIT	1	2		01590-001	01590-001	AXIS Digital Audio Extension Kit enables AXIS T8355 Digital Microphone to extend to distances up to 100m (328 ft).	19
AXIS T8508 POE+ NETWORK SWITCH	1	8		01191-002	01191-003	PoE+ managed fanless gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 8 PoE+ ports with 130W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products	399
AXIS AUDIO EXTENSION CABLE B 5M	1	8		01589-001	01589-001	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in).	19
AXIS T8516 PoE+ NETWORK SWITCH	1	15		5801-692	5801-693	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 16 PoE+ ports with 250W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	699
AXIS AUDIO EXTENSION CABLE A 5M	1			5505-131	5505-131	Audio extension cable for Axis 3.5mm mono microphones. Length 5m (197 in)	16
AXIS T8524 POE+ NETWORK SWITCH	1	8		01192-002	01192-003	PoE+ managed gigabit network switch, optimized for Axis network products. 2 SFP/RJ45 uplink ports and 24 PoE+ ports with 370W power supply. Built in DCHP server for plug-and-play camera setup. Easy system configuration for effective installation of Axis network products.	899
TERMINAL BLOCK TO 3.5MM AUDIO EXT	1	10		01714-001	01714-001	3.5mm audio jack extension for Axis Network Video products with terminal block audio connection.	10
AXIS MULTICABLE A I/O AUDIO PWR 1M	1	2		5505-031	5505-031	Multi-connector cable for power (12VDC), audio and I/O port. 1m (40 in)	66
AXIS T8640 POE+ OVER COAX ADAP	1	100		5026-401	5026-401	Pair of Ethernet over COAX adapters that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. Powered by either PoE or power supply, dependent on power requirement at the device end. Diagnostics LEDs for power and link status in both base and device unit. Connectors: BNC and RJ45 connector and power input (for optional power supply). The package contains one base unit and one device unit.	348
AXIS MULTICABLE A I/O AUDIO PWR 5M	1	4		5505-021	5505-021	Multi-connector cable for power (12VDC), audio and I/O port. 5m (197 in)	83
AXIS T8641 POE+ OVER COAX BASE	1	8		5028-411	5028-411	Single Base unit of Ethernet over COAX adapter. The package contains one base unit.	174
AXIS MULTICABLE B I/O AUDIO PWR 2.5M	1	1		5505-511	5505-511	Multi-connector cable for AC/DC power, audio in/out and I/O connectivity. 2.5m (8.2 ft)	66
AXIS T8642 POE+ OVER COAX DEVI	1	10		5027-421	5027-421	Single Device unit of Ethernet over COAX adapter. The package contains one device unit.	174
AXIS MULTICABLE C I/O AUDIO PWR 1M	1	10		5506-201	5506-201	Multi-connector cable for power, audio and I/O connectivity. 1m (3.3 ft)	92

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T8643 POE+ OVER COAX COMPACT	1	2		01468-001	01468-001	AXIS T8643 PoE+ over Coax Compact enables legacy coax cabling to be kept when converting an analog system to digital. The design allows for improved installation and cable management as it can easily be integrated in housings and backboxes. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling.	207
AXIS MULTICABLE C I/O AUDIO PWR 5M	1	1		5506-191	5506-191	Multi-connector cable for power, audio and I/O connectivity. 5m (16.4 ft)	117
AXIS T8645 PoE+ COAX COMPACT KIT	1	20		01489-001	01489-001	AXIS T8645 PoE+ over Coax Compact Kit enables legacy coax cabling to be kept when converting an analog system to digital, and comprises AXIS T8641 PoE+ Over Coax Base and AXIS T8643 PoE+ over Coax Compact. It delivers standard Power over Ethernet (PoE) and centrally-sourced power through existing coax cabling. The compact design of the AXIS T8643 PoE+ over Coax Compact allows for improved installation and cable management as it can easily be integrated in housings and backboxes.	414
AXIS T8646 POE+ OVER COAX BLADE	1	2		5026-461	5026-461	Ethernet over COAX blade (6ch) that enable use of COAX cables for PoE applications, supports IEEE802.3af/at. For use with Axis video encoder chassis together with our AXIS T8082 or AXIS T8085 power supplies. Requires one AXIS T8642 POE+ OVER COAX DEVICE for every channel at the camera end.	587
AXIS T8646 POE+ OVER COAX BLADE KIT	1	1		5026-471	5026-471	A Kit that contains one (1) AXIS T8646 POE+ OVER COAX BLADE and six (6) AXIS T8642 POE+ OVER COAX DEVICE for a complete 6 channel solution.	1.427
AXIS T8648 PoE+ COAX BLADE COMP KIT	1	6		01490-001	01490-001	AXIS T8648 PoE+ Coax Blade Compact Kit contains one (1) AXIS T8646 PoE+ over Coax Blade and six (6) AXIS T8643 POE+ over Coax Compact for a complete 6 channel solution with improved installation and cable management as it can easily be integrated in housings and backboxes.	1.699
USB POWER CABLE 1M	1			5505-661	5505-661	USB power cable to power our M10 cameras. Perfect to use with AXIS M1025 as PVM. Connect camera to a TV through HDMI and use this cable to the USB port on the TV to power the camera, no need for external power supply. DC plug 1.35x3.5mm. Length 1M (3.3 ft). White color.	12
AXIS OUTDOOR RJ45 CABLE 5M	1	10		5502-731	5502-731	Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 5m (16ft). Color: black.	66
AXIS OUTDOOR RJ45 CABLE 15M	1	20		5504-731	5504-731	Outdoor CAT6 Ethernet cable for outdoor AXIS PTZ and panoramic cameras. IP66-rated male push pull connector on one end, IP20 rated male RJ45 connector on the other end. Length: 15m (50ft). Color: black.	125
AXIS Q60XX-C MULTI CONNECT CABLE 12M	1	2		5504-651	5504-651	Cable between AXIS Q60XX-C and connection box AXIS T8605. Length: 12m (39ft).	209
AXIS CABLE 24 VDC/24-240 VAC 22M	1	1		5801-741	5801-741	Heavy duty power cable, 22m (72ft) in length, 3-wire, 12AWG, jacket diameter 10mm (0.4in). Suitable for outdoor installation. UL20626 up to 90°C (194°F) ambient temperature. Designed for use with AXIS Positioning Cameras and Positioning Units, such as AXIS Q8685-E. Material: TPE insulation, copper wire, PVC-free and halogen-free. Color: Black.	199
NETWORK CABLE COUPLER INDOOR	1	20		5503-771	5503-771	Female/female RJ45 coupler. For indoor use. Perfect when you need to extend a pre-terminated cable.	9
NETWORK CABLE COUPLER INDOOR SLIM	1	1		5503-272	5503-272	Female/female RJ45 coupler. Slim and compact size. For indoor use. Perfect when you need to extend a pre-terminated cable.	16



Axis Communications		DECEMBER-2020, EUR						
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP	
AXIS T98A15-VE MEDIA CONVERTER CABINET A (230 V AC)	1	8		5505-401	5505-401	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	755	
AXIS T98A16-VE MEDIA CONVERTER CABINET A (230 V AC)	1	8		5505-411	5505-411	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	755	
AXIS T98A17-VE MEDIA CONVERTER CABINET A (230 V AC)	1	8		5505-421	5505-421	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	755	
AXIS T98A18-VE MEDIA CONVERTER CABINET A (230 V AC)	1	4		5505-431	5505-431	Pre-assembled T98A18-VE Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3) AXIS T8604 Media Converter, (4) Power cable and DIN clip for midspan AXIS T8124, (5) Internal cables and mounts. Tested and verified with Axis cameras.	755	
AXIS T98A19-VE MEDIA CONVERTER CABINET A (230 V AC)	1	2		5505-441	5505-441	Pre-assembled T98A Surveillance cabinet with following system components: (1) Breaker and surge protection, (2), 12 VDC DIN PSU, (3)AXIS T8604 Media Converter, (4) Internal cables and mounts. Tested and verified with Axis cameras.	755	
ACC MAINS ADAPTOR AXIS PS24	1	1		5000-001	5000-001	24VAC power adapter for outdoor use. Output max 63VA.	125	
AXIS T8008 PS24	1	2		5801-701	5801-701	24V DC power supply 250W with extended temperature (-40 to +75C (-40 to 167F)).	399	
AXIS T8051 Power Converter AC/DC to DC	1			5505-051	5505-051	AC/DC to DC power converter for AXIS Q35-VE, 24 V AC or 12/24 V DC input. Backbox designed to match perfectly with camera.	167	
AXIS T8061 ETHERNET SURGE PROTECTOR	1	250		5801-641	5801-641	Protect your Ethernet networks device, i.e. cameras, switches, midspans, etc..., from lightning. Protects up to 10KV surge, IP66 and UL certified.	99	
CONNECTOR M12 MALE 4P 10PCS	1	1		5502-131	5502-131	Rugged, male D-coded M12 connector compatible with AXIS M31XX-R M12 and Connector M12 Female 4P . Field installable with screw-in contacts. 10 pcs	125	
AXIS 10-PIN PUSH-PULL SYSTEM CONN	1	3		5506-251	5506-251	10-pin system connector for power, audio and I/O.	33	
RJ45 FIELD CONNECTOR 10 PCS	1	40		01996-001	01996-001	RJ45 Field Connector (10 PCS) for easy assembly in the field without the need for special tools. Due to its compact size, it has a wide compatibility with Axis devices, like AXIS P32 Series or Network Cable Coupler IP66. Ready to be used with CAT6a ethernet cabling, AWG 26-22. Suitable for IEEE 802.3af, 802.3at, 802.3bt and Axis HighPoE solution.	129	
ELECTRICAL SAFETY KIT B 230VAC	1	1		5503-531	5503-531	Electrical safety kit for AXIS T98A in countries where the mains power is 230 V DC. Included products: Surge protector class 2, Fuse/main switch, terminal blocks and an intrusion door switch.	117	
AXIS STEREO-TO-MONO ADAPTER	1	20		5801-681	5801-681	AXIS Stereo-to-mono Adapter. Spare part to AXIS F44 Dual Audio Input Main Unit. Allows two microphones or line inputs to be connected to AXIS F44 Dual Audio Input.	29	
AXIS POWER CABLE 24 V 7m (23ft)	1	1		02198-001	02198-001	AXIS Power Cable 24V 7m (23ft) helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50° (-58°F) when installed in extreme cold environments.The power cable requires a 24V DC mains adapter (Not included).	39	
AXIS 30W MIDSPAN	1	20	To be launched	02172-002	02172-003	Single port midspan for Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4 products	79	

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS SURVEILLANCE CARD 64 GB	1	900		5801-951	5801-951	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	59
AXIS SURVEILLANCE CARD 64 GB 10P	1	90		5801-961	5801-961	AXIS Surveillance Card 64 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter. 10pack.	569
AXIS SURVEILLANCE CARD 128 GB	1	400		01491-001	01491-001	AXIS Surveillance Card 128 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	99
AXIS SURVEILLANCE CARD 128 GB 10P	1	40		01678-001	01678-001	The 10 pack variant of the AXIS Surveillance Card 128 GB, a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras.	959
AXIS SURVEILLANCE CARD 256GB	1	350		02021-001	02021-001	AXIS Surveillance Card 256 GB is a high endurance microSDXC™ card optimized for video surveillance. It has support for health status monitoring with Axis cameras. The card enables flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapter.	199
AXIS SURVEILLANCE CARD 256GB 10PCS	1	30		02021-021	02021-021	AXIS Surveillance Card 256 GB (10pcs) are high endurance microSDXC™ cards optimized for video surveillance. They have support for health status monitoring with Axis cameras. The cards enable flexible edge recording solutions with de-centralized video recording, eliminating the need of an onsite server, DVR or NVR. Optimizes bandwidth usage as video is recorded onboard each camera even when bandwidth is limited or absent. Combined with Axis Zipstream technology, even high quality video or longer retention times can be used effectively. Includes SD card adapters.	1.930



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
SURVEILLANCE HARD DRIVE 4TB	1	4		01858-001	01858-001	Surveillance Hard Drive 4TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	239
SURVEILLANCE HARD DRIVE 6TB	1	4		01859-001	01859-001	Surveillance Hard Drive 6TB is a 3.5-inch internal drive designed and tested for 24/7 reliable video surveillance. It is optimized for high-definition continuous or event triggered recordings and high write-cycle workloads. Suitable for storage expansion of compatible appliances, it enables for flexible storage solutions. Storage needs can be estimated with AXIS Site Designer 2 and appropriate recommendation will be provided.	359
AXIS T8310 CONTROL BOARD	1	20		5020-001	5020-001	Modular control board for professional camera and video management. AXIS T8310 Control Board is a complete control board solution which includes AXIS T8311 Joystick, AXIS T8312 Keypad and AXIS T8313 Jog Dial. Includes required USB cables interconnecting the units and a 2 meter USB cable to the workstation. AXIS T8310 Video Surveillance Control Board is supported in ACS ver. 3.3 or later.	965
AXIS T8311 JOYSTICK	1	80		5020-101	5020-101	Professional joystick for accurate control of Axis pan/tilt/zoom and dome network cameras. Connects to the workstation over USB. Features a three-axis joystick with X/Y-axis for positioning and turning knob for zoom and 6 push-buttons. Includes a 2 meter USB cable for connection to the workstation. AXIS T8311 Joystick is supported in ACS ver. 3.3 or later.	335
AXIS T8312 KEYPAD	1	6		5020-201	5020-201	Professional 22 button keypad for quick navigation between workspaces, camera views and PTZ. Connects to the workstation over USB. Includes a 2 meter USB cable for connection to the workstation. AXIS T8312 Keypad is supported in ACS ver. 3.3 or later.	377
AXIS T8313 JOG DIAL	1	5		5020-301	5020-301	Professional video surveillance jog dial for high precision playback, facilitating functions such as play, pause, index, image steps and fast search. 6 built-in push buttons additionally simplifies video forensics. AXIS T8313 Jog Dial is supported in ACS ver. 3.3 or later.	335
AXIS T8604 MEDIA CONVERTER SWITCH	1	20		5027-041	5027-041	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F).	335
AXIS T8606 MEDIA CONV SWITCH 24VDC	1	2		5901-261	5901-261	Four port media converter switch with 2 RJ45 ports and 2 SFP slots for optical fiber connection (SFP modules not included). Shelf or DIN-rail mount. Temp spec: -40°C to +75°C (-40°F to 167°F). 24 V DC power in.	399
AXIS T8331 PIR MOTION DETECTOR	1	1		5506-931	5506-931	Indoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	39
AXIS T8331-E PIR MOTION DETECTOR	1	5		5506-941	5506-941	Outdoor PIR detector especially made for Axis cameras to enhance motion detection. Easy plug and play connectivity to Axis I/O camera port.	129
AXIS T8341 PIR MOTION SENSOR EUR	1	1		01202-002	01202-002	PIR Motion Sensor for Axis Wireless I/O using Z-wave technology.	49
AXIS T8342 DOOR/WINDOW SENSOR EUR	1	2		01203-002	01203-002	Door/window sensor for Axis Wireless I/O using Z-wave technology.	49
AXIS T8343 ALERT BUTTON EUR	1	1		01204-002	01204-002	Panic button for Axis Wireless I/O using Z-wave technology.	49



Axis Communications		DECEMBER-2020, EUR						
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP	
AXIS T8353A MICROPHONE 3.5MM	1	20		5032-531	5032-531	AXIS T8353A Microphone 3.5mm is an omnidirectional microphone with a 3.5mm adaptor, compatible with all Axis network video products supporting a 3.5mm jack for microphone input. AXIS T8353A Microphone offers great details and resolution, the capsule has a neutral sonic character and is very natural sounding. The discreet microphone is very reliable even in demanding environments.	377	
AXIS T8353 MOUNT	1	3		5505-041	5505-041	Mounting accessory for AXIS T8353 Microphones	16	
AXIS T8415 WIRELESS INSTALLATION TOOL	1	15		5506-231	5506-231	Camera installation made easy. Battery driven Wi-Fi access point with PoE+ to camera for use with AXIS Installation application on your iOS or Android device.	599	
AXIS T8415 WIRELESS INST TOOL KIT	1	10		5506-881	5506-881	Kit including AXIS T8415 Wireless Installation Tool, one extra AXIS Installation Tool Battery 12V3.4Ah and one AXIS Installation Bag.	699	
AXIS P55/Q60 MULTI CONN CABLE 5M	1	1		5502-491	5502-491	Multi-connector cable for power, audio and I/O. Used for Indoor AXIS P55-series and Indoor Q60-series PTZ Dome Network Camera.	92	
AXIS T8415 INSTALLATION BAG	1	2		5506-871	5506-871	Durable soft bag to carry the AXIS T8415 Wireless Installation Tool, with space for extra battery, charger, network cables etc.	49	
AXIS INSTALLATION TOOL BATTERY 12V3.4Ah	1	10		5506-551	5506-551	Additional battery for AXIS T8415 Wireless Installation Tool.	99	
ACC MAINS ADAP PS-P T-C	1	1		5502-241	5502-251	Power supply PS-P T-C for AXIS Q1755 and AXIS Q7404	33	
AXIS INSTALLATION CHARGER ADAPTOR 12V1A	1	2		5506-561	5506-561	Charging adaptor for AXIS T8415 Wireless Installation Tool.	41	
AXIS P8221	1	1		0321-002	0321-002	Network I/O and audio module. Eight digital ports configurable as inputs or outputs. Two-way audio configurable to simplex, half or full duplex. Built-in pre-amp, phantom power and gain control for a balanced microphone. Line and speaker output. Serial port RS-232/422/485. Power over Ethernet enabled. Includes power supply.	299	
AXIS T8006 PS12	1	10		5030-062	5030-063	Power supply with extended temperature specification -40°C to +75°C (-40°F to +167°F) providing 12 V DC to units such as AXIS T8604 and AXIS Q7424-R.	75	
NETWORK CABLE COUPLER IP66	1	50		5503-431	5503-431	Compact IP66-rated female/female RJ45 cable coupler. Perfect when you need to extend a pre-terminated outdoor cable.	24	
ACC MAINS ADAP PS-K TERM-CONN	1	10		5503-681	5503-681	Power supply for AXIS P1311/43/44 and AXIS Q7401 as a spare part.	33	
AXIS T8003 PS57	1	15		5029-032	5029-033	Power supply for the AXIS T8640 Coax Over Ethernet Adapter. If connected to the base end COAX adapter part, it powers up the connection, the device end unit and the PoE camera and thereby removes the need for a separate midspan. Can also be connected to the device end, to secure enough power (max 30W) to the connected PoE camera (COAX cable quality/long distance).	45	
AXIS T8007 PS24	1	5		5503-102	5503-103	Indoor mains power supply. Output 24V DC 1.5A.	58	
AXIS T8008 PS12	1	1		5503-661	5503-661	Power supply for AXIS Q60XX-C series -40 to +75°C (-40 to 167°F). In 90-264V AC 47-63Hz. Out 12,5V DC 85W.	335	
AXIS T8085 PS57 500W 1U	1	3		5504-862	5504-863	Power supply 500W for use with AXIS T8646 POE+ OVER COAX BLADE in a 1U rack.	965	
CONNECTOR M12 FEMALE 4P 10PCS	1		Discontinued - contact Order dept for availability	5502-141	5502-141	Rugged, female D-coded M12 connector compatible with Connector M12 male 4P, 209FD-R M12 /209MFD-R M12. Field installable with screw-in contacts. 10 pcs	125	
AXIS T90C10 FIXED DOME IR-LED	1	1		5024-101	5024-101	IR-illuminator for AXIS P334X-VE cameras. 18-56 VDC input. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m power cable cable with gaskets.	293	
AXIS T90C20 FIXED DOME IR-LED	1	1		5024-201	5024-201	IR-illuminator for AXIS P334X-VE cameras. PoE IEEE802.3af compliant. Operating temperature -40 °C to 55 °C (-40 °F to 131 °F). IP66-, Nema 4X rated, vandal resistant. Premounted 5m network cable cable with gaskets.	293	



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS T90D20 IR-LED	1	6		01210-001	01210-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	449
AXIS T90D20 POE IR-LED	1	15		01211-001	01211-001	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 36m to 144m (118 ft to 472 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	449
AXIS T90D25 W-LED	1	4		01215-001	01215-001	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input	449
AXIS T90D25 POE W-LED	1	3		01216-001	01216-001	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 25 m to 110 m (80 ft to 360 ft). Made of IK09 impact resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	449
AXIS T90D30 IR-LED	1	4		01212-001	01212-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	799
AXIS T90D30 POE IR-LED	1	3		01213-001	01213-001	PoE powered IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 70m to 350m (230ft to 1150 ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). PoE+ IEEE 802.3at required.	799
AXIS T90D35 W-LED	1	1		01217-001	01217-001	White LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	799
AXIS T90D35 POE W-LED	1	1		01218-001	01218-001	PoE powered white LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°, 35°, 60° & 80° beam angles. Beam distance ranges 35m to 180m (115ft to 590ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F).PoE+ IEEE 802.3at required.	799
AXIS T90D40 IR-LED	1	3		01214-001	01214-001	IR LED illuminator for Axis network cameras. Included interchangeable diverging lenses providing 10°-140° beam angles. Beam distance ranges 105m to 500m (345ft to 1640ft). Made of IK09 impact-resistant aluminium and polycarbonate. IP66 and NEMA 4X ratings. Operating temperature -50°C to 50°C (-58 °F to 122 °F). 12/24 V DC or AC input.	1.199
AXIS WL LENS A 120 DEG	1			5505-671	5505-671	Accessory lens providing 120° beam angle, beam distance 10 m (33 ft). Compatible with AXIS T90B15 W-LED.	21
AXIS WL LENS B 120 DEG	1	1		5505-681	5505-681	Accessory lens providing 120° beam angle, beam distance is 15 m (49 ft). Compatible with AXIS T90B25 W-LED.	24



Axis Communications		DECEMBER-2020, EUR						
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP	
AXIS IR LENS B 120 DEG	1	1		5505-701	5505-701	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B20 IR-LED.	24	
AXIS WL LENS C 120 DEG	1	1		5505-691	5505-691	Accessory lens providing 120° beam angle, beam distance 20 m (66 ft). Compatible with AXIS T90B35 W-LED.	29	
AXIS IR LENS C 120 DEG	1	2		5505-711	5505-711	Accessory lens compatible with AXIS T90B30 IR-LED providing 120° beam angle, beam distance 30 m (98 ft). Also compatible with AXIS T90B40 IR-LED (two lenses are required as the illuminator has two panels). The beam angle can be adjusted between 120° and 180°, with a beam distance stretching from 65 m to 45 m (213 ft to 148 ft). This sales part includes one lens.	29	
AXIS IR LENS D 120 DEG	1	1		01235-001	01235-001	Accessory lens providing 120° beam angle	39	
AXIS T90B REMOTE CONTROL	1	3		5800-931	5800-931	The remote control is compatible with all Axis T90B illuminators and provides the possibility to adjust settings of light intensity, photocell sensitivity and more conveniently from the ground level. No lift or ladder required. The remote control feature can be disabled after the installation is finalized to avoid tampering.	33	
AXIS T90 WALL-AND-POLE MOUNT	1	20		01219-001	01219-001	Mounting bracket for AXIS T90 illuminators.	39	
AXIS T90 SINGLE BRACKET	1	7		01220-001	01220-001	Mounting bracket for AXIS T90 illuminators.	49	
AXIS T90 MULTI BRACKET	1	1		01221-001	01221-001	Mounting bracket for AXIS T90 illuminators.	69	
AXIS DOOR SWITCH A	1	2		5503-841	5503-841	Intrusion door switch for AXIS T98A, connection to I/O port.	24	
AXIS DOME INTRUSION SWITCH C	1	10		01802-001	01802-001	AXIS Dome Intrusion Switch C can be placed in compatible Axis dome cameras and devices to trigger an event upon removal of the casing. Connects directly to the I/O port.	19	
MAINS CABLE ANGL C13-OPN 0.5M	1	5		5506-242		Angled C13 mains cable for use when limited space. Open ends for installation in terminal blocks etc. Use when installing midspan into AXIS T98A Surveillance cabinet.	12	
AXIS FIXED BOX IR ILLUMINATOR KIT A	1	10		01534-001	01534-001	AXIS Fixed Box IR Illuminator Kit A for AXIS P1375-E. For mounting on AXIS P13 Series camera. Range of reach 50 m (164 ft) or more depending on the scene. Powered by AXIS P13 Series camera. Requires Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 4 midspan power for AXIS P13 Series camera.	99	
AXIS I/O INDICATION LED 4P	1	3		01765-001	01765-001	AXIS I/O Indication LED is an easy to install signaling accessory for all AXIS devices that support 12 V I/O and can be setup through the event handling of the device to address desired deterrence or privacy concerns. The LED comes with IP44 rating. Up to three LEDs could be installed with AXIS devices that support 50 mA load on their I/O ports. This product comes in a 4-pack.	69	
AXIS CAMERA HEATER POWER SUPPLY	1	2		02040-001	02040-001	AXIS Camera Heater Power Supply helps extending the operating temperature of AXIS Q6010 / Q6100 -E up to -50°C (-58°F) when installed in extreme cold environments.	99	
AXIS D2110-VE	1	70		01564-001	01564-001	AXIS D2110-VE Security Radar, 24.05–24.25 GHz, FMCW, for wall mounting outdoor. Reliable 180 degrees horizontal field of detection 24/7 with built-in analytics including classification of humans and vehicles. Complement to video surveillance enables filtering on distance, customized detection zones, and auto-tracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light source for deterrence. Open API for software integration, microSD/SDHC memory card slot for edge storage, 30W PoE out to power an additional device, 4 input/output ports, 24 V DC relay port. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4) or DC 8-28V. IP66, IK08 and NEMA 4. Operating conditions -40°C to 60°C (-40°F to 140°F).	1.499	

Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS D2050-VE	1	8		01033-001	01033-001	Phased array FMCW (Frequency Modulated Continuous Wave), 24 GHz outdoor radar motion detector. 120 degrees horizontal and 5-50 meter detection range (16-164 feet). Serves as a complement to video surveillance and enables filtering on distance, customizable detection zones, and autotracking for PTZ cameras. Trigger events to activate camera recording, audio notification or light for deterrence Open API for software integration, microSD/SDHC memory card slot for edge storage, 4 input/output ports, 24 V DC relay port. Wall mount. Powered by PoE+ (IEEE 802.3at, Type 2 Class 4), IP66, IK08 and NEMA 4X Operating conditions -40°C to 60°C (-40°F to 140°F). Midspan not included	1.299
AXIS D8004 UNMANAGED POE SWITCH	1	70		02101-002	02101-003	AXIS D8004 Unmanaged PoE Switch is a 4 channel 10/100 Mbps PoE+ switch with plug & play installation. The unmanaged switch comes with a 60 W power budget and is perfect as an entry-level switch for small systems with PoE requirements.	99
AXIS T8504-E OUTDOOR POE SWITCH	1	15		01449-001	01449-001	Outdoor 4-port managed PoE switch for surveillance applications. 4 PoE ports with up to 60W PoE per port and one SFP port for uplink. Robust metal enclosure with wide temperature range, IP67 and surge protection for demanding installations. Managed switch for remote configuration and management.	1.199
AXIS T8504-R INDUSTRIAL POE SWITCH	1	20		01633-001	01633-001	AXIS T8504-R Industrial PoE Switch is a 4-port managed industrial PoE++ Gigabit switch. In addition, the switch is equipped with 2 x RJ45 and 2x SFP data ports that allows for extra devices to be connected. The switch uses the same intuitive administrator interface as AXIS T85 PoE Network Switch Series, is ruggedized with a wide temperature range and NEMA TS2 compliant.	699
AXIS T6101 AUDIO AND I/O INTERFACE	1	40		01160-001	01160-001	AXIS T6101 Audio and I/O Interface enabling two-way audio and configurable supervised inputs / digital outputs for Axis cameras that do not have such functionality built-in. Powered by standard Power over Ethernet, no midspan included. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	99
AXIS T6112 AUDIO AND I/O INTERFACE	1	60		01230-001	01230-001	AXIS T6112 Audio and I/O Interface combines AXIS T6101 Audio and I/O Interface with an omnidirectional microphone in a discreet casing suitable for indoor installation on wall or ceiling. Powered by standard Power over Ethernet, no midspan included. Two-way audio and configurable supervised inputs / digital outputs for Axis cameras that do not have such functionality built-in. Allows the connected camera to provide one stream for audio and video, without the need for any additional IP address.	149
AXIS P8221 BULK 10PCS	1	1		0321-021	0321-021	AXIS P8221 in 10-pack/bulk. Cannot be sold separately as single pack. NO midspans. Power supplies not included.	2.949
AXIS TW1100 Clip Mount 5P	1	4		02126-001	02126-001	AXIS TW1100 Clip Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The clip mount is an easy to use, versatile mount suitable for many types of clothing.	99
AXIS TW1101 MOLLE Mount 5P	1	7		02127-001	02127-001	AXIS TW1101 MOLLE Mount 5P. 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The MOLLE mount is especially suitable for the MOLLE system found on tactical equipment and such.	69
AXIS TW1102 Magnet Mount 5P	1	7		02128-001	02128-001	AXIS TW1102 Magnet Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The magnet mount is a rugged, versatile mount suitable for many types of clothing	429



Axis Communications		DECEMBER-2020, EUR					
Product Name	Minimum order quantity	High volume order	Status	Product Number EUR	Product Number UK	Product Description	MSRP
AXIS TW1103 Chest Harness Mount 5P	1	7		02129-001	02129-001	AXIS TW1103 Chest Harness Mount 5P 5 pack mount for the Klick Fast adaptor on the AXIS W100 Body Worn Camera. The chest harness mount holds the camera independent of choice of clothing.	169
AXIS TW1200 BW MINI BULLET SENSOR	1	10		01952-001	01952-001	As an accessory to the W100 Body Worn Camera the AXIS TW1200 Body Worn Mini Bullet Sensor is designed to offer a flexible recording position. It supports the Picatinny mounting system, making it compatible with many kinds of available gear, and especially suitable for helmets. AXIS TW1200 offers the same optical performance as AXIS W100 with sharp images even in challenging conditions. Mounting options are included.	199
AXIS TW1900 ADHESIVE PICATINNY RAIL 5P	1	2		02031-001	02031-001	5 pack adhesive picatinny rail to mount the AXIS TW1200 Body Worn Mini Bullet Sensor on general equipment.	59
AXIS TW1901 CABLE HOLDER 5P	1	2		02030-001	02030-001	5 pack replacement cable holder to securely connect the AXIS TW1200 Body Worn Mini Bullet Sensor cable to the W100 Body Worn Camera.	29
AXIS TW1902 LENS PROTECTOR 5P	1	2		02032-001	02032-001	5 pack replacement lens protector for AXIS TW1200 Body Worn Mini Bullet Sensor.	69
AXIS TW1904 Body Worn Mount Flight	1	10		02191-001	02191-001	Demonstration kit consisting of 3 mounts, 1 of each AXIS TW1101, AXIS TW1102 and AXIS TW1103.	149
AXIS W100 BODY WORN CAMERA	1	150		01722-001	01722-001	AXIS W100 Body Worn Camera is an easy-to-use, lightweight and robust body worn camera with an operating time of over 12 hours at 1080p. It delivers sharp images even in challenging conditions and has dual microphones for excellent audio and noise suppression. AXIS W100 features the Klick Fast System, making it compatible with most available mounting options, the TW1100 Clip Mount is included. In addition, Axis Zipstream technology allows users to store as much footage as they require without compromising image quality. The camera also features a GPS/GNSS receiver for location data, Bluetooth Low Energy 4.1, IEEE 802.11b/g/n, and a 6-axis gyro and accelerometer. Docking stations and system controller are sold separately.	649
AXIS W800 SYSTEM CONTROLLER	1	15		01964-002	01964-003	AXIS W800 System Controller is the central integration and management point of the body worn solution. It ensures a high speed and supervised data offloading from the cameras and has built in temporary storage. A single AXIS W800 supports up to five docking stations and 40 cameras and larger body worn systems can easily be extended with additional system controllers. Power adaptor and mounting bracket are included.	1.099
AXIS W700 DOCKING STATION 1 BAY	1	20		01723-002	01723-003	AXIS W700 Docking Station 1 Bay charges the battery and ensures easy data offloading of a single body worn camera. Power adaptor included.	99
AXIS W701 DOCKING STATION 8 BAY	1	20		01724-002	01724-003	AXIS W701 Docking Station 8 Bay charges the batteries and ensures easy data offloading of up to eight body worn cameras. Power adaptor included.	549