

Data Sheet FUJITSU Display B19-7 LED

Advanced display: 48.3 cm (19-inch)
Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B19-7 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office ensured by In-Plane Switching (IPS) technology

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with DVI (HDCP) and Analog

Ready for remote inventory and administration tasks due to the DisplayView Manageability tools

Representative design with space saving front frame and smart details like discretely integrated speakers

Full support for Fujitsu ESPRIMO Q and Fujitsu FUTRO backpack solutions















Technical details

Special features	
ppecial leatules	4-in-1 Stand, In-Plane Switching (IPS) technology, Eco button for Eco mode and 3-coloured Eco status LED, Pivot,
	DisplayView™ IT Suite, 24/7 usage
rgonomic stand	
tand	4-in-1 Stand
eight adjust range	130 mm
icture height over desk (min)	45 mm
otation to portrait	90°
ilt angle	-5° / +35°
wivel angle	340°
icture performance	
anel and backlit	IPS/LED
creen Surface Treatment	Anti-glare, 3H hard coating
ontrast - typical	1000:1
ontrast - advanced	2,000,000:1
esponse time gray to gray typical	5 ms (in video mode)
iewing angle (h/v) - typical	178°/178° CR10:1
olor performance	16.7 million colors (Hi-FRC)
rightness - typical	250 cd/m2
ze and resolution	
spect ratio	5:4
iagonal Size	48.3 cm (19-inch)
esolution (native)	1,280 x 1,024 pixel
esolution (interpolated)	1,024 x 768 pixel, 800 x 600 pixel, 720 x 400 pixel, 640 x 480 pixel
cture size	375 x 300 mm
xel Pitch	0.293 mm
equencies	0.255 (1111)
orizontal	30 - 82 kHz
ertical	56 - 76 Hz
equencies - bandwidth	165 Mhz
onnectivity	TOO WITE
VI	1 x DVI-D (HDCP)
GA/D-SUB	1 x D-SUB
	3.5 mm stereo phone jack for head phone
udio signal output udio signal input	3.5 mm stereo phone jack for fread phone
udio signai input udio sound output	2 x 1.5 W
uaio souna output ase-of-use menu	AN C' I Y 7
anguages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian,
	Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
rightness / Contrast	Brightness, Contrast, Black level, Auto level
olor	sRGB, 6500K, 7500K, Native, Custom Color (R,G,B)
nage adjust	Clock, Phase, H-Position, V-Position
udio	Mute, Volume
formation	Model name, Serial number, Resolution/mode, Signal input
etup	Input select, Language, DDC-CI, OSD-Timeout, Factory preset
ower consumption (typical)	
oft switch off	0.2 W
ower save mode	0.23 W
perating with EPA settings	14.6 W
perating maximum brightness	17 W
Power supply	integrated

	c l «
Power notes	Speakers off
Electrical values	4001/-0/01/
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	Energy Efficiency Class: A, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco-Declaration, EN 60601-1-2
Model	DY19-7
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Japan	VCCI
South Korea	KC (planned)
Argentina	TÜV-S
Singapore	S-Mark
Taiwan	BSMI (planned)
China	CCC
Saudi Arabia	SASO
Global	TCO Displays 6.0, ENERGY STAR® 6.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70,000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	414 x 64 x 349 mm
	16.30 x 2.52 x 13.74 inch
Dimension with stand $(W \times D \times H)$	414 x 209 x 370 mm
	16.30 x 8.23 x 14.57 inch
Weight (packed)	7.2 kg
	15.9 lbs
Weight (unpacked)	5.48 kg
	12.1 lbs
Weight (Monitor only)	2.85 kg
	6.3 lbs
Operating ambient temperature	5 - 35 ℃
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m D-SUB Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Utility CD Warranty booklet Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1471-V140
EAN Code	4051554619824

Order information	
Country specific order code	BDL:K1471V140-UK - with UK power cable, mandatory for Arabian countries BDL:K1471V140-CHN - with China power cable and CEL, mandatory for China BDL:K1471V140-ID - with Import label, mandatory for Indonesia BDL:K1471V140-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/ dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B19-7 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B19-7 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-08-09 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH