Fujitsu recommends Windows 10 Pro.



Data Sheet FUJITSU Notebook LIFEBOOK E547


Reliable Business Performer

Enjoy reliability and powerful performance with FUJITSU Notebook LIFEBOOK E547 through latest technology enhancements. A comprehensive business feature-set with common port replicator and connectivity options support you to work with ease and efficiency wherever your meeting room or workplace is situated. Choose a 39.6 cm (15.6-inch) or 35.6 cm (14-inch) display and even reduce weight with an interchangeable modular bay element.

Reliable and powerful performance

Technology enhancement offer advanced functionality

■ 7th generation Intel® Core™ processors and DDR4 RAM boost performance empowering you to work faster



Reduce complexity and drive down evaluation and deployment costs

■ BIOS and mainboard for one bit image, components, modular bay elements, accessories and port replicator are shared across the LIFEBOOK E5 Series. Unique to Fujitsu, one port replicator befits 7 devices across the LIFEBOOK Ultrabook™, notebook, 2 in 1 and mobile workstation and is compatible with the predecessor

Secure and solid protection

Smart security and resistant design

 Integrated fingerprint sensor, SmartCard reader, TPM, among other security options protect your data, a solid housing and spill-resistant keyboard your notebook

Different high-capacity battery packs

Long lasting performance for extra working hours

 Choose from three different high-capacity battery packs to support efficient working in business environments













Page 1 / 7 www.fujitsu.com/fts/mobile

Components

Base unit	LIFEBOOK E547 non vPro	LIFEBOOK E547 vPro	
Operating systems			
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Home	Nindows 10 Pro.	
Operating system notes	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle.		
Processor	Intel® Core™ i7-7600U processor (2.8 C	iHz, up to 3.9 GHz, 4 MB)	
	Intel® Core™ i7-7500U processor (2.7 (iHz, up to 3.5 GHz, 4 MB) *	
	Intel® Core™ i5-7300U processor (2.6 C	GHz, up to 3.5 GHz, 3 MB)	
	Intel® Core™ i5-7200U processor (2.5 C	GHz, up to 3.1 GHz, 3 MB) *	
	Intel® Core™ i3-7100U processor (2.4 0	GHz, 3 MB) *	
	Intel® Celeron® processor 3865U (1.8 0	GHz, 2 MB) *	
	*Processor only for retail, SMB, educat	ion and government	
Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,133	MHz, SO DIMM	
•	8 GB (1 module(s) 8 GB) DDR4, 2,133		
	16 GB (1 module(s) 16 GB) DDR4, 2,13	33 MHz, SO DIMM	
Hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch, SED		
	SSD SATA III, 256 GB, 2.5-inch, SED		
	SSD SATA III, 256 GB, 2.5-inch		
	SSD SATA III, 128 GB, 2.5-inch		
	HDD SATA III, 7,200 rpm, 500 GB, 2.5-i	nch, S.M.A.R.T.	
	HDD SATA III, 5,400 rpm, 500 GB, 2.5-i		
	HDD SATA III, 5,400 rpm, 1 TB, 2.5-inch		
Hard disk notes	One Gigabyte equals one billion bytes, Accessible capacity may vary, also dep Up to 20 GB of HDD space is reserved f		
	Internal storage interface: S-ATA III (60		
	If configured with an HDD, the drive ha	as an integrated shock sensor.	
Modular bay options	2nd hard disk drive		
	Blu-ray Disc™ Triple Writer		
	SuperMulti-format DVD burner (with d	ouble layer support)	
	Weight saver		
Interface add on cards/components (optional)			
3G/4G (optional)	LTE Sierra Wireless EM7305 (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)		
WLAN (optional)	Intel® Dual Band Wireless-AC8265 11a	c with integrated Bluetooth 4.2	
Display	35.6 cm (14-inch),LED backlight,(HD),	Anti-glare display,compound,1,366 x 768 pixel,350:1,200 cd/m²	
	35.6 cm (14-inch),LED backlight,(Full	HD),Anti-glare IPS display,compound,1,920 x 1,080 pixel,700:1,300 cd/m²	
Multimedia			
Camera	Optional: Built-in webcam, HD (Micros	oft® Lync™)	

Base unit

Page 2 / 7 www.fujitsu.com/fts/mobile

Base unit	LIFEBOOK E547 non vPro	LIFEBOOK E547 vPro
General system information		
Chipset	Integrated	Integrated
Chipset notes		Supports iAMT 11.6 Intel® vPro™ requires Core i5-73xx & i7-76xx CPU, Intel WLAN 8265ac, TPM module
Supported capacity RAM (max.)	32 GB	32 GB
Memory slots	2 DIMM (DDR4)	2 DIMM (DDR4)
Memory notes	DDR4 - 2133 MHz	DDR4 - 2133 MHz
LAN	10/100/1,000 MBit/s Intel® I219V	10/100/1,000 MBit/s Intel® I219LM
BIOS version	UEFI Specification 2.5	UEFI Specification 2.5
BIOS features	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board
Audio codec	Realtek ALC255	Realtek ALC255
Audio features	Stereo speakers	Stereo speakers
Display		·
Display notes	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 40°, Top 10°, Bottom 30°; Color Gammut: 42% FHD - Viewing angle: Left/Right 80°, Top 80°, Bottom 80°; Color Gammut: 45%	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 40°, Top 10°, Bottom 30°; Color Gammut: 42% FHD - Viewing angle: Left/Right 80°, Top 80°, Bottom 80°; Color Gammut: 45%
Graphics		
Base unit	LIFEBOOK E547 non vPro	LIFEBOOK E547 vPro
TFT resolution (DisplayPort)	up to 4,096 × 2,160	up to 4,096 × 2,160
TFT resolution (VGA)	up to 1,920 x 1,200	up to 1,920 x 1,200
TFT resolution (DVI on Port Replicator)	up to 1,920 x 1,200	up to 1,920 x 1,200
Graphics brand name	Intel® HD Graphics 620	Intel® HD Graphics 620
Graphics features	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)
Graphics notes	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system
Interfaces		
DC-in	1	
Audio: line-out / headphone	1	
Audio: line-in / microphone	1	
Internal microphones	2x digital array microphones (optional)	
USB 3.1 Gen1 (USB 3.0) total	3 (1 with Anytime USB Charge functionality)	
VGA	1	
DisplayPort	1	
Ethernet (RJ-45)	1	
Memory card slots	1 (SD up to 2GB, SDHC up to 32GB, SDXC up to 128GB)	
SmartCard slot	1 (optional)	
SIM card slot	1 (only for models with integrated 4G/LTE module)	
Port Replicator interfaces (optional)		
DC-in	1 (19V)	
Power on switch	1	
Audio: headphone	1	
Audio: microphone	1	
USB 3.1 Gen1 (USB 3.0) total	4	
DisplayPort	2 - 1 DP (next to DVI) is shared with DVI, works when DVI	not connected
VGA	1	

Page 3 / 7 www.fujitsu.com/fts/mobile

Internate (R) + 2 shared with DP (next to DW) - works when DP (next to DW) not connected in the themet (R) + 2 (10 (10 01 00 00)	Port Replicator interfaces (optional)			
Rehemet (R)-45) 1 (10/10/1000) Rensington Lock support 1 (Porrug & System) SSATA 1 Rotes Part replicator supports 0-Watts functionality Reyboard and pointing devices Spill resistant keyboard Mays: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status (EP) Application buttons Power Button Wireless technologies Internas 2 Dual band WLAN antennas, 2 LTE antennas optional Bilduetooth v4.2 WLAN encryption WFP, WPA, WPA2 WLAN notes import and usage according to country specific regulations. Power Button WA Adapter 19 Y / 65 W (3 A2 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) Sim and light AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.22 A), 100 Y - 240 Y, 50 Hz - 60 Hz, 3-pm (grounded) AC-Adapter 19 Y / 80 W (4.20 W), 100 W (DVI	1 - shared with DP (next to DVI) - works when DP (next to DVI) not connected		
Ceresington Lock support 1 Portice & System		, , ,		
Votes Port replicator supports 0-Watts functionality				
Specific Company Specific Co	eSATA	1 (1 of ticp & System)		
Spill-resistant keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status LED Application buttons Power Button Wireless technologies Internas 2 Dual band WIAN antennas, 2 LIE antennas optional Silusteooth 4-2 WIAN encryption WEP, WPA, WPA2 WIAN notes Import and usage according to country specific regulations. Power supply KC Adapter 19 1/ 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) silm and light AC-Adapter 19 1/ 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) G-Watt AC Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) G-Watt AC Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 8 90W AC Adapter for usage with Port Replicator Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery up to 12 h Battery unite information is based on worldwide acknowledged BAPCo* MobileMark* 2014 (office productivity). Refer to www. bapoc com for additional details. The BAPCo* MobileMark* Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee any specific battery unitem which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Wolse emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental 13.3 x 9 09 x 0.98 - 1.23 inch Weight (Ibs) from 4.2 lbs Weight (Ibs) from 4.2 lbs Operating ambient temperature 5 3 3°C (41 - 59°T) Operating relative humidity 20 - 80 %	Notes	Port replicator supports 0-Watts functionality		
Spill-resistant keyboard Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status LED Application buttons Power Button Wireless technologies Internas 2 Dual band WIAN antennas, 2 LIE antennas optional Silusteooth 4-2 WIAN encryption WEP, WPA, WPA2 WIAN notes Import and usage according to country specific regulations. Power supply KC Adapter 19 1/ 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) silm and light AC-Adapter 19 1/ 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) G-Watt AC Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) G-Watt AC Adapter (19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 8 90W AC Adapter for usage with Port Replicator Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery up to 12 h Battery unite information is based on worldwide acknowledged BAPCo* MobileMark* 2014 (office productivity). Refer to www. bapoc com for additional details. The BAPCo* MobileMark* Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee any specific battery unitem which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Wolse emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental 13.3 x 9 09 x 0.98 - 1.23 inch Weight (Ibs) from 4.2 lbs Weight (Ibs) from 4.2 lbs Operating ambient temperature 5 3 3°C (41 - 59°T) Operating relative humidity 20 - 80 %	Keyboard and pointing devices			
Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm Multi gesture touchpad with two mouse buttons Status LED Application buttons Power Button Wicless technologies Vaterinas 2 Dual band WLAN antennas, 2 LIE antennas optional Siluetooth v4.2 WLAN notes Import and usage according to country-specific regulations. Power supply VC Adapter 19 17 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 17 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) -WART AC Adapter technology 19 V 19 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded)	ne, see a consequences	Spill-resistant keyboard		
Multi gesture touchpad with two mouse buttons Status ECD Application buttons Power Button Wireless technologies Interenas 2 Dual band WILAN antennas, 2 LTE antennas optional v4.2 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country specific regulations. Power supply LC Adapter 19 19 V 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V 180 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC Adapter technology 19 V 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC Adapter technology 19 V 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC Adapter for usage with Port Replicator Ist battery options Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 5,600/5,800 mAh, 72 Wh Li-lon battery 6-cell, 5,600/5,800 mAh, 49 Wh Runtime 1st battery up to 12 h Battery untime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufactures. It does not guarantee any specific battery untime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Salvey N x y y x y x y x y x y x y x y x y x				
Status LED Application buttons Power Button Wireless technologies Intennas 2 Dual band WLAN antennas, 2 LTE antennas optional Blauteooth v.4.2 WLAN encryption WEP, WPA, WPA2 WLAN notes Import and usage according to country-specific regulations. WAN notes Import and usage according to country-specific regulations. CA dapter Intended Status Int				
Power Button Power Button Power Button Power Button Wireless technologies Victorians		Status LED		
Viciens technologies				
Street Auton Aut		POWEI BULLOII		
MEN encryption MEP, MPA, MPA2 Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage according to country-specific regulations. MEN notes Import and usage with year of the Lag application. MEN notes Import and usage with year of the Lag application. MEN notes Import and usage with a specific product Acdapter technology Import and usage with a policy of the Lag application and power management settings. MEN notes Import and usage with a policy of the Lag and usage with Port Replicator. MEN notes Import and usage with year of additional details. MEN notes Import and usage with year of additional details. MEN notes Import and usage with year of additional details. MEN notes Import and usage with port Replicator and power management settings. The battery capacity depending on product model, configuration, application and power management settings. The battery capacity depending on product model, configuration, application and power management settings. The battery capacity depending on with a power management settings. The battery capacity depending on with a power mana		22 11 10000		
WLAN encryption WLAN notes Import and usage according to country-specific regulations. Power supply WC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system 80 & 90W AC Adapter for usage with Port Replicator Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery up to 12 h Sattery notes Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Poincesions / Weight / Environmental Dimensions / Weight / Environmental Dimensions / Weight / Environmental Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Sattery one A 2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature Diperating ambient temperature Diperating relative humidity 20 - 80 %		<u> </u>		
WEAN notes Import and usage according to country-specific regulations. Power supply AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) O-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (and the properties of the properties				
AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter (by / 90 W (4.74 A), 100 V - 240 V, 50 Hz, 40 W (4.74 A), 100 V - 240 V, 50 Hz, 40 W (4.74 A), 100 V -				
AC Adapter 19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter 19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter 65W AC Adapter for usage with system 80 8 90W AC Adapter for usage with Port Replicator 81st battery options 65W AC Adapter for usage with system 80 8 90W AC Adapter for usage with Port Replicator 81st battery options 82 Ei-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh 12-lon battery 6-cell, 4,500 mAh, 49 Wh 12-lon battery 6-cell, 4,500 mAh, 49 Wh 12-lon battery 6-cell, 4,500 mAh, 49 Wh 12-lon battery options 93 Eastery description 19 Eastery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. **Noise emission** **Noise emission** **Please refer to the Eco Declaration** **Please refer t		import and usage according to country-specific regulations.		
19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology 19 V / 90 W (4.74 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 4,5000 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery Battery charging time 30 The system of t				
Notes 65W AC Adapter for usage with system/ 80 & 90W AC Adapter for usage with Port Replicator Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Quntime 1st battery Quit 12 h Stattery charging time Also main (63Wh) ~ 180 min (72Wh) Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Noise the Eco Declaration Please refer to the Eco Declaration Noise the Eco Declaration Please refer to the Eco Declaration	AC Adapter			
Set battery options				
Li-lon battery 6-cell, 5,600/5,800 mAh, 63 Wh Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery Battery charging time Battery rontes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Noise emission (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Weight from 1.9 kg Weight (lbs) from 4.2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Departing relative humidity 20 - 80 %				
Li-lon battery 6-cell, 6,400/6,700 mAh, 72 Wh Li-lon battery 6-cell, 4,500 mAh, 49 Wh Runtime 1st battery Battery charging time -150 min (63Wh) ~ 180 min (72Wh) Battery routime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Weight from 1.9 kg Weight (Ibs) from 4.2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Diperating relative humidity 20 - 80 %				
Li-lon battery 6-cell, 4,500 mAh, 49 Wh Stattery charging time -150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Dimensions / Weight / Environmental Dimensions (W x D x H)	ist battery options	·		
Runtime 1st battery Battery charging time -150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Noise emissions (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Neight (lbs) from 1.9 kg Neight (lbs) from 4.2 lbs Neight notes Incl. weight saver. Weight may vary depending on actual configuration. Deparating ambient temperature 5 - 35 °C (41 - 95 °F) Deparating relative humidity 20 - 80 %		<u> </u>		
Sattery charging time - 150 min (63Wh) ~ 180 min (72Wh) Battery notes Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Noise emissions / Weight / Environmental Dimensions / Weight / Environmental Dimensions / Weight / Environmental Dimensions (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Neight (lbs) From 1.9 kg Neight (lbs) From 4.2 lbs Neight notes Incl. weight saver. Weight may vary depending on actual configuration. Diperating ambient temperature 5 - 35 °C (41 - 95 °F) 20 - 80 %	Puntime 1st hattery			
Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Otherstons (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch From 1.9 kg Weight (Ibs) From 4.2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Departing ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	·			
Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime. Noise emission Please refer to the Eco Declaration Please refer to the Eco Declaration Please refer to the Eco Declaration Neight / Environmental Dimensions (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Neight (Ibs) From 1.9 kg Neight notes Incl. weight saver. Weight may vary depending on actual configuration. Deparating ambient temperature Deparating relative humidity 20 - 80 %				
Noise emission Please refer to the Eco Declaration Please refer to the Eco Declarat	succes, notes	Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity		
Dimensions / Weight / Environmental Dimensions (W x D x H) $ \begin{array}{l} 338 \times 231 \times 25.1 - 31.4 \text{ mm} \\ \hline 13.3 \times 9.09 \times 0.98 - 1.23 \text{ inch} \end{array} $ Weight Weight (Ibs) From 1.9 kg Weight (Ibs) From 4.2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Departing ambient temperature Departing relative humidity $ \begin{array}{l} 5 - 35 ^{\circ}\text{C} (41 - 95 ^{\circ}\text{F}) \\ \hline 20 - 80 ^{\circ}\text{C} \end{array} $	Noise emission			
Dimensions (W x D x H) 338 x 231 x 25.1 - 31.4 mm 13.3 x 9.09 x 0.98 - 1.23 inch Weight (lbs) Weight (lbs) Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Deperating ambient temperature 5 - 35 °C (41 - 95 °F) Deperating relative humidity 20 - 80 %	Noise emission	Please refer to the Eco Declaration Please refer to the Eco Declaration		
13.3 x 9.09 x 0.98 - 1.23 inch Weight from 1.9 kg Weight (lbs) from 4.2 lbs Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Dimensions / Weight / Environmental			
Weightfrom 1.9 kgWeight (lbs)from 4.2 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %	Dimensions (W x D x H)	338 x 231 x 25.1 - 31.4 mm		
Weight (lbs)from 4.2 lbsWeight notesIncl. weight saver. Weight may vary depending on actual configuration.Operating ambient temperature5 - 35 °C (41 - 95 °F)Operating relative humidity20 - 80 %		13.3 x 9.09 x 0.98 - 1.23 inch		
Weight notes Incl. weight saver. Weight may vary depending on actual configuration. Departing ambient temperature 5 - 35 °C (41 - 95 °F) Departing relative humidity 20 - 80 %	Weight			
Operating ambient temperature 5 - 35 °C (41 - 95 °F) Operating relative humidity 20 - 80 %	Weight (lbs)			
Operating relative humidity 20 - 80 %	Weight notes			
	Operating ambient temperature			
iompliance	Operating relative humidity	20 - 80 %		
·	Compliance			
GS planned (Full HD Display only) in progress	Germany			
Europe CE CB	Europe			
	USA/Canada			

Page 4 / 7 www.fujitsu.com/fts/mobile

Warranty period

RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 EPEAT® Gold (dedicated regions)		
https://sp.ts.fujitsu.com/sites/certificates		
McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Waves MaxxAudio (audio enhancer) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver and utility tool)		
LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS) Microsoft Office (buy license to activate the pre-installed Microsoft Office) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software) Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows®		
DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 11.6 (depending on processor)	
DeskView Client DeskView Instant BIOS Management		
Inventory Management BIOS Management Driver Management Security Management Alarm Management		
WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) BootP (made4you)		
http://www.fujitsu.com/fts/manageability		
Kensington Lock support	Kensington Lock support	
Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	
Access protection via internal SmartCard reader (optional) Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Access protection via internal SmartCard reader (optional Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	
	WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHOL) ENERGY STAR® 6.1 EPEAT® Gold (dedicated regions) CCC (depending on configuration) https://sp.ts.fujitsu.com/sites/certificates McAfee Multi Access Security (anti-virus and internet security waves MaxxAudio (audio enhancer) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver and utility tool) LTE / UMTS Connection Manager (if configured with 4G/LTE Microsoft Office (buy license to activate the pre-installed M CyberLink PowerDVD DVD (playback software for Blu-ray DiscyberLink PowerDVD DVD (playback software for DVD) CyberLink PowerDVD DVD (playback software for DVD) CyberLink PowerDVD DVD (playback software) Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows® DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) DeskView Client DeskView Client DeskView Instant BIOS Management Inventory Management BIOS Management Driver Management Alarm Management WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) BootP (made4you) http://www.fujitsu.com/fts/manageability Kensington Lock support Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional) Access protection via internal SmartCard reader (optional) Embedded fingerprint sensor (optional) Hard disk password User and supervisor BIOS password	

Page 5 / 7 www.fujitsu.com/fts/mobile

1 year (for countries in EMEIA)

Warranty		
Warranty type	Collect & Return Service / Bring-in Service (depending on country)	
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty	
Product Support Services - the perf	ect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	5 years after end of product life	
Service Weblink	htttp://ts.fuiitsu.com/Supportservice	

Recommended Accessories

Port Replicator for LIFEBOOK T7, E5, E7 Series and CELSIUS H730, H760



Flexibility, expandability, desktop replacement, investment protection – to Order Code: name just a few benefits of Fujitsu's docking options.

S26391-F1337-L109

Dicota TopTraveler Base 13-14



The Decota Top Traveler Base 13-14 protects notebooks with up to 14-inch screens. A padded top-loading notebook compartment ensures added protection. It is equipped with a front compartment for storage of power adapters, office supplies or personal items. It's lightweight design ensures flexibility in the office or at home.

Order Code: S26391-F1193-L120

Sneaker Sleeve 14



The Sneaker Sleeve 14 protects notebooks with up to 14-inch screens. The front half of the bag has dedicated compartments for your notebook, power \$26391-F1194-L401 cord, office supplies and personal items. The back half of the bag has an expanding, divided compartment for your files.

Order Code:

Wireless Notebook Mouse WI610



The Wireless Notebook Mouse WI610 uses the latest wireless 2.4 GHz technology, and an ultra-high resolution switchable sensor to give you the precision and reliability you need (1000/1500/2000 dpi). Sporting a stylish silver-black finish, the WI610 wireless mouse is well suited to all environments.

Order Code: S26381-K460-L100

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Notebook LIFEBOOK E547, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Notebook LIFEBOOK E547, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-08-18 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH