

TS-877-1700-16G

| | |
|--------------------------------|---|
| CPU | <p>Processor: AMD Ryzen™ 7 1700 8-core/16-thread 3.0 GHz processor, Turbo Core 3.7 GHz</p> <p>Architecture: 64-bit</p> <p>Graphics: Optional (with PCIe expansion card)</p> <p>Encryption Engine: AES-NI</p> |
| System Memory | 16 GB DDR4 (2 x 8 GB) |
| Maximum Memory | 64 GB (4 x 16 GB) |
| Memory Slot | <p>4 x UDIMM DDR4</p> <p>(For dual- or quad-DIMM configurations, you must use a pair of identical DDR4 modules.)</p> |
| Flash Memory | 512MB DOM |
| Drive Bay | <p>6 x 3.5-inch SATA 6 Gbps bays</p> <p>2 x 2.5-inch SATA 6 Gbps bays</p> |
| Drive Compatibility | <p>3.5-inch bays:</p> <p>3.5-inch SATA hard disk drives</p> <p>2.5-inch SATA hard disk drives</p> <p>2.5-inch SATA solid state drives</p> <p>2.5-inch bays:</p> <p>2.5-inch solid state drives</p> |
| M.2 SSD Slot | <p>2 x M.2 2240/2260/2280/22110 SATA 6Gb/s SSDs</p> <p>Note:</p> <ol style="list-style-type: none"> The M.2 SSD is not included as standard. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD. |
| SSD Cache Acceleration Support | <p>3.5-inch drive bays 1 to 6</p> <p>2.5-inch drive bays 1 to 2</p> <p>M.2 slots 1 to 2</p> <p>Optional: SSD using PCIe expansion slot</p> |
| Hot-swappable | <p>Yes</p> <p>The following are not hot-swappable: M.2 SSDs, SSD cache drives, SSDs using PCIe expansion slots.</p> |

| | |
|---|---|
| 10 Gigabit Ethernet Port | Optional: With PCIe expansion card |
| Gigabit Ethernet Port | 4 x RJ45 |
| PCIe Slot | 1 x PCIe 3.0 x8 1 x PCIe 3.0 x4 1 x PCIe 2.0 x4 |
| USB Port | 2 x USB 3.1 10 Gbps Back: 1 x USB 3.1 10 Gbps Type-C Back: 1 x USB 3.1 10 Gbps Type-A 6 x USB 3.0 Front: 1 x USB 3.0 Type-A (Note: It comes with the One-Touch Copy button) Back: 5 x USB 3.0 Type-A |
| HDMI Output | Optional: With PCIe expansion card |
| Audio | 2 x 3.5 mm dynamic microphone jacks 1 x 3.5 mm line-out jack 2 x speakers Note: You cannot use the speakers and the line-out jack simultaneously. |
| Display Panel | Monochrome backlit LCD display with Enter and Select buttons |
| USB One Touch Copy | Front: USB 3.0 Type-A |
| Form Factor | Tower |
| Dimensions (H x W x D) | 231.9 x 292.8 x 319.8 mm 9.13 x 11.53 x 12.59 inch |
| Net Weight | 8.86 kg (19.53 lbs) Shipping: 10.69 kg (23.57 lbs) |
| Power Supply Unit | 450W, 100-240V AC, 50/60Hz |
| Fan | System: 2 x 80 mm CPU: 2 x 90 mm |
| Operating Temperature & Relative Humidity | 0 ~ 40°C (32°F ~ 104°F), 5 ~ 95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Security Slot | Kensington security slot |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.