

Data Sheet

FUJITSU Storage CELVIN® NAS QE707 Storage

Powerful 2-Drive NAS

The CELVIN® NAS QE707 satisfies the business need for centralized data management needs. Both partners and users can set up and administrate the state of the art CELVIN® NAS easily and at an affordable price. Saving data, managing and sharing files over multiple platforms has never been so simple or so easy.

Business Server Feature

- 2 hot swappable drives
- Backup and replication center
- Multimedia features
- Multipurpose App center

Reliability

- Service-friendly cabinet
- 3-years spare part supply
- Country-specific warranty
- Top-up services are available



CELVIN® NAS QE707

Technical specifications

| | |
|---------------------------|--|
| | <p>Firmware based on 4.2.6 Processor: Annapurna Labs Alpine AL-212, dual core with 1.7GHz Memory: 1GB DDR3DRAM, 512 MB Flash Memory FAN: 1 x quiet cooling fan 120mm, 12V DC USB3.0 x3 (frontx1, rear x2), Gigabit LAN x2 Swappable trays x2 Buzzer, LED indication lights for USB, HDD, LAN, System</p> |
| Hard disk capacity | <p>Up to 2 x 3.5" or 2.5" SATA 3Gb/s or 6Gb/s HDD / SSD Up to 2x6TB raw capacity, consult HDD compatibility list</p> |
| System controls | <p>Power, USB One-Touch-Copy, reset</p> |

Interfaces

| | |
|-----------------------|--|
| LAN / Ethernet | <p>Rear side: x2 Gigabit RJ-45 Ethernet port (always on)</p> |
|-----------------------|--|

Network

| | |
|-------------------|---|
| Networking | <p>TCP/IP (IPv4 /IPv6 dual stack), multi IP setting,LACP, DHCP client, DHCP server including PXE boot CIFS/SMB(1.0,2.0,2.1,3.0selectable), AFP/Netatalk3.2, NFS v3, HTTP, HTTPS, FTP,SFTP(admin), DDNS, NTP, Telnet, SSH, iSCSI, SNMP,WebDAV,SMSC Gigabit w/ Jumbo Frame, Bonjour</p> <p>iSCSI target (with multi-LUNs per target), Up to 256 LUNs/targets combined iSCSI LUN online expansion LUN mapping / LUN masking Online LUN capacity expansion SCSI Primary Commands -3 (SPC-3) support / persistent reservation Supports MPIO & MC/S iSCSI LUN Backup, One-time-Snapshot and Restore iSCSI initiator for virtual disks (max 8 disks); stack chaining master Virtual disk support for EXT3/ EXT4/ NTFS/ FAT32/ HFS+ iSCSI Connection and Management by Fujitsu Finder (Windows)</p> <p>VLAN 802.1Q USB WiFi-Adapter support IEEE 802.11b/g/n/ac WEP, WPA-personal (AES/TKIP), WPA2-personal (AES) Connection to wireless network or Ad Hoc network</p> |
|-------------------|---|

| | |
|--------------------------|---|
| Backup Management | <p>Client backup software Time machine backup (OS X Lion support) 3rd party backup software support Encrypted block-level remote replication (instant, scheduled backup management); synchronization mode/Rsync Real-time remote replication (RTRR protocol) for real-time backup of server & client, 3 sync modes, filter, policy definition, SSL protected RTRR/Rsync work as server or client with bandwidth control Backup to Cloud Backup to (encryptable) USB/eSATA storage devices LUN backup and restore LUN point-in-time snapshot (1x)</p> |
|--------------------------|---|

Network

| | |
|-------------------------------|---|
| File System Management | <p>Network share management (max. 512 shares) Share folder level ACL support Unicode support Journaling file system</p> <p>File Station Supports ISO Mounting (Up to 256 ISO Files) Support thumbnail display of multimedia files Support share download link and upload link Drag-n-drop Files via Chrome and Firefox Support mounting Cloud drive via FTP/SMB/CIFS</p> <p>Browsers Photo, music, and video preview and playback File Compression and decompression (ZIP and 7z)</p> <p>Qsync Syncs files among multiple devices with SSL support Selective synchronization for syncing specific folders only Share team folder as a file center for team collaboration Shares files by links via e-mail Policy settings for conflicted files and file type filter support Incremental synchronization for HDD space saving Supports Windows & Mac OS</p> |
| Disk Management | <p>Flexible Volume/LUN with thin provisioning and space reclaim Volume types: RAID 0/1, JBOD, single Supports storage pools Online volume expansion & storage pool expansion Online RAID capacity expansion and online RAID level migration SMART data migration SSD read-only/read-write cache Bad block scan, recovery, and hard drive S.M.A.R.T. RAID recovery Bitmap support</p> <p>ISO mounting support up to 256 ISO-files</p> |
| User Management | <p>User quota management Windows Active Directory support, Domain Controller LDAP directory service supports Open LDAP User account management (max. 2048users) User group management (max. 256 groups) Shared folders (max. 256) Concurrent connections (max. 256) Support batch creating users User Import/ Export for Multiple CELVIN NAS Deployment Subfolder Permission (File/Directory ACL) Microsoft Networking (Samba) Host Access Control (Domain/IP)</p> |
| VPN Server | <p>Secure remote access: PPTP/OpenVPN VPN services Max number of clients: 15</p> |

Network

| | |
|--------------------------------------|--|
| System Tools | E-mail alert (SMTP authentication); SMS alert notification HDD standby mode Disk usage alert Automatic power on after power loss System firmware upgrade Back-up, restore, reset system settings Smart fan setting Configurable management port Policy-based unauthorized IP blocking; import user list Secure remote login by SSH connection Remote login by Telnet connection USB, SNMP v3, UPS support Scheduled power on/off Import SSL certificate Network recycle bin Password strength checker |
| Event Logs | Complete system logs (file level): system events management, connection logs, current connection of on-line users Centralized monitoring / syslog server (TCP / UDP) Manually and advanced log filtering via wizard |
| Multilingual (Online) Support | Chinese (Traditional & Simplified), Czech, Danish, Dutch, English, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese (Brazil), Romanian, Russian, Spanish, Swedish, Thai, Turkish |
| FTP Server | FTP remote access (max. 256 concurrent connections) FTP with SSL/ TLS (explicit) mode FTP bandwidth control and connection control Passive FTP port range control FXP and Unicode support TFTP server (PXE boot) SFTP |
| Printer Server | Max. 3 printers; Internet Printing Protocol; Apple Bonjour Printing; Print Job display and management IP/Domain based privilege control |
| Web Server | Built-in editable php.ini, SQLite and MySQL Web-based management via phpMyAdmin Max. 32 virtual hosts |
| MySQL Server | MySQL database server |
| Security | Network access protection with autoblocking (SSH, Telnet, HTTP(S), FTP, CIFS/SMB, AFP) Policy based automatic IP blocking and IP filter Encrypted access (HTTPS, FTP with SSL/TLS(explicit),SSH/SFTP, RSync over SSH, CIFS host access control for shared folders ClamAV antivirus protection FIPS 140-2 validated AES 256-bit volume based data encryption Importable SSL certificates VPN Client: Supported VPN protocols: PPTP & OpenVPN services PPTP Authentication: PAP, CHAP, MS-CHAP, MS-CHAPv2 PPTP Encryption: None, AES 40/128 bit, AES 256 bit OpenVPN Encryption: None, AES 40/128 bit, AES 256 bit Transmission package monitor OpenVPN port control OpenVPN link compression VPN Server: Secure remote access: PPTP/L2TP/IPsec & OpenVPN VPN services Max number of clients: 30 Radius Server Instant alert via E-mail, SMS, Instant Messaging, LCD |

Network**Multimedia**

DLNA Server

Supports DLNA/UPnP TVs and Players such as PlayStation 3 and Xbox 360
 Supported audio format: AIFF, APE, DSD (DSF, DFF), FLAC, M4A, M4A Apple Lossless (ALAC), MP3, Ogg Vorbis, WAV (PCM, LPCM), WMA, WMA PRO, WMA VBR
 *DRM encryption format is not supported.
 Support CUE indexing file for APE, FLAC audio format.
 Video and Audio On-the-fly Transcoding

Video Station

Show photos in thumbnails, list, timeline, or folder view
 Tags videos with text, color, and rating
 Animated thumbnails for videos
 Shares video collection link to social websites or through email
 Display movie information from IMDB

Transcode Management

Offline video transcoding: 240p, 360p, 480p, 720p and 1080p resolution
 Automatic video transcoding for watched folders

Music Station

Plays or Shares Music Collections with Web Browser
 Automatic Classification via Media Library
 Supported audio format: AIFF, APE, FLAC, M4A, M4A Apple Lossless (ALAC), MP3, Ogg Vorbis, WAV (PCM, LPCM), WMA, WMA PRO, WMA VBR
 * DRM encryption format is not supported.
 Internet Radio (MP3)
 Up to 8 Music Alarms

Photo Station

Show photos in thumbnails, list, timeline, or folder view
 Supports virtual/smart album
 Tags photos with text, color, and rating
 Slideshows with background music and different transition effects
 Animated thumbnails for videos
 Geotags photos and display them on Google maps
 Shares slideshows link to social websites or through email

iTunes Server

Audio and Video Sharing for Windows & Mac iTunes

AirPlay

Streams videos, photos and music from NAS to Apple TV via Qfile

Application center

Diverse applications downloadable via App center
 Fujitsu NAS Explorer, Fujitsu NAS Manager for Android / iOS

Download Station

PC-less BT, FTP/FTPS, and HTTP/HTTPS download (up to 500 Tasks)
 BT download with Magnet Link and PT support
 Scheduled download and bandwidth control
 RSS subscription and download (broadcatching)
 Bulk download with wildcard settings
 BT search
 Proxy support for BT download
 PC utility: Qget for downloads browsing and management

System requirements**Browser Support**

Internet Explorer 10+ / Mozilla Firefox 8, 9, 10 / Apple Safari 4, 5 / Google Chrome / Edge

| | | | |
|--|--|--------------------|--------------------|
| Device Classification | Information according to ErP Regulation (EC) No. 1275/2008 – Standby/networked standby requirements: All CELVIN® NAS Servers have a so called “EUP-mode” implemented. With activated “EuP-mode” the device has a maximum power consumption of 0.5 W in standby mode by limited functionality. (Details are described in the operating manual) The intended use of these type of networked infrastructure device is providing always available data access while operating (i.e. “always on”). The requirement of networked standby mode function as described in Regulation (EC) No. 1275/2008 Annex II, 3(b) (“Power management for networked equipment”) would be inappropriate for this intended use of the equipment. It could only be achieved by turning off vital components of the equipment that are essential for the maintenance of the intended use. | | |
| Power consumption | Off-mode (WoL-mode): 0.44W HDD-Sleep mode: 8.46W HDD R/W-mode: 15.6 W Idle mode: 12W (2x WD10EFRX-HDD) | | |
| Power supply input | External power supply 100 - 240V | | |
| Power supply output | 12V; 65W | | |
| Humidity (operating) | 5 - 95 % (relative humidity), wet bulb 27° C | | |
| Compliance | | | |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates | | |
| Dimensions / Weight / Environmental | | | |
| Dimensions (W x D x H) | 102 x 219 x 169 mm | | |
| Weight | 1.28 kg | | |
| Operating ambient temperature | 0 - 40 °C | | |
| Operating relative humidity | 5 - 95 % (relative humidity), wet bulb 27° C | | |
| Acoustic noise level | Sound Pressure Level (LpAm) bystander position 1m (front) in dB(A): idle: 16.6 operating medium speed(1200) 25.6; HDD sleep: 11.7 | | |
| Package content | | | |
| | CELVIN NAS Server QE707; Power Cord, LAN cable, trays, Quick Start Guide, Service flyer | | |
| Order code | | | |
| | S26341-F108-L707 | EAN: 4059595404355 | w/o HDD EU |
| | S26341-F108-L722 | EAN: 4059595404379 | 2x2 TB NAS HDD EU |
| | S26341-F108-L723 | EAN: 4059595404386 | 2x3 TB NAS HDD EU |
| | S26341-F108-L724 | EAN: 4059595404393 | 2x4 TB NAS HDD EU |
| | S26341-F108-L726 | EAN: 4059595404409 | 2x6 TB NAS HDD EU |
| | S26341-F108-L730 | EAN: 4059595404454 | w/o HDD INT |
| | S26341-F108-L732 | EAN: 4059595404423 | 2x2 TB NAS HDD INT |
| | S26341-F108-L734 | EAN: 4059595404430 | 2x4 TB NAS HDD INT |
| | S26341-F108-L736 | EAN: 4059595404447 | 2x6 TB NAS HDD INT |
| Warranty | | | |
| Warranty period | 2 years | | |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty | | |
| Recommended Service | X - 2/3 years, 9x5, Onsite Response Time: Next Business Day or Second Business Day | | |
| Service Weblink | http://www.fujitsu.com/fts/services/support | | |

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Storage CELVIN® NAS QE707, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Storage CELVIN® NAS QE707, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/accessories

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



**Green
Policy
Innovation**

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2017-11-24 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2017 Fujitsu Technology Solutions GmbH