

Overview

Affordable color, maximum uptime, and strong security from a smart, efficient MFP.

Business moves fast, and slowing down means falling behind. It's why HP built the next generation of HP PageWide MFPs—to power productivity with a smart, efficient design that delivers the lowest color cost,[1] maximum uptime, and strong security.

The lowest cost for color[1]

Get the quality you expect with HP PageWide Technology that delivers the lowest cost per color page.[1]

Minimal interruptions. Maximum uptime.

Minimize interruptions with an HP PageWide MFP designed for the least maintenance in its class.[4]

Strong security designed to detect and stop attacks

A suite of embedded security features help protect this MFP from being an entry point for attacks.

Designed with the environment in mind

Conserve resources with HP PageWide—designed to use less energy than any laser MFP in its class.[2]

Features

| Breakthrough value—the lowest cost per color page ^[1] | General Office mode for faster, lower-cost prints ^[3] |
|--|--|
| Best-in-class energy efficiency ^[2] | Fewer parts, less maintenance ^[4] |
| Up to 50% faster than competitors—as fast as 55 ppm ^[5] | |

- [1] Lowest cost per color page claim applies to devices that are not sold under contract: Comparison of HP PageWide A3 devices with the majority of in-class color ink/laser MFPs (\$3,000-\$7,499 and €2,820-€7,049) and color ink/laser single function printers (\$1,500-\$2,999 and €1,410-€2,819) as of January/February 2017; market share as reported by IDC as of Q4 2016. Cost per page (CPP) reported by gap intelligence Pricing & Promotions Report January/February 2017; comparisons for devices/supplies not sold under contract are based on published specifications of the manufacturers' highest-capacity cartridges, inclusive of long life consumables and page yield. Average HP yield based on ISO/IEC 24711 and continuous printing in default mode. Actual yield varies based on content of printed pages and other factors. For more information, see http://hp.com/go/learnaboutsupplies and http://hp.com/go/PageWideClaims.
- [2] Energy claim based on TEC data reported on energystar.gov as of February 2018. Data normalized to determine energy efficiency of in-class A3 color laser printers and MFPs with published speeds of 20 to 80 ppm, excluding other HP PageWide products. Subject to device settings. Actual results may vary.
- [3] Comparison based on printing in Professional mode.
- [4] Fewer service parts claim based on HP analysis of leading in-class A3 color laser printers and MFPs as of February 2018; calculations use publicly available and/or published manufacturer rated yields for long-life consumables and assume 600,000 pages printed (using a 60% black/40% color ratio). Learn more at http://hp.com/go/pagewideclaims.
- [5] Comparison of HP PageWide A3 devices with the majority of in-class color ink/laser MFPs (\$3,000-\$10,299 and €2,820-€10,199), and color ink/laser single function printers (\$1,500-\$4,299 and €1,410-€4,099) as of April 2018 excluding other HP PageWide products; competitive set based on market share data as reported by IDC as of Q4 2017, MSRP data provided by gap intelligence and/or Buyers Lab. HP PageWide speeds based on General Office mode and exclude first page. Learn more at http://hp.com/go/printerspeeds.

Specifications

| | HP PageWide Technology up to 1200 x 1200 optimized dpi from 600 x 600 |
|-----------------------------------|---|
| Print Resolution Technologies | input dpi |
| Print quality black (best) | Up to 1200×1200 optimized dpi from 600×600 input dpi (on Unspecified, Plain, HP Premium Presentation Matte, and HP Brochure Matte) |
| Print quality color (best) | Up to 2400 x 1200 optimized dpi from 600 x 600 input dpi (on HP Advanced Photo Papers) |
| Print speed black (ISO, A4) | Up to 35 ppm |
| Print speed black (ISO, letter) | Up to 35 ppm |
| Print Speed Color (ISO) | Up to 35 ppm |
| Print speed color (ISO) | Up to 35 ppm |
| Print speed | Print speed up to 35 ppm (black) and 35 ppm (color) |
| Functions | Print, copy, scan, fax (optional) |
| Duplex printing | Automatic (standard) Manual (driver support provided) |
| Duty cycle (monthly, A4) | Up to 75,000 pages |
| Duty cycle (monthly, letter) | Up to 75,000 pages ^[7] |
| Printer smart software features | HP Trusted Platform Module; HP JetAdvantage Security Manager; HP Web Jetadmin; HP ePrint, Apple AirPrint™, HP Auto-On/Auto-Off technology, HP Color Access Control, HP EasyColor, Front-facing USB printing, store print jobs, print preview, automatic two-sided printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, booklet printing, cover pages, tray selection, scaling, Portrait/Landscape orientation, High Quality Grayscale and Black Ink Only, General Office/Professional/Presentation dpi print modes, Optional: wireless |
| Copier smart software features | Auto scale; Reduce/enlarge from scanner glass (25 to 400 percent); Collate; Auto color detection; Two-sided copying; Image adjustments (darkness, background cleanup, sharpness); Job build |
| Scanner advanced features | Optimize text/picture; Image adjustments; Job build; Output quality setting; Selectable scan resolution 75 to 600 dpi; Auto detect color; Edge Erase; Job notification; Blank page suppression; HP Quick Sets; Scan and save to destinations: network folder, FTP, SharePoint, USB flash drive, email; see software section for more details. |
| Fax smart software features | Stored faxes; Fax archiving; Fax forwarding; Scale to fit; Fax address book; LAN/Internet fax; Fax number confirmation; Holiday fax schedule |
| Energy savings feature technology | HP Auto-on/Auto-off Technology |
| | |

HP 990A Black PageWide Cartridge (US/CA) (~10,000 pages) MOJ85AN; HP 990A Cyan PageWide Cartridge (US/CA) (~8,000 pages) MOJ73AN; HP 990A Magenta PageWide Cartridge (US/CA) (~8,000 pages) MOJ77AN; HP 990A Yellow PageWide Cartridge (US/CA) (~8,000 pages) MOJ81AN; HP 990X Black PageWide Cartridge (US/CA) (~20,000 pages) MOK01AN; HP 990X Cyan PageWide Cartridge (US/CA) (~16,000 pages) MOJ89AN; HP 990X Magenta PageWide Cartridge (US/CA) (~16,000 pages) MOJ93AN; HP 990X Yellow PageWide Cartridge (US/CA) (~16,000 pages) MOJ97AN; HP 991A Black PageWide Cartridge (EU) (~10,000 pages) MOJ86AE; HP 991A Cyan PageWide Cartridge (EU) (~8,000 pages) MOJ74AE; HP 991A Magenta PageWide Cartridge (EU) (~8,000 pages) MOJ78AE; HP 991A Yellow PageWide Cartridge (EU) (~8,000 pages) MOJ82AE; HP 991X Black PageWide Cartridge (EU) (~20,000 pages) MOK02AE; HP 991X Cyan PageWide Cartridge (EU) (~16,000 pages) MOJ90AE; HP 991X Magenta PageWide Cartridge (EU) (~16,000 pages) MOJ94AE; HP 991X Yellow PageWide Cartridge (EU) (~16,000 pages) MOJ98AE; HP 992A Black PageWide Cartridge (LAR) (~10,000 pages) MOJ87AL; HP 992A Cyan PageWide Cartridge (LAR) (~8,000 pages) MOJ75AL; HP 992A Magenta PageWide Cartridge (LAR) (~8,000 pages) MOJ79AL; HP 992A Yellow PageWide Cartridge (LAR) (~8,000 pages) MOJ83AL; HP 992X Black PageWide Cartridge (LAR) (~20,000 pages) MOK03AL; HP 992X Cyan PageWide Cartridge (LAR) (~16,000 pages) MOJ91AL; HP 992X Magenta PageWide Cartridge (LAR) (~16,000 pages) MOJ95AL; HP 992X Yellow PageWide Cartridge (LAR) (~16,000 pages) MOJ99AL; HP 993A Black PageWide Cartridge (AP) (~10,000 pages) MOJ88AA; HP 993A Cyan PageWide Cartridge (AP) (~8,000 pages) MOJ76AA; HP 993A Magenta PageWide Cartridge (AP) (~8,000 pages) MOJ80AA; HP 993A Yellow PageWide Cartridge (AP) (~8,000 pages) MOJ84AA; HP 993X Black PageWide Cartridge (AP) (~20,000 pages) MOK04AA; HP 993X Cyan PageWide Cartridge (AP) (~16,000 pages) MOJ92AA; HP 993X Magenta PageWide Cartridge (AP) (~16,000 pages) MOJ96AA; HP 993X Yellow PageWide Cartridge (AP) (~16,000 pages) MOK00AA 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network Internal, 33.6 kbps Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-TX, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gigabit Ethernet; IPsec (standard) Optional, enabled with purchase of a hardware accessory HP ePrint; Apple AirPrint™; Mopria™-certified; Wireless Direct Printing; Google Cloud Print; Mobile Apps IPv4/IPv6: Apple Bonjour Compatible (Mac OS v10.2.4 or higher), SNMPv1/v2c/v3, HTTP, HTTPS, FTP, TFTP, Port 9100, LPD, WS Discovery, IPP, Secure-IPP, IPsec/Firewall; IPv6: DHCPv6, MLDv1, ICMPv6; IPv4: Auto-IP, SLP, Telnet, IGMPv2, BOOTP/DHCP, WINS, IP Direct Mode, WS Print

Replacement cartridges

Connectivity, standard

Modem

Network capabilities

Wireless capability

Mobile printing capability

Network protocols, supported

Software included

HP Device Experience (DXP), HP PCL 6 Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.HP.com or OS App Source for printer software), Online user manuals

| Compatible Operating Systems | (Full solution software available only for Windows 7 and newer, UPD software available only for Windows 7 and newer HP Software for Mac and Windows is no longer included on the CD, but can be downloaded from 123.hp.com, Legacy Windows Operating Systems (XP, Vista, and equivalent servers) get print drivers only, with a reduced feature set Windows RT OS for Tablets (32- & 64-bit) uses a simplified HP print driver built into the RT OS) |
|-----------------------------------|---|
| Sustainable impact specifications | Mercury free |
| Energy star certified | Yes |
| Ecolabels | Blue Angel; EPEAT® Silver registered; ENERGY STAR® certified |
| Blue Angel compliant | Yes, Blue Angel DE-UZ 219—only ensured when using Original HP supplies |
| Copy speed black (best, A4) | Up to 35 ppm |
| Copy speed black (best, letter) | Up to 35 ppm |
| Copy speed color (best, A4) | Up to 35 ppm |
| Copy speed color (best, letter) | Up to 35 ppm |
| Digital sending standard features | Scan-to E-mail with LDAP email address lookup; Scan-to Network Folder; Scan-to USB; Scan-to SharePoint, Scan to FTP; Send to LAN Fax; Send to Internet Fax; Color Access Control; Native authorization and authentication; Quick Sets; two-sided copying; scalability; image adjustments (darkness, contrast, background cleanup, sharpness); N-up, N or Z-ordering; content orientation; collation; booklet; ID Scan; job build; edge-to-edge; job storage |
| Fax Resolution Black (best) | Up to 300 x 300 dpi (400 x 400 dpi for received faxes only) |
| Faxing | Yes, color |
| Scan speed (normal, A4) | Up to 60 ipm (mono and color), LEF* |
| Scan speed (normal, letter) | Up to 60 ipm (mono and color), LEF* |
| Scan file format | Scan File Type supported by Software: Bitmap (.bmp), JPEG (.jpg), PDF (.pdf), PNG (.png), Rich Text (.rtf), Searchable PDF (.pdf), Text (.txt), TIFF (.tif) |
| Scan input modes | Front panel applications: Copy, Scan to E-mail with LDAP e-mail address lookup, Scan to Network Folder, Scan to USB, Scan to SharePoint. Client applications: EWS, HP Scan App |
| Scan technology | Contact Image Sensor (CIS) |
| Scanner type | Flatbed, ADF |
| Display | 4.3" CGD (Color Graphic Display) with 480 x 272 (WQVGA) resolution. |
| Minimum dimensions (W x D x H) | 604 x 604 x 664 mm |
| Minimum dimensions (W x D x H) | 23.8 x 23.8 x 26.2 in |
| Weight | 64.8 kg ^[1] |
| Weight | 142.8 lb |
| Power consumption | 525 watts (max. printing), 78 watts (printing), 30 watts (ready), 1.22 watts (sleep), 0.2 watts (auto-off/manual-on), 0.2 watts (off) ^[2] (Power consumption values typically based on measurement of 115V device.) |

Windows 11; Windows 8; Windows 7; Windows Vista; Android; macOS 10.12 Sierra; macOS X 10.10 Yosemite; macOS 10.11 El Capitan; Linux

| Power supply type | Internal (built-in) power supply |
|-----------------------|--|
| What's in the box | HP PageWide Color MFP 774dn Printer; HP Setup Ink Cartridges; Installation guide; Support flyer, documentation on CD; power cord |
| Manufacturer Warranty | One-year, on-site warranty, service and support; one-year technical phone support, chat, and e-mail |

Additional specifications

| ADF Capacity | 100 |
|---|---|
| Accessories | HP PageWide 550-Sheet Paper Tray (A7W99A); HP PageWide 550-sheet Paper Tray and Stand (W1B50A); HP PageWide 3x550-sheet Paper Tray and Stand (W1B51A); HP PageWide 4000-sheet Paper Tray and Stand (W1B52A); HP Internal USB Ports (B5L28A); HP Foreign Interface Harness (B5L31A); HP LaserJet MFP Analog 500 Fax Accessory (CC487A); HP Jetdirect 2900nw Print Server (J8031A); HP Jetdirect 3000w NFC/Wireless Accy (J8030A); HP Accessibility Assistant (2MU47A), HP Staple Cartridge Refill (J8J96A) |
| Acoustic power emissions (active scan) | 6.7 B(A) |
| Acoustic power emissions (active, printing) | 6.7 B(A) |
| Acoustic power emissions (ready) | Inaudible |
| Acoustic pressure emissions | 53 dB(A) (Printing at 45 ipm) |
| Acoustic pressure emissions bystander (active scan) | 52 dB(A) |
| Acoustic pressure emissions bystander (ready) | Inaudible |
| Auto fax reduction supported | Yes |
| Automatic document feeder capacity | 100 sheets |
| Automatic paper sensor | Yes |
| Best technical electricity consumption (TEC) | 1.25 kWhr/wk |
| Best technical electricity consumption (TEC) footnote | Based on the BA TEC method with the following possible exceptions: 1 minute or less sleep delay setting, Wi-Fi disabled. |
| Bit depth | 24-bit |
| Borderless printing | No |
| Bottom margin (A4) | 4.23 mm |
| Business filter | cMPS |
| Cable included | No, please purchase (USB) cable separately |
| Camera phone description | No |
| Camera phone supported | No |
| Cartons per layer | 1 |
| Color copy capability | Yes |
| Color or black | Color |
| Color scanning | Yes |
| Color(s) of printing supplies | Black, cyan, magenta, yellow |
| | |

| Compatible Network Operating Systems | Windows 11; Windows Server; Citrix; Novell |
|--|---|
| Component type | Printer |
| Control panel | 4.3" CGD (Color Graphic Display) with IR touchscreen |
| Copier settings | Two-sided copying, scalability, image adjustments (darkness, contrast, background cleanup, sharpness), N-up, N or Z-ordering, content orientation, collation, booklet, ID Scan, job build, edge-to-edge, job storage |
| Copies, maximum | Up to 9999 copies |
| Copy Speed Black (maximum, A4) | Up to 35 cpm |
| Copy Speed Color (maximum, A4) | Up to 35 ppm |
| Copy reduce / enlarge settings | 25 to 400% |
| Copy resolution (black graphics) | Up to 600 dpi |
| Copy resolution (black text) | Up to 600 dpi |
| Copy resolution (color text and graphics) | Up to 600 dpi |
| Copy speed black (ISO) | Up to 35 ppm |
| Copy speed black (draft, letter) | Up to 35 ppm |
| Copy speed black (normal, A3) | Up to 35 ppm |
| Copy speed black (normal, Tabloid) | Up to 35 ppm |
| Copy speed black duplex (A3) | Up to 35 ppm |
| Copy speed black duplex (Tabloid) | Up to 35 ppm |
| Copy speed color (ISO) | Up to 35 ppm |
| Copy speed color (draft, letter) | Up to 35 ppm |
| Copy speed note | First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. |
| Count of layers in pallet | 1 |
| Country of origin | NA and LAR: Product of Mexico; APJ: Product of Malaysia; EMEA: Product of Netherlands |
| Dimensions with trays up (W \times D \times H) | 604 x 604 x 664 mm |
| Distinctive ring detection supported | No |
| Duplex ADF scanning | Yes |
| Dynamic security | Dynamic security enabled printer |
| Electromagnetic compatibility | CISPR 22:2008 Class A; CISPR 32:2012 Class A / EN 55032:2012 Class A; EN 55024:2010; EN 61000-3-2:2014; EN 61000-3-3:2013; FCC CFR 47 Part 15 Class A; ICES-003, Issue 6 Class A |

| Engine life | 1000000 |
|--------------------------------------|--|
| Enhanced scanning resolution | Up to 600 ppi |
| Envelope Feeder | No |
| Exifprint supported | No |
| Fax Auto Redial | Yes |
| Fax Broadcast Locations | 210 |
| Fax Memory Note | Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory. |
| Fax Modem Speed | Internal, 33.6 kbps |
| Fax PC Interface Supported | Yes, HP Software support provided |
| Fax Polling | Yes (poll to receive only) |
| Fax Remote Retrieval | No |
| Fax Speed Dials, Maximum Number | Up to 1000 numbers (each with 210 destinations) |
| Fax Transmission Speed | 33.6 kbps |
| Fax Transmission Speed Note | Based on standard ITU-T test image #1 at standard resolution and MMR encoding, the HP fax device can transmit at 3 sec/page for V.34 and 6 sec/page for V.17 |
| Fax delayed sending | No No |
| Fax forwarding | Yes |
| Fax memory | Up to 500 pages (black and white) |
| Fax memory | Up to 500 pages (black and white) |
| Fax phone TAM interface supported | No |
| Fax phone features | No |
| Fax resolution black | 204 x 196 dpi |
| Fax resolution color (fine) | Up to 300 x 300 dpi (400 x 400 dpi for received faxes only) |
| Fax resolution color (standard) | Up to 300 x 300 dpi (400 x 400 dpi for received faxes only) |
| Fax telephone mode supported | No |
| Fax transmission speed (letter) | 5 Sec per page |
| Faxing options (ADF) | Two-sided |
| File Format Supported | PDF, PDF/A, JPEG, TIFF, XPS |
| Finished output handling | Finisher not available |
| First copy out black (letter) | As fast as 8.8 seconds |
| First copy out color (letter) | As fast as 10.3 seconds |
| First page out black (A4, ready) | As fast as 8.4 seconds |
| First page out black (A4, sleep) | As fast as 12 seconds |
| First page out black (letter, ready) | As fast as 8.5 seconds |
| | |

| First page out black (letter, sleep) | As fast as 11.3 seconds |
|---|---|
| First page out color (A4, ready) | As fast as 8.5 seconds |
| First page out color (A4, sleep) | As fast as 11.8 seconds |
| First page out color (letter, ready) | As fast as 8.6 seconds |
| First page out color (letter, sleep) | As fast as 11.6 seconds |
| Fonts and typefaces | 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at http://www.hp.com/go/laserjetfonts |
| Geographic availability | NA; LAR; AP; EMEA |
| HP Real Life technologies™ | No |
| Image scaling or enlargement range | 25 to 400% in 1% increments (flatbed) |
| Ink types | Pigment-based (black and color) |
| Input capacity | Up to 550 sheets Universal Tray; Up to 100 sheets - MP Tray |
| Internal Storage | None. Printer uses eMMC solid state drive (SSD); Standard eMMC memory = 16GB |
| Junk fax barrier | Yes |
| Left margin (A4) | 4.23 mm |
| Levels of grayscale | 256 |
| Mac compatible | Yes |
| Maximum Input Capacity (envelopes) | Up to 10 |
| Maximum Memory | 3584 MB System Total Standard; 2048 MB on Formatter (with 1024 MB DIMM); 1024 MB on the SCB; 512 MB on the ECB |
| Maximum dimensions (W x D x H) | 1270 x 1027 x 946 mm |
| Maximum dimensions (W x D x H) | 50.0 x 40.4 x 37.3 in |
| Maximum input capacity (10x15cm photos) | Up to 40 sheets |
| Maximum input capacity (4x6 photo) | Up to 40 sheets |
| Maximum input capacity (cards) | Up to 1600 + 200 + 40 for A5 size and larger; Up to 40 for smaller than A5 size |
| Maximum input capacity (labels) | Up to 1600 + 200 + 40 sheets |
| Maximum input capacity (photo | Up to 1600 + 200 + 40 sheets |
| paper) | op to 1000 200 10 sheets |
| paper) Maximum input capacity (sheets) | Up to 4000 + 550 + 100 sheets |

| Maximum metric depth | 1027 |
|--|--|
| Maximum metric height | 946 |
| Maximum metric width | 1270 |
| Maximum output capacity (cards) | Up to 200 cards |
| Maximum output capacity (envelopes) | Up to 50 envelopes |
| Maximum output capacity (labels) | Up to 100 sheets |
| Maximum output capacity (photo paper) | Up to 200 sheets |
| Maximum output capacity (sheets) | Up to 500 sheets |
| Maximum output capacity (transparencies) | None |
| Maximum print area | 296.5 x 448.7 mm |
| Media size (ADF) | A3; Ledger; B4-JIS; Legal; 8.5 x 13; Letter; A4; B5-JIS; A5; B6-JIS; A6 |
| Media size, tray 1 | A3; A4; A4-R; A5; A5-R; A6; RA3; RA4; SRA4; B4; B5 (JIS); 8K (270x390mm); 16K (195x270mm); 8k (260x368mm); 16k (184x260mm); 8k (273x394mm); 16k (197x273mm); 0ficio 216x340mm; Imperial: Letter; Letter-R; Legal; Executive; Statement; Oficio (8.5x13); 11x17; 12x18; 4x6; 5x7; 5x8; Envelope #10; Envelope B5; Envelope C5; Envelope C6; Envelope DL; Envelop Chou #3 |
| Media size, tray 2 | Letter; Letter-R; Legal; Executive; Oficio (8.5x13); 11x17 A3; A4; A4-R; A5; SRA4; B4; B5 (JIS); 8K (270x390mm); 16k (195x270mm); 8k (260x368mm); 16k (184x260mm); 8k (273x394mm); 16k (197x273mm); Oficio (216x340mm) |
| Media size, tray 3 | 1x550/stand & 3x550/stand: A3; A4; A4-R; A5; A5-R; A6; RA3; RA4; SRA4; B4; B5 (JIS); 8K (270x390mm); 16K (195x270mm); 8k (260x368mm); 16k (184x260mm); 8k (273x394mm); 16k (197x273mm); 0ficio 216x340mm |
| Media sizes supported | 12 x 18; 11 x 17; RA3; A3; 8K: 273 x 394 mm, 270 x 390 mm, 260 x 368 mm; B4 (JIS); Legal; Oficio 216 x 340 mm; Oficio 8.5 x 13; C4; SRA4; RA4 - R; Arch A-R; A4/3; A4 - R; Letter - R; 16K; 197 x 273 mm - R, 195 x 270 mm - R; executive - R; A5 - R; 16K: 184 x 260 mm - R; B5 (JIS) - R; Arch A; Statement; Letter; RA4; A4; 5 x 8; Double Japan Postcard Rotated; 16K: 197 x 273 mm, 195 x 270 mm, 184 x 260 mm; Executive; B5 (JIS); B6 (JIS); 5 x 7; 4 x 6; 10 x 15 cm; A5; Double Japan Postcard Rotated - R; A6; Japanese Postcard; Custom-sized media; Envelopes; Envelope B5; Envelope #10; Japanese Envelope Chou #3; Japanese Envelope - Flap Open; Envelope C5; Envelope #9; Envelope DL; Envelope Monarch; Envelope C6; Cards; 5 x 8 Index card; Double Japan Postcard Rotated; 4 x 6 Index card; Double Japan Postcard Rotated; 4 x 6 Index card; Custom-sized media; Photo Media; 5 x 7 Photo Media; 4x6 Photo media; 10 x 15 cm; Japanese Postcard Hagaki Photo Cards |

| Media sizes supported | 12 x 18; 11 x 17; RA3; A3; 8K: 273 x 394 mm, 270 x 390 mm, 260 x 368 mm; B4 (JIS); Legal; Oficio 216 x 340 mm; Oficio 8.5 x 13; C4; SRA4; RA4 - R; Arch A-R; A4/3; A4 - R; Letter - R; 16K; 197 x 273 mm - R, 195 x 270 mm - R; executive - R; A5 - R; 16K: 184 x 260 mm - R; B5 (JIS) - R; Arch A; Statement; Letter; RA4; A4; 5 x 8; Double Japan Postcard Rotated; 16K: 197 x 273 mm, 195 x 270 mm, 184 x 260 mm; Executive; B5 (JIS); B6 (JIS); 5 x 7; 4 x 6; 10 x 15 cm; A5; Double Japan Postcard Rotated - R; A6; Japanese Postcard; Custom-sized media; Envelopes; Envelope B5; Envelope #10; Japanese Envelope Chou #3; Japanese Envelope - Flap Open; Envelope C5; Envelope #9; Envelope DL; Envelope Monarch; Envelope C6; Cards; 5 x 8 Index card; Double Japan Postcard Rotated; 4 x 6 Index card; Double Japan Postcard Rotated - R; A6 Index card; Japanese Postcard; Custom-sized media; Photo Media; 5 x 7 Photo Media; 4 x 6 Photo media; 10 x 15 cm; Japanese Postcard Hagaki Photo Cards |
|---------------------------------|--|
| Media sizes supported, key | 4 x 6 in; Letter; Legal; 11 x 17 in |
| Media sizes, custom | Tray 1 supports (3.9 to 12 in) x (5.83 to 18 in), Universal Trays support (8.27 to 11.70 in) x (5.83 to 17.00 in) |
| Media sizes, custom | Tray 1 supports (99.06mm to 304.8mm) x (148.08mm to 457.2mm), Universal Trays support (210.05mm to 297.18mm) x (148.08mm to 431.8mm) |
| Media type and capacity, ADF | 100 |
| Media type and capacity, tray 1 | Sheets: 100; cards: 60; envelopes: 15 |
| Media type and capacity, tray 2 | Sheets: 550 |
| Media type and capacity, tray 3 | Up to 1,650 sheets in 3 x 550; Up to 2 x 2000 sheets in HCI |
| Media types | Plain paper, HP EcoFFICIENT, HP Premium Presentation Matte 120g, HP Brochure Matte 180g, HP Brochure Glossy, HP Advanced Photo Papers, Light 60-74g, Intermediate 85-95g, Mid-Weight 96-110g, Heavy 111-130g, Extra Heavy 131-175g, Cardstock 176-220g, Labels, Letterhead, Envelope, Heavy Envelope, Preprinted, Prepunched, Colored, Bond, Recycled, Rough |
| Media weight (tray 1) | 60 - 220 gsm; 300 gsm photo paper only |
| Media weight (tray 2) | 16 - 58 lb, 80 lb Photo Paper Only |
| Media weight (tray 3) | 60 - 220 gsm; 300 gsm photo paper only |
| Media weight, recommended | 16 - 58 lb, 80 lb Photo Paper Only ^[10] |
| Media weight, recommended | 60 - 220 gsm; 300 gsm Photo Paper Only |
| Media weight, supported | Tray 1: 60-220 gsm, 300 gsm Photo Paper Only; Trays 2-5: 60-220 gsm; HCI trays 3 & 4: 60-220 gsm |
| Media weight, supported | Tray 1: 16-58 lb, 80 lb Photo Paper Only; Trays 2-5: 16-58 lb; HCI Trays 3 & 4: 16-58 lb |
| Media weights, supported ADF | 60 to 120 g/m² (plain paper); 125 to 300 g/m² (photo); 75 to 90 g/m² (envelope); 120 to 180 g/m² (brochure); 163 $$ g/m² (card) |
| Media weights, supported ADF | 16 to 32 lb (plain paper); 33 to 80 lb (photo); 20 to 24 lb (envelope); 32 to 48 lb (brochure); 90lb (card) |
| Memory | 2816 MB System Total Standard; 1280 MB on Formatter; 1024 MB on the SCB; 512 MB on the ECB |
| Memory Slots | 1 slot, 144-pin DDR3 DIMM |
| | |

| Memory card compatibility | 16GB eMMC solid state drive (SSD) for printer operating system and job storage. |
|---|---|
| Metric depth | 604 |
| Metric height | 664 |
| Metric width | 604 |
| Minimum System Requirements | Windows® 10, 8.1, 8, 7: 1 GHz 32-bit or 64-bit processor, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer. Windows Vista®: 800 MHz processor (32-bit only), 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8. Windows® XP SP3 or higher (32-bit only): any Intel® Pentium® II, Celeron® or 233 MHz compatible processor, 850 MB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer 8 |
| Minimum System Requirements for Macintosh | Apple® OS X v10.12 Sierra, OS X v10.11 El Capitan, OS X v10.10 Yosemite, minimum 1.2 GB available HD space; Internet required; USB port |
| Model number | 774dn |
| Multitasking supported | No |
| Non-Operating Humidity Range | 10 to 80% RH |
| Number of print cartridges | 4 (1 each black, cyan, magenta, yellow) |
| Number of users | 5-15 users |
| Operating altitude | Up to 10,000 ft |
| Operating altitude | Up to 3048 m |
| Operating humidity range | 10 to 80% RH |
| Operating temperature range | 59 to 86°F |
| Operating temperature range | 15 to 30℃ |
| Orderable supplies | HP PageWide Printhead Wiper Kit (W1B43A); HP PageWide Service Fluid Container (W1B44A); HP PageWide Roller Kit (W1B45A); HP ADF Roller Replacement Kit (W1B47A) |
| Output capacity | Up to 500 sheets |
| Package dimensions (W x D x H) | 790 x 760 x 941 mm |
| Package dimensions (W x D x H) | 31.1 x 29.9 x 37.1 in |
| Package weight | 87.5 kg |
| Package weight | 193 lb |
| Pallet dimensions | 31.1 x 29.9 x 37.1 in |
| Pallet dimensions (W x D x H) | 790 x 760 x 941 mm |
| Pallet weight | 193 lb |
| Pallet weight | 87.5 kg |
| Paper handling input, optional | Optional 550-sheet tray; Optional cart with integrated 550-sheet tray; Optional cart with 3 integrated 550 sheet trays; Optional cart with 2 integrated 2000-sheet in HCI |
| Paper handling input, standard | 550-sheet Universal Input Tray; 100-sheet Multi-purpose Tray |

| Paper handling output, optional | None |
|-------------------------------------|--|
| Paper handling output, standard | 500-sheet face-down output bin |
| Paper sizes supported (ADF) | Executive (7.25x10.5); Statement (5.5x8.5); Ledger (11x17); 12x18; 4x6; 5x7; 5x8; Oficio 8.5x13/215x330 mm (Foolscap); Oficio 216x340 mm; A3 (297x420 mm); A4 (long edge feed) (297x210 mm); A4 Rotated (short edge feed) (210x297 mm); A5 (148x210 mm); A6 (105x148 mm); RA3 (12x16.9); RA4 (8.5x12); SRA4 (8.9x12.6); B4 (JIS) (257x364 mm); B5 (JIS) (182x257 mm); B6 (JIS) (125x176 mm); 10x15cm 8K 270x390 mm; 16K 195x270 mm; 8K 260x368 mm; 16K 184x260 mm; 8K 273x394 mm; 16K 197x273 mm; Postcard(JIS) (100x148 mm); Dpostcard(JIS) (148x200 mm); Envelope #9 (3.9x8.9); Envelope #10 (4.1x9.5); Envelope Monarch (3.9x7.5); Envelope B5 (6.9x9.8); Envelope C5 (6.4x9); Envelope C6 (4.5x6.4); Envelope DL (4.3x8.6); Mixed Letter/Legal Mixed; A4/A3 Mixed Letter/Ledger Fixed Width Mixed Media; Long Scan Size (8.5x "up to 34") Custom; Any Custom |
| Paper trays, maximum | Up to 5 |
| Paper trays, standard | 2 |
| Photo proofsheets supported | No |
| PictBridge description | No |
| PictBridge supported | No |
| Power | Input voltage: 100 to 240 VAC, 50/60 Hz. Not dual voltage, power supply varies by part number with # Option code identifier. |
| Power consumption (active copy) | 475 watts |
| Print Technology | PageWide |
| Print colors | Yes |
| Print colors maximum | 4 |
| Print head nozzles | 1056/color/die, 4 color/die, total 14 dies, so total 59136 nozzles |
| Print heads | 1 printhead 4 colors |
| Print languages | HP PCLXL (PCL6), PCL5, native PDF, HP Postscript Level 3 emulation, PJL, JPEG, PCLM |
| Print speed black (ISO) | Up to 35 ppm |
| Print speed black (best, A4) | Up to 35 ppm |
| Print speed black (best, letter) | Up to 35 ppm |
| Print speed black (draft, A4) | Up to 55 ppm |
| Print speed black (draft, letter) | Up to 55 ppm |
| Print speed black (normal, A3) | Up to 21 ppm |
| Print speed black (normal, tabloid) | Up to 19 ppm |
| Print speed color (ISO) | Up to 35 ppm |
| Print speed color (draft, A4) | Up to 55 ppm |
| Print speed color (draft, letter) | Up to 55 ppm |
| Print speed color (normal, A3) | Up to 20 ppm |
| Print speed color (normal, tabloid) | Up to 19 ppm |

| Print speed duplex (A3) | Up to 8 ppm |
|--|---|
| Print speed duplex (A3) | Up to 8 ppm |
| Print speed duplex (A4) | Up to 24 ppm |
| Print speed duplex (A4) | Up to 24 ppm |
| Print speed duplex (letter) | Up to 24 ppm |
| Print speed duplex (letter) | Up to 24 ppm |
| Print speed duplex (tabloid) | Up to 8 ppm |
| Print speed duplex (tabloid) | Up to 8 ppm |
| Print technology | HP PageWide Technology with pigmented inks |
| Printer Management | HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web Jetadmin Software; Printer Administrator Resource Kit for HP Universal Print Driver |
| Printer black pages (MPV black) | 1950 |
| Printer color pages (MPV color) | 1050 |
| Printer drivers included | Windows PCL 6 Discrete; Mac PS; Windows HP UPD (PCL 6, PS); Linux; UNIX; SAP |
| Processor speed | 1.2GHz |
| | |
| Product logos | ENERGY STAR® certified; Blue Angel; EPEAT (Silver) |
| Product logos Quantity per pallet | ENERGY STAR® certified; Blue Angel; EPEAT (Silver) 1 |
| - | |
| Quantity per pallet | 1 |
| Quantity per pallet RMN number Recommended media weight | 1 BOISB-1606-05 |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight | 1 B0ISB-1606-05 60 - 220 gsm |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight (duplex) Recommended monthly page | 1 B0ISB-1606-05 60 - 220 gsm 16 - 58 lb |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight (duplex) Recommended monthly page volume Recommended operating humidity | 1 BOISB-1606-05 60 - 220 gsm 16 - 58 lb 2500 to 15,000 ^[8] |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight (duplex) Recommended monthly page volume Recommended operating humidity range Recommended operating | 1 B0ISB-1606-05 60 - 220 gsm 16 - 58 lb 2500 to 15,000 ^[8] 30 to 70% RH |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight (duplex) Recommended monthly page volume Recommended operating humidity range Recommended operating temperature range Recommended operating | 1 BOISB-1606-05 60 - 220 gsm 16 - 58 lb 2500 to 15,000 ^[8] 30 to 70% RH 63 to 77°F |
| Quantity per pallet RMN number Recommended media weight (duplex) Recommended media weight (duplex) Recommended monthly page volume Recommended operating humidity range Recommended operating temperature range Recommended operating temperature range Resolution (black and white, | 1 B0ISB-1606-05 60 - 220 gsm 16 - 58 lb 2500 to 15,000 ^[8] 30 to 70% RH 63 to 77°F 17 to 25°C |

| Safety | IEC 60950 -1: 2005+ A1:2009 + A2: 2013/EN 60950-1: 2006+A11: 2009 +A1:2010 +A12:2011 +A2: 2013/+AC:2011; IEC 62479:2010/EN 62479:2010; IEC 62471:2006/EN 62471:2008; Australia/New Zealand AS/NZS 60950.1: 2011; Canada/America CAN/CSA-C22.2 No 60950-1-07, Amendment 1:2011, ANSI/UL Std No 60950-1, 2nd Ed.; Low Voltage Directive 2014/35/EU with CE Marking (Europe); ; Singapore PSB; Korea KCC; Taiwan BSMI; Other safety approvals as required by individual countries. |
|--|--|
| Scan resolution, hardware | Up to 600 ppi |
| Scan resolution, optical | Up to 600 ppi |
| Scan size (ADF), maximum | 11.7 \times 16.59 in; Up to 8.5 \times 34 in when "long scan size" selected |
| Scan size (ADF), maximum | 280 x 432 mm; Up to 216 x 864 mm when "long scan size" selected |
| Scan size (ADF), minimum | 101 x 152 mm |
| Scan size (ADF), minimum | 4 x 6 in |
| Scan size, maximum | 297 x 432 mm |
| Scan size, maximum | 11.7 X 17 in |
| Scan speed (normal, A3) | Up to 38 ipm (mono and color) |
| Scan speed (normal, tabloid) | Up to 38 ipm (mono and color) |
| Scan speed duplex (normal, A3) | Up to 38 ipm (mono and color) |
| Scan speed duplex (normal, A4) | Up to 120 ipm (mono and color), LEF* |
| Scan speed duplex (normal, Tabloid) | Up to 38 ipm (mono and color) |
| Scan speed duplex (normal, letter) | Up to 120 ipm (mono and color), LEF* |
| Security management | Kerberos authentication, LDAP authentication, 2000 user PIN codes, Network: IPsec/firewall with Certificate, Pre-Shared Key, and Kerberos authentication, Supports WJA-10 IPsec configuration Plug in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control List, HP Trusted Platform Module (TPM) comes standard; Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), Secure Erase, SSL/TLS (HTTPS), Encrypted Credentials; Device: Security lock slot, USB port disablement, HP Security Management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in ArcSight and Splunk SIEMs; For more security settings for HP JetAdvantage Security Manager go to http://h10032.www1.hp.com/ctg/Manual/c03602120 |
| Segment (filter) | Business |
| Send to email capability | Yes |
| Service & support features | Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to http://www.hp.com/support/colorpw774mfp; Outside the US, go to http://www.hp.com/support 1 Select the country/region 2 Select Software and Drivers 3 Select Printer 4 Enter a product name/number 5 The operating system is automatically detected 6 Select a driver or other software 7 Then select DOWNLOAD |

| Service & support options | Free telephone support for basic setup, installation, and troubleshooting in Americas, Europe, and Asia Pacific during warranty; Optional care packs include installation, and up to five years onsite exchange |
|--|---|
| Standard input capacity (cards) | Up to 1600 + 200 + 40 for A5 size and larger; Up to 40 for smaller than A5 size |
| Standard input capacity (envelopes) | Up to 10 |
| Standard input capacity (legal) | 550 Universal Tray 100 - MP Tray |
| Standard input capacity (secondary tray) | Up to 100 sheets |
| Standard input capacity (transparencies) | None |
| Standard media sizes (duplex) | A3; A4; A5; B5 |
| Standard media sizes (duplex, imperial) | Letter; legal; Oficio; Executive; Ledger(B) |
| Standard memory note | Internal DDR3 DRAM contained on the controller and scanner boards. |
| Standard output capacity (cards) | Up to 200 cards |
| Standard output capacity (envelopes) | Up to 50 envelopes |
| Standard output capacity (labels) | Up to 200 sheets |
| Standard output capacity (legal) | Up to 500 sheets |
| Standard output capacity (transparencies) | None |
| Storage altitude | 15,000 ft |
| Storage altitude | 4572 m |
| Storage temperature range | Before initial setup (Non-Purged): -40 to 140°F; After initial setup (Purged): 32 to 140°F. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating |
| | temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). |
| Storage temperature range | |
| Storage temperature range Target user and print volume | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior |
| | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). |
| Target user and print volume | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). For teams up to 15 users |
| Target user and print volume Tariff numbers | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). For teams up to 15 users AMS: 8443310000;EMEA: 8443310000;APJ: 84433111 |
| Target user and print volume Tariff numbers Telephone handset supported | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). For teams up to 15 users AMS: 8443310000;EMEA: 8443310000;APJ: 84433111 No 100-sheet ADF; Front-facing USB printing; Scan to email; Two-sided |
| Target user and print volume Tariff numbers Telephone handset supported Top key features | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). For teams up to 15 users AMS: 8443310000;EMEA: 8443310000;APJ: 84433111 No 100-sheet ADF; Front-facing USB printing; Scan to email; Two-sided printing |
| Target user and print volume Tariff numbers Telephone handset supported Top key features Top margin (A4) | temperature prior to using the printer). Before initial setup (Non-Purged): -40 to 60°C; After initial setup (Purged): 0 to 60°C. If stored below the lowest specified operating temperature, unit must slowly warm up to an approved operating temperature (HP recommends waiting 24 hours at approved operating temperature prior to using the printer). For teams up to 15 users AMS: 8443310000;EMEA: 8443310000;APJ: 84433111 No 100-sheet ADF; Front-facing USB printing; Scan to email; Two-sided printing 4.23 mm |

| Typical electricity consumption (TEC) footnote | Energy Star TEC value typically based on measurement of 115V device. |
|--|--|
| Typical electricity consumption (TEC) number | 1.245 kWh/Week (Blue Angel); 0.473 kWh/Week (Energy Star 3.0) |
| UNSPSC code | 43212110 |
| UPC number | (AB0) 193015192843; (AB2) 193015192850; (ABJ) 193015192867; (ABT) 193015192904; (ABY) 193015192959; (AC4) 193015192973; (AC8) 193015192980; (ACJ) 193015192874; (ACQ) 193015192942; (B13) 193015192935; (B16) 193015192997; (B19) 193015192928; (B1H) 193015192966; (BAZ) 193015192911; (BBU) 193015192898; (BGM) 193015192881 |
| Video action printing note | No |
| Video action printing supported | No |

[1] With ink installed, no media in trays.

[2] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption in Sleep modes depends on customer network switch capability, user configuration and network activity.

[7] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

[8] HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

[10] All HP media listed as compatible with the printer in the HP PageWide Printing Supplies Compatibility Guide, regardless of weight, may be used.

Ink/Toner/Paper/Printer Supplies

HP PageWide Supplies

HP PageWide Supplies

| HP 991X High Yield Black Original PageWide Cartridge | MOKO2AE ★ |
|---|--------------------|
| HP 991X High Yield Cyan Original PageWide Cartridge | MOJ90AE ★ |
| HP 991X High Yield Magenta Original PageWide Cartridge | MOJ94AE ★ |
| HP 991X High Yield Yellow Original PageWide Cartridge | MOJ98AE ★ |
| HP 993X High Yield Black Original PageWide Cartridge | MOKO4AA ★ |
| HP 993X High Yield Cyan Original PageWide Cartridge | MOJ92AA ★ |
| HP 993X High Yield Magenta Original PageWide Cartridge | MOJ96AA ★ |
| HP 993X High Yield Yellow Original PageWide Cartridge | MOKOOAA ★ |
| HP 993A Black Original PageWide Cartridge | MOJ88AA ★ |
| HP 993A Cyan Original PageWide Cartridge | MOJ76AA ★ |
| HP 993A Magenta Original PageWide Cartridge | MOJ80AA ★ |
| HP 993A Yellow Original PageWide Cartridge | MOJ84AA ★ |
| HP 990A Black Original PageWide Cartridge | M0J85AN |
| HP 990A Cyan Original PageWide Cartridge | M0J73AN |
| HP 990A Magenta Original PageWide Cartridge | M0J77AN |
| HP 990A Yellow Original PageWide Cartridge | MOJ81AN |
| HP 990X High Yield Black Original PageWide Cartridge | M0K01AN |
| HP 990X High Yield Cyan Original PageWide Cartridge | M0J89AN |
| HP 990X High Yield Magenta Original PageWide Cartridge | M0J93AN |
| HP 990X High Yield Yellow Original PageWide Cartridge | M0J97AN |
| HP 992A Black Original PageWide Cartridge | M0J87AL |
| HP 992A Cyan Original PageWide Cartridge | M0J75AL |
| HP 992A Magenta Original PageWide Cartridge | M0J79AL |
| HP 992A Yellow Original PageWide Cartridge | MOJ83AL |
| | |
| HP 992X High Yield Black Original PageWide Cartridge | M0K03AL |
| HP 992X High Yield Black Original PageWide Cartridge HP 992X High Yield Cyan Original PageWide Cartridge | MOKO3AL MOJ91AL |
| | |

★ : Recommended

HP Paper for Multiple Uses

HP Recycled Paper

HP Business Papers

HP Business Papers for laser and inkjet

| HP Professional Business Paper Glossy 48 lb 8.5 x 11 in. (216 x 279 mm) 150 sheets | Q1987A |
|---|--------|
| HP Professional Business Paper, Glossy, 180 g/m2, A4 (210 x 297 mm), 150 sheets | 3VK91A |
| HP Professional Tri-Fold Business Paper Glossy 48 lb 8.5 x 11 in. (216 x 279 mm) 150 sheets | 4WN12A |

Accessories

Printer Supply Accessories

Ink Supply Accessories

| HP ADF Roller Replacement Kit | W1B47A ★ |
|-------------------------------------|----------|
| HP PageWide Printhead Wiper Kit | W1B43A ★ |
| HP PageWide Roller Kit | W1B45A ★ |
| HP PageWide Service Fluid Container | W1B44A ★ |
| HP 110V Heated Pressure Roller | ЗММЗ9А |

★ : Recommended

Paper Handling

Staple Cartridges

| HP Staple Cartridge Refill | J8J96A ★ |
|--|----------|
| Fax Upgrades | |
| HP MFP Analog Fax Accessory 700 | 2EH31A ★ |
| HP MFP Analog Fax Accessory 701 | 5UT59A ★ |
| Input Trays | |
| HP PageWide 550 sheet Paper Tray/Stand | 9UW01A ★ |
| HP PageWide 550-sheet Paper Tray | A7W99A ★ |
| HP PageWide 3x550 sheet Paper Tray/Stand | 9UW02A |
| HP PageWide 3x550 sheet Paper Tray/Stand | W1B51A |
| HP PageWide 4K Sheet HC Paper Tray/Stand | 9UW03A |
| HP PageWide 4K Sheet HC Paper Tray/Stand | W1B52A |
| HP PageWide 550 sheet Paper Tray/Stand | W1B50A |
| Output Trays and Stackers | |

Accessory Bundles

Printer Accessibility Accessories

HP LaserJet Stapler/Stacker Finisher Staples

| HP Accessibility Assistant | 2MU47A ★ |
|-----------------------------|----------|
| HP Printing Voice Assistant | 478C2A |

Y1G14A

Cables/Cable Kits/Cable Adapters

Printer Cables

| HP Foreign Interface Harness | B5L31A ★ |
|--------------------------------|----------|
| Port Cables and Cable Adapters | |
| HP Internal USB Ports | B5L28A ★ |

Network Print Servers

External Print Servers

| HP Jetdirect 2900nw Print Server | J8031A ★ |
|---|----------|
| HP Jetdirect 3000w NFC/Wireless Accessory | J8030A ★ |
| HP Jetdirect 3100w BLE/NFC/Wireless Accessory | 3JN69A |

HP Care Pack Services

Imaging and Printing Hardware Support Onsite Svc

| HP 1 year Post Warranty 4 hour 9x5 w/Defective Media Retention Service for PageWide Pro 774 MFP | UA4L0PE |
|---|---------|
| HP 1 year Post Warranty NBD w/Defective Media Retention Service for PageWide Pro 774 MFP | UA4K8PE |
| HP 3 year 4 hour 9x5 w/Defective Media Retention Service for PageWide Pro 774 MFP | UA4K2E |
| HP 3 year Next Business Day w/Defective Media Retention Service for PageWide Pro 774 MFP | UA4J9E |
| HP 4 year Next Business Day w/Defective Media Retention Service for PageWide Pro 774 MFP | UA4K0E |

★ : Recommended

Imaging and Printing Commercial Care Pack Services

| HP 1 year Post Warranty Parts Exchange Service for PageWide Pro 774 MFP | UA4L2PE |
|--|---------|
| HP 3 year Parts Exchange Service for PageWide Pro 774 MFP | UA4K5E |
| HP Full Kit plus Heated Pressure Roller 110 Volt Maintenance Kit Repair Service for PageWide | UB8L7E |
| HP Full Kit plus Heated Pressure Roller 220 Volt Maintenance Kit Repair Service for PageWide | UB8L8E |
| HP Installation Service with network configuration for Department Printer (1 unit) | U9JT3E |
| HP Service Fluid Maintenance Kit Replacement Service for PageWide 75x 76x 77x 78x | U9QW3E |

Solutions

HP Document and Workflow Solutions

★: Recommended

HP Document and Workflow Solutions Printing Security

| HP Access Control Secure Printing and Job Accounting Solution | HPACSOLUTION |
|---|--------------------|
| HP Proximity Card Reader | HPPROXIMTYRDR |
| HP Secure Print and Insights | HPJETADSECUREPRINT |
| HP Security Manager | HPJETADSECMGR |
| Kofax SafeCom Security and Job Accounting Solution | HPNSAFECOMSOL |
| MyQ Solutions | MYQSOL |

HP Document and Workflow Solutions Mobile Printing

| HP Roam for Business | HPROAM |
|-----------------------|-------------|
| THE MODIFIED BUSINESS | 111 110/111 |

HP Document and Workflow Solutions Print Management

| HP Universal Print Driver | HPUNIVPRNTDRV |
|---------------------------|---------------|
| HP Web Jetadmin | HPWEBJETADMIN |
| Kofax ControlSuite | HP_CSUITE |

HP Document and Workflow Solutions Printer Workflow

| HP Workpath Apps | HPJA_AP |
|------------------|---------|
|------------------|---------|

Disclaimer — Copyright

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Apr 25, 2024 4:13 AM UTC+0000