

Malleable Iron 90° Liquidtight Connectors

For Liquidtight Flexible Metallic Conduit

Application:

To secure, ground seal Liquidtight Flexible Metal conduit, to boxes and enclosures

Features:


- Tapered threaded male hub NPT
- Compact, slim diameter with small turning radius
- Furnished with an insulated throat with steel locknut and sealing ring
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit "pop-out"
- UL Listed liquidtight flexible metal conduit fittings are suitable for use in the following Hazardous Locations under NEC 501-4(b), 502-4(a)(2); Class I, Div.2; Class II, Div. 1 and 2; and Class III, Div. 1 and 2 and are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-I

Standard Materials:

Malleable Iron/Steel Ferrule

Standard Finish:

Zinc Plated



All Furnished with Insulated Throats

| CATALOG NUMBER | TRADE SIZE | KO SIZE | DIM A | DIM B | DIM C | DIM D | UNIT PACK | STANDARD PACK | WEIGHT (LBS.) PER 100 | NAED MFG #78-5994 UPC/DCI # |
|----------------|------------|---------|-------|-------|-------|-------|-----------|---------------|-----------------------|-----------------------------|
| SLT25T | 3/8" | 1/2" | 1.31 | 0.50 | 1.15 | 1.37 | 10 | 100 | 28 | 14259 |
| SLT35T | 1/2" | 1/2" | 1.43 | 0.50 | 1.28 | 1.37 | 10 | 100 | 31 | 14690 |
| SLT36T | 3/4" | 3/4" | 1.62 | 0.52 | 1.55 | 1.50 | 10 | 100 | 46 | 14700 |
| SLT37T | 1" | 1" | 1.93 | 0.65 | 1.80 | 1.81 | 5 | 50 | 77 | 14710 |
| SLT38T | 1-1/4" | 1-1/4" | 2.37 | 0.66 | 2.25 | 1.94 | - | 10 | 98 | 14389 |
| SLT39T | 1-1/2" | 1-1/2" | 2.68 | 0.73 | 2.44 | 2.40 | - | 10 | 124 | 14399 |
| SLT40T | 2" | 2" | 3.18 | 0.75 | 2.97 | 2.64 | - | 5 | 179 | 14409 |
| SLT65T | 2-1/2" | 2-1/2" | 8.31 | 1.01 | 4.01 | 7.81 | - | 1 | 847 | 14659 |
| SLT66T | 3" | 3" | 9.80 | 1.15 | 4.18 | 9.15 | - | 1 | 1243 | 14669 |
| SLT67T | 3-1/2" | 3-1/2" | 11.18 | 1.18 | 5.25 | 11.22 | - | 1 | 1914 | 14679 |
| SLT68T | 4" | 4" | 12.98 | 1.25 | 5.78 | 12.54 | - | 1 | 2399 | 14689 |

