

Ultrastar® SSD800MH.B

Enterprise Solid-State Drives

Highlights

- MLC NAND Flash for ultra-high performance and endurance
- High endurance 25DW/D for 5 years
- Best IOPS/Watt for reduced TCO
- 12Gb/s SAS interface for maximum throughput
- Advanced power loss data management technology
- Self-encrypting models conform to TCG's Enterprise specification

Applications/Environments

- Ultra-high performance tier-0 enterprise storage
- Enterprise-class servers and high performance computing
- Space and/or power constrained environments
- Online Transaction Processing (OLTP)
- Financial and e-commerce
- Database analytics



800GB, 400GB, 200GB and 100GB
MLC | 2.5-inch SFF | SAS 12Gb/s

HGST Enterprise Storage Experience

HGST leverages decades of proven enterprise storage expertise in Serial Attached SCSI (SAS) design, reliability, firmware, customer qualification and system integration to the Ultrastar® SSD800MH.B solid-state drive (SSD) family. The synergistic relationship between HGST's throughput-enhancing SSDs and traditional HDDs provides cost effective, end-to-end enterprise-class storage solutions, delivering reliability, compatibility, capacity, cost and system performance. This combination makes HGST a leading SSD/HDD provider with the experience and technology needed to meet escalating reliability, endurance and performance in the most demanding enterprise environments.

Maximum Performance, Reliability and Endurance

The Ultrastar SSD800MH.B delivers high sequential throughput, up to 1100MB/s read and 765MB/s write (12Gb/s SAS). The Ultrastar SSD800MH.B also delivers up to 130,000 read and 110,000 write IOPS, reaching speeds >100 times faster than HDDs and double the speed of current 6Gb/s SSDs, allowing rapid access to "hot" enterprise data for improved productivity and operational efficiency. The Ultrastar SSD800MH.B family offers significant value in terms of IOPS per Watt, while reducing total cost of ownership (TCO) through low power consumption, efficient cooling and reduced space requirements.

The Ultrastar SSD800MH.B family combines enterprise-grade MLC NAND Flash memory, advanced endurance management firmware and power loss data management techniques to extend reliability, endurance and sustained performance over the life of the SSD. The Ultrastar SSD800MH.B family achieves an extraordinary 0.44% annual failure rate (AFR) or two million hour mean-time-between-failure (MTBF). The 800GB capacity model endures up to 36.5 Petabytes (PB) of random writes over the life of the drive—the equivalent of writing 20 Terabytes (TB) per day for five years.

For complete end-to-end data protection and reliability, the Ultrastar SSD800MH.B family incorporates the T10 Data Integrity Field (DIF) standard, extended error correction code (ECC), Exclusive-OR (XOR) parity to protect against flash die failure, parity-checked internal data paths without an external write cache, and an exclusive power loss data management feature that does not require supercapacitors. The Ultrastar SSD800MH.B family is backed by a five year limited warranty, or the maximum Petabytes (PB) written (based on capacity).

Features and Benefits

	Feature / Function	Benefits
Performance	SAS 12Gb/s	12Gb/s / 6Gb/s Active-Active Dual Port
	MLC NAND Flash memory	Highest write performance with cost improved NAND for high endurance
	1100MB/s / 765MB/s sequential R/W	Maximum throughput and IOPS for ultra-fast access to data; >100x faster than typical HDD
	130K / 110K IOPS random R/W	
	110K IOPS on 70/30 mix R/W	
Power	9.0 and 11.0 Watt options	Improved performance with higher power option
Capacity	800GB, 400GB, 200GB, 100GB	More capacity for less space and power
Reliability	0.44% AFR (2M hours MTBF)	Reduced field replacement effort
	1E-17 bit error rate	Enhanced error detection and correction for optimal data integrity
	T10 end-to-end data protection	
	Exclusive-OR (XOR) NAND	Protection against Flash die failure
	Power loss data management	Assures data integrity during power failure
	Unlimited reads, up to 36.5PB random writes (800GB)	Maximum endurance over the life of SSD
Integration	HDD architecture commonality	Compatibility with Ultrastar SAS HDDs
	Systems integration and test lab	Extensive interoperability and compliance testing

HGST Quality and Service

HGST's Ultrastar SSD800MH.B family extends the company's long-standing tradition of performance and reliability leadership. A balanced combination of new and proven technologies enables high reliability and availability to customer data.

HGST drives are backed by an array of technical support and services, which may include customer and integration assistance. HGST is dedicated to providing a complete portfolio of SSD/HDD solutions to satisfy today's monumental computing needs.

How to Read the Ultrastar Model Number

HUSMH8080BSS200 = 800GB, SAS 12Gb/s

H = HGST
 U = Ultrastar
 S = Standard
 MH = Multi level cell, high endurance (25DW/D)
 80 = Full capacity (800GB)
 80 = Capacity of this model (80 = 800GB, 40 = 400GB, 20 = 200GB, etc.)
 B = Generation code
 S = Small form factor (vs. L for Large FF)
 S2 = Interface, SAS 12Gb/s
 0 = Reserved
 0 = Crypto sanitize (1 = TCG encryption, 4 = No encryption, 5 = TCG + FIPS certified encryption)

Information and Technical Support

www.hgst.com (main website)
 www.hgst.com/partners (partner website)

North America

support_usa@hgst.com
 Toll Free: +1 888 426-5214, Direct: +1 408 717-8087

Asia Pacific

support_ap@hgst.com / +65 6840 9595

EMEA and UK

support_uk@hgst.com / +44 20 7133 0032

Germany

support_uk@hgst.com / +49 6929 993601

Program Support

Partners First Program: channelpartners@hgst.com

Specifications

Model # / Part #	
HUSMH8080BSS204 / 0B32071	
HUSMH8080BSS200 / 0B31072	
HUSMH8080BSS201 / 0B32043	
HUSMH8080BSS205 / 0B32093	
HUSMH8040BSS204 / 0B32070	
HUSMH8040BSS200 / 0B31071	
HUSMH8040BSS201 / 0B32043	
HUSMH8040BSS205 / 0B32092	
HUSMH8020BSS204 / 0B32069	
HUSMH8020BSS200 / 0B31070	
HUSMH8020BSS201 / 0B32041	
HUSMH8020BSS205 / 0B32091	
HUSMH8010BSS204 / 0B32068	
HUSMH8010BSS200 / 0B31069	
HUSMH8010BSS201 / 0B32040	
HUSMH8010BSS205 / 0B32090	

Configuration	
Interface	SAS 12Gb/s
Capacity (GB) ¹ at 512 bytes/sector	800 / 400 / 200 / 100
Form factor	2.5-inch
Flash memory technology	Multi Level Cell (MLC)

Performance	
Read throughput (max MB/s, sequential 64K)	1100
Write throughput (max MB/s, sequential 64K)	765
Read IOPS (max IOPS, random 4K)	130,000
Write IOPS (max IOPS, random 4K)	110,000

Reliability	
Error rate (non-recoverable bits read)	1 in 10 ¹⁷
MTBF ² (M hours)	2.0
Annual failure rate ² (AFR)	0.44%
Availability (hrs/day x days/wk)	24x7
Endurance (max PB ¹ , random write)	36.5 / 18.3 / 9.1

Power	
Requirement	+5 VDC (+/-5%) +12 VDC (+/-5%)
Operating (W, typical)	9.0 and 11.0
Idle (W)	2.2

Physical	
z-height (mm)	15.0
Dimensions (width x depth, mm)	70.1 x 100.6
Weight (g, max)	187

Environmental (operating)	
Ambient temperature	0° to 60°C
Shock (half-sine wave)	1000G (0.5ms) 500G (2ms)
Vibration, random (G RMS)	2.16, all axis (5 to 700 Hz)

¹ One gigabyte (GB) is equal to one billion bytes, one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB (one quadrillion bytes) when referring to solid-state drive or hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the drive, the computer's operating system, and other factors.

² MTBF and AFR targets are based on a sample population and are estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

