



## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 058005  
Product name: PRESTIGE UNIVERSAL ADHESIVE 10 ml

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: For professional use only. Adhesive for impression silicones.

#### 1.3. Details of the supplier of the safety data sheet

Name: VANNINI DENTAL INDUSTRY SRL  
Full address: Via di Campigliano 55/A – 50012 Grassina Bagno a Ripoli – FI– Italy  
District and Country: Tel. +39 055 644698 Fax: +39 055 644697  
www.vanninidental.com  
Tel. +39 055 644698 Fax: +39 055 644697  
e-mail address of the competent person responsible for the Safety Data Sheet: E-mail: info@vanninidental.com  
Jaime Sandoval

#### 1.4. Emergency telephone number

For urgent inquiries refer to

CAV Italia: Centro Antiveleni di Milano: 02 66101029; Centro Antiveleni di Pavia: 0382 24444; Centro Antiveleni di Bergamo: 800 883300; Centro Antiveleni di Firenze: 055 7947819; Centro Antiveleni di Roma: 06 3054343; Centro Antiveleni di Roma: 06 49978000; Centro Antiveleni di Napoli: 081 7472870

Servicio de Información Toxicológica (España): + 34 91 562 04 20 (24h/365 días)

Numéro ORFILA (INRS-France): + 33 (0)1 45 42 59 59 (24h/ 7 jours sur 7)

UK Emergency number: 844 892 0111 (24 hours)

Deutschland Notruf: BERLIN Tel.: 030/19240; HOMBURG Tel.: 06841/19240; BONN Tel.: 0228/19240; MAINZ Tel.: 06131/19240; ERFURT Tel.: 0361/730 730; MÜNCHEN Tel.: 089/19240; FREIBURG Tel.: 0761/19240; NÜRNBERG Tel.: 0911/398-2451; GÖTTINGEN Tel.:0551/19 240

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

##### 2.1.1. Regulation 1272/2008 (CLP) and following amendments and adjustments.

Hazard classification and indication:

|               |       |
|---------------|-------|
| Flam. Liq. 2  | H225  |
| Repr. 2       | H361d |
| Asp. Tox. 1   | H304  |
| STOT RE 2     | H373  |
| Skin Irrit. 2 | H315  |

##### 2.1.2. 67/548/EEC and 1999/45/EC Directives and following amendments and adjustments.



**Danger Symbols:**

F-Xn

R phrases:

11-20/21-38-48/20-Repr. Cat. 3 63-65

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

**2.2. Label elements.**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



Signal words:

Danger

|              |  |
|--------------|--|
| <b>H225</b>  | Highly flammable liquid and vapour.                                |
| <b>H361d</b> | Suspected of damaging the unborn child.                            |
| <b>H304</b>  | May be fatal if swallowed and enters airways.                      |
| <b>H373</b>  | May cause damage to organs through prolonged or repeated exposure. |
| <b>H315</b>  | Causes skin irritation.  |

|                       |  |
|-----------------------|--|
| <b>P201</b>           | Obtain special instructions before use.  |
| <b>P210</b>           | Keep away from heat/sparks/open flames/hot surfaces. No smoking.   |
| <b>P233</b>           | Keep container tightly closed.   |
| <b>P280</b>           | Wear protective gloves / protective clothing / eye protection / face protection.                           |
| <b>P301+P310</b>      | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  |
| <b>P303+P361+P353</b> | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |

**Contains:** TOLUENE  
XYLENE (MIXTURE OF ISOMERS)

**2.3. Other hazards.**

Information not available.

**SECTION 3. Composition/information on ingredients.**

**3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

Contains:

| Identification.     | Conc. %. | Classification 67/548/EEC.       | Classification 1272/2008 (CLP).             |
|---------------------|----------|----------------------------------|---|
| <b>ETHYLBENZENE</b> |          |                                  |   |
| CAS. 100-41-4       | 9 - 19   | F R11, Xn R20                    | Flam. Liq. 2 H225, Acute Tox. 4 H332        |
| EC. 202-849-4       |          |                                  |   |
| INDEX. 601-023-00-4 |          |                                  |   |
| <b>TOLUENE</b>      |          |                                  |   |
| CAS. 108-88-3       | 10 - 20  | Repr. Cat. 3 R63, R67, F R11, Xn | Flam. Liq. 2 H225, Repr. 2 H361d, STOT RE 2 |



EC. 203-625-9

R48/20, Xi R38

H373, Skin Irrit. 2 H315, STOT SE 3 H336

INDEX. 601-021-00-3

Reg. no. 01-2119471310-51-XXXX

**XYLENE (MIXTURE OF ISOMERS)**

CAS. 1330-20-7

10 - 20

R10, Xn R20/21, Xn R48/20, Xn R65, Xi  
R36/37/38, Note C

Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox.  
4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye  
Irrit. 2A H319, Skin Irrit. 2 H315, STOT SE 3  
H335, Note C

EC. 215-535-7

INDEX. 601-022-00-9

Reg. no. 01-2119488216-32-XXXX

Note: Upper limit is not included into the range.

The full wording of the Risk (R) and hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures.**

### **4.1. Description of first aid measures.**

**EYES:** Remove contact lenses, if present Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice  
**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.  
**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.  
**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### **4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

### **4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

## **SECTION 5. Firefighting measures.**

### **5.1. Extinguishing media.**

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

### **5.2. Special hazards arising from the substance or mixture.**

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

### **5.3. Advice for firefighters.**

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for



extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6. Accidental release measures.**

### **6.1. Personal precautions, protective equipment and emergency procedures.**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### **6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### **6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### **6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

## **SECTION 7. Handling and storage.**

### **7.1. Precautions for safe handling.**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

### **7.2. Conditions for safe storage, including any incompatibilities.**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### **7.3. Specific end use(s).**

Information not available.

## **SECTION 8. Exposure controls/personal protection.**

### **8.1. Control parameters.**



Regulatory References:

United Kingdom EH40/2005 Workplace exposure limits. Containing the list of workplace exposure limits for use with the Control of Substances Hazardous to Health Regulations (as amended).  
Éire Code of Practice Chemical Agent Regulations 2011.  
OEL EU Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.  
TLV-ACGIH ACGIH 2012

**ETHYLBENZENE**

| Type      | Country | TWA/8h |     | STEL/15min |     |      |
|-----------|---------|--------|-----|------------|-----|------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |      |
| WEL       | UK      | 441    | 100 | 552        | 125 | SKIN |
| OEL       | IRL     | 442    | 100 | 884        | 200 | SKIN |
| OEL       | EU      | 442    | 100 | 884        | 200 | SKIN |
| TLV-ACGIH |         | 20     | 100 |            | 87  |      |

**TOLUENE**

| Type      | Country | TWA/8h |     | STEL/15min |     |      |
|-----------|---------|--------|-----|------------|-----|------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |      |
| WEL       | UK      | 191    | 50  | 384        | 100 | SKIN |
| OEL       | IRL     | 192    | 50  | 384        | 100 | SKIN |
| OEL       | EU      | 192    | 50  | 384        | 100 | SKIN |
| TLV-ACGIH |         | 75,4   | 20  |            |     |      |

**XYLENE (MIXTURE OF ISOMERS)**

| Type      | Country | TWA/8h |     | STEL/15min |     |      |
|-----------|---------|--------|-----|------------|-----|------|
|           |         | mg/m3  | ppm | mg/m3      | ppm |      |
| OEL       | EU      | 221    | 50  | 442        | 100 | SKIN |
| OEL       | IRL     | 221    | 50  | 442        | 100 | SKIN |
| TLV-ACGIH |         | 434    | 100 | 651        | 150 |      |
| WEL       | UK      | 220    | 50  | 441        | 100 |      |

**Predicted no-effect concentration - PNEC.**

|  |       |       |
|--|-------|-------|
| Normal value in fresh water                  | 2,31  | mg/kg |
| Normal value for water, intermittent release | 0,327 | mg/l  |
| Normal value in marine water                 | 0,327 | mg/l  |
| Normal value for fresh water sediment        | 12,46 | mg/kg |
| Normal value for marine water sediment       | 12,46 | mg/kg |
| Normal value of STP microorganisms           | 6,58  | mg/l  |

| Route of exposure    | Effects on consumers.<br>Acute local | Effects on consumers |                  |                         | Effects on workers<br>Acute local | Effects on workers |               |                       |
|----------------------|--------------------------------------|----------------------|------------------|-------------------------|-----------------------------------|--------------------|---------------|-----------------------|
|                      |                                      | Acute systemic       | Chronic local    | Chronic systemic        |                                   | Acute systemic     | Chronic local | Chronic systemic      |
| Oral.                |                                      |                      | VND              |                         |                                   |                    |               |                       |
| Inhalation.<br>Skin. | VND                                  | 174 mg/m3            | 174 mg/m3<br>VND | 14,8 mg/m3<br>108 mg/kg | VND                               | 289 mg/m3          | VND<br>VND    | 77 mg/m3<br>180 mg/kg |

Legend:



(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.  
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

#### **HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### **SKIN PROTECTION**

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

#### **RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## **SECTION 9. Physical and chemical properties.**

### 9.1. Information on basic physical and chemical properties.

|                                  |                           |
|----------------------------------|---------------------------|
| Appearance                       | liquid                    |
| Colour                           | red                       |
| Odour                            | characteristic of solvent |
| Odour threshold.                 | Not available.            |
| pH.                              | Not available.            |
| Melting point / freezing point.  | Not available.            |
| Initial boiling point.           | Not available.            |
| Boiling range.                   | Not available.            |
| Flash point.                     | 20 °C.                    |
| Evaporation Rate                 | Not available.            |
| Flammability of solids and gases | Not available.            |
| Lower inflammability limit.      | Not available.            |
| Upper inflammability limit.      | Not available.            |
| Lower explosive limit.           | Not available.            |



|  |                    |
|--|--------------------|
| Upper explosive limit.                 | Not available.     |
| Vapour pressure.                       | Not available.     |
| Vapour density.                        | Not available.     |
| Relative density.                      | 1,011 Kg/l         |
| Solubility                             | partially miscible |
| Partition coefficient: n-octanol/water | Not available.     |
| Auto-ignition temperature.             | Not available.     |
| Decomposition temperature.             | Not available.     |
| Viscosity                              | Not available.     |
| Explosive properties                   | Not available.     |
| Oxidising properties                   | Not available.     |

**9.2. Other information.**

Information not available.

**SECTION 10. Stability and reactivity.**

**10.1. Reactivity.**

There are no particular risks of reaction with other substances in normal conditions of use.

TOLUENE: breaks down in sunlight.

**10.2. Chemical stability.**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions.**

The vapours may also form explosive mixtures with the air.

ETHYLBENZENE: reacts violently with strong oxidising agents and attacks various types of plastics. Can form explosive mixtures with the air.

TOLUENE: risk of explosion on contact with fuming sulphuric acid, nitric acid, silver perchlorates, nitrogen dioxide, non-metal halogenides, acetic acid, organic nitrocompounds. Can form explosive mixtures with the air. May react dangerously with: strong oxidising agents, strong acids, sulphur (in the presence of heat).

XILENE: è stabile, ma può dare reazioni violente in presenza di ossidanti forti come acido solforico, nitrico, perclorati. Può formare miscele esplosive con l'aria.

**10.4. Conditions to avoid.**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

**10.5. Incompatible materials.**

Information not available.

**10.6. Hazardous decomposition products.**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE: methane, styrene, hydrogen, ethane.

**SECTION 11. Toxicological information.**

**11.1. Information on toxicological effects.**



In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible teratogenic effects, which may be toxic and damage the foetus development.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Vapour inhalation may slightly irritate the upper respiratory tract. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

#### ETHYLBENZENE

LD50 (Oral). 3500 mg/kg Rat

LD50 (Cutánea). 15354 mg/kg Rabbit

LC50 (Inhalación). 6,2 mg/l/4h (publication, mouse, ECHA dossier).

Irritation/Corrosion

Skin irritation: Slightly irritating (publication, rabbit, in vivo, ECHA dossier).

Eye irritation: Slightly irritating (publication, rabbit, in vivo, ECHA dossier).

Skin Sensitization: No data available.

STOT Repeated exposure: Insufficient data. Liver, lung, thyroid and pituitary pathology was observed in mice that inhaled  $\geq$  250 ppm ethylbenzene for 2

years. (ECHA dossier).

Genotoxicity: Negative (OECD 473, in vitro mammalian chromosome aberration test and OECD 486, in vivo, ECHA dossier).

Carcinogenicity: Insufficient data. According to NTP there was some evidence of carcinogenicity in a test conducted on mice (lung tumors and hepatocellular neoplasms) (NTP study, GLP, ECHA dossier).

Toxicity to reproduction: Negative (OECD 415, rat, ECHA dossier).

ETHYLBENZENE: like the benzene homologues, may exert an effect on the CNS with depression, narcosis, often preceded by dizziness and accompanied by headache. It is irritating to the skin, conjunctivae and respiratory apparatus.

#### TOLUENE

LD50 (Oral). 5580 mg/kg (rat, ECHA dossier).

LD50 (Dermal). 12124 mg/kg (rabbit, ECHA dossier).

LC50 (Inhalation). 28,1 mg/l/4h (rat, ECHA dossier).

Irritation/Corrosion

Skin irritation: Irritating (OECD 404, in vivo, rabbit, ECHA dossier).

Eye irritation: Not irritating (OECD 405, in vivo, rabbit, ECHA dossier).

Skin Sensitization: Not sensitising (OECD 406, Magnusson-Kligman, ECHA dossier).

STOT – Repeated/single exposure: Target organ: central nervous system (inhalation exposure, tests on animals, ECHA dossier).

Genotoxicity in vitro: Negative (OECD 471, OECD 476, mutation assay, ECHA dossier).

Genotoxicity in vivo: Negative (Chromosome aberration assay, rat, ECHA dossier).

Carcinogenicity: No data available.

Toxicity to reproduction: Possible adverse effects on fetal development (OECD 416 and EPA OTS 798.4350, rat, ECHA dossier).

TOLUENE: it has a toxic effect on the central and peripheral nervous system (with encephalopathies and polyneuritis). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

#### XYLENE (MIXTURE OF ISOMERS)

LD50 (Oral). 3523 mg/kg (EU Method B.1, GLP, rat, ECHA dossier).

LD50 (Dermal). 4350 mg/kg Rabbit

LC50 (Inhalation). 6350 ppm (EU Method B.2, rat, ECHA dossier).

Acute toxicity:

Dermal: No data available.

Irritation/Corrosion

Skin irritation: Slightly irritating (weight of evidence approach, in vivo, rabbit, ECHA dossier).

Eye irritation: Slightly irritating (weight of evidence approach, in vivo, rabbit, ECHA dossier).

Skin Sensitization: Insufficient data (ECHA dossier).

STOT –

Repeated exposure: There was no evidence of treatment-related systemic toxicity or carcinogenicity following gavage administration of mixed xylenes (oral and inhalation exposure, ECHA dossier).

Genotoxicity in vitro: Negative (in vitro mammalian chromosome aberration test, ECHA dossier).

Genotoxicity in vivo: Negative (similar to OECD 478, mixed xylenes, chromosome aberration, ECHA dossier).

Carcinogenicity: Negative (EU Method B.32, rat, ECHA dossier).

Toxicity to reproduction: Negative (EPA OPPTS 870.3800, rat, ECHA dossier).





## **SECTION 12. Ecological information.**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or sewers or contaminate soil or vegetation.

### **12.1. Toxicity.**

#### **TOLUENE**

LC50 - for Fish.

5,5 mg/l/96h (Oncorhynchus kisutch, dynamic, freshwater, ECHA dossier).

EC50 - for Crustacea.

3,78 mg/l/48h (Daphnia magna, semi-static, freshwater, ECHA dossier).

EC50 - for Algae / Aquatic Plants.

134 mg/l/72h (ECHA dossier).

### **12.2. Persistence and degradability.**

#### **ETHYLBENZENE**

Rapidly biodegradable.

#### **TOLUENE**

Rapidly biodegradable.

### **12.3. Bioaccumulative potential.**

Information not available.

### **12.4. Mobility in soil.**

Information not available.

### **12.5. Results of PBT and vPvB assessment.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### **12.6. Other adverse effects.**

Information not available.

## **SECTION 13. Disposal considerations.**

### **13.1. Waste treatment methods.**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Avoid littering. Do not contaminate soil, sewers and waterways.

Waste transportation may be subject to ADR restrictions.

#### **CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## **SECTION 14. Transport information.**

These goods must be transported by vehicles authorized to the carriage of dangerous goods according to the provisions set out in the current edition of the Code of International Carriage of Dangerous Goods by Road (ADR) and in all the applicable national regulations. These goods must be packed in their original packagings or in packagings made of materials resistant to their content and not reacting dangerously with it. People loading and



unloading dangerous goods must be trained on all the risks deriving from these substances and on all actions that must be taken in case of emergency situations.

**Road and rail transport:**

ADR/RID Class: 3 UN: 1133

Packing Group: II

Label: 3

Nr. Kemler: 33

Limited Quantity: 5 L

Tunnel restriction code: (D/E)

Proper Shipping Name: ADHESIVES

Special Provision: 640C

**Carriage by sea (shipping):**

IMO Class: 3 UN: 1133

Packing Group: II

Label: 3

EMS: F-E, S-D

Marine Pollutant: NO

Proper Shipping Name: ADHESIVES

**Transport by air:**

IATA: 3 UN: 1133

Packing Group: II

Label: 3

Cargo:

Packaging instructions: 355 Maximum quantity: 60 L

Pass.: Y341 Maximum quantity: 0,5 L

Special Instructions: A3

Proper Shipping Name: ADHESIVES

**SECTION 15. Regulatory information.**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

Seveso category. 7b

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product  
Point. 3 - 40

Contained substance.



Point. 48 TOLUENE

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment.**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|               |  |
|---------------|--|
| Flam. Liq. 2  | Flammable liquid, category 2                                   |
| Flam. Liq. 3  | Flammable liquid, category 3                                   |
| Repr. 2       | Reproductive toxicity, category 2                              |
| Acute Tox. 4  | Acute toxicity, category 4                                     |
| Asp. Tox. 1   | Aspiration hazard, category 1                                  |
| STOT RE 2     | Specific target organ toxicity - repeated exposure, category 2 |
| Eye Irrit. 2A | Eye irritation, category 2A                                    |
| Skin Irrit. 2 | Skin irritation, category 2                                    |
| STOT SE 3     | Specific target organ toxicity - single exposure, category 3   |
| H225          | Highly flammable liquid and vapour.                            |
| H226          | Flammable liquid and vapour.                                   |
| H361d         | Suspected of damaging the unborn child.                        |
| H312          | Harmful in contact with skin.                                  |
| H332          | Harmful if inhaled.  |
| H304          | May be fatal if swallowed and enters airways.                  |



|      |  |
|------|--|
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H319 | Causes serious eye irritation.                                     |
| H315 | Causes skin irritation.  |
| H335 | May cause respiratory irritation.                                  |
| H336 | May cause drowsiness or dizziness.                                 |

Text of risk (R) phrases mentioned in section 2-3 of the sheet:

|              |   |
|--------------|---|
| R10          | FLAMMABLE.  |
| R11          | HIGHLY FLAMMABLE.   |
| R20          | HARMFUL BY INHALATION.  |
| R20/21       | HARMFUL BY INHALATION AND IN CONTACT WITH SKIN.                                       |
| R36/37/38    | IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN.                                      |
| R38          | IRRITATING TO SKIN.   |
| R48/20       | HARMFUL: DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE THROUGH INHALATION. |
| Repr. Cat. 3 | Reproductive toxicity, development, category 3.                                       |
| R63          | POSSIBLE RISK OF HARM TO THE UNBORN CHILD.  |
| R65          | HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED.  |
| R67          | VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.   |

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation.

**GENERAL BIBLIOGRAPHY**

1. Directive 1999/45/EC and following amendments
2. Directive 67/548/EEC and following amendments and adjustments
3. Regulation (EC) 1907/2006 (REACH) of the European Parliament
4. Regulation (EC) 1272/2008 (CLP) of the European Parliament
5. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament



6. Regulation (EC) 453/2010 of the European Parliament
7. Regulation (EC) 286/2011 (II Atp. CLP) of the European Parliament
8. The Merck Index. - 10th Edition
9. Handling Chemical Safety
10. Niosh - Registry of Toxic Effects of Chemical Substances
11. INRS - Fiche Toxicologique (toxicological sheet)
12. Patty - Industrial Hygiene and Toxicology
13. N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
14. ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.