

ThinkCentre[®]

*Product Specifications Reference
Lenovo[®] ThinkCentre Desktops
2014 to present - withdrawn*

May 2014 - Version 454



Lenovo ThinkCentre M92z AIO

lenovo.com

Contents

Summary of Changes	1	ThinkCentre M78 Tower (1565) - ES 5.2 (GMP) - withdrawn	70
ThinkCentre M72e Tiny, Small, Tower	2	ThinkCentre M78 Tower (1565) - ES 5.2 (GMP) - Win 8 - withdrawn.....	71
ThinkCentre M72e Tiny (4004) - TopSeller - withdrawn	3	ThinkCentre M82 Small and Tower.....	72
ThinkCentre M72e Tiny (4004) - TopSeller - II - withdrawn.....	4	ThinkCentre M82 Small (3306) - TopSeller - withdrawn.....	73
ThinkCentre M72e Tiny (4004) - TopSeller (Thin Client) - withdrawn.....	5	ThinkCentre M82 Small (3306) - TopSeller - II - withdrawn.....	74
ThinkCentre M72e Tiny (4004) - TopSeller (Win 8) - withdrawn.....	6	ThinkCentre M82 Small (3306) - TopSeller - III - withdrawn.....	75
ThinkCentre M72e Tiny (4004) - TopSeller (Win 8) - II - withdrawn	7	ThinkCentre M82 Small (3306) - TopSeller (Win 8) - withdrawn	76
ThinkCentre M72e Small (0967) - TopSeller - withdrawn.....	8	ThinkCentre M82 Tower (3302) - TopSeller - withdrawn	77
ThinkCentre M72e Small (0967) - TopSeller - II - withdrawn.....	9	ThinkCentre M82 Tower (3302) - TopSeller - II - withdrawn	78
ThinkCentre M72e Small (0967) - TopSeller (Win 8) - withdrawn	10	ThinkCentre M82 Tower (3302) - TopSeller - III - withdrawn	79
ThinkCentre M72e Tower (0958) - TopSeller - withdrawn	11	ThinkCentre M82 Tower (3302) - TopSeller (Win 8) - withdrawn	80
ThinkCentre M72e Tower (0958) - TopSeller - II - withdrawn	12	ThinkCentre M82 Small (3395) - withdrawn	81
ThinkCentre M72e Tower (0958) - TopSeller (Win 8) - withdrawn	13	ThinkCentre M82 Small (3395) - II - withdrawn.....	82
ThinkCentre M72e Tower (3675) - ES 5.2 (TopSeller) - withdrawn	14	ThinkCentre M82 Small (3395) - Windows 8 - withdrawn	83
ThinkCentre M72e Tiny (3264) - withdrawn	15	ThinkCentre M82 Small (2756) - ENERGY STAR 5.2 - withdrawn	84
ThinkCentre M72e Tiny (3264) - II - withdrawn	16	ThinkCentre M82 Small (2756) - ENERGY STAR 5.2 - II - withdrawn	85
ThinkCentre M72e Tiny (3264) - Thin Client - withdrawn	17	ThinkCentre M82 Small (2756) - ES 5.2 (Win 8) - withdrawn	86
ThinkCentre M72e Tiny (3264) - Windows 8 - withdrawn.....	18	ThinkCentre M82 Small (2756) - ES 5.2 (Win 8) - II - withdrawn	87
ThinkCentre M72e Tiny (3264) - Windows 8 - II - withdrawn	19	ThinkCentre M82 Small (2929) - ES 5.2 (GMP) - withdrawn	88
ThinkCentre M72e Tiny (3267) - GMP - withdrawn.....	20	ThinkCentre M82 Small (2929) - ES 5.2 (GMP) - Win 8 - withdrawn	89
ThinkCentre M72e Tiny (3267) - GMP (Thin Client) - withdrawn	21	ThinkCentre M82 Tower (3392) - withdrawn	90
ThinkCentre M72e Tiny (3267) - GMP (Win 8) - withdrawn	22	ThinkCentre M82 Tower (3392) - II - withdrawn	91
ThinkCentre M72e Small (3598) - withdrawn	23	ThinkCentre M82 Tower (3392) - Windows 8 - withdrawn	92
ThinkCentre M72e Small (3598) - II - withdrawn.....	24	ThinkCentre M82 Tower (3392) - Windows 8 - II - withdrawn	93
ThinkCentre M72e Small (3598) - Windows 8 - withdrawn	25	ThinkCentre M82 Tower (2697) - ENERGY STAR 5.2 - withdrawn	94
ThinkCentre M72e Small (3660) - ES 5.2 - withdrawn.....	26	ThinkCentre M82 Tower (2697) - ES 5.2 (Win 8) - withdrawn	95
ThinkCentre M72e Small (3660) - ES 5.2 - II - withdrawn.....	27	ThinkCentre M82 Tower (2742) - ES 5.2 (GMP) - withdrawn	96
ThinkCentre M72e Small (3660) - ES 5.2 (Win 8) - withdrawn	28	ThinkCentre M82 Tower (2742) - ES 5.2 (GMP) - Win 8 - withdrawn	97
ThinkCentre M72e Small (3660) - ES 5.2 (Win 8) - II - withdrawn	29	ThinkCentre M82 Accessories	98
ThinkCentre M72e Small (3664) - ES 5.2 (GMP) - withdrawn	30	ThinkCentre M83 SFF Pro (10AN) - 1-year Onsite - withdrawn.....	99
ThinkCentre M72e Small (3664) - ES 5.2 (GMP) - Win 8 - withdrawn	31	ThinkCentre M92/M92p Tiny, Small, Tower	100
ThinkCentre M72e Tower (3597) - withdrawn.....	32	ThinkCentre M92 Tiny (3234) - TopSeller - withdrawn	101
ThinkCentre M72e Tower (3597) - II - withdrawn	33	ThinkCentre M92p Tiny (2121) - TopSeller (Thin Client)	102
ThinkCentre M72e Tower (3597) - Windows 8 - withdrawn	34	ThinkCentre M92p Tiny (2121) - TopSeller	103
ThinkCentre M72e Tower (3655) - ES 5.2 - withdrawn.....	35	ThinkCentre M92p Tiny (2121) - TopSeller (Win 8)	104
ThinkCentre M72e Tower (3655) - ES 5.2 - II - withdrawn	36	ThinkCentre M92p Small (2988) - TopSeller	105
ThinkCentre M72e Tower (3655) - ES 5.2 (Win 8) - withdrawn	37	ThinkCentre M92p Small (2988) - TopSeller - II	106
ThinkCentre M72e Tower (3655) - ES 5.2 (Win 8) - II - withdrawn	38	ThinkCentre M92p Small (2988) - TopSeller (Win 8)	107
ThinkCentre M72e Tower (3662) - ES 5.2 (GMP) - withdrawn	39	ThinkCentre M92p Tower (2992) - TopSeller	108
ThinkCentre M72e Tower (3662) - ES 5.2 (GMP) - Win 8 - withdrawn	40	ThinkCentre M92p Tower (2992) - TopSeller - II	109
ThinkCentre M72e Accessories	41	ThinkCentre M92p Tower (2992) - TopSeller (Win 8)	110
ThinkCentre M72z All-In-One.....	42	ThinkCentre M92 Tiny (3229) - GMP (Thin Client)	111
ThinkCentre M72z (3543) - TopSeller (Win 8)	43	ThinkCentre M92 Small (3207) - withdrawn	112
ThinkCentre M72z (3548) - TopSeller	44	ThinkCentre M92 Tower (3208)	113
ThinkCentre M72z (3548) - TopSeller - II	45	ThinkCentre M92p Tiny (3238) - Thin Client	114
ThinkCentre M72z (3548) - TopSeller (Win 8)	46	ThinkCentre M92p Tiny (3243)	115
ThinkCentre M72z (3548) - TopSeller (Win 8) - III	47	ThinkCentre M92p Tiny (3238)	116
ThinkCentre M72z (3548) - TopSeller (Win 8) - II	48	ThinkCentre M92p Tiny (3238) - II	117
ThinkCentre M72z (3554)	49	ThinkCentre M92p Tiny (3238) - Windows 8	118
ThinkCentre M72z (3554) - Windows 8.....	50	ThinkCentre M92p Tiny (3237) - GMP (Thin Client)	119
ThinkCentre M72z (3554) - Windows 8 - II	51	ThinkCentre M92p Tiny (3237) - GMP	120
ThinkCentre M72z (3558) - GMP	52	ThinkCentre M92p Tiny (3237) - GMP (Win 8)	121
ThinkCentre M72z (3558) - GMP (Thin Client)	53	ThinkCentre M92p Small (3209)	122
ThinkCentre M72z (3558) - GMP (Win 8)	54	ThinkCentre M92p Small (3209) - II	123
ThinkCentre M72z (3538) - Multi-touch (GMP)	55	ThinkCentre M92p Small (3209) - Windows 8	124
ThinkCentre M72z Accessories	56	ThinkCentre M92p Small (3209) - Windows 8 - II	125
ThinkCentre M78 Small (5100) - TopSeller - withdrawn	57	ThinkCentre M92p Small (3209) - Windows 8 - III	126
ThinkCentre M78 Small (5100) - TopSeller (Win 8) - withdrawn	58	ThinkCentre M92p Small (3227) - GMP	127
ThinkCentre M78 Small (4865) - withdrawn.....	59	ThinkCentre M92p Small (3227) - GMP (Win 8)	128
ThinkCentre M78 Small (4865) - Windows 8 - withdrawn	60	ThinkCentre M92p Tower (3212)	129
ThinkCentre M78 Small (2113) - ES 5.2 - withdrawn	61	ThinkCentre M92p Tower (3212) - II	130
ThinkCentre M78 Small (2113) - ES 5.2 (Win 8) - withdrawn	62	ThinkCentre M92p Tower (3212) - III	131
ThinkCentre M78 Small (2114) - ES 5.2 (GMP) - withdrawn	63	ThinkCentre M92p Tower (3212) - Windows 8	132
ThinkCentre M78 Small (2114) - ES 5.2 (GMP) - Win 8 - withdrawn	64	ThinkCentre M92p Tower (3212) - Windows 8 - II	133
ThinkCentre M78 Tower (2111) - TopSeller - withdrawn	65	ThinkCentre M92p Tower (3212) - Windows 8 - III	134
ThinkCentre M78 Tower (2111) - TopSeller (Win 8) - withdrawn	66	ThinkCentre M92p Tower (3228) - GMP	135
ThinkCentre M78 Tower (1766) - withdrawn	67	ThinkCentre M92p Tower (3228) - GMP (Win 8)	136
ThinkCentre M78 Tower (1562) - ENERGY STAR® 5.2 - withdrawn	68	ThinkCentre M92, M92p Accessories	137
ThinkCentre M78 Tower (1562) - ES 5.2 (Win 8) - withdrawn	69	ThinkCentre M92z All-In-One.....	138

Contents

ThinkCentre M92z (3280) - 20" (TopSeller) - Win 8 - withdrawn	139
ThinkCentre M92z (3291) - 20" (TopSeller) - withdrawn	140
ThinkCentre M92z (3291) - 20" (TopSeller) - II - withdrawn	141
ThinkCentre M92z (3291) - 20" (TopSeller) - III - withdrawn	142
ThinkCentre M92z (3291) - 20" (TopSeller) - Win 8 - withdrawn.....	143
ThinkCentre M92z (3296) - 20" - withdrawn	144
ThinkCentre M92z (3296) - 20" - III - withdrawn	145
ThinkCentre M92z (3296) - 20" - II - withdrawn	146
ThinkCentre M92z (3296) - 20" (Win 8) - withdrawn.....	147
ThinkCentre M92z (3296) - 20" (Win 8) - II - withdrawn.....	148
ThinkCentre M92z (3298) - 20" (GMP) - withdrawn.....	149
ThinkCentre M92z (3298) - 20" (GMP) - Win 8 - withdrawn.....	150
ThinkCentre M92z (3315) - 23" (TopSeller) - Win 8 - withdrawn.....	151
ThinkCentre M92z (3318) - 23" (TopSeller) - withdrawn	152
ThinkCentre M92z (3318) - 23" (TopSeller) - II - withdrawn.....	153
ThinkCentre M92z (3318) - 23" (TopSeller) - III - withdrawn	154
ThinkCentre M92z (3318) - 23" (TopSeller) - Win 8 - withdrawn.....	155
ThinkCentre M92z (3318) - 23" (TopSeller) - Win 8 - II - withdrawn....	156
ThinkCentre M92z (3318) - 23" (TopSeller) - Win 8 - III - withdrawn....	157
ThinkCentre M92z (3325) - 23" - withdrawn	158
ThinkCentre M92z (3325) - 23" - II - withdrawn	159
ThinkCentre M92z (3325) - 23" - III - withdrawn	160
ThinkCentre M92z (3325) - 23" (Win 8) - withdrawn.....	161
ThinkCentre M92z (3325) - 23" (Win 8) - II - withdrawn.....	162
ThinkCentre M92z (3327) - 23" (GMP) - withdrawn.....	163
ThinkCentre M92z (3327) - 23" (GMP) - Win 8 - withdrawn.....	164
ThinkCentre M92z (3311) - 23" (Multi-touch) - TS - withdrawn.....	165
ThinkCentre M92z (3311) - 23" (Multi-touch) - TS - II - withdrawn.....	166
ThinkCentre M92z (3314) - 23" (Multi-touch) - withdrawn	167
ThinkCentre M92z (3329) - 23" (Multi-touch) - GMP - withdrawn	168
ThinkCentre M92z Accessories	169
ThinkCentre Edge 72 Small and Tower	170
ThinkCentre Edge 72 Small (3493) - TopSeller.....	171
ThinkCentre Edge 72 Small (3493) - TopSeller - II	172
ThinkCentre Edge 72 Small (3493) - TopSeller (Win 8)	173
ThinkCentre Edge 72 Tower (3484) - TopSeller	174
ThinkCentre Edge 72 Tower (3484) - TopSeller - II	175
ThinkCentre Edge 72 Tower (3484) - TopSeller (Win 8).....	176
ThinkCentre Edge 92z	177
ThinkCentre Edge 92z (3396) - TopSeller - withdrawn.....	178
ThinkCentre Edge 92z (3396) - TopSeller (Win 8) - withdrawn	179
ThinkCentre Edge 92z (3399) - TopSeller (Win 8) - withdrawn	180
ThinkCentre Edge 92z (3418) - TopSeller - withdrawn.....	181
ThinkCentre Edge 92z (3418) - TopSeller - II - withdrawn	182
ThinkCentre Edge 92z (3418) - TopSeller (Win 8) - withdrawn	183
ThinkCentre Edge 92z (3426) - TopSeller (Win 8) - withdrawn	184
ThinkCentre Edge 92z (3414) - Multi-touch (TopSeller) - withdrawn ...	185
ThinkCentre Edge 92z (3414) - Multi-touch (TS) - Win 8 - withdrawn..	186
ThinkCentre Edge 92z (3417) - Multi-touch (TS) - Win 8 - withdrawn..	187
ThinkCentre Edge 92z Accessories	188

Summary of Changes

This section describes the withdrawn products which are added in this edition and in previous editions.

May 27, 2014 - Version 454

► Withdrawn product(s)

ThinkCentre M72z is withdrawn and added in the book

ThinkCentre Edge 72 is withdrawn and added in the book

ThinkCentre M72e Tiny, Small, Tower

ThinkCentre®



Lenovo ThinkCentre M72e Tiny
with Optional Serial Port



Lenovo ThinkCentre M72e Tiny, Small, and Tower
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M72e Small



Lenovo ThinkCentre M72e Tiny
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M72e Tower



Lenovo ThinkCentre M72e Tiny
with External Optical Box

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Win7 preload	Ann date (mm/dd/yy)
4004-A1U	i3-2120T	4GBx1	320G 5400	DVD±RW	HD 2000	None	None	None	None	Mount	ES52	None	Pro 64 06/05/12
4004-A2U	G630T	4GBx1	320G 5400	DVD±RW	Intel HD	None	None	None	None	Mount	ES52	None	Pro 64 06/05/12
4004-A7U	G630T	2GBx1	320G 5400	None	Intel HD	None	None	None	Stand	Mount	ES52	None	Pro 64 06/05/12
4004-A9U	i3-2120T	4GBx1	500G 5400	None	HD 2000	None	None	None	Stand	Mount	ES52	None	Pro 64 06/05/12
4004-B2U	i3-2120T	4GBx1	320G 5400	None	HD 2000	None	None	None	Stand	Mount	ES52	None	Pro 64 06/05/12
4004-C3U	i3-2120T	4GBx1	500G 7200	DVD±RW	HD 2000	None	Intel 2230 + BT	None	None	Mount	ES52	None	Pro 64 06/19/12
4004-C4U	i3-2120T	4GBx1	500G 7200	None	HD 2000	None	Intel 2230 + BT	None	Stand	Mount	ES52	None	Pro 64 06/19/12
4004-B8U	i3-2120T	4GBx1	500G 7200	None	HD 2000	None	None	None	Stand	Mount	ES52	None	Pro 64 07/10/12
4004-B5U	i3-2120T	4GBx1	500G 7200	None	HD 2000	None	None	None	Stand	Mount	ES52	None	Pro 32 07/10/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>											Preloaded operating system														
Processor	Intel® Pentium® G630T Processor (2 cores / 2 threads, 2.3GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller											Some: Genuine Windows® 7 Professional 32														
Implementation	Intel Core™ i3-2120T Processor (2 cores / 4 threads, 2.6GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller											Some: Genuine Windows 7 Professional 64														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>											Ready to install applications (only some listed)														
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>											Preloaded applications (only some listed)														
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 														
Disk	SATA 3.0Gb/s, 2.5" Wide																									
External optical	<i>Some:</i> Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in																									
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																									
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar																									
eSATA port	None																									
Chipset	Intel H61 Express Chipset																									
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																									
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)																									
PCIe Mini Card	One PCI Express® Mini Card slot																									
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																									
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																									
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																									
Speaker	Internal speaker for business audio																									
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																									
Intel AMT	None																									
Modem	None																									
Security chip	None																									
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																									
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																									
Floor Stand	<i>Some:</i> System floor stand for vertical orientation																									
VESA mount	Supports VESA 75mm and 100mm mount standard																									
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU																									
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 																									
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																									
Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 																										
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																										
Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																										

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
4004-A8U	i5-3470T	4GBx1	750G 5400	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Pro 64	06/05/12
4004-B1U	i5-3470T	4GBx1	500G 5400	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Pro 64	06/05/12
4004-B4U	i5-3470T	4GBx2	750G 5400	None	HD 2500	None	None	None	Stand	None	ES52	None	Pro 64	06/05/12
4004-C1U	i5-3470T	4GBx1	500G 7200	None	HD 2500	None	Intel 2230 + BT	None	Stand	Mount	ES52	None	Pro 64	06/19/12
4004-C2U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	Intel 2230 + BT	None	None	Mount	ES52	None	Pro 64	06/19/12
4004-B7U	i5-3470T	2GBx1	320G 7200	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Pro 64	07/10/12
4004-B6U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	None	Pro 64	07/10/12
4004-E7U	i3-3220T	4GBx1	500G 5400	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Pro 64	09/04/12
4004-E8U	i3-3220T	4GBx1	500G 5400	DVD±RW	HD 2500	None	Intel 2230 + BT	None	None	Mount	ES52	None	Pro 64	09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i3-3220T Processor (2 cores / 4 threads , 2.8GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470T Processor (2 cores / 4 threads , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate 			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)														
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>														
DP dongle	None														
Disk	SATA 3.0Gb/s, 2.5" Wide														
External optical	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in														
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset														
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar														
eSATA port	None														
Chipset	Intel H61 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®														
Intel AMT	None														
Modem	None														
Security chip	None														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	Some: System floor stand for vertical orientation														
VESA mount	Some: Supports VESA 75mm and 100mm mount standard														
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU														
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
	<p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p> <p>For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet</p>														

See footnotes for important warranty information

US models announced June 5, June 19, July 10, or September 4, 2012

©Lenovo

(MOSI1-2) September 2012

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
4004-D1U	G460	2GBx1	8G SSD	None	Intel HD	None	None	None	Stand	Mount	ES52	None	Emb 32	07/10/12
4004-E9U	G640T	2GBx1	8G SSD	None	Intel HD	None	None	None	Stand	Mount	ES52	None	Emb 32	08/14/12
4004-K4U	i5-3470T	2GBx1	8G SSD	None	HD 2500	None	Intel 105	None	Stand	None	ES52	None	Emb 32	03/05/13
4004-K3U	G640T	2GBx1	8G SSD	None	Intel HD	None	Intel 105	None	Stand	None	ES52	None	Emb 32	03/05/13
4004-LJU	G470	2GBx1	8G SSD	None	Intel HD	None	None	None	Stand	None	ES52	None	Emb 32	06/11/13
4004-LKU	G1610T	2GBx1	8G SSD	None	Intel HD	None	None	None	None	Mount	ES52	None	Emb 32	06/11/13
4004-LGU	G2020T	2GBx1	8G SSD	None	Intel HD	None	None	None	None	Mount	ES52	None	Emb 32	06/11/13
4004-LHU	G2020T	2GBx1	8G SSD	None	Intel HD	None	Intel 2230 + BT	None	None	Mount	ES52	None	Emb 32	06/11/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G1610T Processor (2 core / 2 threads, 2.3GHz, 2MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller Intel Pentium® G640T Processor (2 cores / 2 threads, 2.4GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Pentium G2020T Processor (2 cores / 2 threads, 2.5GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Embedded 32
Implementation													Preloaded applications (only some listed) <ul style="list-style-type: none">• Adobe® Reader®• Adobe Flash® Player• Citrix® Receiver• IIS Web Server• Microsoft® Management Console• Microsoft Silverlight• Remote Desktop Protocol• ThinPrint .print Client• TightVNC Viewer• VMware® View Client• vWorkspace• Windows Media Player
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller												
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz												
DP dongle	None												
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide												
External optical	None												
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset												
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar												
eSATA port	None												
Chipset	Intel H61 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	Some: System floor stand for vertical orientation												
VESA mount	Some: Supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box)												
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet												

See footnotes for important warranty information

US models announced July 10, 2012, August 14, 2012, March 5, 2013, or June 11, 2013

©Lenovo

(MOSI1-22) June 2013

Type-model	Processor	Memory ^b	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
4004-C6U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	Intel 2230 + BT	None	None	Mount	ES52	None	Win8 Pro64	10/23/12
4004-C7U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	None	Win8 Pro64	10/23/12
4004-C8U	i5-3470T	4GBx1	500G 7200	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Win8 Pro64	10/23/12
4004-F2U	i3-3220T	4GBx1	500G 7200	None	HD 2500	None	None	None	Stand	Mount	ES52	None	Win8 Pro64	10/23/12
4004-F3U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	None	Win8 Pro64	10/23/12
4004-G6U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	None	Win7 Pro64	10/23/12
4004-G7U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	Intel 105	None	None	Mount	ES52	None	Win7 Pro64	10/23/12
4004-G8U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	Intel 2230 + BT	None	None	Mount	ES52	None	Win7 Pro64	10/23/12
4004-H1U	i3-3220T	4GBx1	500G 7200	None	HD 2500	None	Intel 105	None	None	Mount	ES52	None	Win7 Pro64	10/23/12
4004-H3U	i3-3220T	4GBx1	500G 5400	None	HD 2500	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	11/20/12
4004-H4U	i3-3220T	4GBx1	180G SSD	None	HD 2500	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	11/20/12
4004-J1U	i3-3220T	4GBx1	500G 7200	None	HD 2500	None	Intel 105	Serial	Stand	None	ES52	None	Win7 Pro64	12/25/12
4004-L2U	i5-3470T	4GBx2	180G SSD	DVD±RW	HD 2500	None	Intel 2230 + BT	None	None	Mount	ES52	None	Win7 Pro64	03/12/13



Positioning	<i>Essential business features, exceptional value</i>												Preloaded operating system
Processor	Intel® Core™ i3-3220T Processor (2 cores / 4 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller												Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation	Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology												Some: Windows 8 Pro 64-bit
Memory	Processor in LGA1155 socket												Preloaded applications (only some listed) - Windows 7 models
Graphics	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												• ThinkVantage® Product Recovery • ThinkVantage Power Manager • ThinkVantage Communication Utility • Lenovo® Message Center Plus • Lenovo SimpleTap® • Adobe® Reader® • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
DP dongle	Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>												- Windows 8 models
Disk	None												• Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Norton™ Studio • AccuWeather® • Evernote® • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
External optical	Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide												- All models
SATA controller	Hard Disk Drive / SATA 3.0Gb/s, 2.5" Wide												• ThinkVantage System Update • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™
Onboard SATA	Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in												Security
eSATA port	Serial ATA, SATA 3.0Gb/s, integrated in chipset												• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
Chipset	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar												• Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
Front ports	None												EPEAT™ Gold rating
Rear ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												ENERGY STAR® 5.2-compliant
PCIe Mini Card	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)												Cisco EnergyWise compatible
PCIe WLAN	One PCI Express® Mini Card slot												GREENGUARD® certified
Bluetooth	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1												RoHS-compliant
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												Supports ThinkVantage Technologies
Speaker	Internal speaker for business audio												For compatible accessories, please go to O-M72E sheet;
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												For Lenovo service upgrade options, please go to S-TC sheet
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
VESA mount	Supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												

Type-model	Processor	Memory ^b	SATA disk GB	External optical rpm	Graphics	Display-Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)	
4004-F1U	G640T	4GBx1	320G	7200	None	Intel HD	None	None	Stand	Mount	ES52	None	Win8 Pro64	10/23/12	
4004-G3U	i3-2120T	4GBx1	500G	7200	None	HD 2000	None	None	Stand	None	ES52	None	Win7 Pro64	10/23/12	
4004-G4U	i3-2120T	4GBx1	500G	7200	None	HD 2000	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	10/23/12
4004-G5U	i3-2120T	4GBx1	500G	7200	None	HD 2000	None	Intel 2230 + BT	None	Stand	None	ES52	None	Win7 Pro64	10/23/12
4004-G9U	i3-2120T	4GBx1	500G	7200	None	HD 2000	None	None	None	Mount	ES52	None	Win7 Pro64	10/23/12	
4004-H2U	i3-2120T	4GBx1	500G	7200	None	HD 2000	None	Intel 2230 + BT	None	None	Mount	ES52	None	Win7 Pro64	10/23/12
4004-H5U	G645T	4GBx1	500G	5400	None	Intel HD	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	11/20/12
4004-J2U	G645T	4GBx1	500G	7200	None	Intel HD	None	Intel 105	Serial	Stand	None	ES52	None	Win7 Pro64	12/25/12
4004-H6U	G1610T	4GBx1	500G	5400	None	Intel HD	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	01/22/13
4004-H7U	G2020T	4GBx1	500G	5400	None	Intel HD	None	Intel 105	None	Stand	None	ES52	None	Win7 Pro64	01/22/13

Positioning Processor	Essential business features, exceptional value Intel® Celeron® G1610T Processor (2 cores / 2 threads, 2.3GHz, 2MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium® G640T Processor (2 cores / 2 threads, 2.4GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Pentium G645T Processor (2 cores / 2 threads, 2.5GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120T Processor (2 cores / 4 threads, 2.6GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation													Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Power Manager• ThinkVantage Communication Utility• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller															
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)															
DP dongle	None															
Disk	SATA 3.0Gb/s, 2.5" Wide															
External optical	None															
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset															
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar															
eSATA port	None															
Chipset	Intel H61 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	Internal speaker for business audio															
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®															
Intel AMT	None															
Modem	None															
Security chip	None															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Floor Stand	Some: System floor stand for vertical orientation															
VESA mount	Some: Supports VESA 75mm and 100mm mount standard															
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU															
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box)															
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															
See footnotes for important warranty information US models announced Oct 23, 2012, Nov 20, 2012, Dec 25, 2012, or Jan 22, 2013															©Lenovo (MOSI1-38) February 2013	

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
0967-A1U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Pro 64	06/05/12
0967-A7U	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Pro 64	09/04/12


- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>								Preloaded operating system							
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller								Genuine Windows® 7 Professional 64							
Implementation	Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket								Ready to install applications (only some listed)							
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets								<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed)							
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>								<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 							
Disk	SATA 3.0Gb/s 7200 rpm															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset															
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar															
eSATA port	None															
Media reader	None															
Chipset	Intel H61 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)															
Audio	High Definition (HD) Audio, Realtek ALC662 codec															
PCIe WLAN ^a	None															
Bluetooth	None															
Speaker	Internal speaker for business audio															
IEEE 1394	None															
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®															
Intel AMT	None															
Modem	None															
Security chip	None															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Floor Stand	System floor stand for vertical orientation															
Power supply	240 watts, autosensing, active Power Factor Correction															
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 															
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk															
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1															
																
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															
 RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
0967-A2U	3x2	G860	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Pro 64	06/19/12
0967-A3U	3x2	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2000	None	Stand	None	None	Pro 64	06/19/12
0967-B2U	3x2	G640	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Pro 64	09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>								Preloaded operating system			
Processor	Intel® Pentium® G640 Processor (2 cores / 2 threads) , 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G860 Processor (2 cores / 2 threads) , 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology								Genuine Windows® 7 Professional 64			
Implementation									Ready to install applications (only some listed)			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066 or 1333MHz DDR3 memory controller</i>								<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>								Preloaded applications (only some listed)			
Disk	SATA 3.0Gb/s 7200 rpm								<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ^a	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo								Security			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo								<ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: - Padlock loop (in rear for opt padlock) - Security slot (in rear for optional Kensington® MicroSaver® cable) 			
Floor Stand	System floor stand for vertical orientation								<ul style="list-style-type: none"> • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
Power supply	240 watts, autosensing, active Power Factor Correction								Cisco EnergyWise compatible RoHS-compliant			
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 								Supports ThinkVantage Technologies			
Bay	Bay 1: 5.25", 1.6" high, access, std optical								For compatible accessories, please go to O-M72E sheet;			
Slot	Bay 2: 3.5", 1" high, no access, std disk								For Lenovo service upgrade options, please go to S-TC sheet			
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
0967-A8U	3x2	G870	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win8 Pro64	10/23/12
0967-A9U	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win8 Pro64	10/23/12
0967-B1U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win8 Pro64	10/23/12
0967-B6U	3x2	G645	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	10/23/12
0967-B3U	3x2	G860	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	10/23/12
0967-B4U	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win7 Pro64	10/23/12
0967-B5U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win7 Pro64	10/23/12
0967-B8U	3x2	G2120	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	12/04/12
0967-C1U	3x2	G2020	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	02/19/13
0967-B9U	3x2	G2120	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	02/19/13
0967-C2U	3x2	i7-3770	4GBx2 1600MHz	250G 7200	DVD±RW	HD 4000	None	Stand	None	None	Win7 Pro64	06/11/13
Positioning Processor	<i>Essential business features, exceptional value</i> Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz) Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G860 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1600MHz) Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology									Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in LGA1155 socket										Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Power Manager• ThinkVantage Communication Utility• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>											
Graphics	Intel HD Graphics, Intel HD Graphics 2500, or Intel HD Graphics 4000 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>											
Disk	SATA 3.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, active Power Factor Correction											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
<p>See footnotes for important warranty information US models announced October 23 or December 4, 2012 or February 19 or June 11, 2013</p>												


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
0958-A1U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	06/05/12
0958-A4U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	Essential business features, exceptional value										
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller										
Implementation	Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets										
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz										
Disk	SATA 3.0Gb/s 7200 rpm										
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset										
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar										
eSATA port	None										
Media reader	None										
Chipset	Intel H61 Express Chipset										
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D										
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)										
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)										
Audio	High Definition (HD) Audio, Realtek ALC662 codec										
PCIe WLAN ⁴	None										
Bluetooth	None										
Speaker	Internal speaker for business audio										
IEEE 1394	None										
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®										
Intel AMT	None										
Modem	None										
Security chip	None										
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo										
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo										
Power supply	280 watts with variable speed fan, manual switch										
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.3" W X 16.6" D X 15.3" H (with handle) 160mm W X 422mm D X 388mm H 20.7 lb (9.4 kg) in maximum configuration Handle on top front Highlighted optical drive button for easy access 										
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk										
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										
	Preloaded operating system Genuine Windows® 7 Professional 64										
	Ready to install applications (only some listed)										
	<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager 										
	Preloaded applications (only some listed)										
	<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Power Manager ThinkVantage Communication Utility View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) 										
	Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> Padlock loop (in rear for opt padlock) Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Serial port I/O control Individual USB port disablement <i>Chassis intrusion switch on selected model(s)</i> 										
	Cisco EnergyWise compatible										
	RoHS-compliant										
	Supports ThinkVantage Technologies										
	For compatible accessories, please go to O-M72E sheet;										
	For Lenovo service upgrade options, please go to S-TC sheet										

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
0958-A2U	3x3	G860	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Pro 64	06/19/12
0958-A3U	3x3	i3-2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2000	None	None	None	Pro 64	06/19/12
0958-A8U	3x3	G640	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Pro 64	09/04/12


- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G860 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066 or 1333MHz DDR3 memory controller</i>										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)	
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA) @60Hz; 1920x1200 (DVI-D) @60Hz</i>											
Disk Optical	SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, manual switch											
Machine	<ul style="list-style-type: none">• Business black color; metal case• 6.3" W X 16.6" D X 15.3" H (with handle)• 160mm W X 422mm D X 388mm H• 20.7 lb (9.4 kg) in maximum configuration• Handle on top front• Highlighted optical drive button for easy access											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk											
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	Security <ul style="list-style-type: none">• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Serial port I/O control• Individual USB port disablement• <i>Chassis intrusion switch on selected model(s)</i> Cisco EnergyWise compatible RoHS-compliant											
	Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet											

ThinkCentre M72e Tower (0958) - TopSeller (Win 8) - withdrawn

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
0958-A5U	3x3	G870	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win8 Pro64	10/23/12
0958-A6U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win8 Pro64	10/23/12
0958-A7U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win8 Pro64	10/23/12
0958-A9U	3x3	G860	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	10/23/12
0958-B1U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
0958-B2U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
0958-B3U	3x3	G645	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	10/23/12
0958-B4U	3x3	G2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	12/04/12
0958-B5U	3x3	G2120	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	02/19/13
0958-B6U	3x3	G2020	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	02/19/13
0958-B7U	3x3	i7-3770	4GBx2 1600MHz	250G 7200	Bay	DVD±RW	HD 4000	None	None	None	Win7 Pro64	06/11/13
Positioning Processor	Essential business features, exceptional value Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz) Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G860 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium C2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1600MHz) Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology									Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in LGA1155 socket										Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Power Manager• ThinkVantage Communication Utility• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>											
Graphics	Intel HD Graphics, Intel HD Graphics 2500, or Intel HD Graphics 4000 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>											
Disk Optical	SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, manual switch											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk											
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											



See footnotes for important warranty information

US models announced October 23 or December 4, 2012 or February 19 or June 11, 2013

©Lenovo

(MOSI1-29) June 2013

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Win7 Global	Win7 preload	Ann date (mm/dd/yy)
3675-A1U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Pro 64	06/05/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>						Preloaded operating system						
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology						Genuine Windows® 7 Professional 64						
Implementation	Processor in LGA1155 socket						Ready to install applications (only some listed)						
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets						<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 						
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz						Preloaded applications (only some listed)						
Disk	SATA 3.0Gb/s 7200 rpm						<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 						
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset												
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	Intel H61 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
PCIe WLAN ⁴	None												
Bluetooth	None												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts with variable speed fan, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk												
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available						<p>Security</p> <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 						
							<p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p>						
							<p>Supports ThinkVantage Technologies</p>						
							<p>For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet</p>						

Type-model	Processor	Memory ^b	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3264-D7U	G630T	4GBx1	320G 5400	DVD±RW	Intel HD	None	None	None	None	Mount	ES52	None	Pro 64 06/05/12
3264-A1U	i3-2120T	4GBx1	320G 5400	None	HD 2000	None	None	None	Stand	None	ES52	None	Pro 64 06/05/12
3264-A2U	G630T	2GBx1	320G 5400	None	Intel HD	None	None	None	Stand	None	ES52	None	Pro 64 06/05/12
3264-A3U	G530T	2GBx1	320G 5400	None	Intel HD	None	None	None	Stand	None	ES52	None	Pro 32 06/05/12
3264-A4U	G460	2GBx1	320G 5400	None	Intel HD	None	None	None	Stand	None	ES52	None	Pro 32 06/05/12
3264-A5U	i3-2120T	4GBx1	500G 5400	None	HD 2000	None	None	None	Stand	None	ES52	None	Pro 64 06/05/12
3264-P7U	i3-2120T	4GBx1	500G 7200	DVD±RW	HD 2000	None	Intel 105	None	None	Mount	ES52	None	Pro 64 06/19/12
3264-P8U	i3-2120T	4GBx1	500G 7200	DVD±RW	HD 2000	None	Intel 105	None	None	Mount	ES52	None	Prem 64 06/19/12
3264-N2U	i3-2120T	2GBx1	320G 7200	None	HD 2000	None	None	None	Stand	None	ES52	None	Pro 32 07/10/12
3264-N3U	i3-2120T	4GBx1	320G 7200	DVD±RW	HD 2000	None	None	None	None	Mount	ES52	None	Pro 32 07/10/12
3264-N4U	G630T	4GBx1	320G 7200	None	Intel HD	None	None	None	Stand	None	ES52	None	Pro 32 07/10/12

•3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Celeron® G460 Processor (1 core / 2 threads , 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G530T Processor (2 cores / 2 threads , 2.0GHz, 2MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Pentium® G630T Processor (2 cores / 2 threads , 2.3GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Core™ i3-2120T Processor (2 cores / 4 threads , 2.6GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller											Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64 Some: Genuine Windows 7 Home Premium 64		
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>													
DP dongle	None													
Disk	SATA 3.0Gb/s, 2.5" Wide													
External optical	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in													
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel H61 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Intel AMT	None													
Modem	None													
Security chip	None													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	Some: System floor stand for vertical orientation													
VESA mount	Some: Supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autotransformer, 87% PSU													
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box)													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Chassis Intrusion switch	Security Cable	Floor stand	VESA mount	ENERGY STAR 5.2	Win7 Global	Ann date (mm/dd/yy)	
3264-A7U	i5-3470T	4GBx1	500G	5400	DVD±RW	None	None	None	None	None	Mount	ES52	None	Pro 64 06/05/12	
3264-B7U	i5-3470T	4GBx1	500G	5400	None	None	None	None	None	Stand	None	ES52	None	Pro 64 06/05/12	
3264-P9U	i5-3470T	4GBx1	500G	7200	DVD±RW	None	Intel 105	None	None	None	Mount	ES52	None	Pro 64 06/19/12	
3264-Q1U	i5-3470T	4GBx1	500G	7200	DVD±RW	None	Intel 2230 + BT	None	None	None	Mount	ES52	None	Pro 64 06/19/12	
3264-Q2U	i5-3470T	4GBx1	500G	7200	None	None	Intel 2230 + BT	None	None	Stand	Mount	ES52	None	Pro 64 06/19/12	
3264-N5U	i5-3470T	4GBx1	500G	7200	None	None	None	None	None	Stand	None	ES52	None	Pro 64 07/10/12	
3264-V1U	i5-3470T	4GBx2	180G	SSD	DVD±RW	None	Intel 2230 + BT	None	Switch	Cable	None	Mount	ES52	None	Pro 64 11/06/12

•3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
DP dongle	None													
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 3.0Gb/s, 2.5" Wide													
External optical SATA controller	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in													
Onboard SATA eSATA port	Serial ATA, SATA 3.0Gb/s, integrated in chipset One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar													
Chipset	Intel H61 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Intel AMT	None													
Modem	None													
Security chip	None													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	Some: System floor stand for vertical orientation													
VESA mount	Some: Supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box)											Security <ul style="list-style-type: none">• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• Chassis intrusion switch on selected model(s)		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet											Supports ThinkVantage Technologies		

Type-model	Processor	Memory ^b	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Win7 preload	Ann date (mm/dd/yy)
3264-R3U	G460	2GBx1	8G SSD	None	Intel HD	None	None	None	Stand	Mount	ES52	None	Emb 32 07/10/12
3264-R6U	G640T	4GBx1	8G SSD	None	Intel HD	None	None	None	None	Mount	ES52	None	Emb 32 09/04/12
3264-AMU	G640T	2GBx1	8G SSD	None	Intel HD	None	Intel 2230 + BT	None	Stand	None	ES52	None	Emb 32 03/05/13
3264-YSU	G2020T	2GBx1	8G SSD	None	Intel HD	None	Intel 2230 + BT	None	Stand	None	ES52	None	Emb 32 06/11/13
3264-YTU	G470	2GBx1	8G SSD	None	Intel HD	None	None	None	Stand	None	ES52	None	Emb 32 06/11/13

•3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Pentium® G640T Processor (2 cores / 2 threads, 2.4GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Pentium G2020T Processor (2 cores / 2 threads, 2.5GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller										Preloaded operating system Genuine Windows® 7 Embedded 32															
Implementation	Processor in LGA1155 socket										Preloaded applications (only some listed) <ul style="list-style-type: none"> • Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player 															
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>																									
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA) @60Hz</i>																									
DP dongle	None																									
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide																									
External optical	None																									
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																									
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar																									
eSATA port	None																									
Chipset	Intel H61 Express Chipset																									
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																									
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)																									
PCIe Mini Card	One PCI Express® Mini Card slot																									
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																									
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																									
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																									
Speaker	Internal speaker for business audio																									
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																									
Intel AMT	None																									
Modem	None																									
Security chip	None																									
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																									
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																									
Floor Stand	<i>Some:</i> System floor stand for vertical orientation																									
VESA mount	<i>Some:</i> Supports VESA 75mm and 100mm mount standard																									
Power supply	65 watts AC/DC adapter, autoselecting, 87% PSU																									
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 																									
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																									
Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement 																										
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant GREENGUARD® certified RoHS-compliant																										
Supports ThinkVantage Technologies																										
For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																										

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Key- board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3264-Q5U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-R1U	i5-3470T	4GBx1	500G 7200	None	HD 2500	Intel 2230 + BT	None	Stand	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-R2U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-R8U	i3-3220T	4GBx1	320G 7200	None	HD 2500	None	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-R9U	i3-3220T	4GBx1	320G 7200	DVD±RW	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-S1U	i5-3470T	4GBx1	320G 7200	DVD±RW	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-S2U	i5-3470T	4GBx1	320G 7200	None	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-T2U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	None	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-T3U	i3-3220T	4GBx1	500G 7200	None	HD 2500	None	None	None	None	ES52	USB	None	Win7 Pro64	10/23/12
3264-T4U	i3-3220T	4GBx1	500G 7200	None	HD 2500	Intel 105	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-T5U	i5-3470T	4GBx1	500G 7200	None	HD 2500	None	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-T7U	i5-3470T	4GBx1	500G 5400	None	HD 2500	None	None	Stand	None	ES52	USB	None	Win7 Pro64	10/23/12
3264-T9U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	Intel 105	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-U1U	i5-3470T	4GBx1	500G 7200	DVD±RW	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-U2U	i5-3470T	4GBx1	500G 7200	None	HD 2500	Intel 2230 + BT	None	Stand	None	ES52	USB	None	Win7 Pro64	10/23/12
3264-U3U	i5-3470T	4GBx1	500G 7200	None	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-YRU	i3-3220T	4GBx1	500G 7200	None	HD 2500	Intel 105	None	None	Mount	ES52	2.4G	None	Win8 Pro64	05/28/13

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i3-3220T Processor (2 cores / 4 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system <i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 8 Pro 64-bit
Implementation														Preloaded applications (only some listed) - Windows 7 models
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>													Windows 8 models
DP dongle	None													
Disk	SATA 3.0Gb/s, 2.5" Wide													
External optical	<i>Some:</i> Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in													
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel H61 Express Chipset													All models
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	<i>Some:</i> Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)													
PCIe Mini Card	<i>Some:</i> One PCI Express® Mini Card slot													
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Intel AMT	None													
Modem	None													
Security chip	None													
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black													
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black													
Floor Stand	<i>Some:</i> System floor stand for vertical orientation													
VESA mount	<i>Some:</i> Supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													Supports ThinkVantage Technologies
														For compatible accessories, please go to O-M72E sheet;
														For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US models announced October 23, 2012 or May 28, 2013

©Lenovo
(MOSI1-34) June 2013

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Key- board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3264-R7U	G640T	4GBx1	320G 7200	None	Intel HD	None	None	None	None	Mount	ES52	USB	None	Win8 Pro64	10/23/12
3264-T1U	G645T	4GBx1	500G 5400	DVD±RW	Intel HD	None	None	None	Stand	Mount	ES52	USB	None	Win7 Pro64	10/23/12
3264-T8U	G645T	2GBx1	500G 5400	None	Intel HD	None	None	None	Stand	None	ES52	USB	None	Win7 Pro64	10/23/12
3264-AEU	G645T	4GBx1	500G 7200	None	Intel HD	None	Intel 105	Serial	None	Mount	ES52	USB	None	Win7 Pro64	12/25/12
3264-V2U	G2020T	4GBx1	500G 5400	None	Intel HD	None	Intel 105	None	Stand	None	ES52	USB	None	Win7 Pro64	01/22/13
3264-V3U	G1610T	4GBx1	500G 5400	None	Intel HD	None	Intel 105	None	Stand	None	ES52	USB	None	Win7 Pro64	01/22/13
3264-YQU	G2020T	4GBx1	500G 7200	None	Intel HD	None	Intel 105	None	None	Mount	ES52	2.4G	None	Win8 Pro64	05/28/13

Positioning Processor	<p><i>Ultimate security, stability, and manageability for the enterprise</i></p> <p>Intel® Celeron® G1610T Processor (2 cores / 2 threads, 2.3GHz, 2MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium® G640T Processor (2 cores / 2 threads, 2.4GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller</p> <p>Intel Pentium G645T Processor (2 cores / 2 threads, 2.5GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G2020T Processor (2 cores / 2 threads, 2.5GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system
Implementation		Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Memory		Some: Windows 8 Pro 64-bit
Graphics	<p>Intel HD Graphics in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</p>	Preloaded applications (only some listed)
DP dongle	None	- Windows 7 models
Disk	SATA 3.0Gb/s, 2.5" Wide	• ThinkVantage® Product Recovery
External optical	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in	• ThinkVantage Power Manager
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset	• ThinkVantage Communication Utility
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar	• Lenovo® SimpleTap
eSATA port	None	• Adobe® Reader®
Chipset	Intel H61 Express Chipset	• Corel® Burn.Now™ (DVD±RW)
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	• Corel DVD MovieFactory® (DVD±RW)
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)	- Windows 8 models
PCIe Mini Card	One PCI Express® Mini Card slot	• Lenovo Support
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1	• Lenovo Companion
Bluetooth	None	• Lenovo Cloud Storage
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	• Norton™ Studio
Speaker	Internal speaker for business audio	• AccuWeather
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®	• Evernote®
Intel AMT	None	• Cyberlink Power2Go (DVD±RW)
Modem	None	• Cyberlink PowerProducer (DVD±RW)
Security chip	None	- All models
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	• ThinkVantage System Update
Mouse	Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black	• Lenovo Solution Center
Floor Stand	Some: Enhanced Optical USB Mouse, black, Lenovo logo	• View Management Utility
VESA mount	Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black	• Norton Internet Security (30 days of virus definitions)
Power supply	Some: System floor stand for vertical orientation	• Microsoft® Office preloaded; purchase a product key to activate
Machine	Some: Supports VESA 75mm and 100mm mount standard 65 watts AC/DC adapter, autosensing, 87% PSU	• Skype™
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	Security
		• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
		• Power-on password
		• Administrator password
		• Hard disk password
		• Boot sequence control
		• Boot without keyboard and mouse
		• Individual USB port disablement
		EPEAT™ Gold rating
		ENERGY STAR® 5.2-compliant
		Cisco EnergyWise compatible
		GREENGUARD® certified
		RoHS-compliant
		Supports ThinkVantage Technologies
		For compatible accessories, please go to O-M72E sheet;
		For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3267-A1U	i5-3470T	4GBx1 1600MHz	320G 5400	DVD±RW	HD 2500	None	None	None	Mount	ES52	G P	Pro 64	06/05/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket							Preloaded operating system Genuine Windows® 7 Professional 64																		
Implementation	Processor in LGA1155 socket							Ready to install applications (only some listed)																		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)							<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager Preloaded applications (only some listed)																		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>							<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Power Manager ● ThinkVantage Communication Utility ● View Management Utility ● Lenovo Solution Center ● Lenovo Message Center Plus ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 																		
DP dongle	None																									
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm																									
External optical	Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in																									
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																									
Onboard SATA eSATA port	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar																									
Chipset	Intel H61 Express Chipset																									
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																									
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)																									
PCIe Mini Card	One PCI Express® Mini Card slot																									
PCIe WLAN ⁴	None																									
Bluetooth	None																									
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																									
Speaker	Internal speaker for business audio																									
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																									
Intel AMT	None																									
Modem	None																									
Security chip	None																									
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																									
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																									
Floor Stand	None																									
VESA mount	Supports VESA 75mm and 100mm mount standard																									
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU																									
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 7.1" W X 7.2" D X 1.4" H ● 179mm W X 182mm D X 34.5mm H ● 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 																									
Security																										
<ul style="list-style-type: none"> ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement 																										
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																										
Supports ThinkVantage Technologies																										
For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																										
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																									

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	PCIe Mini Card WLAN / BT	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3267-A2U	G460	2GBx1	8G SSD	None	Intel HD	None	None	Serial	None	None	ES52	G P	Emb 32	07/10/12
3267-A5U	G465	2GBx1	8G SSD	None	Intel HD	None	None	Serial	None	None	ES52	G P	Emb 32	01/08/13
3267-A6U	G465	2GBx1	8G SSD	None	Intel HD	None	Intel 105	Serial	None	None	ES52	G P	Emb 32	03/12/13
3267-A7U	G470	2GBx1	8G SSD	None	Intel HD	None	Intel 105	Serial	None	None	ES52	G P	Emb 32	07/09/13
3267-A8U	G470	2GBx1	8G SSD	None	Intel HD	None	None	Serial	None	None	ES52	G P	Emb 32	07/09/13

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G465 Processor (1 core / 2 threads, 1.9GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller Processor in LGA1155 socket											Preloaded operating system
												Genuine Windows® 7 Embedded 32
Implementation												Preloaded applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller											• Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz											
DP dongle	None											
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide											
External optical	None											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar											
eSATA port	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)											
PCIe Mini Card	One PCI Express® Mini Card slot											
PCIe WLAN ⁴	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1											
Bluetooth	None											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	None											
Mouse	None											
Floor Stand	None											
VESA mount	None											
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											Security
												<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement
												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant GREENGUARD® certified RoHS-compliant
												Supports ThinkVantage Technologies
												For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	Display- Port dongle	Optional port	Floor stand	VESA mount	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3267-A3U	i5-3470T	4GBx1 1600MHz	320G 5400	DVD±RW	HD 2500	None	None	None	Mount	ES52	G P	Win8 Pro64	10/23/12
3267-A4U	i5-3470T	4GBx1 1600MHz	320G 5400	DVD±RW	HD 2500	None	None	None	Mount	ES52	G P	Win7 Pro64	10/23/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit															
Implementation											Preloaded applications (only some listed) - Windows 7 models															
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage Power Manager ● ThinkVantage Communication Utility ● Lenovo® Message Center Plus ● Lenovo SimpleTap ● Adobe® Reader® ● Windows Live™ Essentials ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 															
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution vary by processor (i5 CPU supports max: 2560x2048)</i>										Windows 8 models															
DP dongle	None										<ul style="list-style-type: none"> ● Lenovo Support ● Lenovo Companion ● Lenovo Cloud Storage ● Norton™ Studio ● AccuWeather ● Evernote® ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) 															
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm										All models															
External optical	Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in										<ul style="list-style-type: none"> ● ThinkVantage System Update ● Lenovo Solution Center ● View Management Utility ● Norton Internet Security (30 days of virus definitions) ● Microsoft® Office preloaded; purchase a product key to activate ● Skype™ 															
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																									
Onboard SATA	One SATA cable (1-drop to device), one SATA 3.0Gb/s connector on planar																									
eSATA port	None																									
Chipset	Intel H61 Express Chipset																									
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																									
Rear ports	Three USB 2.0 (external ODD occupies dedicated USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial on selected models)																									
PCIe Mini Card	One PCI Express® Mini Card slot																									
PCIe WLAN ⁴	None																									
Bluetooth	None																									
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																									
Speaker	Internal speaker for business audio																									
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																									
Intel AMT	None																									
Modem	None																									
Security chip	None																									
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																									
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																									
Floor Stand	None																									
VESA mount	Supports VESA 75mm and 100mm mount standard																									
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU																									
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 7.1" W X 7.2" D X 1.4" H ● 179mm W X 182mm D X 34.5mm H ● 4.6 lb (2.1 kg) in maximum configuration (not including External Optical Box) 																									
Security																										
<ul style="list-style-type: none"> ● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Individual USB port disablement 																										
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																										
Supports ThinkVantage Technologies																										
For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																										
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																									

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3598-D4U	3x2	G630	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Pro 64	06/05/12
3598-C4U	3x2	G850	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Pro 64	06/05/12
3598-A7U	3x2	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2000	None	Stand	None	None	Pro 64	06/05/12
3598-F3U	3x2	G630	2GBx1 1600MHz	250G 7200	DVD±RW	Intel HD	None	Stand	None	None	Pro 64	07/10/12

•3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)	
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz										Security <ul style="list-style-type: none">• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Serial port I/O control• Individual USB port disablement• Chassis intrusion switch on selected model(s)	
Disk Optical	SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										Cisco EnergyWise compatible RoHS-compliant	
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset										Supports ThinkVantage Technologies	
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar										For compatible accessories, please go to O-M72E sheet;	
eSATA port	None										For Lenovo service upgrade options, please go to S-TC sheet	
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, active Power Factor Correction											
Machine	<ul style="list-style-type: none">• Business black color; metal case• 13.2" W X 15.0" D X 3.9" H• 335mm W X 382mm D X 101mm H• 14.6 lb (6.6 kg) in maximum configuration• Highlighted optical drive button for easy access											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3598-A5U	3x2	i5-3550	4Gb×1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Pro 64	06/05/12
3598-E3U	3x2	i5-3570	4Gb×1 1600MHz	250G 7200	DVD±RW	HD 2500	None	Stand	None	None	Pro 32	06/05/12

•3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>							Preloaded operating system																					
Processor	Intel® Core™ i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology							<i>Some: Genuine Windows® 7 Professional 32</i>																					
Implementation	Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket							<i>Some: Genuine Windows 7 Professional 64</i>																					
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets							Ready to install applications (only some listed)																					
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>							<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed)																					
Disk	SATA 3.0Gb/s 7200 rpm							<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 																					
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																												
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																												
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar																												
eSATA port	None																												
Media reader	None																												
Chipset	Intel H61 Express Chipset																												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																												
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D																												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)																												
Audio	High Definition (HD) Audio, Realtek ALC662 codec																												
PCIe WLAN ⁴	None																												
Bluetooth	None																												
Speaker	Internal speaker for business audio																												
IEEE 1394	None																												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																												
Intel AMT	None																												
Modem	None																												
Security chip	None																												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																												
Floor Stand	System floor stand for vertical orientation																												
Power supply	240 watts, autosensing, active Power Factor Correction																												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 																												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk																												
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1																												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																												
Cisco EnergyWise compatible RoHS-compliant																													
Supports ThinkVantage Technologies																													
For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																													


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3598-F9U	3x2	G870	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win8 Pro64	10/23/12
3598-G9U	3x2	G640	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	10/23/12
3598-H1U	3x2	G870	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	10/23/12
3598-H2U	3x2	G640	2GBx1 1600MHz	250G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	10/23/12
3598-H3U	3x2	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win7 Pro64	10/23/12
3598-K2U	3x2	G2120	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	None	None	Win7 Pro64	12/04/12
3598-PEU	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	None	None	Win7 Pro64	06/25/13

• 3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation												Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Power Manager• ThinkVantage Communication Utility• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller											
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, HDCP, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz											
Disk Optical	SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, active Power Factor Correction											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 											
Bay	 Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
Cisco EnergyWise compatible RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3660-B6U	3x2	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2000	None	Stand	ES52	None	Pro 64	06/05/12

•3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>							Preloaded operating system Genuine Windows® 7 Professional 64																					
Processor	Intel® Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket							Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager																					
Implementation								Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)																					
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i>																												
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA) @60Hz; 1920x1200 (DVI-D) @60Hz</i>																												
Disk	SATA 3.0Gb/s 7200 rpm																												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																												
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																												
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar																												
eSATA port	None																												
Media reader	None																												
Chipset	Intel H61 Express Chipset																												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																												
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D																												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)																												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																												
PCIe WLAN ⁴	None																												
Bluetooth	None																												
Speaker	Internal speaker for business audio																												
IEEE 1394	None																												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																												
Intel AMT	None																												
Modem	None																												
Security chip	None																												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																												
Floor Stand	System floor stand for vertical orientation																												
Power supply	240 watts, autosensing, 85% PSU																												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 																												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk																												
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1																												
																													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																												
Security <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 																													
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																													
Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet																													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3660-C1U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	None	Pro 32	06/05/12

•3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>							Preloaded operating system Genuine Windows® 7 Professional 32				
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket							Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager				
Implementation								Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)				
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets											
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>											
Disk	SATA 3.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosingling, 85% PSU											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3660-D3U	3x2	G645	2GBx1 1600MHz	250G 7200	DVD±RW	Intel HD	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-D4U	3x2	G870	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-E2U	3x2	i3-2130	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2000	None	Stand	ES52	None	Win7 Pro64	10/23/12
3660-E3U	3x2	G2020	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	Stand	ES52	None	Win7 Pro64	01/22/13

•3-year limited warranty

Positioning Processor	<i>Essential business features, exceptional value</i> Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket									Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation										Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Power Manager• ThinkVantage Communication Utility• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>											
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>											
Disk	SATA 3.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3660-D5U	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-D6U	3x2	i3-3240	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-D7U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-D8U	3x2	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	HD 2500	None	Stand	ES52	None	Win8 Pro64	10/23/12
3660-D9U	3x2	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	HD 7450	None	Stand	ES52	None	Win8 Pro64	10/23/12

• 3-year limited warranty

Positioning Processor	<p><i>Essential business features, exceptional value</i></p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system
Implementation		Windows® 8 Pro 64-bit
Memory	<p>16GB max, UDIMM, PC3-12800 1600MHz DDR3, two 240-pin DIMM sockets</p>	Preloaded applications (only some listed)
Graphics	<p><i>Some:</i> Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11 one VGA, one DVI-D, supports dual independent display;</p> <p><i>Maximum resolution:</i> 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</p> <p><i>Some:</i> AMD Radeon™ HD 7450, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 25 watts;</p> <p><i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors</p>	<ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
Disk	<p>SATA 3.0Gb/s 7200 rpm</p>	Security
Optical	<p>Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive</p>	<ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s)
SATA controller	<p>Serial ATA, SATA 3.0Gb/s, integrated in chipset</p>	
Onboard SATA	<p>Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar</p>	
eSATA port	<p>None</p>	
Media reader	<p>None</p>	
Chipset	<p>Intel H61 Express Chipset</p>	
Front ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>	
Rear ports	<p>Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D</p>	
Rear audio ports	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)</p>	
Internal connector	<p>Two USB 2.0 planar conn (1 used; one open for additional USB devices)</p>	
Audio	<p>High Definition (HD) Audio, Realtek® ALC662 codec</p>	
PCIe WLAN ⁴	<p>None</p>	
Bluetooth	<p>None</p>	
Speaker	<p>Internal speaker for business audio</p>	
IEEE 1394	<p>None</p>	
Ethernet	<p>Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®</p>	
Intel AMT	<p>None</p>	
Modem	<p>None</p>	
Security chip	<p>None</p>	
Keyboard	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p>	
Mouse	<p>Enhanced Optical USB Mouse, black, Lenovo logo</p>	
Floor Stand	<p>System floor stand for vertical orientation</p>	
Power supply	<p>240 watts, autosensing, 85% PSU</p>	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.2" W X 15.0" D X 3.9" H • 335mm W X 382mm D X 101mm H • 14.6 lb (6.6 kg) in maximum configuration • Highlighted optical drive button for easy access 	
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p>	
Slot	<p>Bay 2: 3.5", 1" high, no access, std disk</p>	
	<p>Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max)</p>	
	<p>Slot 2: Low Profile, PCIe 2.0 x1</p>	
	<p>Slot 3: Low Profile, PCIe 2.0 x1</p>	
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet


Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2 Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3664-A1U	3x2	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	Switch	Stand	ES52	G P	Pro 64
3664-A2U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	G P	Pro 64
3664-A4U	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	Switch	Stand	ES52	G P	Pro 64
3664-A6U	3x2	i3-3240	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	Switch	Stand	ES52	G P	Pro 64
											05/28/13

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket								Preloaded operating system Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Implementation	Memory 16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets										
Memory	Graphics Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz										
Disk Optical SATA controller	Disk SATA 3.0Gb/s 7200 rpm Optical Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive SATA controller Serial ATA, SATA 3.0Gb/s, integrated in chipset										
Onboard SATA eSATA port Media reader	Onboard SATA Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar eSATA port None Media reader None										
Chipset	Intel H61 Express Chipset										
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										
Rear ports	Rear ports Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D										
Rear audio ports	Rear audio ports Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)										
Internal connector	Internal connector Two USB 2.0 planar conn (1 used; one open for additional USB devices)										
Audio	Audio High Definition (HD) Audio, Realtek® ALC662 codec										
PCIe WLAN ^d	None										
Bluetooth	None										
Speaker	Speaker Internal speaker for business audio										
IEEE 1394	None										
Ethernet	Ethernet Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®										
Intel AMT	Intel AMT None										
Modem	Modem None										
Security chip	Security chip None										
Keyboard	Keyboard Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo										
Mouse	Mouse Enhanced Optical USB Mouse, black, Lenovo logo										
Floor Stand	Floor Stand System floor stand for vertical orientation										
Power supply	Power supply 240 watts, autosensing, 85% PSU										
Machine	Machine <ul style="list-style-type: none">• Business black color; metal case• 13.2" W X 15.0" D X 3.9" H• 335mm W X 382mm D X 101mm H• 14.6 lb (6.6 kg) in maximum configuration• Highlighted optical drive button for easy access										
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk										
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1										
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3664-A3U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	Switch	Stand	ES52	G P	Win8 Pro64	10/23/12
3664-A5U	3x2	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	Stand	ES52	G P	Win7 Pro64	10/23/12

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Essential business features, exceptional value</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket								Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation	Processor in LGA1155 socket								Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">● ThinkVantage® Product Recovery● ThinkVantage Power Manager● ThinkVantage Communication Utility● Lenovo® Message Center Plus● Lenovo SimpleTap● Adobe® Reader®● Windows Live™ Essentials● Corel® Burn.Now™ (DVD±RW)● Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">● Lenovo Support● Lenovo Companion● Lenovo Cloud Storage● Norton™ Studio● AccuWeather● Evernote®● Cyberlink Power2Go (DVD±RW)● Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">● ThinkVantage System Update● Lenovo Solution Center● View Management Utility● Norton Internet Security (30 days of virus definitions)● Microsoft® Office preloaded; purchase a product key to activate● Skype™			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets											
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>											
Disk	SATA 3.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosingling, 85% PSU											
Machine	<ul style="list-style-type: none">● Business black color; metal case● 13.2" W X 15.0" D X 3.9" H● 335mm W X 382mm D X 101mm H● 14.6 lb (6.6 kg) in maximum configuration● Highlighted optical drive button for easy access											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk											
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	Security <ul style="list-style-type: none">● One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)● Power-on password● Administrator password● Hard disk password● Boot sequence control● Boot without keyboard and mouse● Serial port I/O control● Individual USB port disablement● Chassis intrusion switch on selected model(s)											
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet											

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3597-A2U	3x3	G630	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	Intel HD	None	None	None	Pro 32	06/05/12
3597-C4U	3x3	i3-2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2000	None	None	None	Pro 64	06/05/12
3597-C5U	3x3	G850	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Pro 64	06/05/12
3597-E4U	3x3	G630	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	Intel HD	None	None	None	Pro 64	07/10/12


•3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>										Preloaded operating system	
Processor	Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology										<i>Some: Genuine Windows® 7 Professional 32</i>	
	Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology										<i>Some: Genuine Windows 7 Professional 64</i>	
Implementation	Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Ready to install applications (only some listed)	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>										<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 	
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>										Preloaded applications (only some listed)	
Disk	SATA 3.0Gb/s 7200 rpm										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, manual switch											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk											
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	<p>Security</p> <ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 											
	Cisco EnergyWise compatible RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet											


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3597-D4U	3x3	i5-3570	4GBx1 1600MHz	250G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 32	06/05/12
3597-C3U	3x3	i5-3550	4GBx2 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	06/05/12
3597-E3U	3x3	i5-3470	2GBx2 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	07/10/12
3597-E2U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	07/10/12
3597-E9U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Pro 64	09/04/12

•3-year limited warranty

Positioning Processor	<p><i>Essential business features, exceptional value</i></p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system
Implementation	<p>Some: Genuine Windows® 7 Professional 32</p> <p>Some: Genuine Windows 7 Professional 64</p>	Ready to install applications (only some listed)
Memory	<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 	Preloaded applications (only some listed)
Graphics	<p>Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i></p>	<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Disk	<p>SATA 3.0Gb/s 7200 rpm</p>	Security
Optical	<p>Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive</p>	
SATA controller	<p>Serial ATA, SATA 3.0Gb/s, integrated in chipset</p>	
Onboard SATA	<p>Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar</p>	
eSATA port	<p>None</p>	
Media reader	<p>None</p>	
Chipset	<p>Intel H61 Express Chipset</p>	
Front ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>	
Rear ports	<p>Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D</p>	
Rear audio ports	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)</p>	
Internal connector	<p>Two USB 2.0 planar conn (1 used; one open for additional USB devices)</p>	
Audio	<p>High Definition (HD) Audio, Realtek® ALC662 codec</p>	
PCIe WLAN ⁴	<p>None</p>	
Bluetooth	<p>None</p>	
Speaker	<p>Internal speaker for business audio</p>	
IEEE 1394	<p>None</p>	
Ethernet	<p>Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®</p>	
Intel AMT	<p>None</p>	
Modem	<p>None</p>	
Security chip	<p>None</p>	
Keyboard	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p>	
Mouse	<p>Enhanced Optical USB Mouse, black, Lenovo logo</p>	
Power supply	<p>280 watts with variable speed fan, manual switch</p>	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 	
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk</p>	
Slot	<p>Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1</p>	
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>	




Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3597-F4U	3x3	i3-2130	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2000	None	None	None	Win7 Pro64	10/23/12
3597-F5U	3x3	i5-3570	4GBx2 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
3597-F6U	3x3	G870	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	10/23/12
3597-F7U	3x3	i5-3470	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
3597-F8U	3x3	G640	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	10/23/12
3597-F9U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
3597-G1U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	None	Win7 Pro64	10/23/12
3597-G2U	3x3	G2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	None	None	Win7 Pro64	12/04/12
Positioning Processor	<p><i>Essential business features, exceptional value</i></p> <p>Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>											
Implementation	<p>Preloaded operating system</p> <p>Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo® Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 											
Memory	<p>16GB max, UDIMM, PC3-12800 1600MHz DDR3, two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i></p>											
Graphics	<p>Intel HD Graphics, Intel HD Graphics 2000, or Intel HD Graphics 2500 in processor, uses main memory, HDCP, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i></p>											
Disk	<p>SATA 3.0Gb/s 7200 rpm</p>											
Optical	<p>Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive</p>											
SATA controller	<p>Serial ATA, SATA 3.0Gb/s, integrated in chipset</p>											
Onboard SATA	<p>Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar</p>											
eSATA port	<p>None</p>											
Media reader	<p>None</p>											
Chipset	<p>Intel H61 Express Chipset</p>											
Front ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>											
Rear ports	<p>Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D</p>											
Rear audio ports	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)</p>											
Internal connector	<p>Two USB 2.0 planar conn (1 used; one open for additional USB devices)</p>											
Audio	<p>High Definition (HD) Audio, Realtek® ALC662 codec</p>											
PCIe WLAN ⁴	<p>None</p>											
Bluetooth	<p>None</p>											
Speaker	<p>Internal speaker for business audio</p>											
IEEE 1394	<p>None</p>											
Ethernet	<p>Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®</p>											
Intel AMT	<p>None</p>											
Modem	<p>None</p>											
Security chip	<p>None</p>											
Keyboard	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p>											
Mouse	<p>Enhanced Optical USB Mouse, black, Lenovo logo</p>											
Power supply	<p>280 watts with variable speed fan, manual switch</p>											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 											
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk</p>											
Slot	<p>Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1</p>											
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>											




Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3655-B6U	3x3	i3-2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2000	None	ES52	None	Pro 64	06/05/12
3655-D3U	3x3	G860	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	ES52	None	Pro 64	07/10/12

•3-year limited warranty

Positioning Processor	<i>Essential business features, exceptional value</i> Intel® Pentium® G860 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket							Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket							Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets; <i>System automatically clocks down for processors with 1333MHz DDR3 memory controller</i>							Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>							
Disk	SATA 3.0Gb/s 7200 rpm							
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive							
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset							
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar							
eSATA port	None							
Media reader	None							
Chipset	Intel H61 Express Chipset							
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)							
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D							
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)							
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)							
Audio	High Definition (HD) Audio, Realtek® ALC662 codec							
PCIe WLAN ⁴	None							
Bluetooth	None							
Speaker	Internal speaker for business audio							
IEEE 1394	None							
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®							
Intel AMT	None							
Modem	None							
Security chip	None							
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo							
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo							
Power supply	280 watts with variable speed fan, autosensing, 85% PSU							
Machine	<ul style="list-style-type: none">• Business black color; metal case• 6.3" W X 16.6" D X 15.3" H (with handle)• 160mm W X 422mm D X 388mm H• 20.7 lb (9.4 kg) in maximum configuration• Handle on top front• Highlighted optical drive button for easy access							
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk							
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1							
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available							
	 A diagram of a drive bay. At the top, there is a rectangular slot labeled "optical". Below it, there is a smaller rectangular slot labeled "disk". To the right of the "disk" slot, there is a small number "(2)" indicating a second drive slot.							
	EEPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant							
	Supports ThinkVantage Technologies							
	For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet							


Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Media reader	Chassis intr switch	ENERGY STAR 5.2	Global	Win7 preload	Ann date (mm/dd/yy)
3655-C1U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	ES52	None	Pro 32	06/05/12
3655-D2U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	None	ES52	None	Pro 64	07/10/12
3655-F2U	3x4	i7-3770	4GBx2 1600MHz	1TB 7200	Bay	DVD±RW	HD 4000	Media	Switch	ES52	None	Pro 64	11/06/12

•3-year limited warranty

Positioning Processor	Essential business features, exceptional value Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none">Rescue and Recovery™Password Manager
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">ThinkVantage® Product RecoveryThinkVantage System UpdateThinkVantage Power ManagerThinkVantage Communication UtilityView Management UtilityLenovo Solution CenterLenovo Message Center PlusLenovo SimpleTapNorton™ Internet Security (30 days of virus definitions)Adobe® Reader®Skype™ for WindowsWindows Live™ EssentialsMicrosoft® Office preloaded; purchase a product key to activateCorel® Burn.Now™ (DVD±RW)Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz											
Disk Optical	SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	Some: 9-in-1 media reader, internal USB 2.0											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none">Business black color; metal case6.3" W X 16.6" D X 15.3" H (with handle)160mm W X 422mm D X 388mm H20.7 lb (9.4 kg) in maximum configurationHandle on top frontHighlighted optical drive button for easy access											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", 1" high, no access, std disk Bay 4: 1.5", .35" high, access, opt reader*											
Slot	*bay only available on models with media reader installed Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											
Limited Warranty	 3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3655-D8U	3x3	G645	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	Intel HD	None	ES52	None	Win8 Pro64	10/23/12
3655-D9U	3x3	G870	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	ES52	None	Win8 Pro64	10/23/12
3655-E8U	3x3	i3-2130	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2000	None	ES52	None	Win7 Pro64	10/23/12
3655-F1U	3x3	G870	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	ES52	None	Win7 Pro64	10/23/12
3655-F3U	3x3	G2020	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	Intel HD	None	ES52	None	Win7 Pro64	01/22/13

•3-year limited warranty

Positioning Processor	<p><i>Essential business features, exceptional value</i></p> <p>Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p>	Preloaded operating system
Implementation		<i>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</i>
Memory	<p><i>Some: Windows 8 Pro 64-bit</i></p> <p>16GB max, UDIMM, PC3-12800 1600MHz DDR3, two 240-pin DIMM sockets; System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</p>	Preloaded applications (only some listed)
Graphics	<p>Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i></p>	- Windows 7 models
Disk Optical SATA controller Onboard SATA eSATA port Media reader	<p>SATA 3.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive Serial ATA, SATA 3.0Gb/s, integrated in chipset Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar</p>	- Windows 8 models
Chipset	<p>Intel H61 Express Chipset</p>	All models
Front ports Rear ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D</p>	<ul style="list-style-type: none"> • ThinkVantage System Update • Lenovo Solution Center • View Management Utility • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Skype™
Rear audio ports Internal connector	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm) Two USB 2.0 planar conn (1 used; one open for additional USB devices)</p>	Security
Audio PCIe WLAN ^a Bluetooth Speaker IEEE 1394	<p>High Definition (HD) Audio, Realtek® ALC662 codec None None Internal speaker for business audio None</p>	<ul style="list-style-type: none"> • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s)
Ethernet Intel AMT Modem Security chip	<p>Gigabit ethernet port, Realtek RTL8111E, Wake on LAN® None None None</p>	<p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p>
Keyboard Mouse Power supply	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 280 watts with variable speed fan, autosensing, 85% PSU</p>	<p>Supports ThinkVantage Technologies For compatible accessories, please go to O-M72E sheet; For Lenovo service upgrade options, please go to S-TC sheet</p>
Machine Bay Slot Limited Warranty	<p>• Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access</p> <p>Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk</p> <p>Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1</p> <p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>	

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3655-E5U	3x3	i7-3770	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	HD 7450	None	ES52	None	Win8 Pro64	10/23/12
3655-E1U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Win8 Pro64	10/23/12
3655-E2U	3x3	i3-3240	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Win8 Pro64	10/23/12
3655-E3U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Win8 Pro64	10/23/12
3655-E4U	3x3	i5-3570	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Win8 Pro64	10/23/12
3655-E9U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	None	Win7 Pro64	10/23/12


•3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>										Preloaded operating system		
Processor	Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										<i>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</i> <i>Some: Windows 8 Pro 64-bit</i>		
Implementation											Preloaded applications (only some listed)		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets										- Windows 7 models		
Graphics	<i>Some: Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11 one VGA, one DVI-D, supports dual independent display;</i> <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i> <i>Some: AMD Radeon™ HD 7450, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 25 watts;</i> <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors										- Windows 8 models		
Disk	SATA 3.0Gb/s 7200 rpm										<ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW)		
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										- All models		
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset										<ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™		
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	Intel H61 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
PCIe WLAN ^a	None												
Bluetooth	None												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts with variable speed fan, autoselecting, 85% PSU												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk												
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1												
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2 GMP (P)	Global (G) preload	Win7	Ann date (mm/dd/yy)
3662-A1U	3x3	i5-3550	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	Switch	ES52	G P	Pro 64	06/05/12
3662-A2U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	G P	Pro 64	06/19/12
3662-A4U	3x3	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	Switch	ES52	G P	Pro 64	08/21/12
3662-A6U	3x3	i3-3240	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	Switch	ES52	G P	Pro 64	05/28/13

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<p>Essential business features, exceptional value</p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>											
Implementation	<p>Preloaded operating system</p> <p>Genuine Windows® 7 Professional 64</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 											
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets											
Graphics	<p>Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display;</p> <p><i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i></p>											
Disk Optical	<p>SATA 3.0Gb/s 7200 rpm</p> <p>Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive</p>											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, autoselecting, 85% PSU											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.3" W X 16.6" D X 15.3" H (with handle) • 160mm W X 422mm D X 388mm H • 20.7 lb (9.4 kg) in maximum configuration • Handle on top front • Highlighted optical drive button for easy access 											
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 3.5", 1" high, no access, opt disk</p> <p>Bay 3: 3.5", 1" high, no access, std disk</p>											
Slot	<p>Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, PCIe 2.0 x1</p>											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											




EPEAT™ Gold rating
ENERGY STAR® 5.2-compliant
Cisco EnergyWise compatible
GREENGUARD® certified
RoHS-compliant
Supports ThinkVantage Technologies

For compatible accessories, please go to O-M72E sheet;
For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	Chassis intr switch	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3662-A3U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	Switch	ES52	G P	Win8 Pro64	10/23/12
3662-A5U	3x3	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	HD 2500	None	ES52	G P	Win7 Pro64	10/23/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>								Preloaded operating system			
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket								Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation									Some: Windows 8 Pro 64-bit			
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets								Preloaded applications (only some listed)			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz								- Windows 7 models			
Disk	SATA 3.0Gb/s 7200 rpm								<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage Power Manager ● ThinkVantage Communication Utility ● Lenovo® Message Center Plus ● Lenovo SimpleTap ● Adobe® Reader® ● Windows Live™ Essentials ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 			
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive								- Windows 8 models			
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset								<ul style="list-style-type: none"> ● Lenovo Support ● Lenovo Companion ● Lenovo Cloud Storage ● Norton™ Studio ● AccuWeather ● Evernote® ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) 			
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar								- All models			
eSATA port	None								<ul style="list-style-type: none"> ● ThinkVantage System Update ● Lenovo Solution Center ● View Management Utility ● Norton Internet Security (30 days of virus definitions) ● Microsoft® Office preloaded; purchase a product key to activate ● Skype™ 			
Media reader	None											
Chipset	Intel H61 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 2.0, serial (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DVI-D											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices)											
Audio	High Definition (HD) Audio, Realtek ALC662 codec											
PCIe WLAN ⁴	None											
Bluetooth	None											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Intel AMT	None											
Modem	None											
Security chip	None											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, autosensing, 85% PSU											
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 6.3" W X 16.6" D X 15.3" H (with handle) ● 160mm W X 422mm D X 388mm H ● 20.7 lb (9.4 kg) in maximum configuration ● Handle on top front ● Highlighted optical drive button for easy access 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk Bay 3: 3.5", 1" high, no access, std disk											
Slot	Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											



Security

- One lock to secure both cover and entire system to fixed object:
 - Padlock loop (in rear for opt padlock)
 - Security slot (in rear for optional Kensington® MicroSaver® cable)
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Serial port I/O control
- Individual USB port disablement
- Chassis intrusion switch on selected model(s)

EPEAT™ Gold rating
ENERGY STAR® 5.2-compliant
Cisco EnergyWise compatible
GREENGUARD® certified
RoHS-compliant

Supports ThinkVantage Technologies
For compatible accessories, please go to O-M72E sheet;
For Lenovo service upgrade options, please go to S-TC sheet

Memory	Security
Tiny 4004/3264/3267 use notebook memory: 2GB PC3-12800 DDR3 SODIMM 4GB PC3-12800 DDR3 SODIMM 8GB PC3-12800 DDR3 SODIMM	Kensington® MicroSaver® Cable Lock ⁵⁶ Kensington Twin Head Cable Lock ⁵⁶ Lenovo Security Cable Lock ⁵⁶ USB Gemplus GemPC Smart Card Reader
0A65722 ann 06/05/12 0A65723 ann 06/05/12 0A65724 ann 06/05/12	73P2582 ann 12/29/03 45K1620 ann 09/30/08 57Y4303 ann 08/24/10 41N3040 ann 02/21/06
Small 0967/3598/3660/3664, and Tower 0958/3675/3597/3655/3662 use desktop memory: 2GB PC3-12800 DDR3 UDIMM 4GB PC3-12800 DDR3 UDIMM 8GB PC3-12800 DDR3 UDIMM	⁵⁶ Attaching to any form factor not only secures the ThinkCentre to the work area, but it also prevents users from opening the chassis itself.
0A65728 ann 06/05/12 0A65729 ann 06/05/12 0A65730 ann 06/05/12	
More information at www.lenovo.com/support/desktopmemorycompatibility	
Optical	Under Desk Mount
Small and Tower support: DVD-ROM DL SATA 1.5Gb/s 16X-48X Max ⁴ Lenovo® Super Multi-Burner SATA Drive	Tiny support: ThinkCentre Tiny Under Desk Mount Bracket
41N5618 ann 09/26/06 0A65618 ann 08/23/11	0B47097 ann 08/07/12
Storage and removable storage	Monitors
Tiny support: 320GB 7200rpm SATA 3.0Gb/s 7mm 4K HDD 500GB 7200rpm SATA 3.0Gb/s 7mm 4K HDD	ThinkVision LT1952p Wide 19" (VGA, DP, DVI-D) ⁶⁹ ThinkVision L2251x Wide 22" (VGA, DP) ThinkVision LT2323p Wide 23" (VGA, DP, DVI-D) ⁶⁹
0A65635 ann 06/05/12 0A65632 ann 06/05/12	2448MB6 ann 09/13/11 2578HB6 ann 10/20/09 3024HC1 ann 05/01/12
Small and Tower support: 500GB SATA 3.0Gb/s Disk (7200 rpm) 1TB SATA 3.0Gb/s Disk (7200 rpm) 180GB Solid State Drive	⁶⁹ DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537).
43R1990 ann 11/06/07 45J7918 ann 08/19/08 0B47308 ann 01/29/13	More information at www.lenovo.com/support/monitors
All: USB 2.0 Portable 500GB Hard Disk USB 3.0 Secure 500GB Hard Drive USB 3.0 Secure 750GB Hard Drive USB 3.0 Secure 1TB Hard Drive Slim USB Portable DVD Burner	Monitor Accessories⁴⁶
45K1690 ann 05/26/09 0A65619 ann 11/29/11 0A65616 ann 11/29/11 0A65621 ann 08/28/12 0A33988 ann 06/14/11	Tiny support: DisplayPort™ to Single-link DVI-D Cable DisplayPort to VGA Monitor Cable DisplayPort to DisplayPort Monitor Cable
	45J7915 ann 08/05/08 57Y4393 ann 08/04/09 0A36537 ann 09/13/11
	Small and Tower support: Lenovo DVI to DVI Monitor Cable
	0B47071
	All: Lenovo USB 3.0 to DVI/VGA Monitor Adapter Lenovo USB Soundbar Kensington MicroSaver Cable Lock ⁵⁶ Kensington Twin Head Cable Lock ⁵⁶ Lenovo Security Cable Lock ⁵⁶ ThinkCentre Extend Arm
	0B47072 ann 08/14/12 0A36190 ann 05/01/12 73P2582 ann 12/29/03 45K1620 ann 09/30/08 57Y4303 ann 08/24/10 57Y4352 ann 07/06/10
	⁴⁶ Compatible on selected Lenovo and ThinkVision monitors.
	More information at www.lenovo.com/support/monitoraccessories
Graphics	
Small 0967/3598/3660/3664 support Low Profile: NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	
NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	0B47077 ann 01/29/13
Tower 0958/3675/3597/3655/3662 support 60 watts max: NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	
⁶⁷ Simultaneously use the graphic card monitor ports along with the systems integrated monitor ports when Multi-Monitor Support is enabled in BIOS Setup.	
More information at www.lenovo.com/support/graphiccards	
Keyboard	
Preferred Pro USB Keyboard Enhanced Performance USB Keyboard Ultrathin Plus Wireless Keyboard and Mouse ⁵² ThinkPad® USB Keyboard with TrackPoint Lenovo USB Fingerprint Keyboard Lenovo USB Smartcard Keyboard	73P5220 ann 06/21/05 73P2620 ann 03/23/04 0A34032 ann 04/05/11 55Y9003 ann 08/18/09 73P4730 ann 02/22/05 51J0155 ann 03/24/09
⁵² Wireless via 2.4GHz technology using a micro-size USB receiver.	
More information at www.lenovo.com/support/keyboards	
Mouse	
Lenovo Optical Mouse (USB) Lenovo ScrollPoint® Mouse(USB, Optical) ThinkPad Travel Mouse (USB, Optical) Lenovo Laser Mouse (USB) Lenovo Wireless Laser Mouse ⁵² ThinkPad USB Laser Mouse	06P4069 ann 05/21/03 31P7405 ann 08/27/02 31P7410 ann 06/04/02 41U3074 ann 01/23/07 0A36188 ann 12/20/11 57Y4635 ann 12/15/09
More information at www.lenovo.com/support/mice	
Modem	
USB 2.0 Lenovo Modem	43R1814 ann 02/26/08
	For more information on accessories: www.lenovo.com/accessories Purchase Lenovo accessories www.lenovo.com/support/accessories Product specifications on Lenovo Support www.lenovo.com/accessoriesguide Option Compatibility Matrix (OCM) and accessory brochures www.lenovoquickpick.com An Options Compatibility Configurator for Lenovo systems
Multimedia	
ThinkPad In-Ear Headphones with mic ⁶⁰ Lenovo Mini Speakers M220 Lenovo Speakers M0520 (black) Lenovo Speakers M0520 (red) Lenovo Headset P550 Lenovo Headset P950 (black)	57Y4488 ann 01/07/10 55Y2033 ann 01/07/10 57Y6360 ann 02/08/11 57Y6361 ann 02/08/11 55Y2065 57Y6605 ann 02/08/11
⁶⁰ Has a 1.2 meter (3.9-foot) cable. Best when systems are in close proximity. Example: SFF placed on a desk.	

ThinkCentre M72z All-In-One

ThinkCentre®



Lenovo ThinkCentre M72z with Frame Stand



Lenovo ThinkCentre M72z with Frame Stand



Lenovo ThinkCentre M72z with Monitor Stand



Lenovo ThinkCentre M72z with Monitor Stand



Dual Independent Display with Optional Lenovo ThinkVision Monitor

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)
3543-B6U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200 HD 2500	Intel 105	Media None	None	None	Frame	USB	None	Win7 Pro64	03/12/13	

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system²⁰ Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW) 		
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk Optical Media reader	Hard Disk Drive / SATA 3.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable 7-in-1 Single Slot SD media reader													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1													
Bluetooth	None													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio Speaker	High Definition (HD) Audio, Realtek ALC269Q Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard Mouse Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 20.0" W X 4.0" D X 16.2" H • 507mm W X 101mm D X 411mm H (including stand) • 14.6 lb (6.6 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 		
Limited Warranty	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
												Supports ThinkVantage Technologies		
												For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Win7 Global preload	Ann date (mm/dd/yy)	
3548-A9U	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	2.4G	None	Pro 64 06/05/12
3548-B1U	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Pro 64 06/05/12
3548-B2U	i7-3770S	4GBx2	1600MHz	2.0M	500G 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	None	Pro 64 06/05/12
3548-B3U	i7-3770S	4GBx2	1600MHz	2.0M	500G 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	2.4G	None	Pro 64 06/05/12
3548-C1U	i3-3220	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	Serial	None	Monitor	USB	None	Pro 64 09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads , 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off	
Disk Optical Media reader	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable <i>Some:</i> 7-in-1 Single Slot SD media reader	
Chipset	Intel H61 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	
Audio	High Definition (HD) Audio, Realtek ALC269Q	
Speaker	Two internal stereo speakers (2watt x 2)	
Intel AMT	None	
Modem	None	
IEEE 1394	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black	EPEAT™ Gold rating
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black	ENERGY STAR® 5.2-compliant
Power supply	150 watts, autosensing, 85% PSU	TCO Certified Edge
Machine	<i>Model(s) with Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • Business black color • 20.0" W X 8.9" D X 17.0" H • 507mm W X 227mm D X 431mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Support VESA mount (100mm) 	Cisco EnergyWise compatible
		GREENGUARD® certified
		RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	Supports ThinkVantage Technologies
		For compatible accessories, please go to O-M7ZZ sheet;
		For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Win7 Global preload	Ann date (mm/dd/yy)	
3548-B4U	G640	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	None	None	None	None	Monitor	USB	None	Pro 64	07/24/12
3548-B9U	G640	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	None	None	Serial	None	Monitor	USB	None	Pro 64	08/14/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system²⁰ Genuine Windows® 7 Professional 64		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook); <i>System automatically clocks down for processors with 1066MHz DDR3 memory controller</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) • InterVideo WinDVD® (DVD, DVD±RW) 		
Graphics	Intel HD Graphics in processor, uses main memory, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>													
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk Optical Media reader	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable None													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)											Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) 		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autoselecting, 85% PSU													
Machine	<i>Model(s) with Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • Business black color • 20.0" W X 8.9" D X 17.0" H • 507mm W X 227mm D X 431mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Support VESA mount (100mm) 													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M7ZZ sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse Global	Preload	Ann date (mm/dd/yy)
3548-C6U	i5-3470T	4GBx1 1600MHz	2.0M	1TB 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3548-C7U	i7-3770S	4GBx2 1600MHz	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3548-C8U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 10/23/12
3548-C9U	i3-3240	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 10/23/12
3548-D1U	G640	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 10/23/12
3548-D2U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Win7 Pro64 10/23/12
3548-D3U	G860	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	None	None	None	None	Monitor	USB	None	Win7 Pro64 10/23/12
3548-F2U	i3-3220	4GBx1 1600MHz	2.0M	180G SSD	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 11/20/12
3548-F4U	G2020	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 01/22/13
3548-F7U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 03/05/13
3548-F9U	i7-3770S	8GBx1 1600MHz	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 03/05/13
3548-G1U	i5-3470S	4GBx1 1600MHz	2.0M	1TB 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 03/12/13

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i>												Preloaded operating system²⁰				
	Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz)	Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz)	Intel Pentium G860 Processor (2 cores / 2 threads, 3.0GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz)	Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz)	Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz)	Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Processor in LGA1155 socket	Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit	Preloaded applications (only some listed)			- Windows 7 models			
Implementation																	
Memory																	
Graphics																	
DP dongle																	
Display																	
Multi-touch Camera																	
Controls																	
Disk																	
Optical Media reader																	
Chipset																	
Rear ports																	
Side ports																	
PCIe Mini Card																	
PCIe WLAN																	
Bluetooth																	
Ethernet																	
Audio																	
Speaker																	
Intel AMT																	
Security chip																	
Keyboard																	
Mouse																	
Power supply																	
Machine																	
Limited Warranty																	

See footnotes for important warranty information

US models announced Oct 23, 2012, Nov 20, 2012, Jan 22, 2013, Mar 5, 2013, or Mar 12, 2013

US models withdrawn effective May 2014

©Lenovo

(MTGI1-6) May 2014

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global	Preload	Ann date (mm/dd/yy)
3548-H2U	i7-3770S	8GBx1	1600MHz	2.0M	500G 7200	HD 4000	11b/g/n	Media	None	None	Monitor	2.4G	None	Win7 Pro64	06/11/13
3548-H3U	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	Monitor	2.4G	None	Win7 Pro64	06/11/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology												Preloaded operating system²⁰ Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• InterVideo WinDVD® (DVD, DVD±RW)		
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)		
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio														
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Media reader	7-in-1 Single Slot SD media reader														
Chipset	Intel H61 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black														
Mouse	Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 8.9" D X 17.0" H• 507mm W X 227mm D X 431mm H (including stand)• 18.5 lb (8.4 kg) in maximum configuration• Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Support VESA mount (100mm)												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Supports ThinkVantage Technologies For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		

See footnotes for important warranty information

US models announced June 11, 2013

US models withdrawn effective May 2014

©Lenovo
(MTGI1-13) May 2014

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse Global	Preload	Ann date (mm/dd/yy)
3548-E9U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 11/20/12
3548-F1U	G645	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 11/20/12
3548-F3U	G645	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	Serial	None	Frame	USB	None	Win7 Pro64 11/20/12
3548-F6U	G2120	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 12/04/12
3548-F5U	G2020	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 01/22/13
3548-F8U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 03/05/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Pentium® G645 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook) <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• InterVideo WinDVD® (DVD, DVD±RW)
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>												
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio												
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off												
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off												
Disk Optical Media reader	Hard Disk Drive / SATA 3.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable 7-in-1 Single Slot SD media reader												
Chipset	Intel H61 Express Chipset												
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)												
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB												
Audio	High Definition (HD) Audio, Realtek ALC269Q												
Speaker	Two internal stereo speakers (2watt x 2)												
Intel AMT	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	150 watts, autosensing, 85% PSU												
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 4.0" D X 16.2" H• 507mm W X 101mm D X 411mm H (including stand)• 14.6 lb (6.6 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Supports ThinkVantage Technologies For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Win7 Global preload	Ann date (mm/dd/yy)
3554-E2U	i7-3770S	4GBx2 1600MHz	2.0M	500G 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	None	Pro 64 06/05/12
3554-E3U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Pro 64 06/05/12
3554-E4U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Prem 64 06/05/12
3554-E5U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	Pro 64 06/05/12
3554-E6U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Prem 32 06/05/12

•3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</i>											Preloaded operating system²⁰ <i>Some: Genuine Windows® 7 Home Premium 32 Some: Genuine Windows® 7 Home Premium 64 Some: Genuine Windows 7 Professional 64</i>		
Implementation	<i>Processor in LGA1155 socket</i>											Ready to install applications (only some listed) <ul style="list-style-type: none">Rescue and Recovery™Password ManagerBusiness-in-a-Box		
Memory	<i>16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)</i>											Preloaded applications (only some listed) <ul style="list-style-type: none">ThinkVantage® Product RecoveryThinkVantage System UpdateThinkVantage Communication UtilityThinkVantage Automatic Lock UtilityThinkVantage Power ManagerView Management UtilityLenovo Solution CenterLenovo Message Center PlusRapidBoot HDD AcceleratorLenovo SimpleTapNorton™ Internet Security (30 days of virus definitions)Adobe® Reader®Skype™ for WindowsWindows Live™ EssentialsMicrosoft® Office preloaded; purchase a product key to activateCorel® Burn.Now™ (DVD±RW)Corel DVD MovieFactory® (DVD±RW)InterVideo WinDVD® (DVD, DVD±RW)		
Graphics	<i>Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Security <ul style="list-style-type: none">Security chip (see information on left)Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)Power-on passwordAdministrator passwordHard disk passwordBoot sequence controlBoot without keyboard and mouseUSB port disablementChassis intrusion switch on selected model(s)		
DP dongle	<i>None</i>											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Display	<i>20.0" (508mm) HD+ (1600x900) TFT color, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio</i>											Supports ThinkVantage Technologies For compatible accessories, please go to O-M72Z sheet;		
Multi-touch Camera	<i>None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off</i>											For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		
Controls	<i>Front facing buttons for brightness up/auto, brightness down, and power on/off</i>													
Disk	<i>SATA 3.0Gb/s, 3.5" Wide, 7200 rpm</i>													
Optical	<i>DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable</i>													
Media reader	<i>Some: 7-in-1 Single Slot SD media reader</i>													
Chipset	<i>Intel H61 Express Chipset</i>													
Rear ports	<i>Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)</i>													
Side ports	<i>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</i>													
PCIe Mini Card	<i>One PCI Express® Mini Card slot</i>													
PCIe WLAN	<i>11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</i>													
Bluetooth	<i>Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter</i>													
Ethernet	<i>One gigabit ethernet port, Realtek® RTL8111E-VB</i>													
Audio	<i>High Definition (HD) Audio, Realtek ALC269Q</i>													
Speaker	<i>Two internal stereo speakers (2watt x 2)</i>													
Intel AMT	<i>None</i>													
Modem	<i>None</i>													
IEEE 1394	<i>None</i>													
Security chip	<i>Trusted Platform Module (TPM 1.2-compliant)</i>													
Keyboard	<i>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</i>													
Mouse	<i>Enhanced Optical USB Mouse, black, Lenovo logo</i>													
Power supply	<i>150 watts, autosensing, 85% PSU</i>													
Machine	<i>Model(s) with Non multi-touch, Frame stand: • Business black color • 20.0" W X 4.0" D X 16.2" H • 507mm W X 101mm D X 411mm H (including stand) • 14.6 lb (6.6 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm)</i>													
	<i>Model(s) with Non multi-touch, Monitor stand: • Business black color • 20.0" W X 8.9" D X 17.0" H • 507mm W X 227mm D X 431mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Support VESA mount (100mm)</i>													
Limited Warranty	<i>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</i>													

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse Global	Preload	Ann date (mm/dd/yy)
3554-H2U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3554-H3U	i3-3240	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3554-H4U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3554-H7U	i5-3570S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3554-H8U	i7-3770S	4GBx1 1600MHz	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	None	Win8 Pro64 10/23/12
3554-M9U	i5-3470S	4GBx1 1600MHz	2.0M	180G SSD	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 11/20/12
3554-Q6U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	Win7 Pro64 07/09/13

Positioning Processor	<p>Mainstream All-In-One PC for the enterprise</p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz)</p> <p>Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz)</p> <p>Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system²⁰
Implementation		Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Memory	Some: Windows 8 Pro 64-bit	Preloaded applications (only some listed)
Graphics	<p>Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz</p>	- Windows 7 models
DP dongle Display	None	• ThinkVantage® Product Recovery
Multi-touch Camera	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio	• ThinkVantage Communication Utility
Controls	None	• ThinkVantage Power Manager
Disk	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off	• Lenovo® Message Center Plus
Optical Media reader	Front facing buttons for brightness up/auto, brightness down, and power on/off	• RapidBoot HDD Accelerator
Chipset	Intel H61 Express Chipset	• Lenovo SimpleTap
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	• Adobe® Reader®
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	• Corel® Burn.Now™ (DVD±RW)
PCIe Mini Card	One PCI Express® Mini Card slot	• Corel DVD MovieFactory® (DVD±RW)
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	• InterVideo WinDVD® (DVD, DVD±RW)
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	- Windows 8 models
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB	• Lenovo Support
Audio	High Definition (HD) Audio, Realtek ALC269Q	• Lenovo Settings
Speaker	Two internal stereo speakers (2watt x 2)	• Lenovo Companion
Intel AMT	None	• Lenovo Cloud Storage
Modem	None	• Norton™ Studio
IEEE 1394	None	• AccuWeather
Security chip	Trusted Platform Module (TPM 1.2-compliant)	• Evernote®
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	• Cyberlink Power2Go (DVD±RW)
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	• Cyberlink PowerProducer (DVD±RW)
Power supply	150 watts, autosensing, 85% PSU	- All models
Machine	Model(s) with Non multi-touch, Monitor stand:	• ThinkVantage System Update
	• Business black color	• ThinkVantage Automatic lock Utility
	• 20.0" W X 8.9" D X 17.0" H	• Lenovo Solution Center
	• 507mm W X 227mm D X 431mm H (including stand)	• View Management Utility
	• 18.5 lb (8.4 kg) in maximum configuration	• Norton Internet Security (30 days of virus definitions)
	• Tilt: 25° back, -5° forward; Lift: 110mm; Swivel: +/-45°	• Microsoft® Office preloaded; purchase a product key to activate
	• Support VESA mount (100mm)	• Skype™
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	Security
		• Security chip (see information on left)
		• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)
		• Power-on password
		• Administrator password
		• Hard disk password
		• Boot sequence control
		• Boot without keyboard and mouse
		• USB port disablement
		• Chassis intrusion switch on selected model(s)
		EPEAT™ Gold rating
		ENERGY STAR® 5.2-compliant
		TCO Certified Edge
		Cisco EnergyWise compatible
		GREENGUARD® certified
		RoHS-compliant
		Supports ThinkVantage Technologies
		For compatible accessories, please go to O-M72Z sheet;
		For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse Global	Preload	Ann date (mm/dd/yy)
3554-H1U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	Win8 Pro64 10/23/12
3554-H5U	i5-3470S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	Win8 Pro64 10/23/12
3554-H6U	i5-3570S	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	Win8 Pro64 10/23/12
3554-H9U	i7-3770S	4GBx1 1600MHz	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Frame	USB	None	Win8 Pro64 10/23/12
3554-M7U	i3-3220	4GBx1 1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 11/20/12
3554-N1U	G2020	2GBx1 1600MHz	2.0M	500G 7200	Intel HD	11b/g/n	Media	None	None	None	Frame	USB	None	Win7 Pro64 01/22/13

Positioning Processor	Mainstream All-In-One PC for the enterprise Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation														Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• InterVideo WinDVD® (DVD, DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook) System automatically clocks down for processors with 1333MHz DDR3 memory controller													
Graphics	Intel HD Graphics / 2500 / 4000 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz													
DP dongle	None													
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio													
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off													
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off													
Disk	Hard Disk Drive / SATA 3.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Media reader	Some: 7-in-1 Single Slot SD media reader													
Chipset	Intel H61 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB													
Audio	High Definition (HD) Audio, Realtek ALC269Q													
Speaker	Two internal stereo speakers (2watt x 2)													
Intel AMT	None													
Modem	None													
IEEE 1394	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosing, 85% PSU													
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 4.0" D X 16.2" H• 507mm W X 101mm D X 411mm H (including stand)• 14.6 lb (6.6 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)													<i>Chassis intrusion switch on selected model(s)</i>
														EPEAT™ Gold rating
														ENERGY STAR® 5.2-compliant
														TCO Certified Edge
														Cisco EnergyWise compatible
														GREENGUARD® certified
														RoHS-compliant
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													Supports ThinkVantage Technologies
														For compatible accessories, please go to O-M7Z sheet;
														For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)	
3558-A2U	i5-3550S	4GBx1	1600MHz	2.0M	250G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	06/05/12
3558-A4U	i5-3570S	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	08/14/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64					
Implementation	Processor in LGA1155 socket																	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>																	
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio																	
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off																	
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off																	
Disk Optical Media reader	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable 7-in-1 Single Slot SD media reader																	
Chipset	Intel H61 Express Chipset																	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																	
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) One PCI Express® Mini Card slot																	
PCIe Mini Card	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																	
PCIe WLAN	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																	
Bluetooth	One gigabit ethernet port, Realtek® RTL8111E-VB																	
Ethernet	High Definition (HD) Audio, Realtek ALC269Q																	
Audio	Two internal stereo speakers (2watt x 2)																	
Speaker	None																	
Intel AMT	None																	
Modem	None																	
IEEE 1394	None																	
Security chip	Trusted Platform Module (TPM 1.2-compliant)																	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																	
Power supply	150 watts, autosensing, 85% PSU																	
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 4.0" D X 16.2" H• 507mm W X 101mm D X 411mm H (including stand)• 14.6 lb (6.6 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)																	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																	
	For compatible accessories, please go to O-M72Z sheet; For Lenovo service upgrade options, please go to S-TC sheet																	
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies																	

Type-model	Processor	Memory ^a	Camera (mega-pixel)	Disk (SATA GB rpm)	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/ Mouse	Global (G) GMP (P) pre-load	Win7 Ann date (mm/dd/yy)
3558-A5U	G460	2GBx1 1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32 11/20/12
3558-A7U	G465	2GBx1 1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32 01/08/13
3558-A8U	G470	2GBx1 1600MHz	None	8G SSD	None	Intel HD	11b/g/n	None	Switch	Serial	None	Frame	USB	G P	Emb 32 06/11/13

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G465 Processor (1 core / 2 threads, 1.9GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Processor in LGA1155 socket												Preloaded operating system²⁰ Genuine Windows® 7 Embedded 32		
Implementation													Preloaded applications (only some listed) <ul style="list-style-type: none"> ● Adobe® Reader® ● Adobe Flash® Player ● Citrix® Receiver ● IIS Web Server ● Microsoft® Management Console ● Microsoft Silverlight ● Remote Desktop Protocol ● ThinPrint .print Client ● TightVNC Viewer ● VMware® View Client ● vWorkspace ● Windows Media Player 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook) <i>System automatically clocks down for processors with 1066MHz DDR3 memory controller</i>														
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort) @ 60Hz</i>														
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio														
Multi-touch Camera	None														
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide														
Optical	None														
Media reader	None														
Chipset	Intel H61 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB														
Audio	High Definition (HD) Audio, Realtek ALC269Q														
Speaker	Two internal stereo speakers (2watt x 2)														
Intel AMT	None														
Modem	None														
IEEE 1394	None														
Security chip	Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> ● Business black color ● 20.0" W X 4.0" D X 16.2" H ● 507mm W X 101mm D X 411mm H (including stand) ● 14.6 lb (6.6 kg) in maximum configuration ● Handle in rear, removable feet ● Support VESA mount (100mm) 														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Keyboard/ Mouse	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3558-A3U	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200 HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Win8 Pro64	10/23/12
3558-A6U	i5-3470S	4GBx1	1600MHz	2.0M	500G 7200 HD 2500	11b/g/n	Media	None	None	None	Frame	USB	G P	Win7 Pro64	10/23/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation													Preloaded applications (only some listed) - Windows 7 models		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)														
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>												Preloaded applications (only some listed) - Windows 8 models		
DP dongle	None														
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio														
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off												Preloaded applications (only some listed) - Windows 8 models		
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off														
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm												Lenovo Support		
Optical Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable												Lenovo Settings		
Media reader	7-in-1 Single Slot SD media reader												Lenovo Companion		
Chipset	Intel H61 Express Chipset												Lenovo Cloud Storage		
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)												Norton™ Studio		
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												AccuWeather		
PCIe Mini Card	One PCI Express® Mini Card slot												Evernote®		
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												Cyberlink Power2Go (DVD±RW)		
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												Cyberlink PowerProducer (DVD±RW)		
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB												All models		
Audio	High Definition (HD) Audio, Realtek ALC269Q												ThinkVantage System Update		
Speaker	Two internal stereo speakers (2watt x 2)												ThinkVantage Automatic lock Utility		
Intel AMT	None												Lenovo Solution Center		
Modem	None												View Management Utility		
IEEE 1394	None												Norton Internet Security (30 days of virus definitions)		
Security chip	Trusted Platform Module (TPM 1.2-compliant)												Microsoft® Office preloaded; purchase a product key to activate		
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												Skype™		
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	<i>Model(s) with Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 4.0" D X 16.2" H• 507mm W X 101mm D X 411mm H (including stand)• 14.6 lb (6.6 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)												Administrator password		
													Hard disk password		
													Boot sequence control		
													Boot without keyboard and mouse		
													USB port disablement		
													Chassis intrusion switch on selected model(s)		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												EPEAT™ Gold rating		
													ENERGY STAR® 5.2-compliant		
													TCO Certified Edge		
													Cisco EnergyWise compatible		
													GREENGUARD® certified		
													RoHS-compliant		
													Supports ThinkVantage Technologies		
													For compatible accessories, please go to O-M72Z sheet;		
													For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Chassis intrusion switch	Serial port	PS/2 port	Stand type	Key-board/Mouse	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)	
3538-A2U	i5-3550S	4GBx1	1600MHz	2.0M	250G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	06/05/12
3538-A3U	i5-3570S	4GBx1	1600MHz	2.0M	500G 7200	HD 2500	11b/g/n	Media	Switch	None	None	Frame	USB	G P	Pro 64	08/14/12

- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty
- Microsoft® Office 2010 Product Key Ready (O10PKR)

Positioning Processor	<i>Mainstream All-In-One PC for the enterprise</i> Intel® Core™ i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	8GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Microsoft Touch Pack• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft Office 2010 preloaded; purchase product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• InterVideo WinDVD® (DVD, DVD±RW)			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)			
DP dongle	None												EPEAT™ Gold rating			
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 dynamic contrast ratio												ENERGY STAR® 5.2-compliant			
Multi-touch Camera	Multi-touch, 2-point support Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, physical switch on/off												TCO Certified Edge			
Controls	Front facing buttons for brightness up/auto, brightness down, and power on/off												Cisco EnergyWise compatible			
Disk	SATA 3.0Gb/s, 3.5" Wide, 7200 rpm												GREENGUARD® certified			
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable												RoHS-compliant			
Media reader	7-in-1 Single Slot SD media reader												Supports ThinkVantage Technologies			
Chipset	Intel H61 Express Chipset												For compatible accessories, please go to O-M72Z sheet;			
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort connector, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)												For Lenovo service upgrade options, please go to S-TC sheet			
Side ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Realtek® RTL8111E-VB															
Audio	High Definition (HD) Audio, Realtek ALC269Q															
Speaker	Two internal stereo speakers (2watt x 2)															
Intel AMT	None															
Modem	None															
IEEE 1394	None															
Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>Model(s) with multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 20.0" W X 4.2" D X 16.2" H• 507mm W X 107mm D X 411mm H (including stand)• 17.5 lb (7.9 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															

Memory

2GB PC3-12800 DDR3 SODIMM
4GB PC3-12800 DDR3 SODIMM
8GB PC3-12800 DDR3 SODIMM

0A65722 ann 06/05/12
0A65723 ann 06/05/12
0A65724 ann 06/05/12

More information at

www.lenovo.com/support/desktopmemorycompatibility

Storage and removable storage

500GB SATA 3.0Gb/s Disk (7200 rpm)
1TB SATA 3.0Gb/s Disk (7200 rpm)
USB 2.0 Portable 500GB Hard Disk
USB 3.0 Secure 500GB Hard Drive
USB 3.0 Secure 750GB Hard Drive
USB 3.0 Secure 1TB Hard Drive
Slim USB Portable DVD Burner

43R1990 ann 11/06/07
45J7918 ann 08/19/08
45K1690 ann 05/26/09
0A65619 ann 11/29/11
0A65616 ann 11/29/11
0A65621 ann 08/28/12
0A33988 ann 06/14/11

Keyboard

Preferred Pro USB Keyboard
Enhanced Performance USB Keyboard
Ultraslim Plus Wireless Keyboard and Mouse⁵²
ThinkPad® USB Keyboard with TrackPoint
Lenovo® USB Fingerprint Keyboard
Lenovo USB Smartcard Keyboard

⁵²Wireless via 2.4GHz technology using a micro-size USB receiver.

More information at www.lenovo.com/support/keyboards

Mouse

Lenovo Optical Mouse (USB)
Lenovo ScrollPoint® Mouse (USB, Optical)
ThinkPad Travel Mouse (USB, Optical)
Lenovo Laser Mouse (USB)
Lenovo Wireless Laser Mouse⁵²
ThinkPad USB Laser Mouse

06P4069 ann 05/21/03
31P7405 ann 08/27/02
31P7410 ann 06/04/02
41U3074 ann 01/23/07
0A36188 ann 12/20/11
57Y4635 ann 12/15/09

More information at www.lenovo.com/support/mice

Modem

USB 2.0 Lenovo Modem

43R1814 ann 02/26/08

Multimedia

ThinkPad In-Ear Headphones with mic
Lenovo Mini Speakers M220
Lenovo Speakers M0520 (black)
Lenovo Speakers M0520 (red)
Lenovo Headset P550
Lenovo Headset P950 (black)

57Y4488 ann 01/07/10
55Y2033 ann 01/07/10
57Y6360 ann 02/08/11
57Y6361 ann 02/08/11
55Y2065 ann 02/08/11
57Y6605 ann 02/08/11

Security

Kensington® MicroSaver® Cable Lock⁵⁶
Kensington Twin Head Cable Lock⁵⁶
Lenovo Security Cable Lock⁵⁶
USB Gemplus GemPC Smart Card Reader

73P2582 ann 12/29/03
45K1620 ann 09/30/08
57Y4303 ann 08/24/10
41N3040 ann 02/21/06

⁵⁶Attaching to any form factor not only secures the ThinkCentre to the work area, but it also prevents users from opening the chassis itself.

Monitors

ThinkVision LT1952p Wide 19" (VGA, DP, DVI-D)⁶⁹ 2448MB6 ann 09/13/11
ThinkVision L2251x Wide 22" (VGA, DP) 2578HB6 ann 10/20/09
ThinkVision LT2323p Wide 23" (VGA, DP, DVI-D)⁶⁹ 3024HC1 ann 05/01/12
⁶⁹ DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537).

More information at www.lenovo.com/support/monitors

Monitor Accessories⁴⁶

Lenovo USB 3.0 to DVI/VGA Monitor Adapter	0B47072 ann 08/14/12
DisplayPort™ to Single-link DVI-D Cable	45J7915 ann 08/05/08
DisplayPort to VGA Monitor Cable	57Y4393 ann 08/04/09
DisplayPort to DisplayPort Monitor Cable	0A36537 ann 09/13/11
Kensington MicroSaver Cable Lock ⁵⁶	73P2582 ann 12/29/03
Kensington Twin Head Cable Lock ⁵⁶	45K1620 ann 09/30/08
Lenovo Security Cable Lock ⁵⁶	57Y4303 ann 08/24/10
ThinkCentre Extend Arm ⁷⁰	57Y4352 ann 07/06/10

⁴⁶ Compatible on selected Lenovo and ThinkVision monitors.

⁷⁰ Desk Mount only.

More information at www.lenovo.com/support/monitoraccessories

For more information on accessories:

www.lenovo.com/accessories

Purchase Lenovo accessories

www.lenovo.com/support/accessories

Product specifications on Lenovo Support

www.lenovo.com/accessoriesguide

Option Compatibility Matrix (OCM) and accessory brochures


www.lenovoquickpick.com

An Options Compatibility Configurator for Lenovo systems

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
5100-A1U	4x3	A8-5500B	4GBx1	1TB 7200	DVD±RW	None	Radeon HD 7560D	None	None	Stand	None	None	Pro 64 08/28/12
5100-A2U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	None	None	Pro 64 08/28/12
5100-A3U	4x3	A4-5300	4GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Pro 64 08/28/12
5100-A4U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Pro 64 08/28/12

- Small and medium business (SMB) model(s), part of the US TopSeller Program
- 3-year limited warranty

Positioning	Mainstream enterprise stability and manageability												
Processor	AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)												
Implementation	Processor in Socket FM2												
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz												
DP dongle	None												
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1												
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	AMD A75 Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	240 watts, autosensing, active Power Factor Correction												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 399mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader												
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												

**Preloaded operating system**

Genuine Windows® 7 Professional 64

Ready to install applications (only some listed)

- Rescue and Recovery™
- Password Manager
- Business-in-a-Box

Preloaded applications (only some listed)

- ThinkVantage® Product Recovery
- ThinkVantage System Update
- ThinkVantage Communication Utility
- ThinkVantage Power Manager
- View Management Utility
- Lenovo Solution Center
- Lenovo Message Center Plus
- Lenovo SimpleTap
- Norton™ Internet Security (30 days of virus definitions)
- Adobe® Reader®
- Google Chrome
- Google Toolbar
- Skype™ for Windows
- Evernote®
- RapidBoot HDD Accelerator
- Symantec™ VIP
- Windows Live™ Essentials
- Microsoft® Office preloaded; purchase a product key to activate
- Corel® Burn.Now™ (DVD±RW)
- Corel DVD MovieFactory® (DVD±RW)

Security

- Security chip (see information on left)
- Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
- Cable lock
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement
- Chassis intrusion switch on selected model(s)

RoHS-compliant


Supports ThinkVantage Technologies

For compatible accessories, please go to O-M78 sheet;
For ThinkPlus™ service upgrade options, please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
5100-B1U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	None	None	Win8 Pro64	10/23/12
5100-B2U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Win8 Pro64	10/23/12
5100-C1U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Win7 Pro64	10/30/12
5100-C2U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	None	None	Win7 Pro64	10/30/12


- Small and medium business (SMB) model(s), part of the US TopSeller Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)													Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation	Processor in Socket FM2													Preloaded applications (only some listed) - Windows 7 models
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													• ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Google Chrome • Google Toolbar • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>													- Windows 8 models
DP dongle	None													• Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • Intel AppUp® • AccuWeather • PC Device Stage • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
Disk	SATA 6.0Gb/s 7200 rpm													- All models
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													• ThinkVantage® System Update • View Management Utility • Lenovo Solution Center • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Evernote® • Skype™
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, active Power Factor Correction													
Machine	<ul style="list-style-type: none"> Business black color; metal case 13.3" W X 15.0" D X 3.9" H 339mm W X 381mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													




Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
4865-A7U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	None	None	Pro 32 08/28/12
4865-C1U	4x3	A8-5500B	4GBx1	1TB 7200	DVD±RW	None	Radeon HD 7560D	None	None	Stand	None	None	Pro 64 08/28/12
4865-C2U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	None	None	Pro 64 08/28/12
4865-C3U	4x3	A4-5300	4GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Pro 64 08/28/12

•3-year limited warranty

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system
Processor	AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)											Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64
Implementation	Processor in Socket FM2											Ready to install applications (only some listed)
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution:</i> 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz											Preloaded applications (only some listed)
DP dongle	None											
Disk	SATA 6.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1											
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	AMD A75 Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Modem	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, active Power Factor Correction											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 399mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader											
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3											
												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 											
	RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet											


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
4865-E1U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	None	None	Win8 Pro64	10/23/12

•3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>										Preloaded operating system																	
Processor	AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz)										Windows® 8 Pro 64-bit																	
Implementation	Processor in Socket FM2										Preloaded applications (only some listed)																	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 																	
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>																											
DP dongle	None																											
Disk	SATA 6.0Gb/s 7200 rpm																											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																											
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1																											
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar																											
eSATA port	None																											
Media reader	None																											
Chipset	AMD A75 Chipset																											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)																											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)																											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																											
Speaker	Internal speaker for business audio																											
IEEE 1394	None																											
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																											
Modem	None																											
Security chip	Trusted Platform Module (TPM 1.2-compliant)																											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																											
Floor Stand	System floor stand for vertical orientation																											
Power supply	240 watts, autosensing, active Power Factor Correction																											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 339mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 																											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader																											
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3																											
																												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																											
Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 																												
RoHS-compliant																												
Supports ThinkVantage Technologies																												
For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet																												


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
2113-A1U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	ES52	None	Pro 32 08/28/12

•3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>										Preloaded operating system		
Processor	AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz)										Genuine Windows® 7 Professional 32		
Implementation	Processor in Socket FM2										Ready to install applications (only some listed)		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 		
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed)		
DP dongle	None										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Google Chrome • Google Toolbar • Skype™ for Windows • Evernote® • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1												
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	AMD A75 Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	240 watts, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 339mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader												
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
													

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2 Global	Preload	Ann date (mm/dd/yy)
2113-D1U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2113-D2U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2113-D3U	4x3	A8-5500B	4GBx1	1TB 7200	DVD±RW	None	Radeon HD 7560D	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2113-D4U	4x3	A8-5500B	4GBx1	1TB 7200	DVD±RW	None	Radeon HD 7450	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2113-E1U	4x3	A4-5300	2GBx1	250G 7200	DVD±RW	None	Radeon HD 7480D	None	None	Stand	ES52	None	Win7 Pro64 10/30/12

• 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)												Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation Processor	Processor in Socket FM2											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">● ThinkVantage® Product Recovery● ThinkVantage Communication Utility● ThinkVantage Power Manager● Lenovo® Message Center Plus● Lenovo SimpleTap● Adobe® Reader®● Google Chrome● Google Toolbar● RapidBoot HDD Accelerator● Symantec™ VIP● Windows Live™ Essentials● Corel® Burn.Now™ (DVD±RW)● Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">● Lenovo Support● Lenovo Companion● Lenovo Cloud Storage● Lenovo QuickLaunch● Norton™ Studio● Intel AppUp®● AccuWeather● PC Device Stage● Cyberlink Power2Go (DVD±RW)● Cyberlink PowerProducer (DVD±RW)	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												
Graphics	Some: AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DP)@60Hz</i> Some: AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors												
DP dongle	None												
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1												
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	AMD A75 Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	240 watts, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 13.3" W X 15.0" D X 3.9" H ● 339mm W X 381mm D X 100mm H ● 16.5 lb (7.5 kg) in maximum configuration ● Toolless cover flips up and tilts backward on rear hinges ● Toolless disk and optical drive removal ● Toolless adapter retention 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader												
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
													
	EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant												
	Supports ThinkVantage Technologies												
	For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet												

See footnotes for important warranty information

US model(s) announced October 23 or 30, 2012

US model(s) withdrawn effective December 2013

©Lenovo

(ANDE1-11) January 2014

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
2114-A1U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	ES52	G P	Pro 64	08/28/12

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Mainstream enterprise stability and manageability</i>										Preloaded operating system			
Processor	AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)										Genuine Windows® 7 Professional 64			
Implementation	Processor in Socket FM2										Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 			
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed)			
DP dongle	None										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Google Chrome • Google Toolbar • Skype™ for Windows • Evernote® • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 339mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader										Security			
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3										<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold RoHS-compliant			
											Supports ThinkVantage Technologies			
											For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet			


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Chassis Intrusion switch	PS/2 port	Floor stand	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
2114-B1U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	ES52	G P	Win8 Pro64	10/23/12
2114-C1U	4x3	A6-5400B	4GBx1	500G 7200	DVD±RW	None	Radeon HD 7540D	None	None	Stand	ES52	G P	Win7 Pro64	10/30/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)										Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation	Processor in Socket FM2										Preloaded applications (only some listed) - Windows 7 models			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Google Chrome • Google Toolbar • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed) - Windows 8 models			
DP dongle	None										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Google Chrome • Google Toolbar • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Disk	SATA 6.0Gb/s 7200 rpm										All models			
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										<ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo Solution Center • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Evernote® • Skype™ 			
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1										Security			
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar										<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
eSATA port	None										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold RoHS-compliant			
Media reader	None										Supports ThinkVantage Technologies			
Chipset	AMD A75 Chipset										For compatible accessories, please go to O-M78 sheet;			
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)										For ThinkPlus™ service upgrade options, please go to S-TC sheet			
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.0" D X 3.9" H • 339mm W X 381mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 													
Bay	<ul style="list-style-type: none"> • Bay 1: 5.25", 1.6" high, access, std optical • Bay 2: 3.5", 1" high, no access, std disk • Bay 3: 3.5", .5" high, access, opt reader 													
Slot	<ul style="list-style-type: none"> • Slot 1: Low Profile, PCI Express 2.0 x16 (40w max) • Slot 2: Low Profile, PCIe 2.0 x1 • Slot 3: Low Profile, 32-bit PCI 2.3 • Slot 4: Low Profile, 32-bit PCI 2.3 													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													


Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2	Win7 Global preload	Ann date (mm/dd/yy)
2111-A1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	None	None	Pro 64 08/28/12
2111-A2U	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	None	None	Pro 64 08/28/12
2111-A3U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	Radeon HD 7560D	None	None	None	None	Pro 64 08/28/12
2111-A4U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	GeForce 605	None	None	None	None	Pro 64 08/28/12

- Small and medium business (SMB) model(s), part of the US TopSeller Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in Socket FM2											Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Google Chrome • Google Toolbar • Skype™ for Windows • Evernote® • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	<p><i>Some:</i> AMD Radeon HD Graphics, integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DP)@60Hz</p> <p><i>Some:</i> NVIDIA® GeForce® 605, PCI Express® 2.0 x16 adapter, DirectX 11, 512MB, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz</p>											
DP dongle	None											
Disk	SATA 6.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1											
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar											
eSATA port	None											
Media reader	None											
Chipset	AMD A75 Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®											
Modem	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, manual switch											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 27.5 lb (12.5 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk											
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3											
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 											
	RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M78 sheet;											
	For ThinkPlus™ service upgrade options, please go to S-TC sheet											

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Chassis intr	PS/2 port	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
2111-B2U	4x5	A4-5300	2GBx1	250G	7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	None	None	Win8 Pro64	10/23/12
2111-B3U	4x5	A6-5400B	4GBx1	500G	7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	None	None	Win8 Pro64	10/23/12
2111-C2U	4x5	A4-5300	2GBx1	250G	7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	None	None	Win7 Pro64	10/30/12
2111-C3U	4x5	A6-5400B	4GBx1	500G	7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	None	None	Win7 Pro64	10/30/12

- Small and medium business (SMB) model(s), part of the US TopSeller Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)													Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit													
Implementation	Processor in Socket FM2													Preloaded applications (only some listed) - Windows 7 models													
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													• ThinkVantage® Product Recovery • ThinkVantage Communication Utility • ThinkVantage Power Manager • Lenovo® Message Center Plus • Lenovo SimpleTap • Adobe® Reader® • Google Chrome • Google Toolbar • RapidBoot HDD Accelerator • Symantec™ VIP • Windows Live™ Essentials • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)													
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz</i>													- Windows 8 models													
DP dongle	None													• Lenovo Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Norton™ Studio • Intel AppUp® • AccuWeather • PC Device Stage • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)													
Disk	SATA 6.0Gb/s 7200 rpm													- All models													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													• ThinkVantage® System Update • View Management Utility • Lenovo Solution Center • Norton Internet Security (30 days of virus definitions) • Microsoft® Office preloaded; purchase a product key to activate • Evernote® • Skype™													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1																										
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar																										
eSATA port	None																										
Media reader	None																										
Chipset	AMD A75 Chipset																										
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																										
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)																										
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																										
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)																										
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																										
Speaker	Internal speaker for business audio																										
IEEE 1394	None																										
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																										
Modem	None																										
Security chip	Trusted Platform Module (TPM 1.2-compliant)																										
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																										
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																										
Power supply	280 watts with variable speed fan, manual switch																										
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 27.5 lb (12.5 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 																										
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk																										
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3																										
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																										
Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Safety slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 																											
RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet																											

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
1766-A7U	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	None	Pro 32	08/28/12
1766-B1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	None	Pro 64	08/28/12
1766-B2U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	None	Prem 32	08/28/12
1766-B3U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	Radeon HD 7560D	None	None	None	Pro 64	08/28/12
1766-B4U	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	None	Pro 64	08/28/12


• 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)											Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64 Some: Genuine Windows 7 Home Premium 32		
Implementation	Processor in Socket FM2										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Google Chrome• Google Toolbar• Skype™ for Windows• Evernote®• RapidBoot HDD Accelerator• Symantec™ VIP• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz													
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts with variable speed fan, manual switch													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 27.5 lb (12.5 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet													

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2	Win7 Global preload	Ann date (mm/dd/yy)
1562-A1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	ES52	None	Pro 32 08/28/12
1562-C1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	ES52	None	Prem 32 08/28/12
1562-C2U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	ES52	None	Pro 64 08/28/12
1562-C3U	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	ES52	None	Pro 64 08/28/12
1562-C4U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	Radeon HD 7560D	None	None	ES52	None	Pro 64 08/28/12
1562-C5U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	GeForce 605	None	None	ES52	None	Pro 64 08/28/12


•3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)												Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64 Some: Genuine Windows 7 Home Premium 32
Implementation Processor	Processor in Socket FM2											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Google Chrome• Google Toolbar• Skype™ for Windows• Evernote®• RapidBoot HDD Accelerator• Symantec™ VIP• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• InterVideo WinDVD® (DVD, DVD±RW)	
Graphics	Some: AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DP)@60Hz Some: NVIDIA® GeForce® 605 , PCI Express® 2.0 x16 adapter, DirectX 11, 512MB, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz											Security <ul style="list-style-type: none">• Security chip (see information on left)• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• Chassis intrusion switch on selected model(s)	
DP dongle	None											EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant	
Disk	SATA 6.0Gb/s 7200 rpm											Supports ThinkVantage Technologies	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet	
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1												
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	AMD A75 Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none">• Business black color; metal case• 6.9" W X 17.4" D X 16.3" H• 175mm W X 442mm D X 414mm H• 27.5 lb (12.5 kg) in maximum configuration• Toolless cover removal, toolless adapter retention• Toolless disk, optical drive removal												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk												
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												




Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
1562-E1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	ES52	None	Win8 Pro64	10/23/12
1562-E2U	4x5	A6-5400B	4GBx1	500G 7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	ES52	None	Win8 Pro64	10/23/12
1562-E3U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	Radeon HD 7560D	None	None	ES52	None	Win8 Pro64	10/23/12
1562-E4U	4x5	A8-5500B	4GBx1	1TB 7200	Bay	DVD±RW	None	Radeon HD 7450	None	None	ES52	None	Win8 Pro64	10/23/12
1562-F1U	4x5	A4-5300	2GBx1	250G 7200	Bay	DVD±RW	None	Radeon HD 7480D	None	None	ES52	None	Win7 Pro64	10/30/12

•3-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> AMD Accelerated Processor A4-5300 (dual-core, 3.4GHz, 1MB L2 cache), Turbo Core technology (up to 3.6GHz), integrated AMD Radeon™ HD 7480D Graphics, integrated DDR3 memory controller (up to 1600MHz) AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz) AMD Accelerated Processor A8-5500B (quad-core, 3.2GHz, 4MB L2 cache), Turbo Core technology (up to 3.7GHz), integrated AMD Radeon HD 7560D Graphics, integrated DDR3 memory controller (up to 1866MHz)											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in Socket FM2											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Google Chrome• Google Toolbar• RapidBoot HDD Accelerator• Symantec™ VIP• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• Intel AppUp®• AccuWeather• PC Device Stage• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage® System Update• View Management Utility• Lenovo Solution Center• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Evernote®• Skype™		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													
Graphics	Some: AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA) @60Hz; 2560x2048 (DP) @60Hz Some: AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I) @60Hz; works along with Intel HD Graphics to support up to four independent monitors													
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 27.5 lb (12.5 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
														
	EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet													


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2	Global (G) GMP (P)	Win7 preloaded	Ann date (mm/dd/yy)	
1565-A1U	4x5	A6-5400B	4GBx1	500G	7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	ES52	G P	Pro 64	08/28/12

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)										Preloaded operating system Genuine Windows® 7 Professional 64			
Implementation	Processor in Socket FM2										Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Business-in-a-Box 			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Google Chrome Google Toolbar Skype™ for Windows Evernote® RapidBoot HDD Accelerator Symantec™ VIP Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) 			
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; Maximum resolution: 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz													
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1													
Onboard SATA	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar													
eSATA port	None													
Media reader	None													
Chipset	AMD A75 Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 27.5 lb (12.5 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										EPEAT™ Gold rating ENERGY STAR 5.2-compliant ULE Gold RoHS-compliant Supports ThinkVantage Technologies			
											For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet			

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay	optical	Media reader	Graphics	Chassis intr switch	PS/2 port	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
1565-B1U	4x5	A6-5400B	4GBx1	500G	7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	ES52	G P	Win8 Pro64	10/23/12
1565-C1U	4x5	A6-5400B	4GBx1	500G	7200	Bay	DVD±RW	None	Radeon HD 7540D	None	None	ES52	G P	Win7 Pro64	10/30/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability AMD Accelerated Processor A6-5400B (dual-core, 3.6GHz, 1MB L2 cache), Turbo Core technology (up to 3.8GHz), integrated AMD Radeon HD 7540D Graphics, integrated DDR3 memory controller (up to 1866MHz)												Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in Socket FM2												Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Google Chrome• Google Toolbar• RapidBoot HDD Accelerator• Symantec™ VIP• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• Intel AppUp®• AccuWeather• PC Device Stage• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage® System Update• View Management Utility• Lenovo Solution Center• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Evernote®• Skype™		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets														
Graphics	AMD Radeon HD Graphics , integrated in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution:</i> 1920x1200 (VGA)@60Hz; 2560x2048 (DisplayPort)@60Hz														
DP dongle	None														
Disk Optical	SATA 6.0Gb/s 7200 rpm														
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Onboard SATA eSATA port	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1														
Media reader	Two SATA cables (each 1-drop to device), four SATA 6.0Gb/s connectors on planar None														
Chipset	AMD A75 Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort, optional keyboard (PS/2), optional mouse (PS/2)														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB device)														
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec														
IEEE 1394	None														
Ethernet Modem	One gigabit ethernet port, Realtek RTL8111E, Wake on LAN®														
Security chip	None														
Keyboard Mouse	Trusted Platform Module (TPM 1.2-compliant)														
Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Machine	Enhanced Optical USB Mouse, black, Lenovo logo														
	280 watts, autosensing, 85% PSU														
Bay	● Business black color; metal case ● 6.9" W X 17.4" D X 16.3" H ● 175mm W X 442mm D X 414mm H ● 27.5 lb (12.5 kg) in maximum configuration ● Toolless cover removal, toolless adapter retention ● Toolless disk, optical drive removal														
Slot	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
	Slot 1: half-length, full-height, PCI Express 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	 3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
	For compatible accessories, please go to O-M78 sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet														

ThinkCentre M82 Small and Tower

ThinkCentre®



Lenovo ThinkCentre M82
Small and Tower



Lenovo ThinkCentre M82 Tower
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M82 Small



Lenovo ThinkCentre M82 Small
with Lenovo ThinkVision Monitor



Lenovo ThinkCentre M82 Tower




Lenovo ThinkCentre M82 Tower

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3306-A1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 06/19/12
3306-A2U	4x3	i5-3470	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 06/19/12
3306-A3U	4x3	i5-3470	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 06/19/12
3306-A4U	4x3	i5-3470	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	None	None	Pro 64 06/19/12
3306-A5U	4x3	i5-3470	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7350	None	None	Stand	None	None	Pro 64 06/19/12
3306-A6U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	None	None	Pro 64 06/19/12
3306-D1U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 07/10/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	<i>Some:</i> Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, VGA)@60Hz <i>Some:</i> AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors <i>Some:</i> AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors											
DP dongle	None											
Disk Optical	SATA 6.0Gb/s 7200 rpm											
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											
eSATA port	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector											
Media reader	None											
Chipset	Intel Q75 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector											
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec											
IEEE 1394	Internal speaker for business audio											
Ethernet	None											
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®											
Modem	Intel Standard Manageability											
Security chip	None											
Keyboard	Trusted Platform Module (TPM 1.2-compliant)											
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Floor Stand	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	System floor stand for vertical orientation											
Machine	240 watts, autosensing, active Power Factor Correction											
Bay	Business black color; metal case 13.3" W X 15.2" D X 3.9" H 338mm W X 385mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention											
Slot	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• <i>Chassis intrusion switch on selected model(s)</i>											
	GREENGUARD® certified											
	RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M82 sheet;											
	For Lenovo service upgrade options, please go to S-TC sheet											


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)	
3306-B1U	4x3	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2000	None	None	Stand	None	None	Pro 64	07/10/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty


Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz												
DP dongle	None												
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector												
eSATA port Media reader	None None												
Chipset	Intel Q75 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector												
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec												
IEEE 1394	Internal speaker for business audio												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Manageability	Intel Standard Manageability												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	240 watts, autosensing, active Power Factor Correction												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader										Security		
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3										<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 		
											GREENGUARD® certified RoHS-compliant		
											Supports ThinkVantage Technologies		
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3306-B2U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 07/10/12
3306-B3U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	None	None	Pro 64 07/10/12
3306-F1U	4x3	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<p>Mainstream enterprise stability and manageability</p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>												<p>Preloaded operating system</p> <p>Genuine Windows® 7 Professional 64</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Implementation	<p>32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets</p>												
Memory	<p>Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</p>												
Graphics	<p>None</p>												
DP dongle	<p>SATA 6.0Gb/s 7200 rpm</p> <p>Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive</p> <p>Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset</p> <p>Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector</p>												
Disk	<p>None</p>												
Optical	<p>None</p>												
SATA controller	<p>Onboard SATA</p>												
eSATA port	<p>None</p>												
Media reader	<p>None</p>												
Chipset	<p>Intel Q75 Express Chipset</p>												
Front ports	<p>Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>												
Rear ports	<p>Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort</p>												
Rear audio ports	<p>Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)</p>												
Internal connector	<p>Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector</p>												
Audio	<p>High Definition (HD) Audio, Realtek® ALC662 codec</p>												
Speaker	<p>Internal speaker for business audio</p>												
IEEE 1394	<p>None</p>												
Ethernet	<p>One gigabit ethernet port, Intel 82579, Wake on LAN®</p>												
Manageability	<p>Intel Standard Manageability</p>												
Modem	<p>None</p>												
Security chip	<p>Trusted Platform Module (TPM 1.2-compliant)</p>												
Keyboard	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p>												
Mouse	<p>Enhanced Optical USB Mouse, black, Lenovo logo</p>												
Floor Stand	<p>System floor stand for vertical orientation</p>												
Power supply	<p>240 watts, autosensing, active Power Factor Correction</p>												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 												
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 3.5", 1" high, no access, std disk</p> <p>Bay 3: 3.5", .5" high, access, opt reader</p>												
Slot	<p>Slot 1: Low Profile, PCI Express 2.0 x16 (45w max)</p> <p>Slot 2: Low Profile, PCIe 2.0 x1</p> <p>Slot 3: Low Profile, 32-bit PCI 2.3</p> <p>Slot 4: Low Profile, 32-bit PCI 2.3</p>												
Limited Warranty	 <p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>												
	<p>For compatible accessories, please go to O-M82 sheet;</p> <p>For Lenovo service upgrade options, please go to S-TC sheet</p>												


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Display-Port Graphics	Chassis intr	Floor stand	ENERGY STAR 5.2 Global	Preload	Ann date (mm/dd/yy)
3306-C1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win8 Pro64 10/23/12
3306-F2U	4x3	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win8 Pro64 10/23/12
3306-F3U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	None	None Win8 Pro64 10/23/12
3306-F4U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win8 Pro64 10/23/12
3306-G1U	4x3	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win7 Pro64 10/23/12
3306-G2U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win7 Pro64 10/23/12
3306-G3U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None Win7 Pro64 10/23/12
3306-H1U	4x3	i7-3770	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	None	None Win7 Pro64 03/05/13
3306-J1U	4x3	i7-3770	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	None	None Win7 Pro64 03/12/13
3306-J2U	4x3	i5-3475S	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	None	None Win7 Pro64 03/12/13
3306-J3U	4x3	i5-3475S	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	None	None Win7 Pro64 03/12/13
Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit	
Implementation	Processor										Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® AppShop• Lenovo Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW)	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™	
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors										Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• Chassis intrusion switch on selected model(s)	
DP dongle	None										GREENGUARD® certified RoHS-compliant	
Disk	SATA 6.0Gb/s 7200 rpm										Supports ThinkVantage Technologies	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive										For compatible accessories, please go to O-M82 sheet;	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset										For Lenovo service upgrade options, please go to S-TC sheet	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector											
eSATA port	None											
Media reader	None											
Chipset	Intel Q75 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®											
Manageability	Intel Standard Manageability											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Floor Stand	System floor stand for vertical orientation											
Power supply	240 watts, autosensing, active Power Factor Correction											
Machine	<ul style="list-style-type: none">• Business black color; metal case• 13.3" W X 15.2" D X 3.9" H• 338mm W X 385mm D X 100mm H• 16.5 lb (7.5 kg) in maximum configuration• Toolless cover flips up and tilts backward on rear hinges• Toolless disk and optical drive removal• Toolless adapter retention											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader											
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											



Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3302-A1U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	06/19/12
3302-A2U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 32	06/19/12
3302-A3U	4x5	i5-3470	4GBx2 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	06/19/12
3302-A4U	4x5	i5-3470	4GBx2 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 7350	None	None	None	Pro 64	06/19/12
3302-A5U	4x5	i5-3470	4GBx2 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	None	Pro 64	06/19/12


- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64		
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Graphics	Some: Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors Some: AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors												
DP dongle	None												
Disk Optical	SATA 6.0Gb/s 7200 rpm												
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
eSATA port	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector												
Media reader	None												
Chipset	Intel Q75 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector												
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec												
IEEE 1394	Internal speaker for business audio												
Ethernet	None												
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Modem	Intel Standard Manageability												
Security chip	None												
Keyboard	Trusted Platform Module (TPM 1.2-compliant)												
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Power supply	Enhanced Optical USB Mouse, black, Lenovo logo												
Machine	280 watts with variable speed fan, manual switch												
Bay	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 												
Slot	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 5.25", 1.6" high, access, open</p> <p>Bay 3: 3.5", 1" high, access, opt reader</p> <p>Bay 4: 3.5", 1" high, no access, std disk</p> <p>Bay 5: 3.5", 1" high, no access, opt disk</p> <p>Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, 32-bit PCI 2.3</p> <p>Slot 4: half-length, full-height, 32-bit PCI 2.3</p>												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												




Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3302-B1U	4x5	i3-2120	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2000	None	None	None	None	Pro 64 07/10/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i3-2120 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz											
DP dongle	None											
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector											
eSATA port	None											
Media reader	None											
Chipset	Intel Q75 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector											
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec											
IEEE 1394	Internal speaker for business audio											
Ethernet	None											
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®											
Modem	Intel Standard Manageability											
Security chip	None											
Keyboard	Trusted Platform Module (TPM 1.2-compliant)											
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Power supply	Enhanced Optical USB Mouse, black, Lenovo logo											
Machine	280 watts with variable speed fan, manual switch											
Bay	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 											
Slot	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 5.25", 1.6" high, access, open</p> <p>Bay 3: 3.5", 1" high, access, opt reader</p> <p>Bay 4: 3.5", 1" high, no access, std disk</p> <p>Bay 5: 3.5", 1" high, no access, opt disk</p> <p>Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, 32-bit PCI 2.3</p> <p>Slot 4: half-length, full-height, 32-bit PCI 2.3</p>											
Limited Warranty	 <p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>											
	<p>Security</p> <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 											
	<p>GREENGUARD® certified</p> <p>RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p>											
	<p>For compatible accessories, please go to O-M82 sheet;</p> <p>For Lenovo service upgrade options, please go to S-TC sheet</p>											


Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3302-B2U	4x5	i5-3570	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	07/10/12
3302-B3U	4x5	i7-3770	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 4000	None	None	None	Pro 64	07/10/12
3302-E1U	4x5	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>											
DP dongle	None											
Disk	SATA 6.0Gb/s 7200 rpm											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector											
eSATA port	None											
Media reader	None											
Chipset	Intel Q75 Express Chipset											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)											
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec											
Speaker	Internal speaker for business audio											
IEEE 1394	None											
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®											
Manageability	Intel Standard Manageability											
Modem	None											
Security chip	Trusted Platform Module (TPM 1.2-compliant)											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											
Power supply	280 watts with variable speed fan, manual switch											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk											
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
												
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 											
	GREENGUARD® certified RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet											

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB	2nd Disk rpm	Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Preload	Ann date (mm/dd/yy)
3302-C1U	4x5	i5-3470	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win8 Pro64	10/23/12
3302-E2U	4x5	i3-3220	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win8 Pro64	10/23/12
3302-E3U	4x5	i5-3570	4GBx1 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win8 Pro64	10/23/12
3302-F1U	4x5	i3-3220	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win7 Pro64	10/23/12
3302-F2U	4x5	i5-3470	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win7 Pro64	10/23/12
3302-F3U	4x5	i5-3570	4GBx1 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win7 Pro64	10/23/12
3302-H1U	4x5	i5-3475S	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	None	Win7 Pro64	03/12/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology													Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation	Processor in LGA1155 socket													Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® AppShop• Lenovo Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA) @60Hz													
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts with variable speed fan, manual switch													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> - Padlock loop (in rear for opt padlock) - Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 													
	GREENGUARD® certified RoHS-compliant													
	Supports ThinkVantage Technologies													
	For compatible accessories, please go to O-M82 sheet;													
	For Lenovo service upgrade options, please go to S-TC sheet													

See footnotes for important warranty information

US models announced October 23, 2012 or March 12, 2013

©Lenovo

(MDTN1-20) March 2013


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Win7 Global	Win7 preload	Ann date (mm/dd/yy)
3395-A2U	4x3	i3-2130	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2000	None	None	Stand	None	None	Pro 64	06/19/12
3395-C6U	4x3	i3-2120	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	None	None	Pro 64	06/19/12
3395-C7U	4x3	G850	2GBx1 1600MHz	250G 7200	DVD±RW	None	Intel HD	None	None	Stand	None	None	Pro 32	06/19/12


•3-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Pentium® G850 Processor (2 cores / 2 threads , 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-2130 Processor (2 cores / 4 threads , 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64			
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, active Power Factor Correction													
Machine	<ul style="list-style-type: none">• Business black color; metal case• 13.3" W X 15.2" D X 3.9" H• 338mm W X 385mm D X 100mm H• 16.5 lb (7.5 kg) in maximum configuration• Toolless cover flips up and tilts backward on rear hinges• Toolless disk and optical drive removal• Toolless adapter retention													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Win7 Global	Ann date (mm/dd/yy)
3395-C4U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 06/19/12
3395-C5U	4x3	i5-3550	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 06/19/12
3395-D5U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 32 06/19/12
3395-D6U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 32 06/19/12
3395-G1U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Pro 64 07/10/12


•3-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology										Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64		
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>												
DP dongle	None												
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector												
eSATA port	None												
Media reader	None												
Chipset	Intel Q75 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Manageability	Intel Standard Manageability												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	240 watts, autosensing, active Power Factor Correction												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader												
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis	Floor intr switch	ENERGY stand	STAR 5.2 Global	Preload	Ann date (mm/dd/yy)														
3395-H7U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	None	None	Win8 Pro64	10/23/12															
3395-N1U	4x3	i3-2130	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	None	None	Win7 Pro64	10/23/12														
3395-N2U	4x3	i3-2120	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	None	None	Win7 Pro64	10/23/12														
3395-N3U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Win7 Pro64	10/23/12														
3395-AAU	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Win8 Pro64	11/27/12														
3395-R1U	4x3	G2120	4GBx1 1600MHz	500G 7200	DVD±RW	None	Intel HD	None	None	Stand	None	None	Win7 Pro64	12/04/12														
3395-R2U	4x3	G2020	4GBx1 1600MHz	500G 7200	DVD±RW	None	Intel HD	None	None	Stand	None	None	Win7 Pro64	01/22/13														
3395-CAU	4x3	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	None	None	Win7 Pro64	03/05/13														
3395-DAU	4x3	i5-3475S	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	None	None	Win7 Pro64	03/12/13														
Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Pentium® G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1600MHz) Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz) Intel Core i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz) Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology																											
Implementation	Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit																
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® AppShop• Lenovo Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™																
Graphics	Intel HD Graphics / 2000 / 2500 / 4000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>																											
DP dongle	None																											
Disk	SATA 6.0Gb/s 7200 rpm																											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																											
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset																											
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector																											
eSATA port	None																											
Media reader	None																											
Chipset	Intel Q75 Express Chipset																											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																											
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																											
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector																											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																											
Speaker	Internal speaker for business audio																											
IEEE 1394	None																											
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																											
Manageability	Intel Standard Manageability																											
Modem	None																											
Security chip	Trusted Platform Module (TPM 1.2-compliant)																											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																											
Floor Stand	Some: System floor stand for vertical orientation																											
Power supply	240 watts, autosensing, active Power Factor Correction																											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 																											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader																											
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3																											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																											
																												
GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet																												


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Win7 Global	Win7 preload	Ann date (mm/dd/yy)
2756-D3U	4x3	i3-2120	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None	Pro 64	06/05/12
2756-D4U	4x3	G850	2GBx1 1600MHz	250G 7200	DVD±RW	None	Intel HD	None	None	Stand	ES52	None	Pro 64	06/05/12
2756-D5U	4x3	G630	2GBx1 1600MHz	250G 7200	DVD±RW	None	Intel HD	None	None	Stand	ES52	None	Pro 64	06/05/12
2756-D6U	4x3	i3-2120	4GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None	Pro 64	06/05/12


•3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none">• Business black color; metal case• 13.3" W X 15.2" D X 3.9" H• 338mm W X 385mm D X 100mm H• 16.5 lb (7.5 kg) in maximum configuration• Toolless cover flips up and tilts backward on rear hinges• Toolless disk and optical drive removal• Toolless adapter retention													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	 The diagram illustrates the internal drive bays of the ThinkCentre M82 Small. It shows two rectangular slots side-by-side. The left slot is labeled "disk" and the right slot is labeled "optical". Below these labels, there are three small horizontal arrows pointing to the right, indicating the direction of insertion for the drives.													
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle		Chassis intr	Floor stand	ENERGY STAR 5.2		Win7 preload	Ann date (mm/dd/yy)
								intr	dongle			Global	Local		
2756-B1U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 64	06/05/12	
2756-B3U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 64	06/05/12	
2756-D1U	4x3	i5-3550	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 64	06/05/12	
2756-D2U	4x3	i7-3770	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	None	Pro 64	06/05/12	
2756-D7U	4x3	i5-3550	4GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 64	06/05/12	
2756-F1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 32	06/05/12	
2756-F2U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 32	06/05/12	
2756-F3U	4x3	i7-3770	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	None	Pro 32	06/05/12	
2756-F4U	4x3	i5-3470	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Pro 64	06/05/12	

- 3-year limited warranty

Positioning	Mainstream enterprise stability and manageability	Preloaded operating system
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads) , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64
Implementation	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager
Memory		Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility Lenovo AppShop Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q75 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Manageability	Intel Standard Manageability	
Modem	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	Security
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	<ul style="list-style-type: none"> Security chip (see information on left)
Floor Stand	System floor stand for vertical orientation	<ul style="list-style-type: none"> Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
Power supply	240 watts, autotransformer, 85% PSU	<ul style="list-style-type: none"> Cable lock Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement <i>Chassis intrusion switch on selected model(s)</i>
Machine	<ul style="list-style-type: none"> Business black color; metal case 13.3" W X 15.2" D X 3.9" H 338mm W X 385mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet




Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Display-Port Graphics	Chassis intr dongle	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
2756-J2U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2756-L4U	4x3	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2756-L5U	4x3	i3-3240	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2756-L6U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win8 Pro64 10/23/12
2756-L7U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	None	Win8 Pro64 10/23/12

• 3-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology										Preloaded operating system Windows® 8 Pro 64-bit Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 												
Implementation	Processor in LGA1155 socket																						
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets																						
Graphics	Some: Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors																						
DP dongle	None																						
Disk	SATA 6.0Gb/s 7200 rpm																						
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																						
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset																						
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector																						
eSATA port	None																						
Media reader	None																						
Chipset	Intel Q75 Express Chipset																						
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																						
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																						
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																						
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector																						
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																						
Speaker	Internal speaker for business audio																						
IEEE 1394	None																						
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																						
Manageability	Intel Standard Manageability																						
Modem	None																						
Security chip	Trusted Platform Module (TPM 1.2-compliant)																						
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																						
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																						
Floor Stand	System floor stand for vertical orientation																						
Power supply	240 watts, autosensing, 85% PSU																						
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 																						
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader																						
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3																						
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																						
																							
Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 																							
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant																							
Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet																							

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port	Chassis intr	Floor stand	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
2756-N3U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N4U	4x3	i3-2130	4GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N5U	4x3	i3-2130	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N6U	4x3	G870	2GBx1 1600MHz	250G 7200	DVD±RW	None	Intel HD	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N7U	4x3	G640	2GBx1 1600MHz	250G 7200	DVD±RW	None	Intel HD	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N8U	4x3	i7-3770	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	None	Win7 Pro64	10/23/12
2756-N9U	4x3	i5-3470	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	None	Win7 Pro64	10/23/12

•3-year limited warranty


Positioning Processor	Mainstream enterprise stability and manageability Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													
Implementation	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo® AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 													
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													
Graphics	Intel HD Graphics / 2000 / 2500 / 4000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm													
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
eSATA port	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													
IEEE 1394	Internal speaker for business audio													
Ethernet	None													
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Modem	Intel Standard Manageability													
Security chip	None													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 													
Bay														
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet													

ThinkCentre M82 Small (2929) - ES 5.2 (GMP) - withdrawn

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Global GMP (P) preload	Win7	Ann date (mm/dd/yy)
	2929-A1U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	G P	Pro 64
2929-B1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	G P	Pro 64	06/19/12
2929-D1U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	G P	Pro 64	08/14/12

- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty


Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads) , 3.3GHz, 6MB cache, Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache, Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q75 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Manageability	Intel Standard Manageability	
Modem	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Floor Stand	System floor stand for vertical orientation	
Power supply	240 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information
US models announced June 5, June 19, or August 14, 2012

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr	Floor switch	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
2929-C1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	G P	Win8 Pro64	10/23/12
2929-E1U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	G P	Win7 Pro64	10/23/12

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	Mainstream enterprise stability and manageability											Preloaded operating system		
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											<i>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</i>		
Implementation												<i>Some: Windows 8 Pro 64-bit</i>		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets											Preloaded applications (only some listed)		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz											- Windows 7 models		
DP dongle	None											<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● Lenovo® AppShop ● Lenovo Message Center Plus ● Lenovo SimpleTap ● Adobe® Reader® ● Windows Live™ Essentials ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 		
Disk Optical	SATA 6.0Gb/s 7200 rpm											- Windows 8 models		
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											<ul style="list-style-type: none"> ● Lenovo Support ● Lenovo Companion ● Lenovo Cloud Storage ● Norton™ Studio ● AccuWeather ● Evernote® ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) 		
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											- All models		
eSATA port	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector											<ul style="list-style-type: none"> ● ThinkVantage System Update ● Lenovo Solution Center ● View Management Utility ● Norton Internet Security (30 days of virus definitions) ● Microsoft® Office preloaded; purchase a product key to activate ● Skype™ 		
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													
IEEE 1394	Internal speaker for business audio													
Ethernet	None													
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Modem	Intel Standard Manageability													
Security chip	None													
Keyboard	Trusted Platform Module (TPM 1.2-compliant)													
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Floor Stand	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	System floor stand for vertical orientation													
Machine	240 watts, autosensing, 85% PSU													
Bay	<ul style="list-style-type: none"> ● Business black color; metal case ● 13.3" W X 15.2" D X 3.9" H ● 338mm W X 385mm D X 100mm H ● 16.5 lb (7.5 kg) in maximum configuration ● Toolless cover flips up and tilts backward on rear hinges ● Toolless disk and optical drive removal ● Toolless adapter retention 													
Slot	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													





ThinkCentre M82 Tower (3392) - withdrawn

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB	2nd Disk rpm	Bay	SATA optical	Media reader	Graphics	Display Port	Chassis intrusion	ENERGY STAR	Global	Win7 preload	Ann date (mm/dd/yy)
										dongle	switch	5.2			
3392-B6U	4x5	i3-2130	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	None	Pro 64	06/19/12
3392-C1U	4x5	i3-2120	4GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	None	Pro 64	06/19/12
3392-C3U	4x5	i3-2120	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	None	Pro 64	06/19/12
3392-C7U	4x5	G630	2GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	None	Pro 64	06/19/12
3392-C8U	4x5	G850	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	None	Pro 64	06/19/12
3392-F3U	4x5	G630	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	None	Pro 64	07/10/12

- 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Pentium® G630 Processor (2 cores / 2 threads) , 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G850 Processor (2 cores / 2 threads) , 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-2130 Processor (2 cores / 4 threads) , 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q75 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Manageability	Intel Standard Manageability	
Modem	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	280 watts with variable speed fan, manual switch	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 	Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i>
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk	
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	



Limited Warranty **3-years, limited onsite service**, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available


please go to O-M82 sheet;
For Lenovo service upgrade options,
please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)
3392-D2U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 32	06/19/12
3392-C2U	4x5	i5-3550	4GBx1 1600MHz	250G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	06/19/12
3392-C4U	4x5	i7-3770	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	None	Pro 64	06/19/12
3392-C5U	4x5	i5-3550	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	06/19/12
3392-D7U	4x5	i5-3570	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 32	06/19/12
3392-D8U	4x5	i7-3770	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	None	Pro 32	06/19/12
3392-D9U	4x5	i5-3470	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	None	HD 2500	None	None	None	Pro 64	06/19/12


•3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												
Implementation													
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz												
DP dongle	None												
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector												
eSATA port	None												
Media reader	None												
Chipset	Intel Q75 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Manageability	Intel Standard Manageability												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts with variable speed fan, manual switch												
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 6.9" W X 17.4" D X 16.3" H ● 175mm W X 442mm D X 414mm H ● 24.2 lb (11.0 kg) in maximum configuration ● Toolless cover removal, toolless adapter retention ● Toolless disk, optical drive removal 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk												
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
	Preloaded operating system <i>Some:</i> Genuine Windows® 7 Professional 32 <i>Some:</i> Genuine Windows 7 Professional 64												
	Ready to install applications (only some listed)												
	<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager 												
	Preloaded applications (only some listed)												
	<ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● View Management Utility ● Lenovo AppShop ● Lenovo Solution Center ● Lenovo Message Center Plus ● Lenovo SimpleTap ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ for Windows ● Windows Live™ Essentials ● Microsoft® Office preloaded; purchase a product key to activate ● Corel® Burn.Now™ (DVD±RW) ● Corel DVD MovieFactory® (DVD±RW) 												
	Security <ul style="list-style-type: none"> ● Security chip (see information on left) ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Cable lock ● Power-on password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Serial port I/O control ● Individual USB port disablement ● Chassis intrusion switch on selected model(s) 												
	GREENGUARD® certified RoHS-compliant												
	Supports ThinkVantage Technologies												
	For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display Port	Chassis intrusion switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3392-G3U	4x5	i5-3470	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win8 Pro64	10/23/12	
3392-K8U	4x5	i7-3770	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	None	Win7 Pro64	10/23/12	
3392-K9U	4x5	i5-3570	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win7 Pro64	10/23/12	
3392-L1U	4x5	i5-3470	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	HD 2500	None	None	None	Win7 Pro64	10/23/12	
3392-R1U	4x5	i5-3475S	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	None	Win7 Pro64	03/12/13	


Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation														Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® AppShop• Lenovo Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton™ Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets															
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz															
DP dongle	None															
Disk	SATA 6.0Gb/s 7200 rpm															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector															
eSATA port	None															
Media reader	None															
Chipset	Intel Q75 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	Internal speaker for business audio															
IEEE 1394	None															
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®															
Manageability	Intel Standard Manageability															
Modem	None															
Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	280 watts with variable speed fan, manual switch															
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 															
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk															
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3															
																
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															
	GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet															

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	Disk Bay	SATA optical	Media reader	Graphics	Display Port	Chassis intrusion switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)
3392-K3U	4x5	i3-2130	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	Win7 Pro64	10/23/12	
3392-K4U	4x5	G870	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	Win7 Pro64	10/23/12	
3392-K5U	4x5	G640	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	Win7 Pro64	10/23/12	
3392-K6U	4x5	i3-2130	4GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	Win7 Pro64	10/23/12	
3392-K7U	4x5	i3-2120	2GBx1 1600MHz	250G	7200	Bay	DVD±RW	None	HD 2000	None	None	None	Win7 Pro64	10/23/12	
3392-N1U	4x5	G2120	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	Win7 Pro64	12/04/12	
3392-N2U	4x5	G2020	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	Intel HD	None	None	None	Win7 Pro64	01/22/13	

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Pentium® G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1066MHz) Intel Pentium G2020 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1333MHz) Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated DDR3 memory controller (up to 1600MHz) Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz) Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz)												Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo® AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Implementation Processor	Processor in LGA1155 socket															
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>															
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>															
DP dongle	None															
Disk	SATA 6.0Gb/s 7200 rpm															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector															
eSATA port	None															
Media reader	None															
Chipset	Intel Q75 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector															
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec															
IEEE 1394	Internal speaker for business audio															
Ethernet	None															
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®															
Modem	Intel Standard Manageability															
Security chip	None															
Keyboard	Trusted Platform Module (TPM 1.2-compliant)															
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Power supply	Enhanced Optical USB Mouse, black, Lenovo logo															
Machine	280 watts with variable speed fan, manual switch															
Bay	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 															
Slot	<ul style="list-style-type: none"> Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk 															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															
																

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2 Global	Win7 preload	Ann date (mm/dd/yy)	
2697-E5U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Pro 32	06/05/12
2697-M1U	4x5	i7-3770	4GBx2 1600MHz	1TB 7200	Bay	DVD±RW	Media	HD 4000	None	Switch	ES52	None	Pro 64	11/06/12


•3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64	
Implementation												Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz											Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)	
DP dongle	None												
Disk	SATA 6.0Gb/s 7200 rpm												
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset												
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector												
eSATA port	None												
Media reader	Some: 29-in-1 media reader, internal USB 2.0												
Chipset	Intel Q75 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)												
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Manageability	Intel Standard Manageability												
Modem	None												
Security chip	Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	280 watts, autosensing, 85% PSU												
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 24.2 lb (11.0 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk												
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
													
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Display Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Global	Preload	Ann date (mm/dd/yy)	
2697-H1U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win8 Pro64	10/23/12
2697-J3U	4x5	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win8 Pro64	10/23/12
2697-J4U	4x5	i3-3240	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win8 Pro64	10/23/12
2697-J5U	4x5	i7-3770	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	None	Win8 Pro64	10/23/12
2697-J6U	4x5	i7-3770	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	None	Win8 Pro64	10/23/12
2697-L2U	4x5	i3-3220	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win7 Pro64	10/23/12
2697-L3U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win7 Pro64	10/23/12
2697-L4U	4x5	i5-3570	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	None	Win7 Pro64	10/23/12
2697-L6U	4x5	i3-2130	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2000	None	None	ES52	None	Win7 Pro64	10/23/12
Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated DDR3 memory controller (up to 1333MHz) Intel Core i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated DDR3 memory controller (up to 1600MHz) Intel Core i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation	Some: Intel HD Graphics 2000 / 2500 / 4000 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7450 , DirectX 11, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors										Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">● ThinkVantage® Product Recovery● ThinkVantage Communication Utility● ThinkVantage Power Manager● Lenovo® AppShop● Lenovo Message Center Plus● Lenovo SimpleTap● Adobe® Reader®● Windows Live™ Essentials● Corel® Burn.Now™ (DVD±RW)● Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">● Lenovo Support● Lenovo Companion● Lenovo Cloud Storage● Norton™ Studio● AccuWeather● Evernote®● Cyberlink Power2Go (DVD±RW)● Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">● ThinkVantage System Update● Lenovo Solution Center● View Management Utility● Norton Internet Security (30 days of virus definitions)● Microsoft® Office preloaded; purchase a product key to activate● Skype™			
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm													
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
eSATA port	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													
IEEE 1394	Internal speaker for business audio													
Ethernet	None													
Manageability	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Modem	Intel Standard Manageability													
Security chip	None													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> ● Business black color; metal case ● 6.9" W X 17.4" D X 16.3" H ● 175mm W X 442mm D X 414mm H ● 24.2 lb (11.0 kg) in maximum configuration ● Toolless cover removal, toolless adapter retention ● Toolless disk, optical drive removal 													
Bay														
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
2742-A1U	4x5	i5-3550	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	G P	Pro 64	06/05/12
2742-B1U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	G P	Pro 64	06/19/12
2742-D1U	4x5	i5-3570	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	G P	Pro 64	08/14/12


•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed)
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	<ul style="list-style-type: none"> Rescue and Recovery™ Password Manager
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA) @60Hz</i>	Preloaded applications (only some listed)
DP dongle	None	<ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Power Manager View Management Utility Lenovo AppShop Lenovo Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW)
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q75 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Manageability	Intel Standard Manageability	
Modem	None	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	280 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 24.2 lb (11.0 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk	
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M82 sheet; For Lenovo service upgrade options, please go to S-TC sheet	

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
2742-C1U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	G P	Win8 Pro64	10/23/12
2742-E1U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	G P	Win7 Pro64	10/23/12

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Mainstream enterprise stability and manageability Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation												Preloaded applications (only some listed) - Windows 7 models		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none">● ThinkVantage® Product Recovery● ThinkVantage Communication Utility● ThinkVantage Power Manager● Lenovo® AppShop● Lenovo Message Center Plus● Lenovo SimpleTap● Adobe® Reader®● Windows Live™ Essentials● Corel® Burn.Now™ (DVD±RW)● Corel DVD MovieFactory® (DVD±RW)		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz											- Windows 8 models		
DP dongle	None											<ul style="list-style-type: none">● Lenovo Support● Lenovo Companion● Lenovo Cloud Storage● Norton™ Studio● AccuWeather● Evernote®● Cyberlink Power2Go (DVD±RW)● Cyberlink PowerProducer (DVD±RW)		
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											- All models		
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset											<ul style="list-style-type: none">● ThinkVantage System Update● Lenovo Solution Center● View Management Utility● Norton Internet Security (30 days of virus definitions)● Microsoft® Office preloaded; purchase a product key to activate● Skype™		
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 6.0Gb/s connector, two SATA 3.0Gb/s connectors, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q75 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none">● Business black color; metal case● 6.9" W X 17.4" D X 16.3" H● 175mm W X 442mm D X 414mm H● 24.2 lb (11.0 kg) in maximum configuration● Toolless cover removal, toolless adapter retention● Toolless disk, optical drive removal													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													



Memory		Multimedia	
2GB PC3-12800 DDR3 UDIMM	0A65728 ann 06/05/12	ThinkPad In-Ear Headphones with mic ⁶⁰	57Y4488 ann 01/07/10
4GB PC3-12800 DDR3 UDIMM	0A65729 ann 06/05/12	Lenovo Mini Speakers M220	55Y2033 ann 01/07/10
8GB PC3-12800 DDR3 UDIMM	0A65730 ann 06/05/12	Lenovo Speakers M0520 (black)	57Y6360 ann 02/08/11
More information at www.lenovo.com/support/desktopmemorycompatibility		Lenovo Speakers M0520 (red)	57Y6361 ann 02/08/11
Optical		Lenovo Headset P550	55Y2065
DVD-ROM DL SATA 1.5Gb/s 16X-48X Max ⁴	41N5618 ann 09/26/06	Lenovo Headset P950 (black)	57Y6605 ann 02/08/11
Lenovo® Super Multi-Burner SATA Drive	0A65618 ann 08/23/11	⁶⁰ Has a 1.2 meter (3.9-foot) cable. Best when systems are in close proximity. Example: SFF placed on a desk.	
Storage and removable storage		Security	
500GB SATA 3.0Gb/s Disk (7200 rpm)	43R1990 ann 11/06/07	Kensington® MicroSaver® Cable Lock ⁵⁶	73P2582 ann 12/29/03
1TB SATA 3.0Gb/s Disk (7200 rpm)	45J7918 ann 08/19/08	Kensington Twin Head Cable Lock ⁵⁶	45K1620 ann 09/30/08
180GB Solid State Drive	0B47308 ann 01/29/13	Lenovo Security Cable Lock ⁵⁶	57Y4303 ann 08/24/10
USB 2.0 Portable 500GB Hard Disk	45K1690 ann 05/26/09	USB Gemplus GemPC Smart Card Reader	41N3040 ann 02/21/06
USB 3.0 Secure 500GB Hard Drive	0A65619 ann 11/29/11	⁵⁶ Attaching to any form factor not only secures the ThinkCentre to the work area, but it also prevents users from opening the chassis itself.	
USB 3.0 Secure 750GB Hard Drive	0A65616 ann 11/29/11	Monitors	
USB 3.0 Secure 1TB Hard Drive	0A65621 ann 08/28/12	ThinkVision LT1952p Wide 19" (VGA, DP, DVI-D) ⁶⁹	2448MB6 ann 09/13/11
Slim USB Portable DVD Burner	0A33988 ann 06/14/11	ThinkVision L2251x Wide 22" (VGA, DP)	2578HB6 ann 10/20/09
Graphics		ThinkVision LT2323p Wide 23" (VGA, DP, DVI-D) ⁶⁹	3024HC1 ann 05/01/12
<i>Small 2756/2929 support Low Profile:</i>		⁶⁹ DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537).	
NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	0B47077 ann 01/29/13	More information at www.lenovo.com/support/monitors	
<i>Tower 2697/2742 support 75 watts max:</i>		Monitor Accessories ⁴⁶	
NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	0B47077 ann 01/29/13	Lenovo USB 3.0 to DVI/VGA Monitor Adapter	0B47072 ann 08/14/12
⁶⁷ Simultaneously use the graphic card monitor ports along with the systems integrated monitor ports when Multi-Monitor Support is enabled in BIOS Setup.		DisplayPort™ to Single-link DVI-D Cable	45J7915 ann 08/05/08
More information at www.lenovo.com/support/graphiccards		DisplayPort to VGA Monitor Cable	57Y4393 ann 08/04/09
Keyboard		DisplayPort to DisplayPort Monitor Cable	0A36537 ann 09/13/11
Preferred Pro USB Keyboard	73P5220 ann 06/21/05	Lenovo USB Soundbar	0A36190 ann 05/01/12
Enhanced Performance USB Keyboard	73P2620 ann 03/23/04	Kensington MicroSaver Cable Lock ⁵⁶	73P2582 ann 12/29/03
Ultraslim Plus Wireless Keyboard and Mouse ⁵²	0A34032 ann 04/05/11	Kensington Twin Head Cable Lock ⁵⁶	45K1620 ann 09/30/08
ThinkPad® USB Keyboard with TrackPoint	55Y9003 ann 08/18/09	Lenovo Security Cable Lock ⁵⁶	57Y4303 ann 08/24/10
Lenovo USB Fingerprint Keyboard	73P4730 ann 02/22/05	ThinkCentre Extend Arm	57Y4352 ann 07/06/10
Lenovo USB Smartcard Keyboard	51J0155 ann 03/24/09	⁴⁶ Compatible on selected Lenovo and ThinkVision monitors.	
⁵² Wireless via 2.4GHz technology using a micro-size USB receiver.		More information at www.lenovo.com/support/monitoraccessories	
More information at www.lenovo.com/support/keyboards		For more information on accessories: www.lenovo.com/accessories Purchase Lenovo accessories	
Mouse		www.lenovo.com/support/accessories Product specifications on Lenovo Support	
Lenovo Optical Mouse (USB)	06P4069 ann 05/21/03	www.lenovo.com/accessoriesguide Option Compatibility Matrix (OCM) and accessory brochures	
Lenovo ScrollPoint® Mouse(USB, Optical)	31P7405 ann 08/27/02	www.lenovoquickpick.com An Options Compatibility Configurator for Lenovo systems	
ThinkPad Travel Mouse (USB, Optical)	31P7410 ann 06/04/02		
Lenovo Laser Mouse (USB)	41U3074 ann 01/23/07		
Lenovo Wireless Laser Mouse ⁵²	0A36188 ann 12/20/11		
ThinkPad USB Laser Mouse	57Y4635 ann 12/15/09		
More information at www.lenovo.com/support/mice			
Modem			
USB 2.0 Lenovo Modem	43R1814 ann 02/26/08		

Type-model	Slot x bay	Pro-cessor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Additional Graphics	2nd Front port	2nd serial port	2nd Parallel port	Chassis PS/2 port	intrusion switch	Floor stand	ENERGY STAR 5.2	Preload	Ann date (mm/dd/yy)
10AN0008US	3x4	i7-4770	8GBx1	1TB 7200	DVD±RW	Intel 105	GT 620	USB	Serial	None	None	None	Stand	None	Win7 Pro64 (DG)	07/30/13
10AN0009US	3x4	i7-4770	4GBx1	500G 7200	DVD±RW	None	HD 4600	USB	None	None	None	None	Stand	None	Win7 Pro64 (DG)	07/30/13
10AN000AUS	3x4	i5-4570	8GBx1	1TB 7200	DVD±RW	Intel 105	HD 4600	USB	None	None	None	None	Stand	None	Win7 Pro64 (DG)	07/30/13
10AN000BUS	3x4	i5-4570	4GBx1	500G 7200	DVD±RW	None	HD 4600	USB	None	None	None	None	Stand	None	Win7 Pro64 (DG)	07/30/13
10AN000CUS	3x4	i5-4570	4GBx1	500G 7200	DVD±RW	Intel 105	HD 4600	USB	Serial	Parallel	PS/2	None	Stand	None	Win7 Pro64 (DG)	07/30/13

• 1-year limited warranty

Positioning Processor	<i>Mainstream enterprise stability and manageability</i> Intel® Core™ i5-4570 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-4770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology													Preloaded operating system	
Implementation	Processor in LGA1150 socket													Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													Ready to install applications (only some listed)	
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: NVIDIA® Geforce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz, works along with Intel HD Graphics to support up to five independent monitors													Preloaded applications (only some listed)	
DP dongle	None													• ThinkVantage® Product Recovery	
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide													• ThinkVantage System Update	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													• ThinkVantage Communication Utility	
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset													• Desktop Power Manager	
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)													• View Management Utility	
eSATA port	None													• Lenovo Cloud Storage by SugarSync	
Media reader	None													• Lenovo Solution Center	
Chipset	Intel Q85 Express Chipset													• Lenovo Message Center Plus	
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													• Norton™ Internet Security (30 days of virus definitions)	
Rear ports	Two USB 3.0, four USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), optional keyboard (PS/2), optional mouse (PS/2), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models													• Adobe® Reader®	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													• Skype™	
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1													• Microsoft Office preloaded; purchase a product key to activate	
Bluetooth	None													• Cyberlink PowerDVD (DVD±RW, DVD)	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													• Cyberlink Power2Go (DVD±RW)	
Speaker	Internal speaker for business audio (1 watt)													• Cyberlink PowerProducer (DVD±RW)	
IEEE 1394	None													• Evernote	
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®													• Intel AppUp	
Manageability	Intel Standard Manageability													• Intel Small Business Advantage	
Modem	None													• Nitro Pro	
Security chip	Trusted Platform Module (TPM1.2-compliant)													Security	
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo													• Security chip (see information on left)	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													• One lock to secure both cover and entire system to fixed object:	
Floor Stand	Optional system floor stand for vertical orientation													• Padlock loop (in rear for opt padlock)	
Power supply	240 watts, autotensioning													• Security slot (in rear for optional Kensington® MicroSaver® cable)	
Machine	<ul style="list-style-type: none"> • SFF Pro (12.9L), business black color; metal case • (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm • 17.20 lb (7.8 kg) in maximum configuration • Toolless cover removal, adapter retention • Toolless disk and optical drive removal 													• Power-on password	
Bay	Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, opt, come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader													• Administrator password	
Slot	Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max)													• Hard disk password	
Limited Warranty	1-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													• Boot sequence control	
														• Boot without keyboard and mouse	
														• Serial port I/O control	
														• Individual USB port disablement	
														• Chassis intrusion switch on selected model(s)	
														EPEAT™ Gold rating	
														ULE Gold	
														Cisco EnergyWise compatible	
														GREENGUARD® certified	
														RoHS-compliant	
														Supports ThinkVantage Technologies	
														For compatible accessories, please go to TC-AQP sheet;	
														For Lenovo service upgrade options, please go to S-TC sheet	

See footnotes for important warranty information

US model(s) announced July 30, 2013

US model(s) withdrawn effective November 2013

©Lenovo

(MSK1S-5) November 2013

ThinkCentre M92/M92p Tiny, Small, Tower

ThinkCentre®



Lenovo ThinkCentre M92/M92p Tiny
with Optional Serial Port or DisplayPort



Lenovo ThinkCentre M92/M92p Tiny
with Floor Stand



Lenovo ThinkCentre M92/M92p Small



Lenovo ThinkCentre M92/M92p Tiny
with VESA Mount



Lenovo ThinkCentre M92/M92p Tower



Lenovo ThinkCentre M92/M92p Tiny
with External Optical Box

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3234-A6U	i3-2120T	4GBx1	500G 5400	None	HD 2000	None	None	None	Stand	None	ES52	None	None	Pro 64 06/05/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>										Preloaded operating system			
Processor	Intel® Core™ i3-2120T Processor (2 cores / 4 threads, 2.6GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Genuine Windows® 7 Professional 64			
Implementation											Ready to install applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>										Preloaded applications (only some listed)			
DP dongle	None										<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate 			
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm													
External optical	None													
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	None													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
VESA mount	None													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 										Security			
Limited Warranty	1-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
											EPEAT™ Gold rating			
											ENERGY STAR® 5.2-compliant			
											ULE Gold			
											Cisco EnergyWise compatible			
											GREENGUARD® certified			
											RoHS-compliant			
											Supports ThinkVantage Technologies			
											For compatible accessories, please go to O-M92 sheet;			
											For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
2121-B2U	i5-3470T	2GBx1	8G SSD	None	HD 2500	None	None	None	Stand	Mount	ES52	vPro	None	Emb 32	07/10/12
2121-B3U	i5-3470T	2GBx1	8G SSD	None	HD 2500	Intel 2230 + BT	None	None	Stand	Mount	ES52	vPro	None	Emb 32	07/10/12
2121-F3U	i5-3470T	2GBx1	8G SSD	None	HD 2500	Intel 105	DP	None	Stand	None	ES52	vPro	None	Emb 32	03/05/13

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	Ultimate security, stability, and manageability for the enterprise											Preloaded operating system			
Processor	Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Genuine Windows® 7 Embedded 32			
Implementation												Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											<ul style="list-style-type: none"> • Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz														
DP dongle	None														
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide														
External optical	None														
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset														
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar														
eSATA port	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo											Security			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo											<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) 			
Floor Stand	System floor stand for vertical orientation											<ul style="list-style-type: none"> • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 			
VESA mount	<i>Some:</i> Supports VESA 75mm and 100mm mount standard														
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU														
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant			
	Supports ThinkVantage Technologies											For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
2121-A1U	i5-3470T	4GBx1	500G	7200	DVD±RW	HD 2500	None	DP	None	Mount	ES52	vPro	None	Pro 64 07/10/12
2121-A2U	i5-3470T	4GBx1	500G	7200	None	HD 2500	None	DP	None	Stand	Mount	ES52	vPro	None Pro 64 07/10/12
2121-A3U	i5-3470T	4GBx1	320G	7200	None	HD 2500	None	DP	None	Stand	Mount	ES52	vPro	None Pro 64 07/10/12
2121-A4U	i5-3470T	4GBx1	500G	7200	DVD±RW	HD 2500	None	Serial	None	Mount	ES52	vPro	None	Pro 64 07/10/12
2121-A5U	i5-3470T	4GBx1	500G	7200	DVD±RW	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	vPro	None	Pro 64 07/10/12
2121-A6U	i5-3470T	4GBx1	500G	7200	None	HD 2500	Intel 2230 + BT	None	None	Mount	ES52	vPro	None	Pro 64 07/10/12
2121-A7U	i5-3470T	4GBx1	500G	7200	None	HD 2500	Intel 2230 + BT	None	None	Stand	Mount	ES52	vPro	None Pro 64 07/10/12
2121-B1U	i5-3470T	4GBx1	500G	7200	None	HD 2500	None	DP	None	Stand	Mount	ES52	vPro	None Pro 64 07/10/12
2121-C8U	i5-3470T	4GBx1	500G	7200	DVD±RW	HD 2500	Intel 2230 + BT	DP	None	Mount	ES52	vPro	None	Pro 64 08/14/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty


Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo Simple Tap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk	SATA 3.0Gb/s, 2.5" Wide, 7200 rpm													
External optical	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in													
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	Some: System floor stand for vertical orientation													
VESA mount	Supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

See footnotes for important warranty information

US models announced October 23, November 20, December 11, or December 25, 2012

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
2988-A1U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A3U	4x3	i7-3770	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A6U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A9U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Pro 64	07/10/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory		Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Modem	None	
Security chip	Trusted Platform Module (TPM1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Floor Stand	System floor stand for vertical orientation	
Power supply	240 watts, autosingling, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	
		
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies	
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet	

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
2988-A4U	4x3	i7-3770	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A5U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A7U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
2988-A8U	4x3	i7-3770	4GBx2 1600MHz	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology												Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Graphics	<p>Some: AMD Radeon™ HD 7350, DirectX® 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors</p> <p>Some: AMD Radeon HD 7450, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors</p>														
DP dongle	None														
Disk	SATA 6.0Gb/s 7200 rpm														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
eSATA port	None														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector														
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec														
IEEE 1394	Internal speaker for business audio														
Ethernet	None														
Intel AMT Modem	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Keyboard	None														
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Floor Stand	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	System floor stand for vertical orientation														
Machine	240 watts, autosensing, 85% PSU														
Bay	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 														
Slot	<ul style="list-style-type: none"> • Bay 1: 5.25", 1.6" high, access, std optical • Bay 2: 3.5", 1" high, no access, std disk • Bay 3: 3.5", .5" high, access, opt reader 														
Limited Warranty	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3														
	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet														

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	Media reader	Graphics	PCIe Mini Card WLAN / BT	Chassis intr	Floor switchstand	ENERGY STAR 5.2	Intel vPro Global	Preload	Ann date (mm/dd/yy)
2988-B2U	4x3	i7-3770	4GBx1	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Win8 Pro64 10/23/12
2988-C6U	4x3	i5-3470	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win8 Pro64 10/23/12
2988-B4U	4x3	i5-3570	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win8 Pro64 10/23/12
2988-C8U	4x3	i7-3770	4GBx1	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win8 Pro64 10/23/12
2988-D9U	4x3	i5-3470	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64 10/23/12
2988-E1U	4x3	i5-3570	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64 10/23/12
2988-E2U	4x3	i7-3770	4GBx1	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win7 Pro64 10/23/12
2988-F2U	4x3	i7-3770	4GBx2	1TB 7200	DVD±RW	None	HD 7450	Intel 6205	None	Stand	ES52	vPro	None	Win7 Pro64 03/12/13
2988-F3U	4x3	i5-3475S	4GBx2	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win7 Pro64 03/12/13
Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® AppShop• Lenovo Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i> Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors													
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort™													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector													
PCIe WLAN	Some: 11a/b/g/n, PCIe Half Mini Card, Intel Centrino® Advanced-N 6205, 2x2													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 													
Bay														
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
2992-A2U	4x5	i5-3550	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A3U	4x5	i7-3770	4GBx2 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A4U	4x5	i7-3770	4GBx2 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A5U	4x5	i7-3770	4GBx1 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A6U	4x5	i5-3550	4GBx1 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Professional 64			
Implementation													Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)			
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors Some: AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors															
DP dongle	None															
Disk	SATA 6.0Gb/s 7200 rpm															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support															
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector															
eSATA port	None															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	Internal speaker for business audio															
IEEE 1394	None															
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Modem	None															
Security chip	Trusted Platform Module (TPM1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	280 watts, autosensing, 85% PSU															
Machine	<ul style="list-style-type: none"> Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 24.2 lb (11.0 kg) in maximum configuration Toolless cover removal, toolless adapter retention Toolless disk, optical drive removal 															
Bay																
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3															
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
2992-A7U	4x5	i5-3470	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A8U	4x5	i5-3470	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-A9U	4x5	i7-3770	4GBx2 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-B1U	4x5	i7-3770	4GBx2 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Pro 64	06/05/12
2992-B2U	4x5	i7-3770	4GBx1 1600MHz	1TB	7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	07/10/12


• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket														Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation															Ready to install applications (only some listed) • Rescue and Recovery™ • Password Manager		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets														Preloaded applications (only some listed) • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)		
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz; Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors Some: AMD Radeon HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors																
DP dongle	None																
Disk	SATA 6.0Gb/s 7200 rpm																
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support																
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector																
eSATA port	None																
Media reader	None																
Chipset	Intel Q77 Express Chipset																
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector																
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																
Speaker	Internal speaker for business audio																
IEEE 1394	None																
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																
Modem	None																
Security chip	Trusted Platform Module (TPM1.2-compliant)																
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																
Power supply	280 watts, autosensing, 85% PSU																
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 																
Bay	<ul style="list-style-type: none"> Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk 																
Slot	<ul style="list-style-type: none"> Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3 																
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
2992-B5U	4x5	i7-3770	4GBx1	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
2992-C9U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
2992-D1U	4x5	i5-3570	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
2992-D2U	4x5	i7-3770	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
2992-E3U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12
2992-E4U	4x5	i5-3570	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12
2992-E5U	4x5	i7-3770	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win7 Pro64	10/23/12
2992-F7U	4x5	i5-3475S	4GBx1	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win7 Pro64	03/12/13
2992-F8U	4x5	i5-3475S	4GBx2	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win7 Pro64	03/12/13

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache, Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3475S Processor (4 cores / 4 threads) , 2.9GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit																			
Implementation													Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• Lenovo SimpleTap• Adobe® Reader®• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™																			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets																															
Graphics	Some: Intel HD Graphics 2500 / 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors																															
DP dongle	None																															
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																															
SATA controller Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector																															
eSATA port Media reader	None None																															
Chipset	Intel Q77 Express Chipset																															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																															
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector																															
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec Internal speaker for business audio																															
IEEE 1394	None																															
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																															
Intel AMT Modem	Intel Active Management Technology 8.0 (Intel AMT 8.0)																															
Security chip	Trusted Platform Module (TPM1.2-compliant)																															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																															
Power supply	280 watts, autosensing, 85% PSU																															
Machine	<ul style="list-style-type: none">• Business black color; metal case• 6.9" W X 17.4" D X 16.3" H• 175mm W X 442mm D X 414mm H• 24.2 lb (11.0 kg) in maximum configuration• Toolless cover removal, toolless adapter retention• Toolless disk, optical drive removal																															
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk																															
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3																															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																															
																																
Security <ul style="list-style-type: none">• Security chip (see information on left)• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">- Padlock loop (in rear for opt padlock)- Security slot (in rear for optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Serial port I/O control• Individual USB port disablement• Chassis intrusion switch on selected model(s)																																
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																																
Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet																																

ThinkCentre M92 Tiny (3229) - GMP (Thin Client)

Product Specifications Reference (PSREF)

Type-model	Processor	SATA disk Memory ⁸	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3229-A1U	G460	2GBx1	8G SSD	None	Intel HD	None	Serial	None	None	ES52	None	G P	Emb 32	07/10/12
3229-A2U	G465	2GBx1	8G SSD	None	Intel HD	None	Serial	None	None	ES52	None	G P	Emb 32	01/08/13
3229-A3U	G470	2GBx1	8G SSD	None	Intel HD	None	Serial	None	None	ES52	None	G P	Emb 32	07/09/13

•Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Celeron® G460 Processor (1 core / 2 threads, 1.8GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G465 Processor (1 core / 2 threads, 1.9GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller Intel Celeron G470 Processor (1 core / 2 threads, 2.0GHz, 1.5MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Embedded 32
Implementation												Preloaded applications (only some listed)	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook), <i>System automatically clocks down for processors with 1066MHz or 1333MHz DDR3 memory controller</i>											• Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player	
Graphics	Intel HD Graphics in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA) @60Hz</i>												
DP dongle	None												
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide												
External optical	None												
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
eSATA port	None												
Chipset	Intel Q77 Express Chipset												
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	None												
Bluetooth	None												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)												
Keyboard	None												
Mouse	None												
Floor Stand	None												
VESA mount	None												
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 												
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 												
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant												
	Supports ThinkVantage Technologies												
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr	Floor stand	ENERGY STAR 5.2	Intel vPro Global	Win7 preload	Ann date (mm/dd/yy)
3207-A8U	4x3	i3-2120	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None None	Pro 32	06/05/12
3207-A9U	4x3	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2000	None	None	Stand	ES52	None None	Pro 32	06/05/12


•3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 32		
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													
eSATA port Media reader	None None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													
IEEE 1394	Internal speaker for business audio													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
Power supply	240 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none">• Business black color; metal case• 13.3" W X 15.2" D X 3.9" H• 338mm W X 385mm D X 100mm H• 16.5 lb (7.5 kg) in maximum configuration• Toolless cover flips up and tilts backward on rear hinges• Toolless disk and optical drive removal• Toolless adapter retention													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant													
	Supports ThinkVantage Technologies													
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA optical	Media reader	Graphics	PCIe Mini Card WLAN / BT	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro Global	Win7 preload	Ann date (mm/dd/yy)
3208-A8U	4x5	i3-2130	4GBx1	500G	7200	Bay	DVD±RW	None	HD 2000	None	None	ES52	None None	Pro 64 06/05/12
3208-A9U	4x5	i3-2120	2GBx1	250G	7200	Bay	DVD±RW	None	HD 2000	None	None	ES52	None None	Pro 32 06/05/12
3208-C5U	4x5	i3-3240	4GBx2	1TB	7200	Bay	DVD±RW	Media	HD 7450	Intel 2230 + BT	Switch	ES52	None None	Pro 64 11/06/12

•3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i3-2120 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-2130 Processor (2 cores / 4 threads) , 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i3-3240 Processor (2 cores / 4 threads) , 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller										Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64			
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Some: Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors										Security <ul style="list-style-type: none">• Security chip (see information on left)• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Serial port I/O control• Individual USB port disablement• Chassis intrusion switch on selected model(s)			
DP dongle	None													
Disk	SATA 6.0Gb/s 7200 rpm													
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													
eSATA port	None													
Media reader	Some: 29-in-1 media reader, internal USB 2.0													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector													
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	280 watts, autosensing, 85% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk													
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													



Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3238-K4U	i5-3470T	2GBx1	8G SSD	None	HD 2500	None	None	None	Stand	Mount	ES52	vPro	None	Emb 32	07/10/12
3238-R6U	i5-3470T	2GBx1	8G SSD	None	HD 2500	Intel 105	DP	None	Stand	None	ES52	vPro	None	Emb 32	03/05/13
3238-R7U	i5-3470T	2GBx1	8G SSD	None	HD 2500	Intel 2230 + BT	None	None	Stand	None	ES52	vPro	None	Emb 32	03/05/13

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning	Ultimate security, stability, and manageability for the enterprise											Preloaded operating system		
Processor	Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Genuine Windows® 7		
Implementation	Processor in LGA1155 socket											Embedded 32		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Preloaded applications (only some listed)		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz											<ul style="list-style-type: none"> • Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player 		
DP dongle	None													
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide													
External optical	None													
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand	System floor stand for vertical orientation													
VESA mount	<i>Some:</i> Supports VESA 75mm and 100mm mount standard													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 													
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant													
	Supports ThinkVantage Technologies													
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet													

Type-model	Processor	Memory ⁸	SATA disk GB rpm	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3243-A3U	i5-3470T	4GBx1	500G 5400	None	HD 2500	None	None	None	Stand	None	ES52	vPro	None	Pro 64 06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 1-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads) , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>												
DP dongle	None												
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm												
External optical	None												
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
eSATA port	None												
Chipset	Intel Q77 Express Chipset												
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	None												
Bluetooth	None												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
VESA mount	None												
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box)												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)• Power-on password• Administrator password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Individual USB port disablement• Chassis intrusion switch on selected model(s)
Limited Warranty	1-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
	Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card	WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3238-A1U	i5-3470T	4GBx1	500G	5400	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	vPro	None	Pro 64	06/05/12
3238-B5U	i5-3470T	4GBx1	500G	5400	None	HD 2500	None	None	None	None	None	ES52	vPro	None	Pro 64	06/05/12
3238-B6U	i5-3470T	4GBx1	320G	5400	None	HD 2500	None	None	None	Stand	None	ES52	vPro	None	Pro 64	06/05/12
3238-B7U	i5-3470T	4GBx1	500G	5400	None	HD 2500	None	None	None	Stand	None	ES52	vPro	None	Pro 32	06/05/12
3238-B8U	i5-3470T	2GBx1	320G	5400	None	HD 2500	None	None	None	Stand	Mount	ES52	vPro	None	Pro 32	06/05/12
3238-D9U	i5-3470T	4GBx1	500G	5400	None	HD 2500	None	USB	None	Stand	Mount	ES52	vPro	None	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64															
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 															
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 															
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>																											
DP dongle	None																											
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm																											
External optical SATA controller	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in																											
Onboard SATA eSATA port	Serial ATA, SATA 6.0Gb/s support, integrated in chipset One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar None																											
Chipset	Intel Q77 Express Chipset																											
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																											
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)																											
PCIe Mini Card	One PCI Express® Mini Card slot																											
PCIe WLAN	None																											
Bluetooth	None																											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																											
Speaker	Internal speaker for business audio																											
IEEE 1394	None																											
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																											
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																											
Modem	None																											
Security chip	Trusted Platform Module (TPM1.2-compliant)																											
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																											
Floor Stand	Some: System floor stand for vertical orientation																											
VESA mount	Some: Supports VESA 75mm and 100mm mount standard																											
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU																											
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 																											
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																											
															Security													
															<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 													
															EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant													
															Supports ThinkVantage Technologies													
															For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet													

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Security Cable	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3238-F5U	i5-3470T	4GBx1	500G	7200	None	Intel 2230 + BT	None	None	None	Mount	ES52	vPro	None	Pro 64 06/19/12
3238-F6U	i5-3470T	4GBx1	500G	7200	None	Intel 105	None	None	None	Mount	ES52	vPro	None	Pro 64 06/19/12
3238-F7U	i5-3470T	4GBx1	500G	7200	None	Intel 105	None	None	None	Stand Mount	ES52	vPro	None	Pro 64 06/19/12
3238-F8U	i5-3470T	4GBx1	500G	7200	DVD±RW	Intel 2230 + BT	None	None	None	Mount	ES52	vPro	None	Pro 64 06/19/12
3238-F9U	i5-3470T	4GBx1	500G	7200	None	Intel 2230 + BT	None	None	None	Stand Mount	ES52	vPro	None	Pro 64 06/19/12
3238-K3U	i5-3470T	4GBx1	500G	7200	None	None	DP	None	None	Stand Mount	ES52	vPro	None	Pro 64 06/19/12
3238-E5U	i5-3470T	4GBx1	500G	7200	None	None	None	None	None	Mount	ES52	vPro	None	Pro 64 07/10/12
3238-E8U	i5-3470T	4GBx1	320G	7200	DVD±RW	None	None	None	None	Mount	ES52	vPro	None	Pro 64 07/10/12
3238-E9U	i5-3470T	4GBx1	320G	7200	None	None	None	None	None	Mount	ES52	vPro	None	Pro 64 07/10/12
3238-F1U	i5-3470T	4GBx1	320G	7200	None	None	None	None	Stand	None	ES52	vPro	None	Pro 64 07/10/12
3238-F2U	i5-3470T	2GBx1	320G	7200	None	None	None	None	Stand	None	ES52	vPro	None	Pro 64 07/10/12
3238-P6U	i5-3470T	4GBx2	180G SSD	DVD±RW	Intel 2230 + BT	None	Switch	Cable	None	Mount	ES52	vPro	None	Pro 64 11/06/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Genuine Windows® 7 Professional 64
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA) @60Hz</i>												
DP dongle	None												
Disk	<i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide <i>Some:</i> Hard Disk Drive / SATA 3.0Gb/s, 2.5" Wide												
External optical													
SATA controller	<i>Some:</i> Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in												
Onboard SATA	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												
eSATA port	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
Chipset	Intel Q77 Express Chipset												
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	<i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	<i>Some:</i> System floor stand for vertical orientation												
VESA mount	<i>Some:</i> Supports VESA 75mm and 100mm mount standard												
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												
Machine	<ul style="list-style-type: none">• Business black color; metal case• 7.1" W X 7.2" D X 1.4" H• 179mm W X 182mm D X 34.5mm H• 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box)												
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant												
	Supports ThinkVantage Technologies												
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Processor	SATA disk Memory ⁸	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intrusion switch	Floor stand	VESA mount	Key- board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3238-K1U	i5-3470T 4GBx1 500G 7200 DVD±RW	HD 2500 Intel 2230 + BT None	None	None	Mount	USB	vPro	None	Win8 Pro64	10/23/12				
3238-K2U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 2230 + BT None	None	Stand	None	USB	vPro	None	Win8 Pro64	10/23/12				
3238-L1U	i5-3470T 4GBx1 320G 7200 DVD±RW	HD 2500 Intel 105	DP	None	None	Mount	USB	vPro	None	Win8 Pro64	10/23/12			
3238-L2U	i5-3470T 4GBx1 320G 7200 None	HD 2500 None	DP	None	None	Mount	USB	vPro	None	Win8 Pro64	10/23/12			
3238-L4U	i5-3470T 4GBx1 320G 5400 None	HD 2500 None	None	None	None	Mount	USB	vPro	None	Win7 Pro64	10/23/12			
3238-L5U	i5-3470T 4GBx1 320G 5400 DVD±RW	HD 2500 None	None	None	Stand	Mount	USB	vPro	None	Win7 Pro64	10/23/12			
3238-L6U	i5-3470T 2GBx1 500G 5400 None	HD 2500 None	None	None	Stand	None	USB	vPro	None	Win7 Pro64	10/23/12			
3238-L7U	i5-3470T 4GBx1 500G 7200 None	HD 2500 None	None	None	None	Mount	USB	vPro	None	Win7 Pro64	10/23/12			
3238-M3U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 2230 + BT None	None	Stand	None	USB	vPro	None	Win7 Pro64	10/23/12				
3238-M4U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 105	None	None	Stand	None	USB	vPro	None	Win7 Pro64	10/23/12			
3238-M5U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 105	None	None	None	USB	vPro	None	Win7 Pro64	10/23/12				
3238-M6U	i5-3470T 4GBx1 500G 7200 DVD±RW	HD 2500 Intel 2230 + BT None	None	Stand	Mount	USB	vPro	None	Win7 Pro64	10/23/12				
3238-M7U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 2230 + BT None	None	None	None	USB	vPro	None	Win7 Pro64	10/23/12				
3238-M8U	i5-3470T 4GBx1 500G 7200 None	HD 2500 None	None	None	Stand	None	USB	vPro	None	Win7 Pro64	10/23/12			
3238-M9U	i5-3470T 4GBx1 500G 5400 None	HD 2500 None	None	None	Stand	None	USB	vPro	None	Win7 Pro64	10/23/12			
3238-Q2U	i5-3470T 4GBx1 180G SSD	None	HD 2500 Intel 105	DP	None	Mount	USB	vPro	None	Win7 Pro64	11/20/12			
3238-Q3U	i5-3470T 4GBx1 180G SSD	DVD±RW	HD 2500 Intel 105	DP	None	Mount	USB	vPro	None	Win7 Pro64	11/20/12			
3238-S9U	i5-3470T 4GBx1 500G 7200 None	HD 2500 Intel 105	None	None	None	Mount	2.4G	vPro	None	Win8 Pro64	05/28/13			

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												
Implementation	Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit												
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA) @ 60Hz												
DP dongle	None												
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 3.0Gb/s, 2.5" Wide												
External optical SATA controller	Some: Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in												
Onboard SATA eSATA port	Serial ATA, SATA 6.0Gb/s support, integrated in chipset One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												
Chipset	Intel Q77 Express Chipset												
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												
Modem	None												
Security chip	Trusted Platform Module (TPM1.2-compliant)												
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												
Mouse	Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black												
Floor Stand	Some: Enhanced Optical USB Mouse, black, Lenovo logo												
VESA mount	Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black												
Power supply	Some: System floor stand for vertical orientation												
Machine	Some: Supports VESA 75mm and 100mm mount standard 65 watts AC/DC adapter, autosensing, 87% PSU												
	● Business black color; metal case ● 7.1" W X 7.2" D X 1.4" H ● 179mm W X 182mm D X 34.5mm H ● 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box)												
	● Chassis intrusion switch on selected model(s)												
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant												
	Supports ThinkVantage Technologies												
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

Type-model	Processor	SATA disk Memory ⁸	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Win7	Ann date preload(mm/dd/yy)
3237-A3U	i5-3470T	2GBx1	8G SSD	None	HD 2500	None	Serial	None	None	ES52	vPro	G P	Emb 32	07/10/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Genuine Windows® 7 Embedded 32			
Implementation											Preloaded applications (only some listed)			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)										<ul style="list-style-type: none"> • Adobe® Reader® • Adobe Flash® Player • Citrix® Receiver • IIS Web Server • Microsoft® Management Console • Microsoft Silverlight • Remote Desktop Protocol • ThinPrint .print Client • TightVNC Viewer • VMware® View Client • vWorkspace • Windows Media Player 			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk	Solid State Drive (SSD) / SATA 3.0Gb/s, 2.5" Wide													
External optical	None													
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset													
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar													
eSATA port	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	None													
Bluetooth	None													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
Speaker	Internal speaker for business audio													
IEEE 1394	None													
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem	None													
Security chip	Trusted Platform Module (TPM1.2-compliant)													
Keyboard	None													
Mouse	None													
Floor Stand	None													
VESA mount	None													
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU													
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 										Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 			
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant			
											Supports ThinkVantage Technologies			
											For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Win7	Ann date preload(mm/dd/yy)	
3237-A1U	i5-3470T	4GBx1	320G	5400	DVD±RW	HD 2500	None	None	None	None	Mount	ES52	vPro	G P	Pro 64	06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads) , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system	
Implementation													Genuine Windows® 7 Professional 64	
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Ready to install applications (only some listed)	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>												Preloaded applications (only some listed)	
DP dongle	None												• Rescue and Recovery™	
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm												• Password Manager	
External optical	Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in												Preloaded applications (only some listed)	
SATA controller	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												• ThinkVantage® Product Recovery	
Onboard SATA	One SATA cable (1-drop to device), one SATA 6.0Gb/s connector on planar												• ThinkVantage System Update	
eSATA port	None												• ThinkVantage Communication Utility	
Chipset	Intel Q77 Express Chipset												• ThinkVantage Power Manager	
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												• View Management Utility	
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												• Lenovo AppShop	
PCIe Mini Card	One PCI Express® Mini Card slot												• Lenovo Solution Center	
PCIe WLAN	None												• Lenovo Message Center Plus	
Bluetooth	None												• Lenovo SimpleTap	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												• Norton™ Internet Security (30 days of virus definitions)	
Speaker	Internal speaker for business audio												• Adobe® Reader®	
IEEE 1394	None												• Skype™ for Windows	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												• Windows Live™ Essentials	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												• Microsoft® Office preloaded; purchase a product key to activate	
Modem	None												• Corel® Burn.Now™ (DVD±RW)	
Security chip	Trusted Platform Module (TPM1.2-compliant)												• Corel DVD MovieFactory® (DVD±RW)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												Security	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												• Security chip (see information on left)	
Floor Stand	None												• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)	
VESA mount	Supports VESA 75mm and 100mm mount standard												• Power-on password	
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												• Administrator password	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 												• Hard disk password	
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												• Boot sequence control	
													• Boot without keyboard and mouse	
													• Individual USB port disablement	
													• Chassis intrusion switch on selected model(s)	
													EPEAT™ Gold rating	
													ENERGY STAR® 5.2-compliant	
													ULE Gold	
													Cisco EnergyWise compatible	
													GREENGUARD® certified	
													RoHS-compliant	
													Supports ThinkVantage Technologies	
													For compatible accessories, please go to O-M92 sheet;	
													For Lenovo service upgrade options, please go to S-TC sheet	

Type-model	Processor	Memory ⁸	SATA disk GB	External optical	Graphics	PCIe Mini Card WLAN / BT	Optional port	Chassis intr switch	Floor stand	VESA mount	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3237-A4U	i5-3470T	4GBx1	320G	5400	DVD±RW	HD 2500	None	None	None	Mount	ES52	vPro	G P	Win8 Pro64	10/23/12
3237-A5U	i5-3470T	4GBx1	320G	5400	DVD±RW	HD 2500	None	None	None	Mount	ES52	vPro	G P	Win7 Pro64	10/23/12


• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system			
Implementation													Some:	Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Some:	Windows 8 Pro 64-bit		
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, one optional DisplayPort, supports up to triple independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>												Preloaded applications (only some listed)			
DP dongle	None												- Windows 7 models			
Disk	SATA 3.0Gb/s, 2.5" Wide, 5400 rpm												• ThinkVantage® Product Recovery			
External optical SATA controller	Slim DVD burner box, SATA 1.5Gb/s, 12.7mm high, tray-in												• ThinkVantage Communication Utility			
Onboard SATA eSATA port	Serial ATA, SATA 6.0Gb/s support, integrated in chipset												• ThinkVantage Power Manager			
Chipset	Intel Q77 Express Chipset												Lenovo® AppShop			
Front ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												Lenovo Message Center Plus			
Rear ports	Two USB 3.0, one USB 2.0 (external ODD occupies USB 2.0 port on some models), ethernet (RJ-45), VGA DB-15, DisplayPort connector, one optional port (USB 2.0 / serial / DisplayPort on selected models)												Lenovo SimpleTap			
PCIe Mini Card	One PCI Express® Mini Card slot												Adobe® Reader®			
PCIe WLAN	None												Windows Live™ Essentials			
Bluetooth	None												Corel® Burn.Now™ (DVD±RW)			
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												Corel DVD MovieFactory® (DVD±RW)			
Speaker	Internal speaker for business audio												- Windows 8 models			
IEEE 1394	None												Lenovo Support			
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®												Norton™ Studio			
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)												AccuWeather			
Modem	None												Evernote®			
Security chip	Trusted Platform Module (TPM1.2-compliant)												Cyberlink Power2Go (DVD±RW)			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												Cyberlink PowerProducer (DVD±RW)			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												- All models			
Floor Stand	None												ThinkVantage System Update			
VESA mount	Supports VESA 75mm and 100mm mount standard												Lenovo Solution Center			
Power supply	65 watts AC/DC adapter, autosensing, 87% PSU												View Management Utility			
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 7.1" W X 7.2" D X 1.4" H • 179mm W X 182mm D X 34.5mm H • 9.1 lb (4.1 kg) in maximum configuration (including External Optical Box) 												Norton Internet Security (30 days of virus definitions)			
													Microsoft® Office preloaded; purchase a product key to activate			
													Skype™			
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Security			
													• Security chip (see information on left)			
													• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)			
													• Power-on password			
													• Administrator password			
													• Hard disk password			
													• Boot sequence control			
													• Boot without keyboard and mouse			
													• Individual USB port disablement			
													• Chassis intrusion switch on selected model(s)			
													EPEAT™ Gold rating			
													ENERGY STAR® 5.2-compliant			
													ULE Gold			
													Cisco EnergyWise compatible			
													GREENGUARD® certified			
													RoHS-compliant			
													Supports ThinkVantage Technologies			
													For compatible accessories, please go to O-M92 sheet;			
													For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3209-A2U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
3209-A4U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
3209-C5U	4x3	i7-3770	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Pro 32	06/05/12
3209-C8U	4x3	i5-3550	4GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
3209-E4U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 32	06/05/12
3209-E5U	4x3	i5-3550	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 32	06/05/12
3209-E6U	4x3	i5-3470	2GBx1 1600MHz	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 32	06/05/12
3209-E7U	4x3	i5-3470	2GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	06/05/12
3209-D7U	4x3	i5-3470	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	07/10/12
3209-D9U	4x3	i5-3570	4GBx1 1600MHz	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	07/10/12
3209-F8U	4x3	i5-3570	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Pro 64	07/10/12
3209-F9U	4x3	i7-3770	4GBx1 1600MHz	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Pro 64	07/10/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty


Positioning	Ultimate security, stability, and manageability for the enterprise																							
Processor	Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology																							
Implementation	Intel Core i5-3550 Processor (4 cores / 4 threads, 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology																							
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets																							
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz																							
DP dongle	None																							
Disk	SATA 6.0Gb/s 7200 rpm																							
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																							
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support																							
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector																							
eSATA port	None																							
Media reader	None																							
Chipset	Intel Q77 Express Chipset																							
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																							
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																							
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																							
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector																							
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																							
Speaker	Internal speaker for business audio																							
IEEE 1394	None																							
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																							
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																							
Modem	None																							
Security chip	Trusted Platform Module (TPM1.2-compliant)																							
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																							
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																							
Floor Stand	System floor stand for vertical orientation																							
Power supply	240 watts, autosensing, 85% PSU																							
Machine	<ul style="list-style-type: none"> Business black color; metal case 13.3" W X 15.2" D X 3.9" H 338mm W X 385mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention 																							
Bay	 Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader																							
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3																							
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																							
Preloaded operating system <ul style="list-style-type: none"> Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64 Ready to install applications (only some listed)																								
<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager Preloaded applications (only some listed)																								
<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 																								
Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch on selected model(s) 																								
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																								
Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet																								

ThinkCentre M92p Small (3209) - II

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Intel vPro	Win7 preload	Ann date (mm/dd/yy)	
3209-D4U	4x3	i7-3770	4GBx1	1600MHz	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Pro 64 06/05/12
3209-D5U	4x3	i5-3550	4GBx1	1600MHz	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Pro 64 06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
 - 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3550 Processor (4 cores / 4 threads) , 3.3GHz, 6MB cache, Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache, Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 30 watts; <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Modem	None	
Security chip	Trusted Platform Module (TPM1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Floor Stand	System floor stand for vertical orientation	
Power supply	240 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet


See footnotes for important warranty information
US models announced June 5, 2012

ThinkCentre M92p Small (3209) - Windows 8

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3209-K2U	4x3	i7-3770	4GBx1	500G 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Win8 Pro64	10/23/12
3209-K9U	4x3	i5-3470	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win8 Pro64	10/23/12
3209-L1U	4x3	i5-3570	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win8 Pro64	10/23/12
3209-L2U	4x3	i7-3770	4GBx1	500G 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win8 Pro64	10/23/12


- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
 - 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache, Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache, Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system Windows® 8 Pro 64-bit Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
Implementation	Processor in LGA1155 socket	
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	
Graphics	<i>Some:</i> Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, VGA)@60Hz <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Modem	None	
Security chip	Trusted Platform Module (TPM1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Floor Stand	System floor stand for vertical orientation	
Power supply	240 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader	
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information
US models announced October 23, 2012


© lenovo

(MHTN1-28) October 2012

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3209-L3U	4x3	i5-3470	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-L4U	4x3	i5-3570	4GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-L5U	4x3	i7-3770	4GBx1	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-L7U	4x3	i5-3470	2GBx1	500G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-L8U	4x3	i5-3570	4GBx1	250G 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-M1U	4x3	i7-3770	4GBx1	500G 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-M2U	4x3	i7-3770	4GBx1	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-M3U	4x3	i7-3770	4GBx1	1TB 7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-M4U	4x3	i5-3570	4GBx1	1TB 7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
3209-M5U	4x3	i5-3570	4GBx1	500G 7200	DVD±RW	None	HD 7350	None	None	Stand	ES52	vPro	None	Win7 Pro64	10/23/12
Positioning Processor		<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache, Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache, Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system	
Implementation															Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Memory		32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													Ready to install applications (only some listed)
Graphics		<i>Some: Intel HD Graphics 2500 / 4000</i> in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, VGA)@60Hz <i>Some:</i> AMD Radeon™ HD 7350 , DirectX 11, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors <i>Some:</i> AMD Radeon HD 7450 , DirectX 11, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors												Preloaded applications (only some listed)	
DP dongle		None													• ThinkVantage® Product Recovery
Disk		SATA 6.0Gb/s 7200 rpm													• ThinkVantage System Update
Optical		Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													• ThinkVantage Communication Utility
SATA controller		Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													• ThinkVantage Power Manager
Onboard SATA		Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													• View Management Utility
eSATA port		None													• Lenovo® AppShop
Media reader		None													• Lenovo Solution Center
Chipset		Intel Q77 Express Chipset													• Lenovo Message Center Plus
Front ports		Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													• Lenovo SimpleTap
Rear ports		Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													• Norton™ Internet Security (30 days of virus definitions)
Rear audio ports		Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													• Adobe® Reader®
Internal connector		Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													• Skype™ for Windows
Audio		High Definition (HD) Audio, Realtek® ALC662 codec													• Windows Live™ Essentials
Speaker		Internal speaker for business audio													• Microsoft® Office preloaded; purchase a product key to activate
IEEE 1394		None													• Corel® Burn.Now™ (DVD±RW)
Ethernet		One gigabit ethernet port, Intel 82579, Wake on LAN®													• Corel DVD MovieFactory® (DVD±RW)
Intel AMT		Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Modem		None													
Security chip		Trusted Platform Module (TPM1.2-compliant)													
Keyboard		Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse		Enhanced Optical USB Mouse, black, Lenovo logo													
Floor Stand		System floor stand for vertical orientation													
Power supply		240 watts, autosensing, 85% PSU													
Machine		<ul style="list-style-type: none"> Business black color; metal case 13.3" W X 15.2" D X 3.9" H 338mm W X 385mm D X 100mm H 16.5 lb (7.5 kg) in maximum configuration Toolless cover flips up and tilts backward on rear hinges Toolless disk and optical drive removal Toolless adapter retention 													• Boot sequence control
Bay		Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													• Boot without keyboard and mouse
Slot		Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													• Individual USB port disablement
Limited Warranty		3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													• Chassis intrusion switch on selected model(s)
															EPEAT™ Gold rating
															ENERGY STAR® 5.2-compliant
															ULE Gold
															Cisco EnergyWise compatible
															GREENGUARD® certified
															RoHS-compliant
															Supports ThinkVantage Technologies
															For compatible accessories, please go to O-M92 sheet;
															For Lenovo service upgrade options, please go to S-TC sheet


Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intr switch	Floor stand	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3209-R5U	4x3	i5-3475S	4GBx2	1TB 7200	DVD±RW	None	HD 7450	None	None	Stand	ES52	vPro	None	Win7 Pro64	03/12/13

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation												Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	AMD Radeon™ HD 7450 , DirectX 11, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</i> works along with Intel HD Graphics to support up to four independent monitors											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo® AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Disk Optical	SATA 6.0Gb/s 7200 rpm														
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
eSATA port	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector														
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec														
IEEE 1394	Internal speaker for business audio														
Ethernet	None														
Intel AMT	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Modem	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	None														
Keyboard	Trusted Platform Module (TPM1.2-compliant)														
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Floor Stand	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	System floor stand for vertical orientation														
Machine	240 watts, autosensing, 85% PSU														
Bay	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 														
Slot	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 3.5", 1" high, no access, std disk</p> <p>Bay 3: 3.5", .5" high, access, opt reader</p> <p>Slot 1: Low Profile, PCI Express 2.0 x16 (45w max)</p> <p>Slot 2: Low Profile, PCIe 2.0 x1</p> <p>Slot 3: Low Profile, 32-bit PCI 2.3</p> <p>Slot 4: Low Profile, 32-bit PCI 2.3</p>														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
															
	<p>EPEAT™ Gold rating</p> <p>ENERGY STAR® 5.2-compliant</p> <p>ULE Gold</p> <p>Cisco EnergyWise compatible</p> <p>GREENGUARD® certified</p> <p>RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p>														
	<p>For compatible accessories, please go to O-M92 sheet;</p> <p>For Lenovo service upgrade options, please go to S-TC sheet</p>														

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Display-Port Graphics	Chassis dongle	Floor intr switch	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Win7 preloaded	Ann date (mm/dd/yy)	
3227-A1U	4x3	i7-3770	4GBx1	1600MHz	500G	7200	DVD±RW	None	HD 4000	None	None	Stand	ES52	vPro G P	Pro 64 06/05/12
3227-A2U	4x3	i5-3470	4GBx1	1600MHz	500G	7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro G P	Pro 64 06/19/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology										Preloaded operating system Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket										Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>													
DP dongle	None													
Disk Optical	SATA 6.0Gb/s 7200 rpm													
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													
	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													
eSATA port	None													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													
IEEE 1394	Internal speaker for business audio													
Ethernet	None													
Intel AMT	One gigabit ethernet port, Intel 82579, Wake on LAN®													
Modem	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Security chip	None													
Keyboard	Trusted Platform Module (TPM1.2-compliant)													
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Floor Stand	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	System floor stand for vertical orientation													
Machine	240 watts, autosensing, 85% PSU													
Bay	Business black color; metal case													
	• 13.3" W X 15.2" D X 3.9" H													
	• 338mm W X 385mm D X 100mm H													
	• 16.5 lb (7.5 kg) in maximum configuration													
	• Toolless cover flips up and tilts backward on rear hinges													
	• Toolless disk and optical drive removal													
	• Toolless adapter retention													
Slot	Bay 1: 5.25", 1.6" high, access, std optical													
	Bay 2: 3.5", 1" high, no access, std disk													
	Bay 3: 3.5", .5" high, access, opt reader													
	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max)													
	Slot 2: Low Profile, PCIe 2.0 x1													
	Slot 3: Low Profile, 32-bit PCI 2.3													
	Slot 4: Low Profile, 32-bit PCI 2.3													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
														
	For compatible accessories, please go to O-M92 sheet;													
	For Lenovo service upgrade options, please go to S-TC sheet													

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Media reader	Display-Port Graphics	Chassis dongle	Floor intr	ENERGY switch	Intel stand STAR 5.2 vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
3227-A3U	4x3	i5-3470	4GBx1	1600MHz	500G	7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro G P	Win8 Pro64 10/23/12
3227-A4U	4x3	i5-3470	4GBx1	1600MHz	500G	7200	DVD±RW	None	HD 2500	None	None	Stand	ES52	vPro G P	Win7 Pro64 10/23/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology


• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system
Implementation														Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets													Some: Windows 8 Pro 64-bit
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz													Preloaded applications (only some listed)
DP dongle	None													- Windows 7 models
Disk Optical	SATA 6.0Gb/s 7200 rpm													• ThinkVantage® Product Recovery
SATA controller Onboard SATA	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													• ThinkVantage Communication Utility
eSATA port	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support													• ThinkVantage Power Manager
Media reader	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector													• Lenovo® AppShop
Chipset	Intel Q77 Express Chipset													• Lenovo Message Center Plus
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													• Lenovo SimpleTap
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort													• Adobe® Reader®
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													• Windows Live™ Essentials
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector													• Corel® Burn.Now™ (DVD±RW)
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec													• Corel DVD MovieFactory® (DVD±RW)
IEEE 1394	None													- Windows 8 models
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®													• Lenovo Support
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													• Lenovo Companion
Modem	None													• Lenovo Cloud Storage
Security chip	Trusted Platform Module (TPM1.2-compliant)													• Norton™ Studio
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													• AccuWeather
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													• Evernote®
Floor Stand	System floor stand for vertical orientation													• Cyberlink Power2Go (DVD±RW)
Power supply	240 watts, autosensing, 85% PSU													• Cyberlink PowerProducer (DVD±RW)
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 13.3" W X 15.2" D X 3.9" H • 338mm W X 385mm D X 100mm H • 16.5 lb (7.5 kg) in maximum configuration • Toolless cover flips up and tilts backward on rear hinges • Toolless disk and optical drive removal • Toolless adapter retention 													- All models
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 3.5", .5" high, access, opt reader													• ThinkVantage System Update
Slot	Slot 1: Low Profile, PCI Express 2.0 x16 (45w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, 32-bit PCI 2.3 Slot 4: Low Profile, 32-bit PCI 2.3													• Lenovo Solution Center
														• View Management Utility
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													• Norton Internet Security (30 days of virus definitions)
														• Microsoft® Office preloaded; purchase a product key to activate
														• Skype™
														Security
														• Security chip (see information on left)
														• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable)
														• Cable lock
														• Power-on password
														• Administrator password
														• Hard disk password
														• Boot sequence control
														• Boot without keyboard and mouse
														• Individual USB port disablement
														• Chassis intrusion switch on selected model(s)
														EPEAT™ Gold rating
														ENERGY STAR® 5.2-compliant
														ULE Gold
														Cisco EnergyWise compatible
														GREENGUARD® certified
														RoHS-compliant
														Supports ThinkVantage Technologies
														For compatible accessories, please go to O-M92 sheet;
														For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3212-A3U	4x5	i5-3550	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-A9U	4x5	i5-3550	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 32	06/05/12
3212-C1U	4x5	i5-3550	4GBx1 1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3550 Processor (4 cores / 4 threads) , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64				
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)				
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>											Security <ul style="list-style-type: none">• Security chip (see information on left)• One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">-Padlock loop (in rear for opt padlock)-Security slot (in rear for optional Kensington® MicroSaver® cable)• Cable lock• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• Serial port I/O control• Individual USB port disablement• <i>Chassis intrusion switch on selected model(s)</i>				
DP dongle	None											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant				
Disk	SATA 6.0Gb/s 7200 rpm											Supports ThinkVantage Technologies				
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive											For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet				
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support															
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector															
eSATA port	None															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)															
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	Internal speaker for business audio															
IEEE 1394	None															
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Modem	None															
Security chip	Trusted Platform Module (TPM1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	280 watts, autosensing, 85% PSU															
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 															
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk															
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3															
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															




Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3212-C6U	4x5	i7-3770	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-C7U	4x5	i5-3550	4GBx1 1600MHz	250G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-C9U	4x5	i7-3770	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-D1U	4x5	i7-3770	4GBx1 1600MHz	250G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-E4U	4x5	i5-3470	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 32	06/05/12
3212-E5U	4x5	i7-3770	4GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 32	06/05/12
3212-E6U	4x5	i5-3470	2GBx1 1600MHz	250G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 32	06/05/12
3212-E7U	4x5	i5-3470	2GBx1 1600MHz	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	06/05/12
3212-K1U	4x5	i7-3770	4GBx1 1600MHz	1TB 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	06/19/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• 3-year limited warranty


Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550 Processor (4 cores / 4 threads , 3.3GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system Some: Genuine Windows® 7 Professional 32 Some: Genuine Windows 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none">Rescue and Recovery™Password Manager
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets	Preloaded applications (only some listed) <ul style="list-style-type: none">ThinkVantage® Product RecoveryThinkVantage System UpdateThinkVantage Communication UtilityThinkVantage Power ManagerView Management UtilityLenovo AppShopLenovo Solution CenterLenovo Message Center PlusLenovo SimpleTapNorton™ Internet Security (30 days of virus definitions)Adobe® Reader®Skype™ for WindowsWindows Live™ EssentialsMicrosoft® Office preloaded; purchase a product key to activateCorel® Burn.Now™ (DVD±RW)Corel DVD MovieFactory® (DVD±RW)
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors	
DP dongle	None	
Disk	SATA 6.0Gb/s 7200 rpm	
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive	
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support	
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector	
eSATA port	None	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort	
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)	
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector	
Audio	High Definition (HD) Audio, Realtek® ALC662 codec	
Speaker	Internal speaker for business audio	
IEEE 1394	None	
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Modem	None	
Security chip	Trusted Platform Module (TPM1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	280 watts, autosensing, 85% PSU	
Machine	<ul style="list-style-type: none">Business black color; metal case6.9" W X 17.4" D X 16.3" H175mm W X 442mm D X 414mm H24.2 lb (11.0 kg) in maximum configurationToolless cover removal, toolless adapter retentionToolless disk, optical drive removal	
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk	
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	
Security <ul style="list-style-type: none">Security chip (see information on left)One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none">Padlock loop (in rear for opt padlock)Security slot (in rear for optional Kensington® MicroSaver® cable)Cable lockPower-on passwordHard disk passwordBoot sequence controlBoot without keyboard and mouseSerial port I/O controlIndividual USB port disablementChassis intrusion switch on selected model(s)		
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	PCIe Mini Card WLAN / BT	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3212-D8U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	07/10/12
3212-D9U	4x5	i7-3770	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Pro 64	07/10/12
3212-E2U	4x5	i5-3570	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	07/10/12
3212-F7U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Pro 64	07/10/12
3212-F8U	4x5	i5-3570	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Pro 64	07/10/12
3212-M2U	4x5	i7-3770	4GBx2	1TB 7200	Bay	DVD±RW	Media	HD 4000	Intel 2230 + BT	Switch	ES52	vPro	None	Pro 64	11/06/12

Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads) , 3.4GHz, 6MB cache, Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads) , 3.4GHz, 8MB cache, Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Preloaded operating system Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors														
DP dongle	None														
Disk Optical	SATA 6.0Gb/s 7200 rpm Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
eSATA port	None														
Media reader	Some: 29-in-1 media reader, internal USB 2.0														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector														
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 														
Bay	 <ul style="list-style-type: none"> Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk 														
Slot	<ul style="list-style-type: none"> Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3 														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
<p>See footnotes for important warranty information US models announced July 10 or November 6, 2012</p> <p>Security</p> <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> <p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p> <p>For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet</p>															

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3212-H1U	4x5	i7-3770	4GBx1	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
3212-K3U	4x5	i5-3470	4GBx1	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
3212-K4U	4x5	i5-3570	4GBx1	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win8 Pro64	10/23/12
3212-K5U	4x5	i7-3770	4GBx1	1TB	7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win8 Pro64	10/23/12


- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads , 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system Windows® 8 Pro 64-bit													
Implementation		Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • View Management Utility • Lenovo® Support • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 													
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets														
Graphics	<p>Some: Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display;</p> <p>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</p> <p>Some: AMD Radeon™ HD 7450, DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts;</p> <p>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors</p>														
DP dongle	None														
Disk Optical	SATA 6.0Gb/s 7200 rpm														
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
eSATA port	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 														
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 5.25", 1.6" high, access, open</p> <p>Bay 3: 3.5", 1" high, access, opt reader</p> <p>Bay 4: 3.5", 1" high, no access, std disk</p> <p>Bay 5: 3.5", 1" high, no access, opt disk</p>														
Slot	<p>Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, 32-bit PCI 2.3</p> <p>Slot 4: half-length, full-height, 32-bit PCI 2.3</p>														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
<p>See footnotes for important warranty information US models announced October 23, 2012</p>															
<p>©Lenovo (MHTN1-31) October 2012</p>															

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)																	
3212-K7U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-K8U	4x5	i7-3770	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-K9U	4x5	i5-3570	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L1U	4x5	i5-3570	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L2U	4x5	i7-3770	4GBx1	500G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L3U	4x5	i5-3570	4GBx1	250G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L4U	4x5	i5-3470	2GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L5U	4x5	i7-3770	4GBx1	500G 7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L6U	4x5	i7-3770	4GBx1	250G 7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L7U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 7350	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L8U	4x5	i5-3470	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
3212-L9U	4x5	i7-3770	4GBx1	1TB 7200	Bay	DVD±RW	None	HD 7450	None	None	ES52	vPro	None	Win7 Pro64	10/23/12																	
Positioning Processor	<i>Ultimate security, stability, and manageability for the enterprise</i> Intel® Core™ i5-3470 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570 Processor (4 cores / 4 threads, 3.4GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit																					
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager																					
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo® AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)																					
Graphics	<i>Some:</i> Intel HD Graphics 2500 / 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, VGA)@60Hz <i>Some:</i> AMD Radeon™ HD 7350 , DirectX 11, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 30 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors <i>Some:</i> AMD Radeon HD 7450 , DirectX 11, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Maximum resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors																															
DP dongle	None																															
Disk	SATA 6.0Gb/s 7200 rpm																															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																															
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support																															
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector																															
eSATA port	None																															
Media reader	None																															
Chipset	Intel Q77 Express Chipset																															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																															
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort																															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)																															
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector																															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																															
Speaker	Internal speaker for business audio																															
IEEE 1394	None																															
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®																															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																															
Modem	None																															
Security chip	Trusted Platform Module (TPM1.2-compliant)																															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																															
Power supply	280 watts, autosensing, 85% PSU																															
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 																															
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 5.25", 1.6" high, access, open</p> <p>Bay 3: 3.5", 1" high, access, opt reader</p> <p>Bay 4: 3.5", 1" high, no access, std disk</p> <p>Bay 5: 3.5", 1" high, no access, opt disk</p>																															
Slot	<p>Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, 32-bit PCI 2.3</p> <p>Slot 4: half-length, full-height, 32-bit PCI 2.3</p>																															
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																															
Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object:<ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 																																
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																																
Supports ThinkVantage Technologies For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet																																

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3212-N4U	4x5	i5-3475S	4GBx1	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	None	Win7 Pro64	03/12/13

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty


Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3475S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets												Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Power Manager • View Management Utility • Lenovo® AppShop • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz														
DP dongle	None														
Disk	SATA 6.0Gb/s 7200 rpm														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
Onboard SATA	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
eSATA port	None														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for additional USB devices), one internal DisplayPort connector														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • Business black color; metal case • 6.9" W X 17.4" D X 16.3" H • 175mm W X 442mm D X 414mm H • 24.2 lb (11.0 kg) in maximum configuration • Toolless cover removal, toolless adapter retention • Toolless disk, optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
Slot	Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
															
	Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Cable lock • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 														
	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies														
	For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet														

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA optical	Media reader	Graphics	Display-Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Win7 Pro	Ann date preload (mm/dd/yy)	
3228-A1U	4x5	i7-3770	4GBx1	1600MHz	500G	7200	Bay	DVD±RW	None	HD 4000	None	None	ES52	vPro	G P	Pro 64 06/05/12
3228-A2U	4x5	i5-3470	4GBx1	1600MHz	500G	7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	G P	Pro 64 06/19/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770 Processor (4 cores / 8 threads , 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Genuine Windows® 7 Professional 64			
Implementation												Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Power Manager• View Management Utility• Lenovo AppShop• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz</i>														
DP dongle	None														
Disk Optical	SATA 6.0Gb/s 7200 rpm														
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
eSATA port	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector														
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec														
IEEE 1394	Internal speaker for business audio														
Ethernet	None														
Intel AMT	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Modem	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	None														
Keyboard	Trusted Platform Module (TPM1.2-compliant)														
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Power supply	Enhanced Optical USB Mouse, black, Lenovo logo														
Machine	280 watts, autosensing, 85% PSU														
Bay	Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 24.2 lb (11.0 kg) in maximum configuration Toolless cover removal Toolless disk, optical drive removal Toolless adapter retention														
Slot	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														



Type-model	Slot x bay	Processor	Memory ^b	SATA disk GB rpm	2nd Disk Bay	SATA optical	Media reader	Display Graphics	Port dongle	Chassis intrusion switch	ENERGY STAR 5.2	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
3228-A3U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	G P	Win8 Pro64	10/23/12
3228-A4U	4x5	i5-3470	4GBx1	500G 7200	Bay	DVD±RW	None	HD 2500	None	None	ES52	vPro	G P	Win7 Pro64	10/23/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Ultimate security, stability, and manageability for the enterprise Intel® Core™ i5-3470 Processor (4 cores / 4 threads) , 3.2GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation													Preloaded applications (only some listed) - Windows 7 models		
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets														
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort, VGA)@60Hz														
DP dongle	None												Windows 8 models		
Disk Optical	SATA 6.0Gb/s 7200 rpm														
SATA controller	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
Onboard SATA	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support														
	Two SATA cables (each 1-drop to device), two SATA 6.0Gb/s connectors, one SATA 3.0Gb/s connector, and one eSATA connector														
eSATA port	None												All models		
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), ethernet (RJ-45), VGA DB-15, DisplayPort														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
Internal connector	Two USB 2.0 planar conn (1 used; one open for media reader or 2 rear USB ports), one internal DisplayPort connector														
Audio Speaker	High Definition (HD) Audio, Realtek® ALC662 codec														
IEEE 1394	Internal speaker for business audio												ThinkVantage System Update		
Ethernet	None														
Intel AMT	One gigabit ethernet port, Intel 82579, Wake on LAN®														
Modem	Intel Active Management Technology 8.0 (Intel AMT 8.0)														
Security chip	None												Norton Internet Security (30 days of virus definitions)		
Keyboard	Trusted Platform Module (TPM1.2-compliant)														
Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo														
Power supply	Enhanced Optical USB Mouse, black, Lenovo logo														
Machine	280 watts, autosensing, 85% PSU												Microsoft® Office preloaded; purchase a product key to activate		
Bay	Business black color; metal case 6.9" W X 17.4" D X 16.3" H 175mm W X 442mm D X 414mm H 24.2 lb (11.0 kg) in maximum configuration Toolless cover removal Toolless disk, optical drive removal Toolless adapter retention												Skype™		
Slot	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk Slot 1: half-length, full-height, PCI Express 2.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, 32-bit PCI 2.3 Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Supports ThinkVantage Technologies		
													For compatible accessories, please go to O-M92 sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Memory	Multimedia
Tiny 3234/3243/3238/3237 use notebook memory: 2GB PC3-12800 DDR3 SODIMM 4GB PC3-12800 DDR3 SODIMM 8GB PC3-12800 DDR3 SODIMM	0A65722 ann 06/05/12 0A65723 ann 06/05/12 0A65724 ann 06/05/12
Small 3207/2988/3209/3227, and Tower 3208/2992/3212/3228 use desktop memory: 2GB PC3-12800 DDR3 UDIMM 4GB PC3-12800 DDR3 UDIMM 8GB PC3-12800 DDR3 UDIMM	0A65728 ann 06/05/12 0A65729 ann 06/05/12 0A65730 ann 06/05/12
More information at www.lenovo.com/support/desktopmemorycompatibility	⁶⁰ Has a 1.2 meter (3.9-foot) cable. Best when systems are in close proximity. Example: SFF placed on a desk.
Optical	Security
Small and Tower support: DVD-ROM DL SATA 1.5Gb/s 16X-48X Max ⁴ Lenovo® Super Multi-Burner SATA Drive	41N5618 ann 09/26/06 0A65618 ann 08/23/11
Storage and removable storage	Under Desk Mount
Small and Tower support: 500GB SATA 3.0Gb/s Disk (7200 rpm) 1TB SATA 3.0Gb/s Disk (7200 rpm) 180GB Solid State Drive	43R1990 ann 11/06/07 45J7918 ann 08/19/08 0B47308 ann 01/29/13
All: USB 2.0 Portable 500GB Hard Disk USB 3.0 Secure 500GB Hard Drive USB 3.0 Secure 750GB Hard Drive USB 3.0 Secure 1TB Hard Drive Slim USB Portable DVD Burner	45K1690 ann 05/26/09 0A65619 ann 11/29/11 0A65616 ann 11/29/11 0A65621 ann 08/28/12 0A33988 ann 06/14/11
Graphics	Monitors
Small 3207/2988/3209/3227 support Low Profile: NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	0B47077 ann 01/29/13
Tower 3208/2992/3212/3228 support: NVIDIA NVS 510 2GB Graphics Card by Lenovo ⁶⁷	0B47077 ann 01/29/13
⁶⁷ Simultaneously use the graphic card monitor ports along with the systems integrated monitor ports when Multi-Monitor Support is enabled in BIOS Setup.	
More information at www.lenovo.com/support/graphiccards	More information at www.lenovo.com/support/monitors
Keyboard	Monitor Accessories ⁴⁶
Preferred Pro USB Keyboard Enhanced Performance USB Keyboard Ultraslim Plus Wireless Keyboard and Mouse ⁵² ThinkPad® USB Keyboard with TrackPoint Lenovo USB Fingerprint Keyboard Lenovo USB Smartcard Keyboard	73P5220 ann 06/21/05 73P2620 ann 03/23/04 0A34032 ann 04/05/11 55Y9003 ann 08/18/09 73P4730 ann 02/22/05 51J0155 ann 03/24/09
⁵² Wireless via 2.4GHz technology using a micro-size USB receiver.	0B47072 ann 08/14/12 45J7915 ann 08/05/08 0B47092 ann 06/05/12 57Y4393 ann 08/04/09 0A36537 ann 09/13/11 0A36190 ann 05/01/12 73P2582 ann 12/29/03 45K1620 ann 09/30/08 57Y4303 ann 08/24/10 57Y4352 ann 07/06/10
More information at www.lenovo.com/support/keyboards	⁴⁶ Compatible on selected Lenovo and ThinkVision monitors. More information at www.lenovo.com/support/monitoraccessories
Mouse	For more information on accessories: www.lenovo.com/accessories Purchase Lenovo accessories
Lenovo Optical Mouse (USB) Lenovo ScrollPoint® Mouse(USB, Optical) ThinkPad Travel Mouse (USB, Optical) Lenovo Laser Mouse (USB) Lenovo Wireless Laser Mouse ⁵² ThinkPad USB Laser Mouse	31P7405 ann 08/27/02 31P7410 ann 06/04/02 41U3074 ann 01/23/07 0A36188 ann 12/20/11 57Y4635 ann 12/15/09
More information at www.lenovo.com/support/mice	www.lenovo.com/support/accessories Product specifications on Lenovo Support www.lenovo.com/accessoriesguide Option Compatibility Matrix (OCM) and accessory brochures www.lenovoquickpick.com An Options Compatibility Configurator for Lenovo systems
Modem	
USB 2.0 Lenovo Modem	43R1814 ann 02/26/08

ThinkCentre M92z All-In-One

ThinkCentre®



Lenovo ThinkCentre M92z with Frame Stand



Lenovo ThinkCentre M92z with Monitor Stand



Toolless Back Cover Removal



Toolless Stand Removal



Dual Independent Display with Optional Lenovo ThinkVision Monitor

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3280-A1U	i5-3470S	4GBx1	2.0M	500G 7200 HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12	
3280-A2U	i5-3470S	4GBx2	2.0M	1TB 7200 HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12	
3280-A5U	i3-3220	4GBx1	2.0M	500G 7200 HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	None	Win7 Pro64	11/20/12	

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit			
Implementation													Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• RapidBoot HDD Accelerator• Lenovo® SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• AccuWeather• Evernote®• CyberLink Power2Go (DVD±RW)• CyberLink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz															
DP dongle	None															
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch Camera	None															
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	All: <ul style="list-style-type: none">• Business black color• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm) Model(s) with 20" Non multi-touch, Frame stand: <ul style="list-style-type: none">• 19.8" W X 3.6" D X 16.1" H,• 503mm W X 92.5mm D X 408mm H (including stand)• 18.5 lb (8.4 kg) in maximum configuration Model(s) with 20" Non multi-touch, Monitor stand: <ul style="list-style-type: none">• 19.8" W X 5.6" D X 17.6" H,• 503mm W X 143mm D X 448mm H (including stand)• 23.0 lb (10.5 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)			
Limited Warranty	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3291-A8U	G630	4GBx1	2.0M	250G 7200	Intel HD	11b/g/n	None	None	S P	None	Frame	USB	None	None	Pro 64	06/05/12
3291-B9U	i3-2120	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64	06/05/12
3291-C1U	i3-2120	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	None	None	None	None	Monitor	USB	None	None	Prem 32	06/05/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Some: Genuine Windows® 7 Home Premium 32 Some: Genuine Windows 7 Professional 64			
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>															
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch Camera	None															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk Optical Onboard SATA	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Media reader	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard mSATA	None															
PCIe Mini Card	One msATA slot															
PCIe WLAN	One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)															
Keyboard Mouse	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>All:</i> <ul style="list-style-type: none">• Business black color• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)												<i>Chassis intrusion switch on selected model(s)</i>			
	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• 19.8" W X 3.6" D X 16.1" H,• 503mm W X 92.5mm D X 408mm H (including stand)• 18.5 lb (8.4 kg) in maximum configuration												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark			
	<i>Model(s) with 20" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• 19.8" W X 5.6" D X 17.6" H,• 503mm W X 143mm D X 448mm H (including stand)• 23.0 lb (10.5 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°												ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Supports ThinkVantage Technologies For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/Mouse	Intel vPro	Win7 Global preload	Ann date (mm/dd/yy)
3291-A4U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3291-A6U	i7-3770S	4GBx1	2.0M	1TB 7200	HD 4000	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3291-A7U	i5-3550S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3291-A9U	i5-3470T	4GBx1	2.0M	250G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	2.4G	vPro	None	Pro 64 06/05/12
3291-B1U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	2.4G	vPro	None	Pro 64 06/05/12
3291-B2U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	None	None	S P	None	Frame	2.4G	vPro	None	Pro 64 06/05/12
3291-B6U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Pro 64 06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 / 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor Multi-touch Camera	None None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons	
Disk Optical Onboard SATA	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports ExpressCard mSATA	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) None One mSATA slot	
PCIe Mini Card PCIe WLAN	One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth Ethernet	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black	EPEAT™ Gold rating
Mouse	Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black	ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark
Power supply	150 watts, autosensing, 85% PSU	ULE Gold EuP 2013
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 19.8" W X 3.6" D X 16.1" H• 503mm W X 92.5mm D X 408mm H (including stand)• 18.5 lb (8.4 kg) in maximum configuration• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)	Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Win7 Global preload	Ann date (mm/dd/yy)
3291-B7U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3291-B8U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3291-C7U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12
3291-C9U	i3-3220	2GBx1	2.0M	250G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12
3291-D1U	i3-3240	2GBx1	2.0M	250G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500 integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz															
DP dongle	None															
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch Camera	None															
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	Some: 11-in-1 Single Slot SD media reader															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Security chip	Trusted Platform Module (TPM 1.2-compliant)												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)			
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge			
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>Model(s) with 20" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• Business black color• 19.8" W X 5.6" D X 17.6" H• 503mm W X 143mm D X 448mm H (including stand)• 23.0 lb (10.5 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)												TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												Supports ThinkVantage Technologies For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial port & PS/2	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3291-C5U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3291-C8U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3291-D2U	i3-3220	2GBx1	2.0M	250G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3291-D3U	i3-3240	2GBx1	2.0M	250G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3291-D6U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win7 Pro64	10/23/12
3291-D7U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win7 Pro64	10/23/12
3291-E1U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	None	Win7 Pro64	12/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation														Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• RapidBoot HDD Accelerator• Lenovo® SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>															
DP dongle	None															
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch Camera	None															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard mSATA	None															
PCIe Mini Card	One mSATA slot															
PCIe WLAN	One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>All:</i> <ul style="list-style-type: none">• Business black color• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm) <i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• 19.8" W X 3.6" D X 16.1" H,• 503mm W X 92.5mm D X 408mm H (including stand)• 18.5 lb (8.4 kg) in maximum configuration <i>Model(s) with 20" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• 19.8" W X 5.6" D X 17.6" H,• 503mm W X 143mm D X 448mm H (including stand)• 23.0 lb (10.5 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°													Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M9ZZ sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Win7 Global preload	Ann date (mm/dd/yy)
3296-B1U	i3-2130	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	None	None	S P	None	Frame	USB	None	None	Pro 64 06/05/12
3296-B6U	G630	4GBx1	None	250G 7200	Intel HD	None	None	None	S P	None	Frame	USB	None	None	Pro 64 06/05/12
3296-B7U	G630	4GBx1	2.0M	250G 7200	Intel HD	11b/g/n	None	None	S P	None	Frame	USB	None	None	Pro 64 06/05/12

•3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Implementation	Memory 16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics or Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz															
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor Multi-touch Camera	None None <i>Some:</i> Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk Optical Onboard SATA	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports ExpressCard mSATA	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) None One mSATA slot															
PCIe Mini Card PCIe WLAN	One PCI Express® Mini Card slot <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth Ethernet Audio support	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel 82579LM, Wake on LAN® High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)															
Keyboard Mouse Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 150 watts, autosensing, 85% PSU													<i>Chassis intrusion switch on selected model(s)</i>		
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 													EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													Supports ThinkVantage Technologies For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3296-E4U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Pro 64	06/05/12
3296-E7U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	vPro	None	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
 - These models have a 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads) , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads) , 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system ²⁰ Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility ThinkVantage Automatic Lock Utility ThinkVantage Power Manager View Management Utility Lenovo Solution Center Lenovo Message Center Plus RapidBoot HDD Accelerator Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DV(D±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle Display	None 20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	None	
Multi-touch Camera	None	
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off <i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	<i>Some:</i> 11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with 20" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> Business black color 19.8" W X 5.6" D X 17.6" H 503mm W X 143mm D X 448mm H (including stand) 23.0 lb (10.5 kg) in maximum configuration Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° Toolless back cover, stand removal Toolless disk, optical drive, memory removal Support VESA mount (100mm) 	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M9Z2 sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US models announced June 5, 2012

US model(s) withdrawn effective December 2013

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Win7 Global preload	Ann date (mm/dd/yy)
3296-B2U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3296-B3U	i5-3550S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3296-B5U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3296-E5U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Pro 64 06/05/12
3296-E6U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	Media	None	None	None	Frame	USB	vPro	None	Pro 64 06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• 3-year limited warranty

Positioning Processor	<p>Premium All-In-One PC for the enterprise</p> <p>Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Implementation	<p>16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)</p>												Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • <i>Chassis intrusion switch on selected model(s)</i> 		
Memory	<p>Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort) @60Hz</i></p>														
Graphics	<p>DP dongle Display</p> <p>20.0" (508mm) HD+ (1600x900) TFT color, LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector</p> <p>Light sensor</p> <p>Multi-touch Camera</p> <p>Controls</p> <p>Disk Optical Onboard SATA</p> <p>Media reader</p> <p>Chipset</p> <p>Rear ports</p> <p>Side ports ExpressCard mSATA</p> <p>PCIe Mini Card PCIe WLAN</p> <p>Bluetooth Ethernet</p> <p>Audio support</p> <p>Intel AMT Security chip</p> <p>Keyboard Mouse</p> <p>Power supply</p> <p>Machine</p>														
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3296-F6U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Win8 Pro64	10/23/12
3296-G6U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	None	Win8 Pro64	10/23/12
3296-G7U	i3-3240	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	None	Win8 Pro64	10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads , 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Windows® 8 Pro 64-bit					
Implementation													Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • ThinkVantage Automatic Lock Utility • View Management Utility • Lenovo® Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 					
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>																	
DP dongle	None																	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector																	
Light sensor	None																	
Multi-touch Camera	None																	
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons																	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar																	
Media reader	None																	
Chipset	Intel Q77 Express Chipset																	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																	
ExpressCard	None																	
mSATA	One mSATA slot																	
PCIe Mini Card	One PCI Express® Mini Card slot																	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®																	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Sync™ certified																	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																	
Security chip	Trusted Platform Module (TPM 1.2-compliant)																	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																	
Power supply	150 watts, autosensing, 85% PSU																	
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 																	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																	

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB	SATA rpm	Graphics	PCIe Mini Card	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3296-F4U	i5-3470S	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3296-F5U	i5-3470S	4GBx2	2.0M	1TB	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3296-G8U	i3-3240	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3296-G9U	i3-3220	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3296-H1U	i5-3470T	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3296-H2U	i5-3570S	4GBx1	2.0M	1TB	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3296-H3U	i5-3570S	4GBx2	2.0M	1TB	7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	vPro	None	Win8 Pro64	10/23/12
3296-H7U	i5-3470S	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win7 Pro64	10/23/12
3296-J8U	i5-3470S	4GBx1	2.0M	180G	SSD	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Win7 Pro64	11/20/12

Positioning Processor	<p>Premium All-In-One PC for the enterprise</p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p>		Preloaded operating system²⁰															
<p>Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit</p> <p>Some: Windows 8 Pro 64-bit</p>																		
Preloaded applications (only some listed)																		
- Windows 7 models																		
<ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• RapidBoot HDD Accelerator• Lenovo® SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)																		
- Windows 8 models																		
<ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW)																		
- All models																		
<ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™																		
Security																		
<ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)																		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz																	
DP dongle	None																	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector																	
Light sensor	None																	
Multi-touch Camera	None																	
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off																	
Disk	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons																	
Optical	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide																	
Onboard SATA	Some: Hard Disk Drive / SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																	
Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																	
Chipset	Intel Q77 Express Chipset																	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																	
ExpressCard	None																	
mSATA	One mSATA slot																	
PCIe Mini Card	One PCI Express® Mini Card slot																	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter																	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®																	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified																	
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)																	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																	
Power supply	150 watts, autosensing, 85% PSU																	
Machine	Model(s) with 20" Non multi-touch, Monitor stand: <ul style="list-style-type: none">• Business black color• 19.8" W X 5.6" D X 17.6" H• 503mm W X 143mm D X 448mm H (including stand)• 23.0 lb (10.5 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)																	
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																	
	For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet																	

See footnotes for important warranty information

US models announced October 23 or November 20, 2012

US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-22) January 2014

Type-model	Processor	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3298-A2U	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media Sensor	None	Switch	Frame	USB	vPro	G P	Pro 64	06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	Premium All-In-One PC for the enterprise	Preloaded operating system ²⁰
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	Ambient Light Sensor	
Multi-touch	None	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with 20" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 19.8" W X 3.6" D X 16.1" H, • 503mm W X 92.5mm D X 408mm H (including stand) • 18.5 lb (8.4 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 	Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s) EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB	SATA rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global GMP (G) P	Global GMP (G) P	Preload	Ann date (mm/dd/yy)
3298-A4U	i5-3470S	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro	G P	Win8 Pro	64	10/23/12
3298-A6U	i5-3470S	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	Media	Sensor	None	None	Frame	USB	vPro	G P	Win7 Pro	64	10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
 - Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470S Processor (4 cores / 4 threads) , 2.9GHz, 6MB cache, Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system ²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit
Implementation		Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">● ThinkVantage® Product Recovery● ThinkVantage Communication Utility● ThinkVantage Power Manager● RapidBoot HDD Accelerator● Lenovo® SimpleTap● Adobe® Reader®● Corel® Burn.Now™ (DVD±RW)● Corel DVD MovieFactory® (DVD±RW)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort) @60Hz	
DP dongle	None	
Display	20.0" (508mm) HD+ (1600x900) TFT color , LED backlight, 250 nits, 16:9 aspect ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	Ambient Light Sensor	
Multi-touch	None	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo	
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	
Power supply	150 watts, autosinging, 85% PSU	
Machine	Model(s) with 20" Non multi-touch, Frame stand: <ul style="list-style-type: none">● Business black color● 19.8" W X 3.6" D X 16.1" H,● 503mm W X 92.5mm D X 408mm H (including stand)● 18.5 lb (8.4 kg) in maximum configuration● Toolless back cover, stand removal● Toolless disk, optical drive, memory removal● Support VESA mount (100mm)	Security <ul style="list-style-type: none">● Security chip (see information on left)● Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)● Power-on password● Hard disk password● Boot sequence control● Boot without keyboard and mouse● USB port disablement● Chassis intrusion switch on selected model(s) <p>EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies</p>
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M9Z2 sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US models announced October 23, 2012

US model(s) withdrawn effective December 2013

Type-model Processor	Processor	Camera (mega-pixel) ^b	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro Global	Preload	Ann date (mm/dd/yy)
3315-A3U	i5-3470S	4GBx1	2.0M	500G 7200 HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	vPro	None	Win8 Pro64 10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system ²⁰ Windows® 8 Pro 64-bit
Implementation													Preloaded applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												• ThinkVantage® System Update • ThinkVantage Automatic Lock Utility • View Management Utility • Lenovo® Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW)
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>												
DP dongle Display	None 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector												
Light sensor	None												
Multi-touch Camera	None												
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off												
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm												
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable												
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar												
Media reader	11-in-1 Single Slot SD media reader												
Chipset	Intel Q77 Express Chipset												
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)												
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
ExpressCard	None												
mSATA	One mSATA slot												
PCIe Mini Card	One PCI Express® Mini Card slot												
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®												
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified												
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)												
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	150 watts, autosensing, 85% PSU												
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• Business black color• 22.4" W X 9.7" D X 17.8" H• 568mm W X 247mm D X 452mm H (including stand)• 25.7 lb (11.7 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)												Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)
Limited Warranty	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3318-C2U	i3-2120	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64	06/05/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
 - 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-2120 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system ²⁰ Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort)@60Hz	
DP dongle Display	None 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Light sensor Multi-touch Camera	None None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons	
Disk Optical Onboard SATA	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	None	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports ExpressCard mSATA	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) One mSATA slot	
PCIe Mini Card PCIe WLAN	One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth Ethernet Audio support	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter One gigabit ethernet port, Intel 82579LM, Wake on LAN® High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)	
Keyboard Mouse Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 150 watts, autosensing, 85% PSU	
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 9.7" D X 17.8" H • 568mm W X 247mm D X 452mm H (including stand) • 25.7 lb (11.7 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	Supports ThinkVantage Technologies For compatible accessories, please go to O-M9Z2 sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US models announced June 5, 2012

US model(s) withdrawn effective November 2013

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3318-A4U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3318-A5U	i5-3550S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3318-A6U	i7-3770S	4GBx2	2.0M	500G 7200	HD 4000	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3318-B7U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Pro 64 06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4000, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Implementation														Security <ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>													
DP dongle Display	None 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor Multi-touch Camera	None None Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons													
Disk Optical Onboard SATA	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports ExpressCard mSATA	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm) None One mSATA slot													
PCIe Mini Card PCIe WLAN	One PCI Express® Mini Card slot 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth Ethernet	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Audio support	One gigabit ethernet port, Intel 82579LM, Wake on LAN® High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)													
Keyboard Mouse Power supply	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Enhanced Optical USB Mouse, black, Lenovo logo 150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

Type-model	Processor	Memory ^b	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3318-B6U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3318-B8U	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3318-B9U	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	None	None	None	None	Monitor	2.4G	vPro	None	Pro 64 06/05/12
3318-C1U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	11b/g/n	None	None	None	None	Monitor	2.4G	vPro	None	Pro 64 06/05/12
3318-E3U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470T Processor (2 cores / 4 threads , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads , 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system ²⁰ Genuine Windows® 7 Professional 64																			
Implementation													Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box																			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)																			
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>																															
DP dongle	None																															
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector																															
Light sensor	None																															
Multi-touch	None																															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off																															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons																															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar																															
Media reader	<i>Some:</i> 11-in-1 Single Slot SD media reader																															
Chipset	Intel Q77 Express Chipset																															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																															
ExpressCard	None																															
mSATA	One mSATA slot																															
PCIe Mini Card	One PCI Express® Mini Card slot																															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®																															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified																															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)																															
Security chip	Trusted Platform Module (TPM 1.2-compliant)																															
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black																															
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black																															
Power supply	150 watts, autosensing, 85% PSU																															
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• Business black color• 22.4" W X 9.7" D X 17.8" H• 568mm W X 247mm D X 452mm H (including stand)• 25.7 lb (11.7 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)																															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																															

Type-model	Processor	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	& PS/2 port	Serial port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)																
3318-E5U i5-3470T	4GBx1	2.0M	1TB 7200	HD 2500	Intel 2230 + BT	Media	None	None	None	Frame	USB	vPro	None	Win8 Pro64	10/23/12																	
3318-E6U i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	Media	None	None	None	Frame	USB	vPro	None	Win8 Pro64	10/23/12																	
3318-E7U i5-3570S	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	Media	None	None	None	Frame	USB	vPro	None	Win8 Pro64	10/23/12																	
3318-H5U i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Frame	USB	vPro	None	Win7 Pro64	11/20/12																	
3318-H7U i3-3220	4GBx1	2.0M	180G SSD	HD 2500	Intel 2230 + BT	None	None	None	None	Frame	USB	None	None	Win7 Pro64	11/20/12																	
3318-J1U i3-3220	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Frame	USB	None	None	Win7 Pro64	12/04/12																	
3318-J5U G870	4GBx1	2.0M	500G 7200	Intel HD	Intel 2230 + BT	None	None	None	None	Frame	USB	None	None	Win7 Pro64	01/22/13																	
3318-J8U i5-3330S	4GBx1	2.0M	1TB 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Frame	USB	None	None	Win7 Pro64	03/12/13																	
Positioning Processor	Premium All-In-One PC for the enterprise Intel® Pentium® G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3330S Processor (4 cores / 4 threads, 2.7GHz, 6MB cache), Turbo Boost 2.0 (3.2GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit																			
Implementation	Processor in LGA1155 socket												Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• RapidBoot HDD Accelerator• Lenovo® SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™																			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																															
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz																															
DP dongle	None																															
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector																															
Light sensor	None																															
Multi-touch	None																															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off																															
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons																															
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																															
Optical	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar																															
Onboard SATA	Some: 11-in-1 Single Slot SD media reader																															
Media reader	Intel Q77 Express Chipset																															
Chipset	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																															
Rear ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																															
Side ports	None																															
ExpressCard	One mSATA slot																															
mSATA	One PCI Express® Mini Card slot																															
PCIe Mini Card	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																															
PCIe WLAN	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																															
Bluetooth	One gigabit ethernet port, Intel 82579LM, Wake on LAN®																															
Ethernet	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified																															
Audio support	Intel Active Management Technology 8.0 (Intel AMT 8.0)																															
Intel AMT	Trusted Platform Module (TPM 1.2-compliant)																															
Security chip																																
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo																															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																															
Power supply	150 watts, autosensing, 85% PSU																															
Machine	Model(s) with 23" Non multi-touch, Frame stand: <ul style="list-style-type: none">• Business black color• 22.4" W X 3.7" D X 17.6" H• 568mm W X 93mm D X 447mm H (including stand)• 21.5 lb (9.8 kg) in maximum configuration• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)																															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																															
See footnotes for important warranty information																																
US models announced Oct 23, 2012, Nov 20, 2012, Dec 4, 2012, Jan 22, 2013, or Mar 12, 2013																																
US model(s) withdrawn effective November or December 2013																																

Type-model Processor	Processor	Camera (megapixel)	Disk SATA GB	Disk rpm	PCIe Graphics	Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3318-E2U i3-3220	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3318-F5U i3-3220	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3318-F6U i3-3240	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3318-F3U i3-3240	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	Media	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3318-F4U G870	4GBx1	2.0M	500G	7200	Intel HD	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win8 Pro64	10/23/12
3318-F9U i3-3220	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win7 Pro64	10/23/12
3318-J3U G2120	4GBx1	2.0M	500G	7200	Intel HD	11b/g/n	None	None	None	None	Monitor	USB	None	None	Win7 Pro64	12/04/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 3-year limited warranty

Positioning Processor	<p>Premium All-In-One PC for the enterprise</p> <p>Intel® Pentium® G870 Processor (2 cores / 2 threads), 3.1GHz, 3MB cache, integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G2120 Processor (2 cores / 2 threads), 3.1GHz, 3MB cache, integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core™ i3-3220 Processor (2 cores / 4 threads), 3.3GHz, 3MB cache, integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i3-3240 Processor (2 cores / 4 threads), 3.4GHz, 3MB cache, integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system²⁰
Implementation		Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Memory	<p>16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)</p> <p>System automatically clocks down for processors with 1333MHz DDR3 memory controller</p>	Some: Windows 8 Pro 64-bit
Graphics	<p>Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz</p>	Preloaded applications (only some listed) - Windows 7 models
DP dongle	None	• ThinkVantage® Product Recovery
Display	<p>23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector</p>	• ThinkVantage Communication Utility
Light sensor	None	• ThinkVantage Power Manager
Multi-touch Camera	None	• Lenovo® SimpleTap
Controls	<p>Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button</p> <p>Side: Volume up and down buttons</p>	• Adobe® Reader®
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	• Corel® Burn.Now™ (DVD±RW)
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	• Corel DVD MovieFactory® (DVD±RW)
Onboard SATA	<p>Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar</p> <p>Some: 11-in-1 Single Slot SD media reader</p>	- Windows 8 models
Media reader		• Lenovo Support
Chipset	Intel Q77 Express Chipset	• Lenovo Settings
Rear ports	<p>Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)</p>	• Lenovo Companion
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	• Lenovo Cloud Storage
ExpressCard	None	• Norton™ Studio
mSATA	One mSATA slot	• AccuWeather
PCIe Mini Card	One PCI Express® Mini Card slot	• Evernote®
PCIe WLAN	<p>11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</p>	• Cyberlink Power2Go (DVD±RW)
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	• Cyberlink PowerProducer (DVD±RW)
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	- All models
Audio support	<p>High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified</p>	• ThinkVantage System Update
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	• ThinkVantage Automatic Lock Utility
Security chip	Trusted Platform Module (TPM 1.2-compliant)	• Lenovo Solution Center
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	• View Management Utility
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	• Norton Internet Security (30 days of virus definitions)
Power supply	150 watts, autosingens, 85% PSU	• Microsoft® Office preloaded; purchase a product key to activate
Machine	<p>Model(s) with 23" Non multi-touch, Monitor stand:</p> <ul style="list-style-type: none"> • Business black color • 22.4" W X 9.7" D X 17.8" H • 568mm W X 247mm D X 452mm H (including stand) • 25.7 lb (11.7 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 	• Skype™
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>	Security
		<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
		EPEAT™ Gold rating
		ENERGY STAR® 5.2-compliant
		TCO Certified Edge
		TUV Green Mark
		ULE Gold
		EuP 2013
		Cisco EnergyWise compatible
		GREENGUARD® certified
		RoHS-compliant
		Supports ThinkVantage Technologies
		For compatible accessories, please go to O-M92Z sheet;
		For Lenovo service upgrade options, please go to S-TC sheet

Type-model Processor	Camera (megapixel) ^b	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel Mouse vPro Global	Preload	Ann date (mm/dd/yy)											
3318-D2U i5-3470S 4GBx1 2.0M 500G 7200 HD 2500 Intel 2230 + BT None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-E1U i5-3470S 4GBx1 2.0M 500G 7200 HD 2500 Intel 2230 + BT Media None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-E8U i7-3770S 4GBx2 2.0M 1TB 7200 HD 4000 Intel 2230 + BT Media None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-E9U i5-3570S 4GBx1 2.0M 1TB 7200 HD 2500 Intel 2230 + BT Media None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-F1U i5-3570S 4GBx1 2.0M 500G 7200 HD 2500 Intel 2230 + BT Media None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-F2U i5-3470T 4GBx1 2.0M 500G 7200 HD 2500 Intel 2230 + BT Media None None None Monitor USB vPro None Win8 Pro64 10/23/12																							
3318-G1U i5-3470S 4GBx1 2.0M 500G 7200 HD 2500 Intel 2230 + BT None None None Monitor USB vPro None Win7 Pro64 10/23/12																							
3318-J4U i5-3470S 4GBx1 2.0M 500G 7200 HD 2500 Intel 6205 None None None Monitor USB vPro None Win7 Pro64 01/22/13																							
3318-J6U i7-3770S 4GBx1 2.0M 1TB 7200 HD 4000 Intel 2230 + BT None None None Monitor 2.4G vPro None Win7 Pro64 03/05/13																							
Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (2 cores / 4 threads , 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3570S Processor (4 cores / 4 threads , 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads , 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system ²⁰											
Implementation	<i>Some:</i> Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 8 Pro 64-bit											Preloaded applications (only some listed)											
Memory	- Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™																						
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution:</i> 2560x1600 (DisplayPort)@60Hz																						
DP dongle Display	None 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector																						
Light sensor	None																						
Multi-touch Camera	None																						
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off																						
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																						
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																						
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar																						
Media reader	<i>Some:</i> 11-in-1 Single Slot SD media reader																						
Chipset	Intel Q77 Express Chipset																						
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)																						
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																						
ExpressCard	None																						
mSATA	One mSATA slot																						
PCIe Mini Card	One PCI Express® Mini Card slot																						
PCIe WLAN	<i>Some:</i> 11a/b/g/n, PCIe Half Mini Card, Intel Centrino® Advanced-N 6205, 2x2 <i>Some:</i> 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																						
Bluetooth	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																						
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®																						
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified																						
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)																						
Keyboard	<i>Some:</i> Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo <i>Some:</i> Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black																						
Mouse	<i>Some:</i> Enhanced Optical USB Mouse, black, Lenovo logo <i>Some:</i> Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black																						
Power supply	150 watts, autosensing, 85% PSU																						
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none">• Business black color• 22.4" W X 9.7" D X 17.8" H• 568mm W X 247mm D X 452mm H (including stand)• 25.7 lb (11.7 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)																						
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																						
Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)																							
EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant																							
Supports ThinkVantage Technologies For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet																							

See footnotes for important warranty information

US models announced October 23, 2012, January 22, 2013 or March 5, 2013

US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-27) January 2014

Type-model	Processor	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Win7 Global preload	Ann date (mm/dd/yy)
3325-A1U	i3-2130	4GBx1	2.0M	500G 7200	HD 2000	11b/g/n	None	None	S P	None	Frame	USB	None None	Pro 64 06/05/12

•3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2000 in processor, uses main memory, HDCP, DirectX® 10.1, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>										Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
DP dongle	None													
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor	None													
Multi-touch Camera	None													
Controls	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Disk	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button													
Optical	Side: Volume up and down buttons													
Onboard SATA	None													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
ExpressCard	None													
mSATA	One mSATA slot													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none">• Business black color• 22.4" W X 3.7" D X 17.6" H• 568mm W X 93mm D X 447mm H (including stand)• 21.5 lb (9.8 kg) in maximum configuration• Toolless back cover, stand removal ,• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)										<i>Chassis intrusion switch on selected model(s)</i>			
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available										EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies			
											For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet			

Type-model Processor	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/Mouse	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3325-B3U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3325-B4U	i5-3550S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	S P	None	Frame	USB	vPro	None	Pro 64 06/05/12
3325-E2U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Pro 64 06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<p>Premium All-In-One PC for the enterprise</p> <p>Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p>											<p>Preloaded operating system²⁰</p> <p>Genuine Windows® 7 Professional 64</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 			
Implementation	<p>Processor in LGA1155 socket</p>														
Memory	<p>16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)</p>														
Graphics	<p>Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort) @ 60Hz</p>														
DP dongle Display	<p>None</p> <p>23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector</p>														
Light sensor	<p>None</p>														
Multi-touch Camera	<p>None</p> <p>Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off</p>														
Controls	<p>Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button</p> <p>Side: Volume up and down buttons</p>														
Disk Optical Onboard SATA	<p>SATA 6.0Gb/s, 3.5" Wide, 7200 rpm</p> <p>DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable</p> <p>Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar</p>														
Media reader	<p>None</p>														
Chipset	<p>Intel Q77 Express Chipset</p>														
Rear ports	<p>Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)</p>														
Side ports	<p>Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>														
ExpressCard mSATA	<p>None</p>														
PCIe Mini Card	<p>One mSATA slot</p>														
PCIe WLAN	<p>One PCI Express® Mini Card slot</p> <p>11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</p>														
Bluetooth	<p>Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter</p>														
Ethernet	<p>One gigabit ethernet port, Intel 82579LM, Wake on LAN®</p>														
Audio support	<p>High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified</p>														
Intel AMT Security chip	<p>Intel Active Management Technology 8.0 (Intel AMT 8.0)</p> <p>Trusted Platform Module (TPM 1.2-compliant)</p>														
Keyboard Mouse	<p>Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo</p> <p>Enhanced Optical USB Mouse, black, Lenovo logo</p>														
Power supply	<p>150 watts, autosensing, 85% PSU</p>														
Machine	<p>Model(s) with 23" Non multi-touch, Frame stand:</p> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal , • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 														
Limited Warranty	<p>3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>														
	<p>EPEAT™ Gold rating</p> <p>ENERGY STAR® 5.2-compliant</p> <p>TCO Certified Edge</p> <p>TUV Green Mark</p> <p>ULE Gold</p> <p>EuP 2013</p> <p>Cisco EnergyWise compatible</p> <p>GREENGUARD® certified</p> <p>RoHS-compliant</p>														
	<p>Supports ThinkVantage Technologies</p> <p>For compatible accessories, please go to O-M92Z sheet;</p> <p>For Lenovo service upgrade options, please go to S-TC sheet</p>														

See footnotes for important warranty information

US models announced June 5, 2012

US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-12) January 2014

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Intel Mouse vPro	Win7 Global preload	Ann date (mm/dd/yy)
3325-E1U	i5-3470T	4GBx1	2.0M	500G	7200	HD 2500	11b/g/n	None	None	None	Monitor	USB vPro	None Pro 64	06/05/12
3325-D9U	i7-3770S	4GBx1	2.0M	500G	7200	HD 4000	11b/g/n	None	None	None	Monitor	USB vPro	None Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	<p>Premium All-In-One PC for the enterprise</p> <p>Intel® Core™ i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>											Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Implementation														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>													
DP dongle	None													
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor	None													
Multi-touch	None													
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons													
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
ExpressCard	None													
mSATA	One mSATA slot													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)													
Security chip	Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, 1000dpi, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	<i>Model(s) with 23" Non multi-touch, Monitor stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 9.7" D X 17.8" H • 568mm W X 247mm D X 452mm H (including stand) • 25.7 lb (11.7 kg) in maximum configuration • Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45° • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 											EPEAT™ Gold rating ENERGY STAR® 6.0-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant		
												Supports ThinkVantage Technologies		
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet		

Type-model	Processor	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global	Preload	Ann date (mm/dd/yy)
3325-F6U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	Frame	USB	vPro	None	Win8 Pro64	10/23/12
3325-G7U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	Frame	USB	None	None	Win8 Pro64	10/23/12
3325-G8U	i3-3240	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	Frame	USB	None	None	Win8 Pro64	10/23/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i3-3240 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket													Preloaded operating system²⁰ Windows® 8 Pro 64-bit		
Implementation														Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • ThinkVantage Automatic Lock Utility • View Management Utility • Lenovo® Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)															
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort) @60Hz</i>															
DP dongle	None															
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector															
Light sensor	None															
Multi-touch	None															
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off															
Controls	<i>Front:</i> Microphone mute, speaker mute, monitor mode, OSD menu, and power button <i>Side:</i> Volume up and down buttons															
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm															
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable															
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar															
Media reader	None															
Chipset	Intel Q77 Express Chipset															
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)															
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
ExpressCard	None															
mSATA	One mSATA slot															
PCIe Mini Card	One PCI Express® Mini Card slot															
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2															
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter															
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®															
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)															
Security chip	Trusted Platform Module (TPM 1.2-compliant)															
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	150 watts, autosensing, 85% PSU															
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal , • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 															
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															

See footnotes for important warranty information

US models announced October 23 or November 20, 2012 or June 25, 2013

US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-29) January 2014

(MTRR1-26) Canada

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global (G) GMP (P)	Win7 preload	Ann date (mm/dd/yy)
3327-A4U	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro	G P	Pro 64	06/05/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	Premium All-In-One PC for the enterprise	Preloaded operating system ²⁰
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Genuine Windows® 7 Professional 64
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	Ambient Light Sensor	
Multi-touch	None	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, WiFi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	Security
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Power supply	150 watts, autosensing, 85% PSU	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Machine	<i>Model(s) with 23" Non multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.7" D X 17.6" H, • 568mm W X 93mm D X 447mm H (including stand) • 21.5 lb (9.8 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 	Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Processor	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)	
3327-A8U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro	G P	Win8 Pro64	10/23/12
3327-B2U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	Media	Sensor	None	None	Frame	USB	vPro	G P	Win7 Pro64	10/23/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit													
Implementation		Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Norton™ Studio• AccuWeather• Evernote®• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic Lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Skype™													
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)														
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>														
DP dongle	None														
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	Ambient Light Sensor														
Multi-touch Camera	None														
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	11-in-1 Single Slot SD media reader														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard mSATA	None														
PCIe Mini Card	One mSATA slot														
PCIe WLAN	One PCI Express® Mini Card slot														
Bluetooth	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter														
Ethernet	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Audio support	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified															
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	150 watts, autosensing, 85% PSU														
Machine	Model(s) with 23" Non multi-touch, Frame stand: <ul style="list-style-type: none">• Business black color• 22.4" W X 3.7" D X 17.6" H,• 568mm W X 93mm D X 447mm H (including stand)• 21.5 lb (9.8 kg) in maximum configuration• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														

Type-model Processor	Processor Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel vPro	Global	Win7 preload	Ann date (mm/dd/yy)
3311-A4U i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	2.4G	vPro	None	Pro 64	06/05/12
3311-C2U i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	vPro	None	Pro 64	11/20/12
3311-C3U i3-3220	4GBx1	2.0M	500G 7200	HD 2500	11b/g/n	None	None	None	None	Frame	USB	None	None	Pro 64	12/11/12

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Premium All-In-One PC for the enterprise</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Preloaded operating system²⁰ Genuine Windows® 7 Professional 64			
Implementation	Processor in LGA1155 socket											Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box			
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Microsoft Touch Pack• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)			
Graphics	Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>											Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)			
DP dongle	None														
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector														
Light sensor	None														
Multi-touch	Multi-touch, 2-point support														
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off														
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons														
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm														
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable														
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar														
Media reader	None														
Chipset	Intel Q77 Express Chipset														
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)														
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
ExpressCard	None														
mSATA	One mSATA slot														
PCIe Mini Card	One PCI Express® Mini Card slot														
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2														
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter														
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®														
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified														
Intel AMT	Trusted Platform Module (TPM 1.2-compliant)														
Security chip															
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo														
Mouse	Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black														
Power supply	Some: Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	Some: Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black														
Machine	150 watts, autosinging, 85% PSU														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														

See footnotes for important warranty information

US models announced June 5, November 20, or December 11, 2012

US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-15) January 2014

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN / BT	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Key-board/ Mouse	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)
3311-B1U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3311-B2U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	Intel 2230 + BT	Media	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3311-B3U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	Intel 2230 + BT	Media	None	None	None	Monitor	2.4G	vPro	None	Pro 64 06/05/12
3311-B9U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12
3311-C1U	i5-3470S	4GBx1	2.0M	180G SSD	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 11/20/12
3311-C4U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	Intel 6205	None	None	None	None	Monitor	USB	vPro	None	Pro 64 01/22/13

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Preloaded operating system²⁰ Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Microsoft Touch Pack• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz	
DP dongle	None	
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color, IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	None	
Multi-touch	Multi-touch, 2-point support	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons	
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	Some: 11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	Some: 11a/b/g/n, PCIe Half Mini Card, Intel Centrino® Advanced-N 6205, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Some: Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black	Security <ul style="list-style-type: none">• Security chip (see information on left)• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Power-on password• Hard disk password• Boot sequence control• Boot without keyboard and mouse• USB port disablement• Chassis intrusion switch on selected model(s)
Mouse	Some: Enhanced Optical USB Mouse, black, Lenovo logo Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Machine	Model(s) with 23" multi-touch, Monitor stand: <ul style="list-style-type: none">• Business black color• 22.4" W X 10.0" D X 17.8" H• 568mm W X 254mm D X 452mm H (including stand)• 28.2 lb (12.8 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)	
Limited Warranty ¹²	3-years, limited onsite service²⁴ , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades ²² available	For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US models announced June 5, 2012, Sep 4, 2012, Nov 20, 2012, or Jan 22, 2013
US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-16) January 2014

Type-model	Processor	Camera (megapixel) ⁸	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial port & PS/2/intrusion switch	Chassis	Stand type	Keyboard/Mouse	Intel vPro	Win7 Global	Ann date preload (mm/dd/yy)	
3314-D8U	i7-3770S	4GBx2	2.0M	1TB 7200	HD 4000	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3314-D9U	i5-3470T	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 06/05/12
3314-E7U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 08/14/12
3314-E6U	i3-3220	4GBx1	2.0M	500G 7200	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	None	None	Pro 64 09/04/12
3314-F1U	i5-3470S	4GBx1	2.0M	180G SSD	HD 2500	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 11/20/12
3314-F2U	i7-3770S	8GBx1	2.0M	1TB 7200	HD 4000	Intel 2230 + BT	None	None	None	None	Monitor	USB	vPro	None	Pro 64 12/11/12
3314-F3U	i5-3470S	4GBx1	2.0M	500G 7200	HD 2500	Intel 6205	None	None	None	None	Monitor	USB	vPro	None	Pro 64 01/22/13

Positioning Processor	Premium All-In-One PC for the enterprise Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3470T Processor (2 cores / 4 threads, 2.9GHz, 3MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket												Preloaded operating system²⁰ Genuine Windows® 7 Professional 64 Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Microsoft® Touch Pack• Lenovo Solution Center• Lenovo Message Center Plus• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)	
Implementation	Processor in LGA1155 socket													
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics 2500 or Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; Maximum resolution: 2560x1600 (DisplayPort)@60Hz													
DP dongle Display	None 23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector													
Light sensor	None													
Multi-touch Camera	Multi-touch, 2-point support Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off													
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons													
Disk	Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide Some: Hard Disk Drive / SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar													
Media reader	None													
Chipset	Intel Q77 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
ExpressCard	None													
mSATA	One mSATA slot													
PCIe Mini Card	One PCI Express® Mini Card slot													
PCIe WLAN	Some: 11a/b/g/n, PCIe Half Mini Card, Intel Centrino® Advanced-N 6205, 2x2 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®													
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified													
Intel AMT Security chip	Intel Active Management Technology 8.0 (Intel AMT 8.0) Trusted Platform Module (TPM 1.2-compliant)													
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	150 watts, autosensing, 85% PSU													
Machine	Model(s) with 23" multi-touch, Monitor stand: <ul style="list-style-type: none">• Business black color• 22.4" W X 10.0" D X 17.8" H• 568mm W X 254mm D X 452mm H (including stand)• 28.2 lb (12.8 kg) in maximum configuration• Tilt: 45° back, -5° forward; Lift: 110mm; Swivel: +/-45°• Toolless back cover, stand removal• Toolless disk, optical drive, memory removal• Support VESA mount (100mm)													
Limited Warranty ¹²	3-years, limited onsite service²⁴ , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades ²² available													
	For compatible accessories, please go to O-M92Z sheet; For Lenovo service upgrade options, please go to S-TC sheet													

See footnotes for important warranty information

US models announced Jun 5, Aug 14, Sep 4, No 20, Dec 11, 2012, or Jan 22, 2013
US model(s) withdrawn effective December 2013

©Lenovo

(MTRL1-17) January 2014

Type-model	Processor	Camera (mega-pixel)	Disk SATA GB rpm	Graphics	PCIe Mini Card WLAN	Media reader	Light sensor	Serial & PS/2 port	Chassis intrusion switch	Stand type	Keyboard/ Mouse	Intel Global (G) vPro	Win7 GMP (P) preloaded	Ann date (mm/dd/yy)	
3329-A4U	i7-3770S	4GBx1	2.0M	500G 7200	HD 4000	11b/g/n	Media	Sensor	None	Switch	Frame	USB	vPro	G P Pro	64 06/05/12

• Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology

• Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	Premium All-In-One PC for the enterprise	Preloaded operating system ²⁰
Processor	Intel® Core™ i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket	Genuine Windows® 7 Professional 64
Implementation		Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Microsoft Touch Pack • Lenovo Solution Center • Lenovo Message Center Plus • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics 4000 in processor, uses main memory, DirectX® 11, external digital monitor support via DisplayPort™, supports dual independent display; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz</i>	
DP dongle	None	
Display	23.0" (580.4mm) Full HD 1080p (1920x1080) TFT color , IPS wide viewing angle, anti-glare, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio, work as standalone monitor via DisplayPort-in connector	
Light sensor	Ambient Light Sensor	
Multi-touch	Multi-touch, 2-point support	
Camera	Camera on top of screen, 2.0-megapixel, fixed focus, integrated digital MIC array with stereo, LED indicator, physical switch on/off	
Controls	Front: Microphone mute, speaker mute, monitor mode, OSD menu, and power button Side: Volume up and down buttons	
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable	
Onboard SATA	Two SATA cables (each 1-drop to device), one SATA 3.0Gb/s connector and one SATA 6.0Gb/s connector on planar	
Media reader	11-in-1 Single Slot SD media reader	
Chipset	Intel Q77 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), DisplayPort-out, DisplayPort-in, optional serial (9-pin), optional keyboard (PS/2), optional mouse (PS/2)	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
ExpressCard	None	
mSATA	One mSATA slot	
PCIe Mini Card	One PCI Express® Mini Card slot	
PCIe WLAN	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
Ethernet	One gigabit ethernet port, Intel 82579LM, Wake on LAN®	
Audio support	High Definition (HD) Audio, Realtek ALC272 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync™ certified	
Intel AMT	Intel Active Management Technology 8.0 (Intel AMT 8.0)	
Security chip	Trusted Platform Module (TPM 1.2-compliant)	
Keyboard	Preferred Pro USB Keyboard (USB connector), 104-key, black, Lenovo® logo	Security
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo	<ul style="list-style-type: none"> • Security chip (see information on left) • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Power-on password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • USB port disablement • Chassis intrusion switch on selected model(s)
Power supply	150 watts, autosensing, 85% PSU	EPEAT™ Gold rating ENERGY STAR® 5.2-compliant TCO Certified Edge TUV Green Mark ULE Gold EuP 2013 Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant
Machine	<i>Model(s) with 23" multi-touch, Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 22.4" W X 3.9" D X 17.6" H, • 568mm W X 100mm D X 447mm H (including stand) • 23.9 lb (10.9 kg) in maximum configuration • Toolless back cover, stand removal • Toolless disk, optical drive, memory removal • Support VESA mount (100mm) 	Supports ThinkVantage Technologies
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	For compatible accessories, please go to O-M9Z sheet; For Lenovo service upgrade options, please go to S-TC sheet

Memory	2GB PC3-12800 DDR3 SODIMM 4GB PC3-12800 DDR3 SODIMM 8GB PC3-12800 DDR3 SODIMM	0A65722 ann 06/05/12 0A65723 ann 06/05/12 0A65724 ann 06/05/12	Monitors ThinkVision LT1952p Wide 19" (VGA, DP, DVI-D) ⁶⁹ 2448MB6 ann 09/13/11 ThinkVision L2251x Wide 22" (VGA, DP) 2578HB6 ann 10/20/09 ThinkVision LT2323p Wide 23" (VGA, DP, DVI-D) ⁶⁹ 3024HC1 ann 05/01/12 ⁶⁹ DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537).
	More information at www.lenovo.com/support/desktopmemorycompatibility		More information at www.lenovo.com/support/monitors
Storage and removable storage	500GB SATA 3.0Gb/s Disk (7200 rpm) 1TB SATA 3.0Gb/s Disk (7200 rpm)	43R1990 ann 11/06/07 45J7918 ann 08/19/08	Monitor Accessories ⁴⁶ Lenovo USB 3.0 to DVI/VGA Monitor Adapter 0B47072 ann 08/14/12 DisplayPort™ to Single-link DVI-D Cable 45J7915 ann 08/05/08 DisplayPort to VGA Monitor Cable 57Y4393 ann 08/04/09 DisplayPort to DisplayPort Monitor Cable 0A36537 ann 09/13/11 Kensington MicroSaver Cable Lock ⁵⁶ 73P2582 ann 12/29/03 Kensington Twin Head Cable Lock ⁵⁶ 45K1620 ann 09/30/08 Lenovo Security Cable Lock ⁵⁶ 57Y4303 ann 08/24/10 ⁴⁶ Compatible on selected Lenovo and ThinkVision monitors.
	USB 2.0 Portable 500GB Hard Disk USB 3.0 Secure 500GB Hard Drive USB 3.0 Secure 750GB Hard Drive USB 3.0 Secure 1TB Hard Drive Slim USB Portable DVD Burner	45K1690 ann 05/26/09 0A65619 ann 11/29/11 0A65616 ann 11/29/11 0A65621 ann 08/28/12 0A33988 ann 06/14/11	More information at www.lenovo.com/support/monitoraccessories
Keyboard	Preferred Pro USB Keyboard Enhanced Performance USB Keyboard Ultraslim Plus Wireless Keyboard and Mouse ⁵² ThinkPad® USB Keyboard with TrackPoint Lenovo® USB Fingerprint Keyboard Lenovo USB Smartcard Keyboard	73P5220 ann 06/21/05 73P2620 ann 03/23/04 0A34032 ann 04/05/11 55Y9003 ann 08/18/09 73P4730 ann 02/22/05 51J0155 ann 03/24/09	More information at www.lenovo.com/support/keyboards
	⁵² Wireless via 2.4GHz technology using a micro-size USB receiver.		
	More information at www.lenovo.com/support/keyboards		
Mouse	Lenovo Optical Mouse (USB) Lenovo ScrollPoint® Mouse (USB, Optical) ThinkPad Travel Mouse (USB, Optical) Lenovo Laser Mouse (USB) Lenovo Wireless Laser Mouse ⁵² ThinkPad USB Laser Mouse	06P4069 ann 05/21/03 31P7405 ann 08/27/02 31P7410 ann 06/04/02 41U3074 ann 01/23/07 0A36188 ann 12/20/11 57Y4635 ann 12/15/09	More information at www.lenovo.com/support/mice
	More information at www.lenovo.com/support/mice		
Modem	USB 2.0 Lenovo Modem	43R1814 ann 02/26/08	
Multimedia	ThinkPad In-Ear Headphones with mic Lenovo Mini Speakers M220 Lenovo Speakers M0520 (black) Lenovo Speakers M0520 (red) Lenovo Headset P550 Lenovo Headset P950 (black)	57Y4488 ann 01/07/10 55Y2033 ann 01/07/10 57Y6360 ann 02/08/11 57Y6361 ann 02/08/11 55Y2065 ann 02/08/11 57Y6605 ann 02/08/11	For more information on accessories: www.lenovo.com/accessories Purchase Lenovo accessories
Security	Kensington® MicroSaver® Cable Lock ⁵⁶ Kensington Twin Head Cable Lock ⁵⁶ Lenovo Security Cable Lock ⁵⁶ USB Gemplus GemPC Smart Card Reader	73P2582 ann 12/29/03 45K1620 ann 09/30/08 57Y4303 ann 08/24/10 41N3040 ann 02/21/06	www.lenovo.com/support/accessories Product specifications on Lenovo Support www.lenovo.com/accessoriesguide Option Compatibility Matrix (OCM) and accessory brochures www.lenovoquickpick.com An Options Compatibility Configurator for Lenovo systems
	⁵⁶ Attaching to any form factor not only secures the ThinkCentre to the work area, but it also prevents users from opening the chassis itself.		

ThinkCentre Edge 72 Small and Tower

ThinkCentre®



Lenovo ThinkCentre Edge 72 Small and
Lenovo ThinkCentre Edge 72 Tower



Lenovo ThinkCentre Edge 72 Small
with Dual Lenovo ThinkVision Monitors



Lenovo ThinkCentre Edge 72 Small



Lenovo ThinkCentre Edge 72 Small



Lenovo ThinkCentre Edge 72 Tower




Lenovo ThinkCentre Edge 72 Tower

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Blue-tooth	Media reader	Parallel port	Serial port	Floor stand	Win7 Global preload	Ann date (mm/dd/yy)
3493-A7U	3x2	G630	2GBx1 1600MHz	250G 7200	DVD±RW	HD 7350	None	None	None	Parallel	Serial	Stand	None Pro 64	06/19/12
3493-A8U	3x2	i3-2120	4GBx1 1600MHz	500G 7200	DVD±RW	HD 7350	None	None	None	Parallel	Serial	Stand	None Pro 64	06/19/12
3493-EKU	3x2	G640	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	None	None	None	Serial	Stand	None Pro 64	07/10/12
3493-F8U	3x2	G640	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	None	None	None	Serial	Stand	None Pro 64	07/17/12
3493-BNU	3x2	G640	2GBx1 1600MHz	250G 7200	DVD±RW	Intel HD	None	None	None	Parallel	Serial	Stand	None Pro 64	08/14/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 1-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>										Preloaded operating system																	
Processor	Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology										Genuine Windows® 7 Professional 64																	
Implementation	Intel Pentium G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology										Ready to install applications (only some listed)																	
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3, two 240-pin DIMM sockets										<ul style="list-style-type: none">• Rescue and Recovery™• Password Manager																	
Graphics	Some: Intel HD Graphics in processor, uses main memory, DirectX® 10.1, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz Some: AMD Radeon™ HD 7350 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz; works along with Intel HD Graphics to support up to four independent monitors										Preloaded applications (only some listed)																	
DP dongle	None										<ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)																	
Disk	SATA 3.0Gb/s 7200 rpm																											
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive																											
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset																											
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar																											
eSATA port	None																											
Media reader	None																											
Chipset	Intel H61 Express Chipset																											
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																											
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D																											
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																											
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)																											
PCIe WLAN	None																											
Bluetooth	None																											
Audio	High Definition (HD) Audio, Realtek® ALC662 codec																											
Speaker	Internal speaker for business audio																											
IEEE 1394	None																											
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®																											
Intel AMT	None																											
Modem	None																											
Security chip	None																											
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo																											
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																											
Floor Stand	System floor stand for vertical orientation																											
Power supply	180 watts, universal, manual switch																											
Machine	<ul style="list-style-type: none">• Glossy black bezel; metal case• 13.2" W X 15.0" D X 3.9" H• 336mm W X 382mm D X 101mm H• 13.2 lb (6.0 kg) in maximum configuration• Highlighted optical drive button for easy access																											
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader*																											
Slot	*bay only available on models with media reader installed Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1																											
																												
Limited Warranty ¹	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																											
See footnotes for important warranty information US model(s) announced June 19, July 10, July 17, or August 14, 2012 US models withdrawn effective May 2014																												
©Lenovo (TAPI1-1) May 2014																												

See footnotes for important warranty information


US model(s) announced June 19, July 10, July 17, or August 14, 2012

US models withdrawn effective May 2014

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Blue-tooth	Media reader	Parallel port	Serial port	Floor stand	Win7 Global preload	Ann date (mm/dd/yy)
3493-A6U	3x2	i5-3550S	4GBx1 1600MHz	1TB 7200	DVD±RW	HD 7350	None	None	None	Parallel	Serial	Stand	None Pro 64	06/19/12
3493-B7U	3x2	i5-3470S	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	None	None	None	None	Stand	None Pro 64	06/19/12
3493-EJU	3x2	i5-3470S	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	None	None	None	Serial	Stand	None Pro 64	07/10/12
3493-BKU	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	None	None	Parallel	None	Stand	None Pro 64	09/04/12
3493-BPU	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	None	None	Parallel	Serial	Stand	None Pro 64	09/04/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 1-year limited warranty

Positioning Processor	<p>Stylish design, reliability, and productivity for small/medium businesses</p> <p>Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller</p> <p>Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>												Preloaded operating system
Implementation													Genuine Windows® 7 Professional 64
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets												Ready to install applications (only some listed)
Graphics	<p>Some: Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display;</p> <p>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</p> <p>Some: AMD Radeon™ HD 7350, DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 30 watts;</p> <p>Maximum resolution: 2560x1600 (DisplayPort, DVI-I)@60Hz;</p> <p>works along with Intel HD Graphics to support up to four independent monitors</p>												Preloaded applications (only some listed)
DP dongle	None												• ThinkVantage® Product Recovery
Disk	SATA 3.0Gb/s 7200 rpm												• ThinkVantage System Update
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												• ThinkVantage Power Manager
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset												• ThinkVantage Communication Utility
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar												• View Management Utility
eSATA port	None												• Lenovo Solution Center
Media reader	None												• Lenovo Message Center Plus
Chipset	Intel H61 Express Chipset												• Norton™ Internet Security (30 days of virus definitions)
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												• Adobe® Reader®
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D												• Skype™ for Windows
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												• Windows Live™ Essentials
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)												• Microsoft® Office preloaded; purchase a product key to activate
PCIe WLAN	None												• Corel® Burn.Now™ (DVD±RW)
Bluetooth	None												• Corel DVD MovieFactory® (DVD±RW)
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Floor Stand	System floor stand for vertical orientation												
Power supply	180 watts, universal, manual switch												
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader*												
Slot	Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1												
Limited Warranty ¹	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
													

See footnotes for important warranty information

US model(s) announced June 19, July 10, or September 4, 2012


US models withdrawn effective May 2014

©Lenovo

(TAPI1-2) May 2014

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	Graphics	PCIe Mini Card WLAN	Blue-tooth	Media reader	Parallel port	Serial port	Floor stand	Global	Preload	Ann date (mm/dd/yy)
3493-DFU	3x2	G640	4GBx1 1600MHz	500G 7200	DVD	Intel HD	None	None	None	None	Serial	Stand	None	Win7 Pro64	10/23/12
3493-DGU	3x2	G640	4GBx1 1600MHz	500G 7200	DVD	Intel HD	None	None	None	Parallel	Serial	Stand	None	Win7 Pro64	10/23/12
3493-GPU	3x2	i3-3220	4GBx1 1600MHz	500G 7200	DVD±RW	HD 2500	None	None	None	Parallel	Serial	Stand	None	Win7 Pro64	11/20/12
3493-GRU	3x2	G645	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	None	None	Parallel	Serial	Stand	None	Win7 Pro64	11/20/12
3493-H5U	3x2	G2120	4GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	None	None	Parallel	Serial	Stand	None	Win7 Pro64	12/25/12
3493-HAU	3x2	G2020	2GBx1 1600MHz	500G 7200	DVD±RW	Intel HD	None	None	None	Parallel	Serial	Stand	None	Win7 Pro64	02/19/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	Stylish design, reliability, and productivity for small/medium businesses Intel® Pentium® G640 Processor (2 cores / 2 threads) , 2.8GHz, 3MB cache, integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G645 Processor (2 cores / 2 threads) , 2.9GHz, 3MB cache, integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2020 Processor (2 cores / 2 threads) , 2.9GHz, 3MB cache, integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads) , 3.1GHz, 3MB cache, integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache, integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit													
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 													
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets System automatically clocks down for processors with 1066MHz DDR3 memory controller	Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo® Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 													
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz														
DP dongle	None														
Disk Optical	SATA 3.0Gb/s 7200 rpm Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar														
eSATA port	None														
Media reader	None														
Chipset	Intel H61 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®														
Intel AMT	None														
Modem	None														
Security chip	None														
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Floor Stand	System floor stand for vertical orientation														
Power supply	180 watts, universal, manual switch														
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 13.2" W X 15.0" D X 3.9" H • 336mm W X 382mm D X 101mm H • 13.2 lb (6.0 kg) in maximum configuration • Highlighted optical drive button for easy access 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, std disk Bay 3: 1.5", .35" high, access, opt reader*														
Slot	*bay only available on models with media reader installed Slot 1: Low Profile, PCI Express® 2.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x1														
Limited Warranty ¹	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														
See footnotes for important warranty information US model(s) announced Oct 23, 2012, Nov 20, 2012, Dec 25, 2012, or Feb 19, 2013 US models withdrawn effective May 2014															
©Lenovo (TAPI1-5) May 2014															

Security

- One lock to secure both cover and entire system to fixed object:
 - Padlock loop (in rear for opt padlock)
 - Security slot (in rear for optional Kensington® MicroSaver® cable)
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement

RoHS-compliant

Supports ThinkVantage Technologies


For compatible accessories, please go to O-Edge72 sheet;

For Lenovo service upgrade options, please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	PCIe Mini Card WLAN	Bluetooth	Media reader	Parallel port	Serial port	Global	Win7 preload	Ann date (mm/dd/yy)
3484-A7U	3x2	i3-2130	4GBx1 1600MHz	500G 7200	None	DVD±RW	HD 7350	None	None	None	Parallel	Serial	None	Pro 64	06/19/12
3484-A8U	3x2	i3-2120	4GBx1 1600MHz	500G 7200	None	DVD±RW	HD 7350	None	None	None	Parallel	Serial	None	Pro 64	06/19/12
3484-A9U	3x2	G630	2GBx1 1600MHz	250G 7200	None	DVD±RW	HD 7350	None	None	None	Parallel	Serial	None	Pro 64	06/19/12
3484-FDU	3x2	G640	4GBx1 1600MHz	500G 7200	None	DVD±RW	Intel HD	None	None	None	None	Serial	None	Pro 64	07/10/12
3484-GAU	3x2	G640	2GBx1 1600MHz	500G 7200	None	DVD±RW	Intel HD	None	None	None	None	Serial	None	Pro 64	07/17/12
3484-BFU	3x2	G640	2GBx1 1600MHz	250G 7200	None	DVD±RW	Intel HD	None	None	None	Parallel	Serial	None	Pro 64	08/14/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning	Stylish design, reliability, and productivity for small/medium businesses												Preloaded operating system		
Processor	Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology												Genuine Windows® 7 Professional 64		
Implementation	Intel Pentium G640 Processor (2 cores / 2 threads, 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology												Ready to install applications (only some listed)		
Memory	Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology												<ul style="list-style-type: none">• Rescue and Recovery™• Password Manager		
Graphics	Intel Core™ i3-2130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), integrated Intel HD Graphics 2000, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology												Preloaded applications (only some listed)		
DP dongle	None												<ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Power Manager• ThinkVantage Communication Utility• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)		
Disk	SATA 3.0Gb/s 7200 rpm														
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset														
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar														
eSATA port	None														
Media reader	None														
Chipset	Intel H61 Express Chipset														
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)														
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)														
PCIe WLAN	None														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio														
IEEE 1394	None														
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®														
Intel AMT	None														
Modem	None														
Security chip	None														
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	180 watts, universal, manual switch														
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 														
Bay	<ul style="list-style-type: none"> Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk <p>*bay only available on models with media reader installed</p>														
Slot	<ul style="list-style-type: none"> Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 														
Limited Warranty ¹	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														



Security
• One lock to secure both cover and entire system to fixed object:
- Padlock loop (in rear for opt padlock)
- Security slot (in rear for optional Kensington® MicroSaver® cable)
• Power-on password
• Administrator password
• Hard disk password
• Boot sequence control
• Boot without keyboard and mouse
• Individual USB port disablement
RoHS-compliant
Supports ThinkVantage Technologies
For compatible accessories, please go to O-Edge72 sheet;
For Lenovo service upgrade options, please go to S-TC sheet

See footnotes for important warranty information

US model(s) announced June 19, July 10, July 17, or August 14, 2012
US models withdrawn effective May 2014


©Lenovo

(TAPI1-3) May 2014

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	2nd Disk Bay	SATA optical	Graphics	PCIe Mini Card WLAN	Blue-tooth	Media reader	Parallel port	Serial port	Global	Win7 preload	Ann date (mm/dd/yy)
3484-A6U	3x2	i5-3550S	4GBx1 1600MHz	1TB 7200	None	DVD±RW	HD 7350	None	None	None	Parallel	Serial	None	Pro 64	06/19/12
3484-C1U	3x2	i5-3470S	4GBx1 1600MHz	500G 7200	None	DVD±RW	HD 2500	None	None	None	None	None	None	Pro 64	06/19/12
3484-FCU	3x2	i5-3470S	4GBx1 1600MHz	500G 7200	None	DVD±RW	HD 2500	None	None	None	None	Serial	None	Pro 64	07/10/12
3484-BGU	3x2	i3-3220	4GBx1 1600MHz	500G 7200	None	DVD±RW	HD 2500	None	None	None	Parallel	Serial	None	Pro 64	09/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	Stylish design, reliability, and productivity for small/medium businesses Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology													Preloaded operating system Genuine Windows® 7 Professional 64		
Implementation	Processor in LGA1155 socket													Ready to install applications (only some listed) <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets													Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Power Manager • ThinkVantage Communication Utility • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 		
Graphics	<p>Some: Intel HD Graphics 2500 in processor, uses main memory, DirectX® 11, one VGA, one DVI-D, supports dual independent display; Maximum resolution: 2560x1600 (VGA) @60Hz; 1920x1200 (DVI-D) @60Hz</p> <p>Some: AMD Radeon™ HD 7350, DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort™, 30 watts; Maximum resolution: 2560x1600 (DisplayPort, DVI-I) @60Hz; works along with Intel HD Graphics to support up to four independent monitors</p>															
DP dongle	None															
Disk	SATA 3.0Gb/s 7200 rpm															
Optical	Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive															
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset															
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar															
eSATA port	None															
Media reader	None															
Chipset	Intel H61 Express Chipset															
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)															
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D															
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)															
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)															
PCIe WLAN	None															
Bluetooth	None															
Audio	High Definition (HD) Audio, Realtek® ALC662 codec															
Speaker	Internal speaker for business audio															
IEEE 1394	None															
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®															
Intel AMT	None															
Modem	None															
Security chip	None															
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo															
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo															
Power supply	180 watts, universal, manual switch															
Machine	<ul style="list-style-type: none"> • Glossy black bezel; metal case • 6.3" W X 15.7" D X 15.6" H (with handle) • 160mm W X 399mm D X 397mm H • 16.5 lb (7.5 kg) in maximum configuration • Ergonomic rubberized handle • Highlighted optical drive button for easy access 															
Bay	<p>Bay 1: 5.25", 1.6" high, access, std optical</p> <p>Bay 2: 1.5", .35" high, access, opt reader*</p> <p>Bay 3: 3.5", 1" high, no access, std disk</p> <p>*bay only available on models with media reader installed</p>															
Slot	<p>Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max)</p> <p>Slot 2: half-length, full-height, PCIe 2.0 x1</p> <p>Slot 3: half-length, full-height, PCIe 2.0 x1</p>															
Limited Warranty ¹	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available															

**Security**

- One lock to secure both cover and entire system to fixed object:
 - Padlock loop (in rear for opt padlock)
 - Security slot (in rear for optional Kensington® MicroSaver® cable)
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement


RoHS-compliant

Supports ThinkVantage Technologies

For compatible accessories,
please go to O-Edge72 sheet;
For Lenovo service upgrade options,
please go to S-TC sheet

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB	2nd Disk rpm	SATA Bay optical	Graphics	PCIe Mini Card WLAN	Blue-tooth	Media reader	Parallel port	Serial port	Global	Preload	Ann date (mm/dd/yy)
3484-DEU	3x2	G640	4GBx1 1600MHz	500G	7200	None	DVD	Intel HD	None	None	Parallel	Serial	None	Win7 Pro64	10/23/12
3484-DFU	3x2	i3-3220	4GBx1 1600MHz	500G	7200	None	DVD	HD 2500	None	None	Parallel	Serial	None	Win7 Pro64	10/23/12
3484-HNU	3x2	G645	2GBx1 1600MHz	500G	7200	None	DVD±RW	Intel HD	None	None	Parallel	Serial	None	Win7 Pro64	11/20/12
3484-HPU	3x2	i3-3220	4GBx1 1600MHz	500G	7200	None	DVD±RW	HD 2500	None	None	Parallel	Serial	None	Win7 Pro64	11/20/12
3484-JJU	3x2	G2120	4GBx1 1600MHz	500G	7200	None	DVD±RW	Intel HD	None	None	Parallel	Serial	None	Win7 Pro64	12/25/12
3484-JMU	3x2	G2020	2GBx1 1600MHz	500G	7200	None	DVD±RW	Intel HD	None	None	Parallel	Serial	None	Win7 Pro64	02/19/13

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning	<i>Stylish design, reliability, and productivity for small/medium businesses</i>												
Processor	Intel® Pentium® G640 Processor (2 cores / 2 threads) , 2.8GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G645 Processor (2 cores / 2 threads) , 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2020 Processor (2 cores / 2 threads) , 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads) , 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads) , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller												
Implementation	Processor in LGA1155 socket												
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets <i>System automatically clocks down for processors with 1066MHz DDR3 memory controller</i>												
Graphics	Intel HD Graphics or Intel HD Graphics 2500 in processor, uses main memory, one VGA, one DVI-D, supports dual independent display; <i>Maximum resolution: 2560x1600 (VGA)@60Hz; 1920x1200 (DVI-D)@60Hz</i>												
DP dongle	None												
Disk	SATA 3.0Gb/s 7200 rpm												
Optical	Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive												
SATA controller	Serial ATA, SATA 3.0Gb/s, integrated in chipset												
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 3.0Gb/s connectors on planar												
eSATA port	None												
Media reader	None												
Chipset	Intel H61 Express Chipset												
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
Rear ports	Four USB 2.0, optional serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), VGA DB-15, DVI-D												
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)												
Internal connector	Three USB 2.0 planar conn (1 used; two open for additional USB devices)												
PCIe WLAN	None												
Bluetooth	None												
Audio	High Definition (HD) Audio, Realtek® ALC662 codec												
Speaker	Internal speaker for business audio												
IEEE 1394	None												
Ethernet	Gigabit ethernet port, Realtek RTL8111E, Wake on LAN®												
Intel AMT	None												
Modem	None												
Security chip	None												
Keyboard	Lenovo® Slim USB Keyboard (USB connector), black, Lenovo logo												
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo												
Power supply	180 watts, universal, manual switch												
Machine	<ul style="list-style-type: none"> Glossy black bezel; metal case 6.3" W X 15.7" D X 15.6" H (with handle) 160mm W X 399mm D X 397mm H 16.5 lb (7.5 kg) in maximum configuration Ergonomic rubberized handle Highlighted optical drive button for easy access 												
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 1.5", .35" high, access, opt reader* Bay 3: 3.5", 1" high, no access, std disk												
Slot	<ul style="list-style-type: none"> *bay only available on models with media reader installed Slot 1: half-length, full-height, PCI Express® 2.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1 												
Limited Warranty ¹	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
													
	Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Power Manager ThinkVantage Communication Utility View Management Utility Lenovo® Solution Center Lenovo Message Center Plus Lenovo SimpleTap Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ for Windows Windows Live™ Essentials Microsoft® Office preloaded; purchase a product key to activate Corel® Burn.Now™ (DVD±RW) Corel DVD MovieFactory® (DVD±RW) 												
	Security <ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> Padlock loop (in rear for opt padlock) Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement 												
	RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-Edge72 sheet; For Lenovo service upgrade options, please go to S-TC sheet												

See footnotes for important warranty information

US model(s) announced Oct 23, 2012, Nov 20, 2012, Dec 25, 2012, or Feb 19, 2013

US models withdrawn effective May 2014

©Lenovo

(TAPI1-6) May 2014

ThinkCentre Edge 92z

ThinkCentre®



ThinkCentre Edge 92z with Frame Stand



ThinkCentre Edge 92z with Frame Stand



ThinkCentre Edge 92z with Frame Stand



Handle



ThinkCentre Edge 92z with Frame Stand



ThinkCentre Edge 92z with Frame Stand

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Keyboard/ Mouse	Global	Win7 preload	Ann date (mm/dd/yy)
3396-A3U	i5-3470S	4GBx1	2.0M	1TB 7200	None	DVD±RW	HD 2500	Intel 105	None	2.4G	None	Pro 64	07/03/12
3396-B2U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	USB	None	Pro 64	07/03/12
3396-B3U	i7-3770S	4GBx2	2.0M	1TB 7200	None	DVD±RW	HD 4000	Intel 2230 + BT	Media	USB	None	Pro 64	07/03/12
3396-B4U	i7-3770S	4GBx2	2.0M	1TB 7200	None	DVD±RW	HD 4000	Intel 2230 + BT	Media	2.4G	None	Pro 64	07/03/12
3396-B5U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	2.4G	None	Pro 64	07/03/12
3396-B6U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	2.4G	None	Prem 64	07/03/12
3396-BUU	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	USB	None	Pro 64	09/04/12
3396-C3U	G870	4GBx1	2.0M	500G 7200	None	DVD±RW	Intel HD	Intel 2230 + BT	None	USB	None	Pro 64	09/11/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 1-year limited warranty

Positioning Processor	Stylish All-In-One PC for small/medium businesses Intel® Pentium® G870 Processor (2 cores / 2 threads , 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads , 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology	Preloaded operating system Some: Genuine Windows® 7 Professional 64 Some: Genuine Windows 7 Home Premium 64
Implementation	Processor in LGA1155 socket	Ready to install applications (only some listed) <ul style="list-style-type: none">• Rescue and Recovery™• Password Manager• Business-in-a-Box
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Preloaded applications (only some listed) <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage System Update• ThinkVantage Communication Utility• ThinkVantage Automatic Lock Utility• ThinkVantage Power Manager• View Management Utility• Lenovo Solution Center• Lenovo Message Center Plus• Intel Small Business Advantage• RapidBoot HDD Accelerator• Lenovo SimpleTap• Norton™ Internet Security (30 days of virus definitions)• Adobe® Reader®• Evernote®• Symantec™ VIP• Skype™ for Windows• Windows Live™ Essentials• Microsoft® Office preloaded; purchase a product key to activate• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)
Graphics	Intel HD Graphics , Intel HD Graphics 2500 , or Intel HD Graphics 4000 in processor, use main memory, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200 (HDMI)@60Hz</i>	
Widescreen display	21.5" (54.52mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector	
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator	
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in	
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical	None	
Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Some: 7-in-1 Single Slot SD media reader	
Chipset	Intel B75 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	Two PCI Express® Mini Card slots	
PCIe WLAN ^d	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2	
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
PCIe mSATA	One Mini PCIe mSATA slot	
Ethernet	One gigabit ethernet port, Intel 82579LM	
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified	
Intel AMT Security chip	None	
Keyboard	Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black	
Mouse	Some: Enhanced Optical USB Mouse, black Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black	
Power supply	150 watts, autosensing, 85% PSU	
Machine	Model(s) with Frame stand: <ul style="list-style-type: none">• Business black color• 21.5" W X 3.2" D X 16.3" H• 545mm W X 81mm D X 414mm H (with feet)• 18.5 lb (8.4 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)	
Limited Warranty ¹	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available	

Security

- Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)
- Boot sequence control
- Boot without keyboard and mouse
- USB port disablement

ENERGY STAR® 5.2-compliant
RoHS-compliant

Supports ThinkVantage Technologies

For compatible accessories, please go to O-Edge92Z sheet;
For ThinkPlus™ service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Keyboard/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3396-BPU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	None	USB	None	Win8 Pro64	10/23/12
3396-BQU	i7-3770S	4GBx2	2.0M	500G 7200	None	DVD±RW	HD 4000	Intel 2230 + BT	None	USB	None	Win8 Pro64	10/23/12
3396-BRU	i7-3770S	4GBx2	2.0M	1TB 7200	None	DVD±RW	HD 4000	Intel 2230 + BT	Media	2.4G	None	Win8 Pro64	10/23/12
3396-BVU	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	USB	None	Win8 Pro64	10/23/12
3396-BTU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	2.4G	None	Win8 Pro64	10/23/12
3396-C6U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	None	USB	None	Win7 Pro64	10/23/12
3396-C7U	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	None	USB	None	Win7 Pro64	10/23/12
3396-CMU	G2120	4GBx1	2.0M	500G 7200	None	DVD±RW	Intel HD	Intel 105	Media	USB	None	Win7 Pro64	12/04/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 1-year limited warranty

Positioning Processor	Stylish All-In-One PC for small/medium businesses Intel® Pentium® G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Lenovo® Message Center Plus• Intel Small Business Advantage• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Symantec™ VIP• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• Intel AppUp®• AccuWeather• PC Device Stage• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Evernote®• Skype™		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	Intel HD Graphics / 2500 / 4000 in processor, use main memory, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200 (HDMI)@60Hz</i>													
Widescreen display	21.5" (54.52mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector													
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator													
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in													
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm													
mSATA™ SSD	None													
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable													
Media reader	Some: 7-in-1 Single Slot SD media reader													
Chipset	Intel B75 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	Two PCI Express® Mini Card slots													
PCIe WLAN ^d	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
PCle mSATA	One Mini PCIe mSATA slot													
Ethernet	One gigabit ethernet port, Intel 82579LM													
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified													
Intel AMT Security chip	None													
Keyboard	Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black Some: Ultralight Plus Wireless Keyboard (2.4GHz via USB receiver), black													
Mouse	Some: Enhanced Optical USB Mouse, black Some: Ultralight Plus Wireless Mouse (2.4GHz via USB receiver), black													
Power supply	150 watts, autosensing, 85% PSU													
Machine	Model(s) with Frame stand: <ul style="list-style-type: none">• Business black color• 21.5" W X 3.2" D X 16.3" H• 545mm W X 81mm D X 414mm H (with feet)• 18.5 lb (8.4 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)													
Limited Warranty ^c	1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
Security <ul style="list-style-type: none">• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Boot sequence control• Boot without keyboard and mouse• USB port disablement ENERGY STAR® 5.2-compliant RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to O-Edge92Z sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet														

Type-model	Processor	Memory ^b	Camera (megapixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Key-board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3399-GJU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 2500	Intel 2230 + BT	Media	USB	None	Win7 Pro64	11/20/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning	<i>Stylish All-In-One PC for small/medium businesses</i>																							
Processor	Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology																							
Implementation	Processor in LGA1155 socket																							
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																							
Graphics	Intel HD Graphics 2500 in processor, use main memory, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200 (HDMI)@60Hz</i>																							
Widescreen display	21.5" (54.52mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector																							
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator																							
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in																							
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																							
Optical	None																							
Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																							
Chipset	Intel B75 Express Chipset																							
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in																							
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																							
PCIe Mini Card	Two PCI Express® Mini Card slots																							
PCIe WLAN ^d	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																							
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																							
PCIe mSATA	One Mini PCIe mSATA slot																							
Ethernet	One gigabit ethernet port, Intel 82579LM																							
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified																							
Intel AMT	None																							
Security chip	None																							
Keyboard	Lenovo® Slim New F5 USB Keyboard (USB connector), black																							
Mouse	Enhanced Optical USB Mouse, black																							
Power supply	150 watts, autosensing, 85% PSU																							
Machine	<i>Model(s) with Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 21.5" W X 3.2" D X 16.3" H • 545mm W X 81mm D X 414mm H (with feet) • 18.5 lb (8.4 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 																							
Security																								
<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Boot sequence control • Boot without keyboard and mouse • USB port disablement 																								
ENERGY STAR® 5.2-compliant																								
RoHS-compliant																								
Supports ThinkVantage Technologies																								
For compatible accessories, please go to O-Edge92Z sheet;																								
For ThinkPlus™ service upgrade options, please go to S-TC sheet																								
Limited Warranty¹ 3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																								

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Key-board/Mouse	Global	Win7 preload	Ann date (mm/dd/yy)
3418-A2U	i3-2120	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64	07/03/12
3418-B2U	i3-2120	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	USB	None	Pro 64	07/03/12
3418-B3U	G630	4GBx1	2.0M	250G 7200	None	DVD±RW	HD 7650A	Intel 105	None	USB	None	Pro 64	07/03/12
3418-B4U	G850	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	USB	None	Pro 64	07/03/12

• Small and medium business (SMB) model(s), part of the US TopSeller™ Program

• 1-year limited warranty

Positioning Processor	<p><i>Stylish All-In-One PC for small/medium businesses</i></p> <p>Intel® Pentium® G630 Processor (2 cores / 2 threads, 2.7GHz, 3MB cache), integrated Intel HD Graphics, integrated 1066MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Pentium G850 Processor (2 cores / 2 threads, 2.9GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>											Preloaded operating system
Implementation												Genuine Windows® 7 Professional 64
Memory	<p>16GB max, PC3-12800 1600MHz DDR3, two 204-pin SODIMM sockets (notebook)</p>											Ready to install applications (only some listed)
Graphics	<p>AMD Radeon™ HD 7650A, 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200(HDMI)@60Hz</i></p> <p>21.5" (545.2mm) Full HD 1080p (1920x1080) TFT color, infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector</p>											Preloaded applications (only some listed)
Widescreen display	<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box 											
Multi-touch Camera	<p>None</p> <p>Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator</p>											
Controls	<p>Front facing buttons for brightness up, brightness down, power on/off, and Video in</p>											
Disk mSATA™ SSD	<p>SATA 6.0Gb/s, 3.5" Wide, 7200 rpm</p>											
Optical Media reader	<p>None</p> <p>DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable</p>											
Chipset	<p>Intel B75 Express Chipset</p>											
Rear ports	<p>Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in</p>											
Side ports	<p>Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)</p>											
PCIe Mini Card	<p>Two PCI Express® Mini Card slots</p>											
PCIe WLAN ⁴	<p>11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1</p>											
Bluetooth	<p>None</p>											
PCIe mSATA	<p>One Mini PCIe mSATA slot</p>											
Ethernet	<p>One gigabit ethernet port, Intel 82579LM</p>											
Audio support	<p>High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified</p>											
Intel AMT Security chip	<p>None</p>											
Keyboard	<p>Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black</p>											
Mouse	<p>Some: Ultraslim Plus Wireless Keyboard (2.4GHz via USB receiver), black</p>											
Power supply	<p>Some: Enhanced Optical USB Mouse, black</p>											
Power supply	<p>Some: Ultraslim Plus Wireless Mouse (2.4GHz via USB receiver), black</p>											
Machine	<p>180 watts, autosensing, 92% PSU</p> <p><i>Model(s) with Frame stand:</i></p> <ul style="list-style-type: none"> • Business black color • 21.5" W X 3.2" D X 16.3" H • 545mm W X 81mm D X 414mm H (with feet) • 18.5 lb (8.4 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 											Security
Limited Warranty ¹	<p>1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>											ENERGY STAR® 5.2-compliant RoHS-compliant
												Supports ThinkVantage Technologies
												For compatible accessories, please go to O-Edge92Z sheet;
												For ThinkPlus™ service upgrade options, please go to S-TC sheet

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Key-board/Mouse	Win7 preload	Ann date (mm/dd/yy)
3418-A8U	i7-3770S	4GBx2	2.0M	500G 7200	64GB	DVD±RW	HD 7650A	Intel 105	Media	2.4G	None	Pro 64 07/03/12
3418-A9U	i5-3550S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3418-B1U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3418-C8U	i7-3770S	4GBx2	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Pro 64 07/03/12
3418-C7U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Pro 64 07/03/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	<p><i>Stylish All-In-One PC for small/medium businesses</i></p> <p>Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3550S Processor (4 cores / 4 threads, 3.0GHz, 6MB cache), Turbo Boost 2.0 (3.7GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p>											Preloaded operating system
Implementation	<p>Genuine Windows® 7 Professional 64</p> <p>Ready to install applications (only some listed)</p> <ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Lenovo Solution Center • Lenovo Message Center Plus • Intel Small Business Advantage • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Evernote® • Symantec™ VIP • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW) 											
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											
Graphics	<p>AMD Radeon™ HD 7650A, 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display;</p> <p><i>Maximum resolution: 1920x1200(HDMI)@60Hz</i></p> <p>21.5" (545.2mm) Full HD 1080p (1920x1080) TFT color, infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector</p>											
Widescreen display												
Multi-touch Camera	<p>None</p> <p>Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator</p>											
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in											
Disk	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
mSATA™ SSD	Some: mSATA Solid State Drive (SSD), via PCIe Mini Card slot											
Optical	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Media reader	Some: 7-in-1 Single Slot SD media reader											
Chipset	Intel B75 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN ⁴	<p>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1</p> <p>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</p>											
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											
PCIe mSATA	One Mini PCIe mSATA slot											
Ethernet	One gigabit ethernet port, Intel 82579LM											
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified											
Intel AMT Security chip	None											
Keyboard	Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black											
Mouse	<p>Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black</p> <p>Some: Enhanced Optical USB Mouse, black</p> <p>Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black</p>											
Power supply	180 watts, autosensing, 92% PSU											
Machine	<p><i>Model(s) with Frame stand:</i></p> <ul style="list-style-type: none"> • Business black color • 21.5" W X 3.2" D X 16.3" H • 545mm W X 81mm D X 414mm H (with feet) • 18.5 lb (8.4 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 											
Limited Warranty ¹	<p>1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available</p>											
<p>Security</p> <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Boot sequence control • Boot without keyboard and mouse • USB port disablement <p>ENERGY STAR® 5.2-compliant RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p> <p>For compatible accessories, please go to O-Edge92Z sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet</p>												

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Key-board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3418-CAU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	None	USB	None	Win8 Pro64	10/23/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	<i>Stylish All-In-One PC for small/medium businesses</i> Intel® Core™ i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket										Preloaded operating system Windows® 8 Pro 64-bit		
Implementation											Preloaded applications (only some listed) <ul style="list-style-type: none"> • ThinkVantage® System Update • ThinkVantage Automatic lock Utility • View Management Utility • Lenovo® Support • Lenovo Settings • Lenovo Companion • Lenovo Cloud Storage • Lenovo QuickLaunch • Lenovo Solution Center • Microsoft® Office preloaded; purchase a product key to activate • Norton™ Internet Security (30 days of virus definitions) • Norton Studio • Intel AppUp® • AccuWeather • PC Device Stage • Evernote® • Skype™ • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) 		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)												
Graphics	AMD Radeon™ HD 7650A , 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200(HDMI)@60Hz</i>												
Widescreen display	21.5" (545.2mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector												
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator												
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in												
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm												
Optical Media reader	None DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable												
Chipset	Intel B75 Express Chipset												
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in												
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)												
PCIe Mini Card	Two PCI Express® Mini Card slots												
PCIe WLAN ⁴	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2												
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter												
PCIe mSATA	One Mini PCIe mSATA slot												
Ethernet	One gigabit ethernet port, Intel 82579LM												
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified												
Intel AMT	None												
Security chip	None												
Keyboard	Lenovo® Slim New F5 USB Keyboard (USB connector), black												
Mouse	Enhanced Optical USB Mouse, black												
Power supply	180 watts, autosensing, 92% PSU												
Machine	<i>Model(s) with Frame stand:</i> <ul style="list-style-type: none"> • Business black color • 21.5" W X 3.2" D X 16.3" H • 545mm W X 81mm D X 414mm H (with feet) • 18.5 lb (8.4 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 												
Limited Warranty ¹	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available												
											Security <ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Boot sequence control • Boot without keyboard and mouse • USB port disablement 		
											ENERGY STAR® 5.2-compliant RoHS-compliant		
											Supports ThinkVantage Technologies		
											For compatible accessories, please go to O-Edge92Z sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet		

Type-model	Processor	Memory ⁸	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN / BT	Media reader	Key-board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3426-HEU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	11/20/12
3426-HFU	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	11/20/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Stylish All-In-One PC for small/medium businesses</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads , 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads , 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit
Implementation												Ready to install applications (only some listed)
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)											Preloaded applications (only some listed)
Graphics	AMD Radeon™ HD 7650A , 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200(HDMI)@60Hz</i>											
Widescreen display	21.5" (54.52mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector											
Multi-touch Camera	None Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator											
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in											
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											
Optical Media reader	None DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable											
Media reader	7-in-1 Single Slot SD media reader											
Chipset	Intel B75 Express Chipset											
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in											
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)											
PCIe Mini Card	Two PCI Express® Mini Card slots											
PCIe WLAN ⁴	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2											
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter											
PCle mSATA	One Mini PCIe mSATA slot											
Ethernet	One gigabit ethernet port, Intel 82579LM											
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified											
Intel AMT Security chip	None None											
Keyboard	Lenovo® Slim New F5 USB Keyboard (USB connector), black											
Mouse	Enhanced Optical USB Mouse, black											
Power supply	180 watts, autosensing, 92% PSU											
Machine	<i>Model(s) with Frame stand:</i> <ul style="list-style-type: none">• Business black color• 21.5" W X 3.2" D X 16.3" H• 545mm W X 81mm D X 414mm H (with feet)• 18.5 lb (8.4 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)											
Limited Warranty ¹	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available											
	Security <ul style="list-style-type: none">• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)• Boot sequence control• Boot without keyboard and mouse• USB port disablement											
	ENERGY STAR® 5.2-compliant RoHS-compliant											
	Supports ThinkVantage Technologies											
	For compatible accessories, please go to O-Edge92Z sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet											

Type-model	Processor	Memory ^b	Camera (megapixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Key-board/Mouse	Win7 preload	Ann date (mm/dd/yy)
3414-A7U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3414-A8U	i5-3570S	4GBx1	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3414-A9U	i7-3770S	4GBx2	2.0M	1TB 7200	64GB	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3414-B3U	i3-2120	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	USB	None	Pro 64 07/03/12
3414-B4U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	USB	None	Pro 64 07/03/12
3414-B5U	i7-3770S	4GBx2	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	None	2.4G	None	Pro 64 07/03/12
3414-C7U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Pro 64 07/03/12
3414-C8U	i7-3770S	4GBx1	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Pro 64 07/03/12
3414-C9U	i7-3770S	4GBx1	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	2.4G	None	Pro 64 07/03/12
3414-CAU	i7-3770S	4GBx2	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	2.4G	None	Pro 64 07/03/12
3414-CPU	i5-3470S	4GBx1	2.0M	1TB 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	2.4G	None	Pro 64 07/10/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	<p>Stylish All-In-One PC for small/medium businesses</p> <p>Intel® Core™ i3-2120 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD 2000 Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i5-3570S Processor (4 cores / 4 threads, 3.1GHz, 6MB cache), Turbo Boost 2.0 (3.8GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology</p> <p>Processor in LGA1155 socket</p>	Preloaded operating system
Implementation		Genuine Windows® 7 Professional 64
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)	Ready to install applications (only some listed)
Graphics	<p>AMD Radeon™ HD 7650A, 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display;</p> <p><i>Maximum resolution: 1920x1200(HDMI)@60Hz</i></p>	Preloaded applications (only some listed)
Widescreen display	<p>21.5" (54.5mm) Full HD 1080p (1920x1080) TFT color, infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector</p>	<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager • Business-in-a-Box
Multi-touch Camera	<p>Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch</p> <p>Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus,</p> <p>integrated digital MIC array with stereo, LED indicator</p>	<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • ThinkVantage Automatic Lock Utility • ThinkVantage Power Manager • View Management Utility • Microsoft Touch Pack • Lenovo Solution Center • Lenovo Message Center Plus • Intel Small Business Advantage • RapidBoot HDD Accelerator • Lenovo SimpleTap • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Evernote® • Symantec™ VIP • Skype™ for Windows • Windows Live™ Essentials • Microsoft® Office preloaded; purchase a product key to activate • Corel® Burn.Now™ (DVD±RW) • Corel DVD MovieFactory® (DVD±RW)
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in	
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm	
Optical Media reader	<p>Some: mSATA Solid State Drive (SSD), via PCIe Mini Card slot</p> <p>DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable</p> <p>Some: 7-in-1 Single Slot SD media reader</p>	
Chipset	Intel B75 Express Chipset	
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in	
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	
PCIe Mini Card	Two PCI Express® Mini Card slots	
PCIe WLAN ⁴	<p>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1</p> <p>Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2</p>	
Bluetooth	Some: Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter	
PCIe mSATA	One Mini PCIe mSATA slot	
Ethernet	One gigabit ethernet port, Intel 82579LM	
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified	
Intel AMT Security chip	None	
Keyboard	<p>Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black</p> <p>Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black</p>	Security
Mouse	<p>Some: Enhanced Optical USB Mouse, black</p> <p>Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black</p>	<ul style="list-style-type: none"> • Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis) • Boot sequence control • Boot without keyboard and mouse • USB port disablement
Power supply	180 watts, autosensing, 92% PSU	
Machine	<p>Model(s) with Frame stand:</p> <ul style="list-style-type: none"> • Business black color • 21.5" W X 3.2" D X 16.3" H • 545mm W X 81mm D X 414mm H (with feet) • 18.5 lb (8.4 kg) in maximum configuration • Handle in rear, removable feet • Support VESA mount (100mm) 	<p>ENERGY STAR® 5.2-compliant</p> <p>RoHS-compliant</p> <p>Supports ThinkVantage Technologies</p>
Limited Warranty ¹	<p>1-year, limited onsite service, 8 am-5 pm, Mon - Fri coverage</p> <p>excluding holidays, next business day response time / service upgrades available</p>	<p>For compatible accessories, please go to O-Edge92Z sheet;</p> <p>For ThinkPlus™ service upgrade options, please go to S-TC sheet</p>

Type-model	Processor	Memory ⁸	Camera (megapixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Key-board/Mouse	Global	Preload	Ann date (mm/dd/yy)
3414-CVU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	None	USB	None	Win8 Pro64	10/23/12
3414-D3U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win8 Pro64	10/23/12
3414-D4U	i7-3770S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win8 Pro64	10/23/12
3414-DJU	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	10/23/12
3414-DKU	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	10/23/12
3414-DLU	G870	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	10/23/12
3414-DNU	i7-3770S	8GBx2	2.0M	1TB 7200	None	BD player	HD 7650A	Intel 2230 + BT	Media	2.4G	None	Win7 Pro64	11/13/12
3414-ELU	G2120	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win8 Pro64	12/04/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 1-year limited warranty

Positioning Processor	Stylish All-In-One PC for small/medium businesses Intel® Pentium® G870 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1333MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Pentium G2120 Processor (2 cores / 2 threads, 3.1GHz, 3MB cache), integrated Intel HD Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit		
Implementation	Processor in LGA1155 socket											Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Microsoft Touch Pack• Lenovo® Message Center Plus• Intel Small Business Advantage• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Symantec™ VIP• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW)• Corel WinDVD® (BD player) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• Intel AppUp®• AccuWeather• PC Device Stage• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW) - All models <ul style="list-style-type: none">• ThinkVantage System Update• ThinkVantage Automatic lock Utility• Lenovo Solution Center• View Management Utility• Norton Internet Security (30 days of virus definitions)• Microsoft® Office preloaded; purchase a product key to activate• Evernote®• Skype™		
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)													
Graphics	AMD Radeon™ HD 7650A , 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; Maximum resolution: 1920x1200(HDMI)@60Hz													
Widescreen display	21.5" (54.52mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector													
Multi-touch Camera	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator													
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in													
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm None													
Optical	Some: Blu-ray™ disc reader (no Blu-ray media burning), DVD recordable, not removable, 12.7mm high, tray-in													
Media reader	Some: DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable Some: 7-in-1 Single Slot SD media reader													
Chipset	Intel B75 Express Chipset													
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in													
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
PCIe Mini Card	Two PCI Express® Mini Card slots													
PCIe WLAN ⁴	11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2													
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter													
PCIe mSATA	One Mini PCIe mSATA slot													
Ethernet	One gigabit ethernet port, Intel 82579LM													
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified													
Intel AMT Security chip	None None													
Keyboard	Some: Lenovo® Slim New F5 USB Keyboard (USB connector), black Some: Ultrathin Plus Wireless Keyboard (2.4GHz via USB receiver), black													
Mouse	Some: Enhanced Optical USB Mouse, black Some: Ultrathin Plus Wireless Mouse (2.4GHz via USB receiver), black													
Power supply	180 watts, autosensing, 92% PSU													
Machine	Model(s) with Frame stand: <ul style="list-style-type: none">• Business black color• 21.5" W X 3.2" D X 16.3" H• 545mm W X 81mm D X 414mm H (with feet)• 18.5 lb (8.4 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)													
Limited Warranty ¹	1-year, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													
For compatible accessories, please go to O-Edge92Z sheet; For ThinkPlus™ service upgrade options, please go to S-TC sheet														

See footnotes for important warranty information

US model(s) announced October 23, November 13, or December 4, 2012

US model(s) withdrawn effective November 2013 or January 2014

©Lenovo

(TROY1-7) January 2014

Type-model	Processor	Memory ^b	Camera (mega-pixel)	Disk SATA GB rpm	mSATA SSD	SATA optical	Graphics	PCIe Mini Card WLAN	Media reader	Key-board/ Mouse	Global	Preload	Ann date (mm/dd/yy)
3417-K1U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	11/20/12
3417-K2U	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 105	Media	USB	None	Win7 Pro64	11/20/12
3417-K3U	i7-3770S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win7 Pro64	11/20/12
3417-K4U	i3-3220	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win8 Pro64	11/20/12
3417-K5U	i5-3470S	4GBx1	2.0M	500G 7200	None	DVD±RW	HD 7650A	Intel 2230 + BT	Media	USB	None	Win8 Pro64	11/20/12

- Small and medium business (SMB) model(s), part of the US TopSeller™ Program
- 3-year limited warranty

Positioning Processor	<i>Stylish All-In-One PC for small/medium businesses</i> Intel® Core™ i3-3220 Processor (2 cores / 4 threads, 3.3GHz, 3MB cache), integrated Intel HD Graphics 2500, integrated 1600MHz dual-channel DDR3 memory controller Intel Core i5-3470S Processor (4 cores / 4 threads, 2.9GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD 2500 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-3770S Processor (4 cores / 8 threads, 3.1GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD 4000 Graphics, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1155 socket											Preloaded operating system Some: Windows® 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit Some: Windows 8 Pro 64-bit														
Implementation												Preloaded applications (only some listed) - Windows 7 models <ul style="list-style-type: none">• ThinkVantage® Product Recovery• ThinkVantage Communication Utility• ThinkVantage Power Manager• Microsoft Touch Pack• Lenovo® Message Center Plus• Intel Small Business Advantage• RapidBoot HDD Accelerator• Lenovo SimpleTap• Adobe® Reader®• Symantec™ VIP• Windows Live™ Essentials• Corel® Burn.Now™ (DVD±RW)• Corel DVD MovieFactory® (DVD±RW) - Windows 8 models <ul style="list-style-type: none">• Lenovo Support• Lenovo Settings• Lenovo Companion• Lenovo Cloud Storage• Lenovo QuickLaunch• Norton™ Studio• Intel AppUp®• AccuWeather• PC Device Stage• Cyberlink Power2Go (DVD±RW)• Cyberlink PowerProducer (DVD±RW)														
Memory	16GB max, PC3-12800 1600MHz DDR3 , two 204-pin SODIMM sockets (notebook)																									
Graphics	AMD Radeon™ HD 7650A , 2GB memory, PCI Express® x16, 35 watts, DirectX® 11, external digital monitor support via HDMI, supports dual independent display; <i>Maximum resolution: 1920x1200(HDMI)@60Hz</i>																									
Widescreen display	21.5" (54.5mm) Full HD 1080p (1920x1080) TFT color , infinity display, IPS wide viewing angle, LED backlight, 250 nits, 16:9 aspect ratio, 1000:1 contrast ratio; works as standalone monitor via HDMI-in connector																									
Multi-touch Camera	Projected Capacitive Touch (PCT) technology, supports 10-point multi-touch Camera on top of screen, 2.0-megapixel, Full HD 1080p, fixed focus, integrated digital MIC array with stereo, LED indicator																									
Controls	Front facing buttons for brightness up, brightness down, power on/off, and Video in																									
Disk mSATA™ SSD	SATA 6.0Gb/s, 3.5" Wide, 7200 rpm																									
Optical Media reader	None																									
Media reader	DVD burner, SATA 1.5Gb/s, 12.7mm high, fixed, not removable																									
7-in-1 Single Slot SD media reader	7-in-1 Single Slot SD media reader																									
Chipset	Intel B75 Express Chipset																									
Rear ports	Four USB 2.0, ethernet (RJ-45), HDMI-out, HDMI-in																									
Side ports	Two USB 3.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)																									
PCIe Mini Card	Two PCI Express® Mini Card slots																									
PCIe WLAN ^d	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® wireless-N 105, 1x1 Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2																									
Bluetooth	Bluetooth 4.0 wireless, integrated in Intel 2230 Wi-Fi + Bluetooth combo adapter																									
PCIe mSATA	One Mini PCIe mSATA slot																									
Ethernet	One gigabit ethernet port, Intel 82579LM																									
Audio support	High Definition (HD) Audio, Realtek® ALC662 / Two internal stereo speakers (3watt x 2), Dolby® Advanced Audio™ v2 certified, Microsoft Lync® certified																									
Intel AMT Security chip	None																									
Keyboard Mouse	Lenovo® Slim New F5 USB Keyboard (USB connector), black Enhanced Optical USB Mouse, black																									
Power supply	180 watts, autosensing, 92% PSU																									
Machine	<i>Model(s) with Frame stand:</i> <ul style="list-style-type: none">• Business black color• 21.5" W X 3.2" D X 16.3" H• 545mm W X 81mm D X 414mm H (with feet)• 18.5 lb (8.4 kg) in maximum configuration• Handle in rear, removable feet• Support VESA mount (100mm)																									
Limited Warranty ¹	3-years, limited onsite service, 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available																									
Security																										
• Security slot (in rear for attachment of optional Kensington® MicroSaver® cable; Kensington lock also locks chassis)																										
• Boot sequence control																										
• Boot without keyboard and mouse																										
• USB port disablement																										
ENERGY STAR® 5.2-compliant																										
RoHS-compliant																										
Supports ThinkVantage Technologies																										
For compatible accessories, please go to O-Edge92Z sheet;																										
For ThinkPlus™ service upgrade options, please go to S-TC sheet																										

Memory	2GB PC3-12800 DDR3 SODIMM 4GB PC3-12800 DDR3 SODIMM 8GB PC3-12800 DDR3 SODIMM	0A65722 0A65723 0A65724	ann 06/05/12 ann 06/05/12 ann 06/05/12	Stand ThinkCentre Edge 91z/92z Stand ⁵⁹ ThinkCentre Extend Arm ⁵⁷ ⁵⁷ Compatible when ThinkCentre Extend Arm is desk (clamp) mounted only, wall mount is not supported. ⁵⁹ Not compatible to Multi-touch models.	0A33969 ann 07/26/11 57Y4352 ann 07/06/10
Storage and removable storage	USB 3.0 Secure 500GB Hard Drive USB 3.0 Secure 750GB Hard Drive USB 3.0 Secure 1TB Hard Drive	0A65619 0A65616 0A65621	ann 11/29/11 ann 11/29/11 ann 08/28/12	Monitor Accessories ⁴⁶ Lenovo HDMI to VGA Monitor Cable Kensington MicroSaver Cable Lock ⁵⁸ Kensington Twin Head Cable Lock ⁵⁶ ⁴⁶ Compatible on selected Lenovo and ThinkVision monitors.	0B47069 ann 06/26/12 73P2582 ann 12/29/03 45K1620 ann 09/30/08
Keyboard	Enhanced Performance USB Keyboard Ultraslim Plus Wireless Keyboard and Mouse ⁵² ThinkPad® USB Keyboard with TrackPoint Lenovo® USB Fingerprint Keyboard Lenovo USB Smartcard Keyboard	73P2620 0A34032 55Y9003 73P4730 51J0155	ann 03/23/04 ann 04/05/11 ann 08/18/09 ann 02/22/05 ann 03/24/09	More information at www.lenovo.com/support/monitoraccessories	
Mouse	Lenovo Laser Mouse (USB) Lenovo Wireless Laser Mouse ⁵²	41U3074 0A36188	ann 01/23/07 ann 12/20/11	For more information on accessories: www.lenovo.com/accessories Purchase Lenovo accessories www.lenovo.com/support/accessories Product specifications on Lenovo Support www.lenovo.com/accessoriesguide Option Compatibility Matrix (OCM) and accessory brochures www.lenovoquickpick.com An Options Compatibility Configurator for Lenovo systems	
Multimedia	ThinkPad In-Ear Headphones with mic	57Y4488	ann 01/07/10		
Security	Kensington® MicroSaver® Cable Lock ⁵⁸ Kensington Twin Head Cable Lock ⁵⁶ 3M ThinkCentre Edge91z/92z Privacy Filter	73P2582 45K1620 4Z10A23290	ann 12/29/03 ann 09/30/08 ann 09/30/08		
	⁵⁶ Attaching to any form factor not only secures the ThinkCentre to the work area, but it also prevents users from opening the chassis itself.				

Availability: All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

Warranty: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC, 27709, Attn: Dept ZPYA/B676. Lenovo makes no representation or warranty regarding third party products or services.

¹ **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.

² **Hard drive:** GB = billion bytes, TB = trillion bytes. Accessible capacity is less; up to 4GB is service partition.

³ **Limited onsite service systems** are designed to be repaired during the applicable warranty period primarily with customer-replaceable parts provided by Lenovo. Lenovo will only send a technician onsite to perform a repair if (a) remote telephone diagnosis and/or customer part replacement are unable to resolve the problem, or (b) the part is one of the few designated by Lenovo for onsite replacement. For a list of onsite replaceable parts, contact Lenovo. In the United States call 1-800-426-7378. Support unrelated to a warranty issue may be subject to additional charges. Lenovo onsite repair (LOR), 8 am to 5 pm, Monday through Friday coverage excluding holidays, next business day (NBD) response time.

⁴ **CD and DVD list** maximum rates; rates are variable and are often less than the maximum.

⁵ **Included software** may differ from its retail version (if available), and may not include user manuals or all program functionality. License agreements may apply.

⁶ **Multi-Burner Plus** (part number 73P3305 or 73P3370) is a DVD±RW device that reads and writes to DVD-RAM, DVD-R, DVD-RW, DVD+R, and DVD+RW. It also reads and writes to CD-R and CD-RW media. 73P3370 also writes to DVD+R double layer media.

⁷ **ThinkPlus Services:** These services are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part will be express shipped to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. P&L means parts and labor. P/U means pick-up. See ThinkPlus terms and conditions for complete details and restrictions.

⁸ **Memory:** For PCs without a separate graphics card, memory supports both system and video. Accessible system memory may be up to 384MB less than the amount stated, depending on video mode.

⁹ **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.

¹⁰ **Modem speeds:** Public network download speeds are limited to 53Kbps. Upload speeds are limited to 48Kbps for V.92 modems. Actual speeds depend on many factors and are often less than the maximum possible. V.92 functions and speeds require compatible phone line and server equipment. Check with your telephone and ISP service providers for availability.

¹¹ **For combination drives,** maximum speeds only are given in the following order: CD read, CD write, CD re-write, DVD read.

¹⁴ **Response times may vary.** May exclude some holidays. Telephone support may be subject to additional charges.

¹⁵ **Update Connector** is available at no charge to registered customers during the limited warranty period. Line charges may apply.

¹⁶ **Embedded Security Subsystem** works with optional VPN software.

¹⁸ **Embedded Security Subsystem** may require download of client security software from the Web.

¹⁹ **Asset ID** allows system-specific information to be stored in a chip inside the system; it does not have any radio frequency support.

²⁰ **Operating System:** Level of support varies by operating system. Operating systems not preloaded on the system may not provide full feature functionality. Refer to lenovo.com/pc/support and enter your machine type and model number for more information.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you.

ThinkCentre®

Trademarks: Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside logo, Intel Core and Core Inside are trademarks of Intel Corporation in the US and other countries. Other company, product, or service names may be trademarks or service marks of others.

Visit lenovo.com/safecomputing periodically for the latest information on safe and effective computing.

© Lenovo, 2014.
All rights reserved.

Lenovo
1009 Think Place
Morrisville, NC 27560
U.S.A.

ldwbook.pdf