Overview

Epson TM-m30 Ethernet USB Printer



Model

Epson TM-m30 Printer (Black) Epson TM-m30 Printer (White) 2HV27AA/AT 6BC95AA/AT

Introduction

The Epson TM-m30 Printer reimagines POS printing with a sleek, 3" receipt printer.

Key Benefits

- Compact footprint; ideal for counter spaces
- Flexible configuration (top load or front load); interchangeable by easily removing the outer case
- Efficient power management use one power source for both your tablet and printer
- Easy setup and versatile connectivity
- ePOSTM print technology for easy setup with iOS[®], AndroidTM and Windows[®] mobile devices and Windows drivers for desktop PCs
- Three-year limited warranty from HP



Overview

Compatibility

The Epson TM-m30 Printer is compatible with the HP Point of Sale Systems.

NOTE: Not all Point of Sale system models are available in all regions. Not all HP Cash Drawer models are available in all regions.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.



Technical Specifications

General	Fonts/Column Capacity	
	Fonds/Column Capacity	Font A: 12 x 24 48 cpl (default);
		Font B: 10 x 24 57 cpl; Font C: 9 x 17 64 cpl
	Character Size	Font A: 1.25 x 3.00 mm;
		Font B: 1.13 x 3.00 mm; Font C: 0.88 x 2.13 mm
	Character Set	95 Alphanumeric, 18 International, 128 x 43
		Graphic
	Receipt-Columns Paper Roll Size	Width: 3.12"/79.5 mm
		Paper Loading: Drop-in
		Roll Diameter (Max): 3.27"/83 mm
		Core Diameter (Min): 0.71"/18 mm
	Knife	Auto Cutter
	Resolution	203 dpi
	Paper Thickness Range	48 – 80 µ m
	Cash Drawers	1 connector can drive 2 cash drawers with separately purchased splitter
		cable (default configuration is connection to 1 cash drawer)
	Bar Codes	UPC-A, UPC-E, JAN8 / EAN8, JAN13 / EAN13,
		Code39, Code93, Code128, ITF, CODABAR(NW-7), GS1-128,
		GS1 DataBar
	Two-Dimensional	PDF417, QR Code, Maxi Code, Data Matrix, Aztec Code, Two dimensional
	Symbol Printing	GS1 DataBar, Composite Symbology
	Print method	Thermal
	Print speed	200 mm/second
	Paper type	Direct thermal POS Grade(s)
Mechanical	Dimensions (WxDxH)	5" x 5" x 5"
		127 x 127 x 127 mm
	Weight	2.64 lb/1200 g
	Color	Epson Black, Epson Ultra White
Interface/Connection	Interface	Interface (Ethernet model): Built-in USB + Ethernet
		10/100Base-T/TX
Power	Power Source	Adapter C, Adapter RA (Printer powers tablet SKU only)



Technical Specifications

	Consumption	Approx. 1.5 A (mean)		
Temperature Range	Operating	5 to 45°C (41 to 113°F) at 10 to 90% Humidity		
	Storage	-10 to 50°C (14 to 122°F) at 5 - 90 % Humidity		
Wireless Security Mode	WEP, WPA, WPA2-Personal/Enterprise			
Supported Mobile Operating Systems	iOS, Android and Windows (Store Apps)			
Easy Setting	SimpleAP, TM Utility, NFC, and QR Code			
Software	TM Utility (iOS, Android), TM-m30 Utility (Windows			
	Desktop), EpsonNet Config (Win, Mac), TM Bluetooth Connector			
LED Indicators	Blue LED - On = Power, Orange LED – Error and/or Paper Out			
NV Bit Image Memory	12KB (max)			
NV Graphics	384KB (max)			
Receive Buffer	4KB or 45byte			
Drivers	ePOS-Print SDK, Windows Driver (APD), OPOS, OPOS.NET, JavaPOS (Win), JavaPOS (Linux), TM Virtual Port			
Operating System Compatibility	Microsoft® Windows (APD, OPOS, OPOS for .NET, JavaPOS)			
compationity	Microsoft Windows 8.1 / iOS / Android (ePOS-Print SDK)			
	Mac® OS X® Linux (CUPS, JavaPOS)			
Reliability	Printer Reliability: 15 million printing lines Auto Cutter Reliability: 1 million cuts			
Agency Certifications	ons EMI FCC Class A, CAN ICES-3(A)/			
	NMB-3(A) Safety Standard UL60950-1/CSA C22.2 No.60950-1			
	RoHS compliant ENERGY STAR® qualified (select SKUs)			
Kit Contents	TM-m30, Power Adapter with AC cable, Sample Paper Roll, Set-up Paper, Set-up Guide, Power Switch Cover, Spacer for 58mm.			
Cable Kits (sold Separately)	2KH42AA	Epson 10' USB Cable		
	2KH40AA	Epson 10' PUSB Y Cable (power and communication)		
	7NX62AA	Epson 12' PUSB Cable		



Summary of Changes

Date of change:	Version History:		Description of change:
September 23, 2019	From v1 to v2	Changed	Service and Support section



© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies.