

**Model: AHC4531ZFZ (FH4531Z)**
**Product Description**

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 50HZ	24747	6236	7251	2913	8.5	2.14	2.49	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

**General**

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 37  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 56.65  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1480

**Electrical**

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 66  
**Rated Load Amps (RLA 50 Hz):** 14  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 26.3  
**Motor Resistance (Ohm) - Main:** .9  
**Motor Resistance (Ohm) - Start:** 3.2  
**Motor Type:** CSR  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

CCC Listed, CE Listed, GOST RUSSIA Listed, NF Listed, VDE Listed