

# Stand-alone Reader

## Outdoor Stand-alone Network Reader

**New!**

### Outdoor Stand-alone Network Ready

#### Main Features:

- Big and clear LCD panel with 4 line messages (1024x64 Graphic)
- Unlimited site code
- 11 sets of Time Zone
- Different time zone for each user
- Up to 120 holiday that can be set in a year starting from the editing date
- Auto-show work status (Set Via Time Zone Edit)
- Master cards range assignable
- On RS-485 port supported for networking (Via Controller or Directly)
- Built-in door sensor and arming On/Off input
- Support with keypad locks immd & all cards entrance allowance before cards editing finished
- Control mode, card capacity and card type assignable by user directly
- Built-in a proximity reader, a external wiegand reader port and IC card
- Auto-discriminating between stand-alone & networking system, AR-950v3 could connect with controller ACC-1000 to have multi-door anti-pass back
- Alarm function is available (Tamper, Force Entrance, Door Open Too Long)



CE FC

### Specifications

Item #: ECL-ACC950
Networking: RS-485, 9600, N, 8, 1
External reader port: Suitable for all WG, ABA reader, 125K, 13.56M (Mifare) or 2.4G reader
RF Frequency / Reading range: 125KHz / 10-18cm
Door relay: 2A/12 VDC N.O./N.C./COM 0.1~600 sec. Latch type
Alarm relay: 2A/12VDC N.O./N.C./(Jumper) 0~600 sec. (COM Common)
DI Input: Egress button / door sensor / arming switch
Transistor output: Arming / door sensor / card sensor
Tamper switch Limit switch (Form C)
Serial port: Supported for AI-401R016, LED display, relay board, printer ETC. (4800, N, 8, 1)
Material: ABS
Dimensions: 127(L) x 91(W) x 46(H)mm

Item # ECL-ACC950

Distributed By:

Security Products Distributors