

IN110xa Series

Unsurpassed lamp life. Outstanding Connectivity.

IN112xa, IN114xa, IN116xa

IN110xa Series projectors do more with ultra-long lamp life, high brightness, and amazing connectivity. Beam more perfect images and engage your audience with 2 HDMI inputs, VGA, video, and audio capability. Plus, compact design and light weight make them as easy to move around as they are to install.

Why choose the IN110xa Series?

- Great performance and connectivity
- Long life lamp of 15,000 hours
- High 26,000:1 contrast ratio and 3,800 lumens
- Compact and light weight for easy portability
- Accurate and vivid color reproduction with BrilliantColor technology
- 2 HDMI connectivity
- Display 3D content from Blu-ray and PCs



IN112xa	IN114xa	IN116xa
SVGA (800 x 600) 3800 lumens Throw ratio: 1.95-2.15 Zoom ratio: 1.1:1	XGA (1024 x 768) 3800 lumens Throw ratio: 1.95-2.15 Zoom ratio: 1.1:1	WXGA (1280 x 800) 3800 lumens Throw ratio: 1.55-1.70 Zoom ratio: 1.1:1

Industry-leading Lamp Life

The IN110xa Series features an unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace, these projectors are an unbeatable value.

High Brightness and High Contrast

Get better, brighter images on any surface, in any light. The IN110xa series has up to 3,800 lumens and a 26,000:1 contrast ratio for whiter whites, darker blacks, and overall image sharpness. Preset modes give you great image quality on beige walls, whiteboards, or blackboards.

3D Ready

The IN110xa Series supports multiple forms of 3D – including Blu-Ray, 3D broadcasting, video games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately) to seamlessly synchronize with the image for an awesome 3D experience.

Advanced Presentation and Setup Features

Equipped with AV Mute, test patterns, image shift and other advanced features, the IN110xa Series delivers your content powerfully without complicated set-up.

Specifications*

	IN112xa	IN114xa	IN116xa
Native Resolution	SVGA 800 x 600	XGA 1024 x 768	WXGA 1280 X 800
Maximum Resolution	WUXGA 1920 X 1200		
Display Technology	DLP 0.55"		DLP 0.65"
Brightness	3,800 lumens Normal Mode (2,800 lumens Low Power)		
Lamp Life**	6,000 hours (Normal Mode), 7,200 hours (Low Power), 15,000 hours (Dynamic Mode***)		
Lamp Power	195W (Normal Mode), 160W (Low Power), 60W (Dynamic Mode)		
Contrast Ratio	26,000:1		
Color Wheel	6 segment, 2x speed		
Audible Noise	26 dB		
Computer Compatibility	PC, Mac		
Projection Offset	15%		12%
Keystone Correction	± 40° vertical		
Lens Type	Manual zoom and focus		
Lens - Throw Ratio - Zoom Ratio	1.95 - 2.15 1:1		1.55 - 1.70 1:1
Projection Distance	1.2m - 12.0 m	1.1m - 12.0 m	
Image Size	27.5" ~ 300"		33" ~ 300"
Aspect Ratio	4:3 Native, Supports 16:9 and 16:10		16:10 Native, supports 4:3 and 16:9
Synch - Horizontal Scan Freq - Vertical Scan Freq	31.469kHz ~ 97.551kHz 56 - 85 Hz (120Hz for 3D feature projector)		
Video Compatibility	Standard (NTSC, NTSC 4.43, PAL / M / N, SECAM), SD (480i, 480p, 576i), HD (720p, 1080i 1080p)		
Number of Colors	1.07 billion		
Input Sources	VGA, Composite S-Video, HDMI v1.4b x 2 (No net), 3.5mm stereo input x 2		
Output Sources	Monitor out (VGA), 3.5 mm stereo out		
Control	RS232		
Speaker	3W Mono		
Product Dimensions - WxDxH	8.8 x 12.4 x 4 in / 223.5 x 314.2 x 101.7 mm		
Product Weight	5.5 lbs / 2.5 kg.		
Shipping Dimensions - WxDxH	12 x 14.3 x 7.8in / 304.8 x 363.2 x 198.1 mm		
Shipping Weight	7.3 lbs / 3.3 kg.		
Operating Conditions	Sea Level to 10,000 feet @ 73.4°F / manual switch to high altitude mode above 5000 feet		
3D	Supports 3D content from Blu-ray, cable boxes, dish services, and more (over HDMI). Also supports PC-based 3D content configured at 1080p running at 60Hz signal. DLP Link 3D glasses required.		
Projector Warranty	2 years		
Lamp Warranty	6 months		
Accessory Warranty	90 days		
Ships with - Accessories	Power cord, VGA cable, Safety instructions, User documentation, Remote control without batteries		
Menu Languages	English, French, German, Italian, Korean, Norwegian, Portuguese, Polish, Hindi, Filipino, Malay, Romania, Russian, Simp. Chinese, Trad. Chinese, Japanese, Hungarian, Czech, Thai, Turkish, Farsi, Vietnamese, Spanish, Swedish, Dutch, Arabic, Indonesian		
Approvals	UL and c-UL (US/Canada), FCC (US/Canada), CE (Europe), CCC+CECP (China), KCC (Korea), IRAM (Argentina), NOM (Mexico), PCT/CU/EAC (Russia), PSB (Singapore), SABS (South Africa), CB, Nemco/GS, KC		

* Product specifications, terms, and offerings are preliminary and subject to change at any time without notice.

** Actual lamp life may vary based on the ambient environment and projector usage. Conditions that may affect lamp life include temperature, altitude, and rapidly switching the projector on and off.

*** Dynamic lamp hours are determined by a power saving algorithm that varies the lamp power according to the input content that is being displayed, conserving energy and extending lamp life.

Optional Accessories

Replacement Lamp (SP-LAMP-097)
 Universal Ceiling Mount (PRJ-MNT-UNIV)
 LiteShow Wireless Adapter (INLITESHOW4DB+)
 LiteShow Mount (PRJ-MNT-LS3)

Soft Carry Case (CA-SOFTVAL-2)
 Extended Warranties (EPW-PJV1, EPW-PJV2)
 Cables and adapters