

Data Sheet

Fujitsu Display P2410 WE CAM

Widescreen 61.13 cm (24.1 inch) superior display
The heart of smart workplaces and video conferencing

The FUJITSU Display P2410 WE CAM is an IPS-based widescreen display that combines smart workplace concepts with advanced ergonomics. It comes with a multi-functional USB Type-C hub that makes it ideal for modern and shared workspaces.

Multifunctional USB Type-C means:

- 95W power delivery for external devices
 - Transmission of video signals, webcam, data, LAN & audio
- It contains a Fujitsu patented solution that generates an All-In-One user experience with Mini PC ESPRIMO G and LIFEBOOK series.

The factory pre-calibrated display provides high color fidelity for single as multi-monitor usage.

KVM function reduces USB hardware needs by using one display for a number of devices.

For an easy log-in and professional video conferencing, the P2410 WE CAM comes with a Microsoft Windows HELLO compatible, bright Full HD Webcam with mechanical lever lock. The directional microphone hides disturbing sounds. Fujitsu innovated the display housing by offering the worldwide first right-hand USB hub that ensures an optimal cable course and is ergonomically perfect for most users.

Retina protection by low blue light panel that culls damaging blue light without any loss or changes of color.

The integrated Autobrightness sensor adapts the brightness of the display to an optimum, saves energy and increases constant productivity due to reduced eye strain.

DisplayView™ software enables you to configure your monitor easily for remote management and administrative tasks.

Prolonged product lifecycle through feasible firmware updates done by the user.

Focusing on environmental friendliness, the packaging is styrofoam free and solely consisting of cardboard, which is more than 90% recycled.



Technical details

Special features

MS Hello compatible WebCam
 In-Plane Switching (IPS) technology
 Color accuracy average DeltaE<2
 DICOM Greyscale Standard Display Function compatible gamma preset
 Eco button for Eco mode and 4-colored status LED
 Presence sensor with PC security solution
 Auto Brightness Control (ABC)
 Auto Pivot
 Workplace Lighting Guide
 DisplayView™ Software
 6-in-1 Stand
 Cable guide
 Always available USB (in operating and standby mode)
 24/7 usage
 Integrated speakers
 Smart Power ON and LED function for AiO-type usage (in combination with a dedicated FUJITSU systems e.g. ESPRIMO G or selected LIFEBOOK models)
 Low blue light mode

Ergonomic stand

Stand	6-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	40 mm
Rotation to portrait	90° clockwise and counterclockwise, Auto Pivot sensor
Tilt angle	-5° / +35°
Swivel angle	345°

Picture performance

Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	3H hard coating, Anti-glare
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in Video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
High color gamut - typical	73% NTSC / 99% sRGB color space
Brightness - typical	300 cd/m ²

Size and resolution

Aspect ratio	16:10
Diagonal Size	61.13 cm (24.1-inch)
Resolution (native)	1,920 x 1,200 pixel
Resolution (interpolated)	1,920 x 1,080 pixel, 1,680 x 1,050 pixel, 1,600 x 1,200 pixel, 1,400 x 900 pixel, 1,280 x 800 pixel, 1,280 x 768 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	518.4 x 324 mm
Pixel Pitch	0.27 mm

Frequencies

Horizontal	30 - 82 kHz
Vertical	48 - 76 Hz

Connectivity

DisplayPort	1 x DisplayPort Out (Daisy Chain), 1 x DisplayPort 1.2
HDMI	1 x HDMI 1.4
Audio signal output	3.5 mm stereo phone jack for head phone

Audio sound output	2 x 2 W
DisplayPort audio	Yes
HDMI audio	Yes
USB downstream	4x USB 3.2 Superspeed 5GBit (1x Type C and 1x Type A on side, 2x Type A on bottom)
USB upstream	1 x USB Type C with alternate mode for video data and power delivery up to 95W 1 x USB 3.2 Gen1 Type B Integrated KVM switch function
Ethernet (RJ-45)	1 x Gigabit LAN PXE, Wake on LAN (from S3), MAC Address Pass Through support with selected LIFEBOOK models
Integrated microphone array	Stereo microphone
Integrated Web Camera	2.0 megapixel webcam (full HD)

Ease-of-use menu

Notes	6 tactile keys on front side
Direct Access Keys	Menu, ECO, Input, Mode, Audio, Brightness
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto Brightness, ACR, Lighting Guide
Mode	D-Mode, sRGB, Low Blue Light, Office, Photo, Video, Custom
Color	5000K, 6500K, 7500K, Native, RGB Adjust
OSD	Language, OSD-Timeout, OSD rotation
Image adjust	Expansion, Saturation, Sharpness
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Signal input, Resolution/ mode, Display mode, Color Temperature, ACR Status, ABC Status
Advanced settings	Presence Sensor, Proximity Adjust, Daisy Chain, Overdrive, DDC/CI, Factory Recall

Power consumption (typical)

Soft switch off	0.26 W
Power save mode	0.28 W
Operating with EPA settings	16.65 W
Total Energy Consumption (Etec)	53.98 kWh/year
Operating maximum brightness	28 W
Power supply	integrated
Power notes	Speakers off, USB not connected Etec and EPA refer to ENERGY STAR® 8.0 Power save mode according to EEL test conditions

Electrical values

Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1

Compliance

Model	P2410W
Global	ENERGY STAR® 8.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified, generation 9, EPEAT® Gold (dedicated regions)
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	(on customer request)
Germany	TÜV GS
Russia	EAC

Singapore	S-Mark
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	532.2 x 59.21 x 368.9 mm 20.95 x 2.33 x 14.52 inch
Dimension with stand (W x D x H)	532.2 x 212.7 x 382.73 mm 20.95 inch x 8.37 x 15.07 inch
Weight (unpacked)	6.57 kg 14.48 lbs
Weight (Monitor only)	4.56 kg 10.05 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Marble grey
Additional Software	
Additional software (optional)	WINDOWS WHQL driver Realtek USB Ethernet Controller driver DisplayView Suite DisplayUpdate Power Delivery Update
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Package content	
Display delivered accessories	DisplayPort data cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m USB cable 1m (USB-C to USB-C) USB-cable 1.8 m (USB-A to USB-B) Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download DisplayView Software is necessary for AutoPivot function and Presence Sensor PC security solution
Packaging information	
Packaging dimension (mm)	162 x 734 x 450 mm
Packaging dimension (inch)	6.38 x 28.9 x 17.72 inch
Weight (packed)	9.36 kg
Weight (packed) (lbs)	20.64 lbs
Order information	
Order Code	S26361-K1698-V145
EAN Code	4065221160243
Country specific order code	BDL:K1698V145-UK - with UK power cable, mandatory for Arabian countries BDL:K1698V145-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
Accessories information	Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty

Warranty

Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Spare Parts availability	at least 7 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

More information

Fujitsu products, solutions & services

In addition to Fujitsu Display P2410 WE CAM, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Display P2410 WE CAM, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/peripheral/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2022 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2023-01-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2022 Fujitsu Technology Solutions GmbH