



ORIGINAL FLAT FINISH KLEARKOTE

5 STAR XTREME #5165 ORIGINAL FLAT FINISH KLEARKOTE is a matte finish clearcoat designed to offer that very popular **Old School, no gloss** look when used with any color basecoat paint, while offering the UV protection and durability of any premium clearcoat finish.



4.4
VOC

FLAT FINISH

6 TO 1 MIX RATIO

**OLD SCHOOL
"FLAT FINISH" LOOK**

Use Medium Hardener #5187, for temps 60°F - 75°F (or small panels), or the **ALL NEW EXTRA SLOW** Hardener #5194, for temps above 75°F (or large panels) to achieve the correct flat finish appearance every time.

FEATURES

**SMALL
PANELS**

**LARGE
PANELS**

#5165-01 Original Flat Finish Klearkote (4.4 VOC), Gallon

#5165-04 Original Flat Finish Klearkote (4.4 VOC), Quart

For temps above 60 ° F thru 75 ° F (or small panels)


#5187-04 Original Hardener - Medium (4.4 VOC), Quart

#5187-16 Original Hardener - Medium (4.4 VOC), Half-Pint

For temps above 75 ° F (or large panels)

#5194-04 Original Hardener - Extra Slow (4.4 VOC), Quart

#5194-16 Original Hardener - Extra Slow (4.4 VOC), Half-Pint



Scan for instant
SDS and **TDS**
information.
#5165

**IMPORTANT! STIR & SHAKE
PRODUCT WELL BEFORE POURING**



ORIGINAL FLAT FINISH KLEARKOTE

5 STAR XTREME #5170 ORIGINAL FLAT FINISH KLEARKOTE is a matte finish clearcoat designed to offer that very popular **Old School, no gloss** look when used with any color basecoat paint, while offering the UV protection and durability of any premium clearcoat finish.



FLAT FINISH

6 TO 1 MIX RATIO

**OLD SCHOOL
"FLAT FINISH" LOOK**

Use Medium Hardener #5182, for temps 60°F - 75°F (or small panels), or the **ALL NEW EXTRA SLOW** Hardener #5184, for temps above 75°F (or large panels) to achieve the correct flat finish appearance every time.

FEATURES

**SMALL
PANELS**

**LARGE
PANELS**

#5170-01 Original Flat Finish Klearkote (2.1 VOC), Gallon

#5170-04 Original Flat Finish Klearkote (2.1 VOC), Quart

For temps above 60 ° F thru 75 ° F (or small panels)


#5182-04 Original Hardener - Medium (2.1 VOC), Quart

#5182-16 Original Hardener - Medium (2.1 VOC), Half-Pint

For temps above 75 ° F (or large panels)

#5184-04 Original Hardener - Extra Slow (2.1 VOC), Quart

#5184-16 Original Hardener - Extra Slow (2.1 VOC), Half-Pint



Scan for instant
SDS and **TDS**
information.
#5170

**IMPORTANT! STIR & SHAKE
PRODUCT WELL BEFORE POURING**