

Data Sheet

FUJITSU PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 OCP

Dual-port 25 Gbit PCIe 3.0

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 OCP

The Fujitsu PLAN EP XXV710-DA2 SFP28 OCP V2 Server Adapter is the most flexible and scalable Ethernet adapter for the current demanding data center environments from Intel.

This adapter family addresses the demanding needs of today's generation agile data center by providing unmatched features for both server and network virtualization, flexibility for LAN networks and proven, reliable performance. The PLAN EP XXV710-DA2 SFP28 adapter delivers superior performance with a throughput 100Gb/s, in a PCI Express 3.0 OCP V2 Type 1 slot.



Main Features	Benefits
Scalable performance <ul style="list-style-type: none"> Intel® XXV710-DA2 SFP28 Dual-Port 25/10 GbE Network Adapter in OCP V2 Type 1 Form Factor 	<ul style="list-style-type: none"> Cost- and energy-efficient design delivers superior performance with a theoretical throughput of 100 Gb/s (50 Gb/s Tx; 50Gb/s Rx) bidirectional throughput
Flexible technology options <ul style="list-style-type: none"> Server Virtualization and VMDq 	<ul style="list-style-type: none"> The host-based virtualization technologies supported by Intel VT include VMDq for Emulated Path: Adapter-based Queue sorting enabling efficient hypervisor-based switching
Efficient networking <ul style="list-style-type: none"> A Complete, Unified Networking Solution 	<ul style="list-style-type: none"> Converging data and storage onto one fabric eliminates the need for multiple adapters, cables and switches
Connectivity <ul style="list-style-type: none"> SR-IOV for Direct Assignment 	<ul style="list-style-type: none"> Adapter-based isolation and switching for various virtual station instances enabling optimal CPU usage in virtualized environments

Technical details

Technical details

Controller Silicon	Intel® XXV710-DA2 25 Gigabit Ethernet Controller
Controller type	Ethernet Ctrl.
Connector type	SFP28
Released drivers list link	http://support.ts.fujitsu.com/Download/Index.asp
Number of ports	2
Data transfer rate(s)	1 Gbit/s; 10 Gbit/s; 25 Gbit/s
Auto Negotiation support	Yes
Bus interface	PCIe 3.0 x8
Bus transfer rate	8GT/s
LEDs	LINK (solid) and ACTIVITY (blinking) LINK SPEED (green = 10Gbps; yellow = 1Gbps)
Network protocol and standards compatibility	IPv4, IPv6 and mixed IPv4/IPv6 network protocols IEEE 802.1p Class of Service IEEE 802.1q VLAN IEEE 802.1Qaz Enhanced Transmission Selection (ETS) IEEE 802.3ae 10Gbit Ethernet IEEE 802.3x Flow Control IEEE 802.1as Timing and Synchronization IEEE 1588 Precision Time Protocol IEEE 802.3az Energy Efficient Ethernet (EEE) SFF 8431 SFP+
Interrupt Levels	MSI-X; INTA; MSI
Virtualization	Server Virtualization - VMDq (up to 256 maximum VMDq VMs supported) - SR-IOV ready (64 virtual function per port) - VEPA: IEEE 802.1Qbg support for Virtual Ethernet Port Aggregator Network Virtualization - VXLAN, NVGRE, GENEVE - VLAN support with VLAN tag insertion, stripping and packet filtering for up to 4096 VLAN tags
Teaming	by OS driver
Remote boot support	PXE 2.0
iSCSI support	Yes
Offloading	- TCP Stateless Offloads (include checksum, TSO, VMDq and RSS) - TX/RX IP, SCTP, TCP & UDP checksum offload (IPv4, IPv6) capabilities - iSCSI Host Initiator - Flow Classification (Trafficking data flows across multiple consumers and connections)
Data transfer rate up to	10 Gbit/s

Order code	Product Name	Height of bracket	Number of ports	Related product
S26361-F4055-E302	Intel XXV710-DA2 25GbE Dual-Port SFP28 PCIe OCP	Matching to system	2	PRIMERGY Server
S26361-F4055-L302	Intel XXV710-DA2 25GbE Dual-Port SFP28 PCIe OCP	Matching to system	2	PRIMERGY Server

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F4055-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4055-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-E701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F4054-L701	Ethernet 25 Gbit/s	MMF (SWL)	LC-style / up to 100m
S26361-F3986-E3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-L3	Ethernet 10 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L4	Ethernet 10 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10Km
S26361-F3986-E5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m

Supported Interface Modules / Cables

Order code	Application	Type / mode	Connector / cable Length
S26361-F3986-L5	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / MMF (SWL)	LC-style / up to 400m
S26361-F3986-E6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3986-L6	Ethernet 10 Gbit/s ; 1 Gbit/s	SFP+ / SMF (LWL)	LC-style / up to 10km
S26361-F3989-E600	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m or 5m
S26361-F3989-L102	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 2m
S26361-F3989-L105	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 5m
S26361-F3989-L110	Ethernet 10 Gbit/s	SFP+ Twinax Cable / active	SFP+ / 10m
Description optional cable	10Gbit/s transceiver module for MMF (S26361-F3986-E3 / -L3 and MC-0JXE51 / MCX0JXE51): - OM1 (Multi Mode Fiber 62.5/125µm, 200 MHz*km) up to 33m - OM2 (Multi Mode Fiber 50.0/125µm, 500 MHz*km) up to 82m - OM3 (Multi Mode Fiber 50.0/125µm, 2000 MHz*km) up to 300m - OM4 (Multi Mode Fiber 50.0/125µm, 4700 MHz*km) up to 400m 10Gbit/s transceiver module for SMF (S26361-F3986-E4 / -L4): - OS1 (Single Mode Fiber 9µm) up to 10km		

Environment

Power consumption	typ. 4.5 W, max. 5.1 W
Power consumption	
Temperature (operating)	0 - 55 °C
Storage temperature	-40 - 70 °C

Compliance

Compliance notes	According to the corresponding system
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 OCP, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PLAN EP Intel® XXV710-DA2 2x25/10GbE SFP28 OCP, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/> Copyright 2024 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited
Website: www.fujitsu.com/primergy
2024-04-06 WW-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/> Copyright 2024 Fujitsu LIMITED