

Fujitsu recommends Windows 11 Pro.

Data Sheet

Fujitsu Desktop ESPRIMO G7012A

A smart and ultra-compact Mini PC for advanced office needs

The Fujitsu ESPRIMO G7012A is a smart Mini PC which offers advanced Desktop PC functionality in an ultra-compact, space-saving design. Making it a perfect device for working from home or in flexible workplaces with its single cable Type-C connection. Provided with the AMD Ryzen™ PRO processors and embedded AMD Radeon™ graphics, the device empowers impressive price/performance ratio.

A smart Mini PC with ultra-compact design

Eye-catching exclusive modern design

- Low noise Mini PC thus providing ergonomic, clean and clutter-free working environment
- Offers advanced desktop PC functionality with a volume of only ~0.87 liters
- Impressive performance/volume ratio and is easy to set up in minutes

Small in size but grand in performance

High performance for best price in a small Mini PC design

- Supreme performance with AMD Ryzen™ PRO processors
- Powerful embedded AMD Radeon™ graphics for low power consumption
- AMD Ryzen Pro /w DASH for high-level security- and manageability demands

Flexibility without limits

Pleasant working environment due to quiet system

- Concept with different heights allows ODD and upgrade options like power supply
- Flexibility for later device upgrades
- Various mounting options

Ultimate usability

Perfect fit for modern offices, shared workplaces or working from home

- Integrated into Fujitsu AIO Display P2410 enables a space saving all-in-one system with flexibility for later upgrades (as shown in 2nd image)
- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls

Made in Europe with best energy efficiency

Reduced environmental impact and reduced energy bills with outstanding quality and stable functions based on European production standard

- High efficient AC adapter or internal 80Plus PLATINUM power supply as option
- Sum of post-consumer recycled content for plastic per weight is up to 50% (min. 11% are from ITE derived post-consumer material and min. 35% are any other post-consumer material)



Components

	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Processor		
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system notes	<p>Windows 11 requires for first device setup:</p> <ul style="list-style-type: none"> - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions <p>After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups.</p> <p>For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&OpenTab=</p> <p>The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program.</p>	
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Memory modules		
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Graphics		
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Hard disk notes		
Hard disk notes	<p>One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.</p> <p>SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height Durability in accordance with the manufacturer's indications on read and write cycles.</p>	
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Optical drive		
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
LAN Notes		
LAN Notes	<p>see flexible interface options</p> <p>Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is available, Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower</p>	
	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Component notes		
Component notes	<p>The listed product components and optional functions are not available in all region/countries;</p> <p>System is available in 3 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter) Internal Power supply version (1.85 Liter)</p>	<p>The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9;</p> <p>System is available in 3 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter) Internal Power supply version (1.85 Liter)</p>

Base unit

Base unit	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Mainboard		
Mainboard type	D4016-A	
Formfactor	proprietary	

Mainboard

Chipset	Integrated in CPU
Processor quantity maximum	1
Supported capacity RAM (max.)	64 GB
Memory slots	2 DIMM (DDR4)
Memory frequency	3,200 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.
LAN	10/100/1,000 MBit/s Realtek RTL8111EPV
Integrated WLAN	optional
BIOS version	UEFI Specification 2.7
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC257N
Audio features	Internal speaker supports audio playback, High Definition audio

I/O controller on board

Serial ATA total	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Front audio: headset	1	1
Flexible Interface Options	One of following flexible Interface options can be added to the system HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) 2x USB 2.0 Type A	One of following flexible Interface options can be added to the system HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) 2x USB 2.0 Type A
USB front	2x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)	2x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)
USB rear	1x USB 2.0 Type-A 3x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink**) see flexible interface options	1x USB 2.0 Type-A 3x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink**) see flexible interface options
DisplayPort	1 (DisplayPort 1.4; DP++)	1 (DisplayPort 1.4; DP++)
HDMI	1 HDMI 2.1	1 HDMI 2.1
Ethernet (RJ-45)	1	1
Interface Module notes	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).
Kensington Lock support	1	1

Input device / components

Input devices (optional)	Keyboard Mouse
--------------------------	-------------------

Drive bays

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	5.25" bay: for slim optical disc drive only as option with ODD bay housing version;
M.2-2280	1 x on mainboard (PCIe 3.0 x4; up to 32Gbit/s) and 1 x optional (PCIe 3.0 x4; up to 32Gbit/s)

Slots		
M.2-2230	on mainboard for WLAN module	
Graphics on board		
Graphics brand name	AMD Radeon™ Graphics	
Graphics features	Support for up to four independent displays DirectX® 12 HDCP support OpenCL® 2.0 OpenGL® 4.6 Vulkan™ DisplayPort interface supports Ver. 1.4 incl. Multi-Stream HDMI™ 2.1 Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) see flexible interface options	
Base unit	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Electrical values		
Power efficiency note	90 Watt AC adapter: power supply efficiency at 115/230V: 89% average efficiency 150 Watt internal PLATINUM power supply (optional): Power supply efficiency in % at 10% / 20% / 50% / 100% load for 230V ; 90/93/94/94 for 115V ; 90/91/93/92	
Rated voltage range	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	AC Adapter: 90 W internal PLATINUM power supply (optional): 150 W	
Base unit	ESPRIMO G7012A	ESPRIMO G7012A ESTAR
Power consumption		
Power consumption note	See white paper Energy Consumption	
Noise emission		
Related Processors for noise	AMD Ryzen 5 PRO 5650U processor and 8GB, no ODD, Windows 11 (tower position)	
Standard noise emission	According to ISO 7779:2010, ECMA-74	
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	
Standard noise operation mode: CPU 50% load	2.9 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2)	
Standard noise operation mode: HDD load	3.0 B / 16 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)	
Standard noise operation mode: Idle mode	2.9 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2)	
Standard noise operation mode: Office applications 2.0		
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	146.5 x 164.5 x 36 mm 5.77 x 6.48 x 1.42 inch	
Dimension notes	With ODD drive bay, the dimensions are: 146.5 x 164.5 x 51 mm (5.77 x 6.48 x 2.01 inch) With internal power supply version, the dimensions are: 146.5 x 176.9 x 71 mm (5.77 x 6.97 x 2.80 inch)	
Operating position	Vertical / horizontal (feet included)	
Weight	Base: Min:0.86kg; 1x mem,1xSSD Max:1.025kg; 2x mem,2xSSD,HDD,Flexi,WLAN ODD vers.: Min:1.2kg/Max:1.29kg int. PSU vers.: Min:1.45kg/Max:1.59kg AC adapt.(0.32kg), power cord(0.175kg) not part of min/max	

Dimensions / Weight / Environmental

Weight (lbs)	Base: Min: 1.89 lbs / Max: 2.246lbs ODD version: Min:2.65 lbs / Max:2.84 lbs Int. PSU version: Min:3.2 lbs / Max:5.51 lbs AC adapter (0.71lbs) and power cord 0.39lbs) are not part of min/max lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO G7012A-1 (AC Adapter) ESPRIMO G7012A-2 (Internal PSU)	ESPRIMO G7012A ESTAR1 (AC Adapter) ESPRIMO G7012A ESTAR2 (Internal PSU)
Model	MPCG	
Germany	GS TÜV NRTL	
Europe	CE	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions) TCO Certified, generation 9
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	

Additional Software

Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which it was acquired.)
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Base unit	ESPRIMO G7012A ESPRIMO G7012A ESTAR

Security

Physical Security	Kensington Lock support Eye for padlock
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby (Legacy Standby no longer supported) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) AuthConductor Client Basic (secure authentication solution)

Security	
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch WoL (Wake on LAN) DASH Out-of-Band management supporting real time inventory, remote on/ off, text console redirection
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/
Miscellaneous	
	Thermal management Extended lifetime (internal power supply version only)
Accessories information	Further helpful options Desktop Accessories: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/ Stands and Mounting kits: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globasp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Packaging information	
Packaging dimension (mm)	395 x 197 x 288 mm
Packaging dimension (inch)	15.55 x 7.76 x 11.34 inch
Packaging notes	If keyboard is included in packaging: 1.) packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) max. quantity/pallet = 42; printed user documentation is bleached in chlorin free process; Bulk packaging for projects (optional)
Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
Product Support - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years

Warranty

Service Weblink

<http://www.fujitsu.com/emeia/products/product-support-services/>

Recommended Accessories

Mounting Kit for Height Adjustable Fujitsu Displays - up to 11th Gen. Display (2022)



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically (2022) designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:
FPCSK834GP

Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:
S26361-F2542-L452

Universal Monitor Stand



Save desk space without compromising productivity with the Universal Monitor Stand that brings together a Desktop ESPRIMO Mini PC (G Series Small and ODD plus Q Series) or Thin Client FUTRO and a VESA compatible Fujitsu Display. For optimum ergonomics the height and tilt angle of the display can be adjusted, whilst hassle-free installation of the devices on the stand makes the life of your IT department easier.

Order Code:
S26361-F2601-L700

Order Code:
S26381-K473-L100

More information

Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO G7012A, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Desktop ESPRIMO G7012A, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/products/computing/pc/desktops/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2024-04-06 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2024 Fujitsu Technology Solutions GmbH