

# JetStream 16-Port Gigabit Easy Smart PoE/PoE+ Switch Datasheet

MODEL: TL-SG1218MPE



## Highlights

- 16 PoE+ 10/100/1000Mbps RJ45 ports, 2 Gigabit SFP slots
- High PoE power budget with up to 30W for each PoE port and 192W for all PoE ports
- Advanced Features for higher performance like 802.1Q VLAN, 802.1p QoS and IGMP Snooping.
- Intelligent power management module like PoE Schedule, PoE Priority, PoE Power Limit.

## Overview

TP-Link's new TL-SG1218MPE PoE switch with all 16 ports supporting the PoE+ standard provides a simple way to expand the wired network while transferring power over the same ethernet cable at the same time. With a total power budget of 192W, up to 30W per port, and the powerful PoE Module, TL-SG1218MPE can power more high-powered devices such as Access Points, IP Cameras, IP Phones. Moreover, TL-SG1218MPE can provide 802.1q VLAN, IGMP Snooping, LAG and other software functions to meet various network configuration needs.

# Power over Ethernet for simplified Network Deployment

- Features 16 802.3af/at compliant PoE+ ports, with a total PoE power budget of 192W
- Flexible deployment for PoE supported devices such as wireless access points, IP Phones and IP Cameras
- Designed to use a single Ethernet cable for both data and power transmission, lowering infrastructure costs.


## Highlight Performance

- Advanced feature - QoS optimizes the performance of quality-sensitive application like Surveillance Video. And IGMP Snooping ensures the multicast stream be forwarded intelligently to the appropriate subscribers by the switch.
- After configure the PoE management module, TL-SG1218MPE can control the Power Limit, Port Priority, and PoE Scheduling of each PoE port.

## Easy to Use

- Plug & play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables
- Auto-negotiation intelligently adjusts for compatibility and optimal performance

## Specifications

Hardware Features & Performance		
Product Picture		
Model		TL-SG1218MPE
General	Interfaces	16 10/100/1000Mbps RJ45 Ports 2 Gigabit SFP Slots
PoE	PoE Standard	802.3 af/at
	PoE Ports	16, up to 30W
	PoE Power Budget	192W

# Specifications

Performance	Switching Capacity	36Gbps
	Packet Forwarding Rate	23.8Mpps
	Max Address Table	8K
	Packet Buffer	4.1Mbit
	Jumbo Frame	9KB
Physical & Environment	Power Supply	100-240V AC, 50/60Hz
	Maximum Power Consumption (220V/50Hz)	18.73W (220V/50Hz. no PD connected) 217.22W (220V/50Hz. with 192W PD connected)
	Maximum Heat Dissipation	63.89 BTU/h (no PD connected) 741.15 BTU/h (with 192W PD connected)
	Dimensions (W×D×H)	17.3 × 7.1 × 1.7 in. (440 × 180 × 44 mm)
	FAN Quantity	2
	Operating Temperature	0°C~50°C (32°F~122°F)
	Storage Temperature	-40°C~70°C (-40°F~158°F)
	Operating Humidity	10% ~ 90%RH, non-condensing
	Storage Humidity	5%~90%RH, non-condensing
Certification	CE, FCC	

## Software Features

L2 Features	<ul style="list-style-type: none"> <li>• Link Aggregation               <ul style="list-style-type: none"> <li>- Static link aggregation</li> <li>- Up to 8 aggregation groups and up to 4 ports per group</li> </ul> </li> <li>• Loopback Detection</li> <li>• Port Statistics</li> <li>• Cable Test</li> <li>• Flow Control</li> <li>• Mirroring               <ul style="list-style-type: none"> <li>- Port Mirroring</li> <li>- Ingress/Egress/Both</li> </ul> </li> </ul>
IGMP Snooping	<ul style="list-style-type: none"> <li>• IGMP v1/v2/v3 Snooping</li> <li>• 128 Max Multicast Entries</li> </ul>
VLAN	<ul style="list-style-type: none"> <li>• 802.1Q VLAN</li> <li>• Port Based VLAN</li> <li>• MTU VLAN</li> </ul>
QoS	<ul style="list-style-type: none"> <li>• Port Based, 802.1p Based, 802.1p CoS/ DSCP priority</li> <li>• Bandwidth Control               <ul style="list-style-type: none"> <li>- Ingress Rate/Egress Rate/Both</li> </ul> </li> <li>• Storm Control               <ul style="list-style-type: none"> <li>- Broadcast/Multicast/Unknown-Unicast Control</li> </ul> </li> </ul>

## Ordering Information

Host Switch	
Product Model	Description
TL-SG1218MPE	JetStream 16-Port Gigabit Easy Smart PoE/PoE+ Switch
SFP Modules	
Product Model	Description
TL-SM311LS	Gigabit SFP module, Single-mode, LC interface, Up to 10km distance
TL-SM311LM	Gigabit SFP module, Multi-mode, LC interface, Up to 550m distance
TL-SM321A	Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1550nm/RX:1310nm, 10km
TL-SM321B	Gigabit WDM Bi-Directional SFP Module, single-mode, LC connector, TX:1310nm/RX:1550nm, 10km
Router	
Product Model	Description
TL-ER6120	SafeStream Gigabit Dual-WAN VPN Router
TL-ER5120	Gigabit Load Balance Broadband Router
Media Converter	
Product Model	Description
MC210CS	Gigabit single-mode SC SFP Transceiver, up to 15Km, chassis mountable
MC200CM	Gigabit multi-mode SC SFP Transceiver, up to 550m, chassis mountable
MC220L	Gigabit SFP slot supporting mini-GBIC modules, chassis mountable
MC1400	14-slot power supply chassis for TP-LINK Media Converter, 19-inch rack-mountable

[www.tp-link.com](http://www.tp-link.com)

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2019 TP-Link Technologies Co., Ltd. All rights reserved.