

OCM818B-RU OCM818W-RU

Universal Projector Flush Mount

Key Features

- Easy to install Great flexibility and adaptability
- Quick projector reconnect/disconnect
- +/- 30° rotation
- 70mm horizontal shift
- +/- 20° pitch and roll
- Adaptable to different projectors
- Load capacity 15kg





OCM818B-RU/OCM818W-RU

SPECIFICATIONS

Universal Projector Flush Mount

Oniversal i rojector i lusti Mount	
OCM818B-RU	OCM818W-RU
1.2kg	
15kg	
+/- 20 degrees	
+/- 20 degrees	
+/- 30 degrees	
70mm	
M3, M4, M5, M6 Screws	
128 mm	
Black	White
5060059046751	5060059046744
	0CM818B-RU 1.2 15 +/- 20 0 +/- 30 0 70i M3, M4, M5 128 Black



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact. For full details of Optoma Project Green please visit our website.



OCM818B-RU



OCM818W-RU



Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.eu