

SD2000P USB-C Single 4K Nano Dock

Part number: K38260EU

EAN code: 5028252594325



Ideal for hot-desking, hoteling, home office and educational environments requiring a single monitor solution, Kensington's SD2000P USB-C Single 4K Nano Dock with 60W Power Delivery is Thunderbolt 3-compatible and provides users with a simple connection to a desktop setup. The SD2000P allows users to choose between HDMI or DP++ video ports to accommodate different monitor setups, connect to their favourite USB accessories using two USB 3.1 Gen1 ports and use the USB-C connection to transfer up to 5Gbps of data while powering their device. Built on USB-C technology and Power Delivery 3.0, users can connect with confidence to a PC, MacBook or Chromebook knowing the SD2000P will let them expand their workspace, use their favourite accessories, and power their device at the same time.

FEATURES AND BENEFITS

- **Cross-platform compatibility** – works with any laptop equipped with USB-C or Thunderbolt 3 and supports Windows, Mac and Chrome operating systems
- **USB-C connectivity** allows users to transfer data, video and audio, while providing up to 60W of Power Delivery¹ to USB-C enabled laptops using the included 1m USB-C cable for a simple plug and play experience
- **Versatile 4K Video** Connections offer output options for HDMI (4K@30Hz) or DP++ (4K@30Hz) to a single external monitor, TV or projector for spectacular true-to-life images²

¹Supported USB-C devices with PD function only

²Host device must support Alt mode over USB-C

- **3 USB ports** –extend productivity capabilities via two USB 3.1 Gen1 ports (up to 5Gbps) with charging up to 5V/1.5A per port³ and one USB-C 3.1 Gen1 port (up to 5Gbps) with power delivery for an external device (5V/3A)
- **Gigabit Ethernet port** provides a reliable 1Gbps wired networking connection
- **Kensington Security Slot** protects your technology investment via easy implementation of a cable lock
- **Zero Footprint Mounting** provides the option to attach the dock to the back of any 75mm or 100mm VESA® compatible external display (mounting plate sold separately – K33959WW)
- **3-Year limited warranty**

³USB charging is supported at 5V/1.5A per port when the laptop is connected, and at 5V/2.4A per port when the laptop is not connected



SD2000P USB-C Single 4K Nano Dock

SYSTEM REQUIREMENT

- **Operating systems supported:**
Windows 7 or later; macOS 10.13 or later;
Chrome OS 44 or above
- **System resource requirement:**
Host device must support DisplayPort Alt mode over USB-C
- **USB-C power delivery:**
 - Supports USB-C PD 3.0
 - 5V/9V/12V/15V/20V up to 3A
 - 60W Maximum

VIDEO CONNECTIONS

- **Video connectors and max resolutions**
 - DP1.2++ (4K@30Hz)
 - HDMI 1.4 (4K@30Hz)

HOST CONNECTIVITY

- **Host docking connector** USB-C™

USB CONNECTIONS

- **Front:**
 - USB-C 3.1 Gen 1, charging up to 5V/3A: One
 - USB-A 3.1 Gen 1, charging up to 5V/1.5A with laptop connected and 5V/2.4A without laptop: Two
- **Right side:**
 - USB-C Upstream Port: One

NETWORK CONNECTIONS

- **Ethernet Port:** RJ45
- **Compatible Ethernet speeds:** 10/100/1000Mbps

PRODUCT DIMENSIONS

- **Unit dimensions:**
 - Width: 98mm (3.86in)
 - Length: 98mm (3.86in)
 - Height: 28mm (1.10in)
- **Unit weight:** 160g (0.35lbs)
- **Enclosure colour and material:** Black PC+ABS
- **Cable length:** 1m

PACKAGING DIMENSIONS

- **Packaging style:** Retail box, brown box
- **Packaging dimensions:**
 - Width: 115mm (4.53in)
 - Length: 220mm (8.67in)
 - Height: 102mm (4.02in)
- **Packaging weight:** 240g
- **Master carton:** 4 pcs
- **Package content:**
 - One SD2000P Dock
 - One USB-C to USB-C Cable, 1m (3ft)
 - One AC Power Adapter with US power cable included (K38260NA); One AC Power Adapter with EU and UK power cables included (K38260EU); One AC Power Adapter with AU/CN power cable included (K38260AU)
 - Quick start guide
 - Warranty information
 - Compliance sheet

POWER AND ENVIRONMENTAL

- **Power adapter rating:**
 - **Input:** 100-240V; 1.5A Max
 - **Output:** 20V DC; 5.5A
 - **AC:** 50/60Hz; 1.5A
- **Operating temperature:** -10 to 45°C (14 to 113°F)
- **Storage temperature:** -10 to 55°C (14 to 131°F)
- **Relative humidity:** 5% to 95% non-condensing

COUNTRY OF ORIGIN, REGULATORY, AND WARRANTY

- **Country of origin:** China
- **Certifications and compliance:** FCC, IC, CE, RCM, REACH, WEEE, RoHS,
- **Warranty:** 3 Year limited warranty

OTHER FEATURES

- **Kensington Security Slot**
- **VESA® mount compatible:** Mounting plate sold separately (K33959WW)

FRONT



Power LED

USB-C Port
(USB3.1 Gen1, charging up to 5V/3A)

USB-A Port
(USB3.1 Gen1, charging up to 5V/1.5A with laptop connected and 5V/2.4A without laptop connected)

BACK



DisplayPort v1.2++

HDMI 1.4

RJ45 Ethernet port

LEFT SIDE



Kensington Lock Slot

RIGHT SIDE



DC 20V

USB-C Port
(Up to 60W of power
at 5Gbps)