

## Be Your Window To The World

The Most Efficient & Conducive Monitor The MSI PRO MP242P eye care monitor. With less blue light and anti-flicker technology, the PRO MP242P helps take care of your eyes and improve your learning efficiency at the same time. The HDMI & VGA interfaces is optimized for the finest image and color quality with a IPS grade panel. It is designed for your programming, coding & on-line learning. It not only makes every line & detail clear for your learning but also protect your eyes while enjoying the smoothest streaming on-line video experience.



Picture and logos

## SELLING POINTS

MSI PRO MP271 - 27 pollici, Risoluzione Full HD, tecnologia di riduzione della luce blu e anti-sfarfallio, MSI Kit Display, supporto per montaggio VESA, altoparlanti incorporati.

- Certificato TÜV per proteggere i tuoi occhi
- Tecnologia di riduzione della luce blu e anti-sfarfallio
- Display anti-riflesso
- Perfetto per lo studio e il lavoro da casa
- Comfort impareggiabile grazie allo stand
- Esclusivo software MSI Display Kit
- Doppia porta d'ingresso video
- Attacco VESA standard
- Speaker interni



1. 1x HDMI™ (1.4b)
2. 1x D-Sub (VGA)
3. 1x Mic-in
4. 1x Headphone-out
5. 1x Kensington Lock

**SPECIFICATION**

Barcode Info	EAN	4719072766016
	UPC	824142230084
	UCC14	10824142230081
Model	Part No	9S6-3PA2CT-034
	MKT Name	PRO MP271
	MKT Spec	PRO MP271
	Color	ID1/Black-Black
Display	Screen Size	27" (69 cm)
	Active Display Area (mm)	597.888(H) x 336.312(V)
	Curvature	Flat
	Panel Type	IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	SDR Brightness (nits)	250
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	30~83 KHz(H) / 56~75 Hz(V)
	Activated Range	48Hz-75Hz
	Refresh Rate	75Hz
	Response Time (GTG)	5ms
	View Angles	178°(H)/178°(V)
	Surface Treatment	Anti-glare
	NTSC (CIE1976 area percentage/overlap)	81.2%/79.1%
	NTSC (CIE1931 area percentage/overlap)	72.23%/71.7%
	sRGB (CIE1976 area percentage/overlap)	93.1%/90.2%
	sRGB (CIE1931 area percentage/overlap)	101.98%/95.9%
	Adobe RGB (CIE1976 area percentage/overlap)	79.8%/79.3%
	Adobe RGB (CIE1931 area percentage/overlap)	75.58%/75%
	DCI-P3 (CIE1976 area percentage/overlap)	74.2%/74.2%
	DCI-P3 (CIE1931 area percentage/overlap)	75.18%/75.2%
	Rec.709 (CIE1976 area percentage/overlap)	93.1%/90.2%
	Rec.709 (CIE1931 area percentage/overlap)	101.98%/95.9%
	Display Colors	16.7M
	Color bit	8 bits (6 bits + FRC)
Note_HDMI™	1920 x 1080 (Up to 60Hz)	
Note_DVI	N/A	
I/O Ports	HDMI™	1
	HDMI™ version	1.4
	D-Sub	1
	Mic-in	1
	Mic-in upstream	N/A
	Headphone-out	1
	Lock type	Kensington Lock
Power	Power Type	Power Cable
	Power Input	100~240V, 50/60Hz
	Energy Efficiency Rating	E
	Power Cord Type	C5

In The Box	DisplayPort Cable	0
	HDMI™ Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	Power Cord	1
	AC Adaptor	0
	Warranty Card	1
	Quick Guide	1
Design	Adjustment (Tilt)	-5° ~ 23°
	VESA Mounting	100x100mm
	Frameless Design	Yes
Outer Carton Dimension (WxDxH)	Outer Carton Dimension (WxDxH) (mm)	699 x 171 x 473
	Outer Carton Dimension (WxDxH) (inch)	27.52 x 6.73 x 18.62
Product Dimension with Stand (WxDxH)	Product Dimension with Stand (WxDxH) (mm)	612.6 x 219.7 x 456.8
	Product Dimension with Stand (WxDxH) (inch)	24.12 x 8.65 x 17.98
Product Dimension without Stand (WxDxH)	Product Dimension without Stand (WxDxH) (mm)	612.6 x 48.8 x 367.1
	Product Dimension without Stand (WxDxH) (inch)	24.12 x 1.92 x 14.45
Stand Dimension (WxDxH)	Stand Dimension (WxDxH) (mm)	219.7 x 219.7 x 180.4
	Stand Dimension (WxDxH) (inch)	8.65 x 8.65 x 7.1
Dimension & Weight	Inside Carton Dimension (WxDxH) (mm)	684 x 156 x 448
	Inside Carton Dimension (WxDxH) (inch)	26.93 x 6.14 x 17.64
	Weight (Net kg)	4.2
	Weight (Gross kg)	6.2
Warranty	Warranty	24M