

# XL fiberTOOLS™ Series

PROFESSIONAL FIBER OPTIC INSTRUMENTS





## XL fiberTOOLS™ Series Instruments Designed for Fiber Optic Cable Testing.

The XL fiberTOOLS™ are designed for the professional to perform installation and maintenance measurements on fiber optic cabling networks. The instrument family consists of individual devices (optical power meters, 850/1300nm LED sources, 1310/1550nm Laser sources, Visual Fault Locator) and complete Insertion Loss Test Sets. The XL fiberTOOLS™ are designed to accurately measure optical power levels and link loss on multimode and singlemode cabling networks. These full feature general purpose fiber optic instruments are easy to operate and economically priced to outfit all technicians performing fiber optic installation and maintenance.

### 560XL Fiber Optic Power Meter



- Easy to use - three buttons control all functions
- Long battery life
- Loss measurements in (dB); power measurements in (dBm)
- 0.01dB measurement resolution
- Snap on connector interface
- adapts to FC, SC and ST connectors. Contact Greenlee for other available adapters.
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

#### Optical Specifications

<b>Calibration Wavelengths</b>	850nm, 1300nm, 1310nm and 1550nm	
<b>Power Range</b>	+3 dBm to -60 dBm	
<b>Accuracy</b>	±0.25dB	
<b>Linearity at:</b>	+3dBm to -3dBm	±0.5dB
	-3dBm to -50dBm	±0.1 dB
	-50dBm to -60dBm	±0.5dB
<b>Resolution</b>	0.01dB	
<b>Power Requirements</b>	Two AA size 1.5V batteries (approx. 100 hours continuous operation)	
<b>Connector Interface</b>	FC, SC or ST	

#### Environmental Specifications

<b>Operating Temperature</b>	-15° C to +55° C
<b>Storage Temperature</b>	-35° C to +70° C
<b>Humidity</b>	0 to 95% non-condensing
<b>Dimensions</b>	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
<b>Weight</b>	241g (8.5 oz.)
<b>CE</b>	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4

*Three Buttons Control  
 ALL Functions!*



# 567XL Silicon Fiber Optic Power Meter



- Easy to use - three buttons control all functions
- Loss measurements in (dB); power measurements in (dBm)
- 0.01dB measurement resolution
- Rugged and splash-proof
- Economically priced
- Snap on connector interface adapts to FC, SC and ST connectors. Contact Greenlee for other available adapters.
- Long battery life
- User selectable auto shut-off

## Optical Specifications

<b>Detector Type</b>	3 x 3.5 mm Silicon	
<b>Calibration Wavelengths</b>	635nm, 780nm, and 850nm	
<b>Power Range</b>	+3 dBm to -60 dBm	
<b>Accuracy</b>	±0.25dB	
<b>Linearity at:</b>	+3dBm to -3dBm	±0.5db
	-3dBm to -50dBm	±0.1db
	-50dBm to -60dBm	±0.5db
<b>Resolution</b>	0.01dB	
<b>Power Requirements</b>	Two AA size 1.5V batteries (approx. 100 hours continuous operation)	
<b>Connector Interface</b>	SOC	

## Environmental Specifications

<b>Operating Temperature</b>	-15° C to +55° C
<b>Storage Temperature</b>	-35° C to +70° C
<b>Humidity</b>	0 to 95% non-condensing
<b>Dimensions</b>	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
<b>Weight</b>	241g (8.5 oz.)
<b>CE</b>	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4

# 568XL High Intensity Optic Power Meter



- Easy to use - three buttons control all functions
- Multi-Wavelength Storage: Store and recall reference power levels for faster, more efficient measurements!
- 0.01dB measurement resolution
- Loss measurements in (dB); power measurements in (dBm)
- Snap on connector interface adapts to FC, SC and ST connectors. Contact Greenlee for other available adapters.
- Long battery life
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

## Optical Specifications

<b>Detector Type</b>	2 mm indium-arsenide (InGaAs)	
<b>Calibration Wavelengths</b>	980nm, 1310nm, and 1550nm	
<b>Power Range</b>	+25 to -30dBm (1310nm and 1550nm); +25 to -27dBm measurement range at 980nm. To avoid thermal damage, limit exposure high power (greater than +23dBm) to less than 30 minutes.; +25 to -27dBm (980nm only)	
<b>Linearity at:</b>	+25dBm to +22dBm	±1.0dB
<b>(1310nm and 1550nm)</b>	+22dBm to +18dBm	±0.5dB
	+18dBm to +10dBm	±0.2dB
	+10dBm to -30dBm	±0.1dB
<b>Absolute Accuracy</b>	±0.25dB at calibration conditions	
<b>Wavelength Dependence</b>	975 to 985nm	0.025dB/nm
	1270 to 1330nm	0.0033dB/nm
	1500 to 1625nm	0.0016dB/nm
<b>Polarization Dependence</b>	<0.1dB	
<b>Resolution</b>	±0.01dB	
<b>Power Requirements</b>	Two AA size 1.5V batteries (approx. 100 hours continuous operation)	
<b>Connector Interface</b>	SOC	

## Environmental Specifications

<b>Operating Temperature</b>	-15° C to +55° C
<b>Storage Temperature</b>	-35° C to +70° C
<b>Humidity</b>	0 to 95% non-condensing
<b>Dimensions</b>	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
<b>Weight</b>	241g (8.5 oz.)
<b>CE</b>	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4



- 850/1300nm wavelengths
- Stable calibrated output
- Easy to use
- Continuous wave and modulated output
- Fixed connector interface FC, SC or ST
- Long battery life - approx. 80 hours
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced



- 1310/1550nm wavelengths
- Stable calibrated output
- Easy to use
- Continuous wave and modulated output
- Fixed connector interface FC, SC or ST
- Long battery life - approx. 80 hours
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

## 570XL 850/1300nm LED Source

### Optical Specifications

Center Wavelength	850nm	1300nm
Range (Typical)	820nm to 870nm	1270nm to 1345nm
Max. Spectral Width (FWHM)	60nm	150nm
Stability (1 hour)	±0.05dB	±0.05dB
Typical Power Output		
100/140um	-20dBm	-20dBm
62.5/125um	-20dBm	-20dBm
50/125um	-21dBm	-21dBm
Modular Frequency	270 kHz, 1 kHz and 2 kHz	270 kHz, 1 kHz and 2 kHz
Power Requirements	Two AA size 1.5V batteries (approx. 40 hours continuous operation)	Two AA size 1.5V batteries (approx. 40 hours continuous operation)
Connector Interface	FC, SC or ST	FC, SC or ST
Operating Temperature	-15° C to +55° C	
Storage Temperature	-35° C to +70° C	
Humidity	0 to 95% non-condensing	
Dimensions	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)	
Weight	241g (8.5 oz.)	
CE	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4	

## 580XL 1310/1550nm Laser Source

### Optical Specifications

Center Wavelength	1310nm	1550nm
Range (Typical)	1280nm to 1340nm	1520nm to 1580nm
Max. Spectral Width (FWHM)	<5nm	<5nm
Stability (1 hour)	±0.05dB	±0.05dB
Typical Power (9/125)		
Minimum	-8dBm	-8dBm
Typical	-7dBm	-7dBm
Modular Frequency	270 kHz, 1 kHz and 2 kHz	270 kHz, 1 kHz and 2 kHz
Power Requirements	Two AA size 1.5V batteries (approx. 80 hours continuous operation)	Two AA size 1.5V batteries (approx. 80 hours continuous operation)
Connector Interface	FC, SC or ST	FC, SC or ST

### Environmental Specifications

Operating Temperature	-15° C to +55° C
Storage Temperature	-35° C to +70° C
Humidity	0 to 95% non-condensing
Dimensions	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
Weight	241g (8.5 oz.)
CE	EN61010; EN50081-1:1992; EN55011 Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4
CDRH Laser Class	Class 1

# 573XL

## 650nm LED Source for Large Core Plastic and Glass Fiber



- 650nm wavelength
- Stable calibrated output
- Easy to use
- Continuous wave and modulated output
- ST connector interface
- Long battery life - approx. 24 hours
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

### Optical Specifications

Center Wavelength	650nm
Range (Typical)	630nm to 670nm
Max. Spectral Width (FWHM)	<40nm
Stability (1 hour)	±0.05dB
Power Output into MM 200/300 SI Fiber	-15dBm ±0.5dB
Modular Frequencies	270 kHz, 1 kHz and 2 kHz ±0.5dB
Power Requirements	Two AA size 1.5V batteries (approx. 24 hours continuous operation)
Connector Interface	ST

### Environmental Specifications

Operating Temperature	-15° C to +55° C
Storage Temperature	-35° C to +70° C
Humidity	0 to 95% non-condensing
Dimensions	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
Weight	241g (8.5 oz.)
CE	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4

# 577XL M90

## 850nm LED Source with M90 Launch Condition using 62.5/125 Fiber



- 850nm wavelength
- Stable calibrated output
- Easy to use
- Continuous wave and modulated output
- Universal connector interface
- Long battery life - approx. 24 hours
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

### Optical Specifications

Center Wavelength	850nm
Range (Typical)	820nm to 880nm
Max. Spectral Width (FWHM)	<60nm
Stability (1 hour)	±0.05dB
Launch Profile	M90
Power Output into MM 62.5/125 GI fiber	-20dBm
Modular Frequencies	270 kHz, 1 kHz and 2 kHz ±5%
Power Requirements	Two AA size 1.5V batteries (approx. 24 hours continuous operation)
Connector Interface	Universal connector interface, physical contact (UCI-PC)

### Environmental Specifications

Operating Temperature	-15° C to +55° C
Storage Temperature	-35° C to +70° C
Humidity	0 to 95% non-condensing
Dimensions	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
Weight	241g (8.5 oz.)
CE	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4

# 577XL AS100

## 850nm LED Source with AS-100 Launch Condition using 100/140 Fiber



- 850nm wavelength
- Stable calibrated output
- Easy to use
- Continuous wave and modulated output
- Universal connector interface
- Long battery life - approx. 24 hours
- User selectable auto shut-off
- Rugged and splash-proof
- Economically priced

### Optical Specifications

Center Wavelength	850nm
Range (Typical)	820nm to 880nm
Max. Spectral Width (FWHM)	<60nm
Stability (1 hour)	±0.05dB
Launch Profile	AS100
Power Output into MM 100/140 GI fiber	-20dBm
Modular Frequencies	270 kHz, 1 kHz and 2 kHz ±5%
Power Requirements	Two AA size 1.5V batteries (approx. 24 hours continuous operation)
Connector Interface	Universal connector interface, physical contact (UCI-PC)

### Environmental Specifications

Operating Temperature	-15° C to +55° C
Storage Temperature	-35° C to +70° C
Humidity	0 to 95% non-condensing
Dimensions	7.2 x 14.2 x 3.5 cm (2.8 x 5.6 x 1.4 in.)
Weight	241g (8.5 oz.)
CE	EN61010; EN50081-1:1992; EN55011, Group 1, Class A EN50082-1: 1992 IEC 801-2, -3, -4

## 5670XL Multimode Fiber Optic Test Set



- Insertion loss test set for multimode fiber
- 850/1300nm loss measurements
- Connector for FC, SC or ST
- Rugged package design
- Easy-to-use portable package
- Economically priced

### 5670-FC Includes

560XL	Optical Power Meter
570XL-FC	850/1300nm LED Source w/FC Connector
T1020	FC/PC SOC Adapter
914B	Carrying Case

### 5670-SC Includes

560XL	Optical Power Meter
570XL-SC	850/1300nm LED Source w/SC Connector
1062	SC/PC SOC Adapter
914B	Carrying Case

### 5670-ST Includes

560XL	Optical Power Meter
570XL-ST	850/1300nm LED Source w/ST Connector
T1030	ST/PC SOC Adapter
914B	Carrying Case

## 5680XL Singlemode Fiber Optic Test Set



- Insertion loss test set for singlemode fiber
- 1310/1550nm loss measurements
- Connector for FC, SC or ST
- Rugged package design
- Easy-to-use portable package
- Economically priced

### 5680-FC Includes

560XL	Optical Power Meter
580XL-FC	1310/1550nm Laser Source w/FC Connector
T1020	FC/PC SOC Adapter
914B	Carrying Case

### 5680-SC Includes

560XL	Optical Power Meter
580XL-SC	1310/1550nm Laser Source w/SC Connector
1062	SC/PC SOC Adapter
914B	Carrying Case

### 5680-ST Includes

560XL	Optical Power Meter
580XL-ST	1310/1550nm Laser Source w/ST Connector
T1030	ST/PC SOC Adapter
914B	Carrying Case

## 5890XL Multimode and Singlemode Fiber Optic Test Set



- Insertion loss test set for multimode and singlemode fiber
- 850/1300nm Loss measurements
- 1310/1550nm Loss measurements
- Connector for FC, SC or ST
- Rugged package design
- Easy-to-use portable package
- Economically priced

### 5890-FC Includes

560XL	Optical Power Meter
570XL-FC	850/1300nm LED Source w/FC Connector
580XL-FC	1310/1550nm Laser Source w/FC Connector
T1020	FC/PC SOC Adapter
915B	Carrying Case

### 5890-SC Includes

560XL	Optical Power Meter
570XL-SC	850/1300nm LED Source w/SC Connector
580XL-SC	1310/1550nm Laser Source w/SC Connector
1062	SC/PC SOC Adapter
915B	Carrying Case

### 5890-ST Includes

560XL	Optical Power Meter
570XL-ST	850/1300nm LED Source w/ST Connector
580XL-ST	1310/1550nm Laser Source w/ST Connector
T1030	ST/PC SOC Adapter
915B	Carrying Case

# 180XL Visual Fault Locator



- Continuous wave output mode for steady fault location
- Find breaks to 7km
- Blinking output mode increases viewing contrast
- Easy-to-use quick interface fits all 2.5mm connector interfaces (FC, SC, ST)
- 1.0mW output power
- Class 2 Operation
- Ergonomic rotary switch permits easy one-handed operation
- Rugged, compact and splash-proof aluminum design
- Two AA batteries provide 80 hours continuous operation
- 1.25mm adapter available for LC and MU connectors (UPC 03579)
- Nylon storage case included

## Optical Specifications

<b>Wavelength</b>	650nm +/-10nm
<b>Emitter Type</b>	Fabry Perot
<b>Output Power</b>	0dBm
<b>Laser Classification</b>	Class 2
<b>Range</b>	7km
<b>Modes of Operation</b>	CW and 2Hz Modulation
<b>Method of Display Operation</b>	Red/Green LED
<b>Fiber Type</b>	Singlemode, Multimode
<b>Connector Interface</b>	2.5mm Universal, Optional 1.25mm adapter

## Environmental Specifications

<b>Battery</b>	AA (2 included)
<b>Battery Life</b>	80 Hours with 3.9Wh Batteries
<b>Weight</b>	0.26lbs, (120g) (not including batteries)
<b>Dimensions</b>	7.08" x 0.91" Dia. (180 x 23mm Dia.)
<b>Operating Temperature</b>	-10°C to +45°C
<b>Storage Temperature</b>	-40°C to +70°C
<b>Certifications</b>	CE, CDRH

## Snap On Connector (SOC) for Fiber Optic Power Meter

Snap On Connectors (SOC) are used on the 560XL Fiber Optic Power Meter. The Snap On Connectors configure the optical power meter for various optical connectors. Contact Greenlee for other available adapters.



## Universal Connector Interface (UCI) for 577XL family

User will need to purchase a Universal Connector Interface (UCI) adapter for use of the instrument. Please specify the desired connector adapter type when ordering. Contact Greenlee for other available adapters.




## Connector Cleaning Tools



### 948 Connector Reel Cleaner

The Reel Cleaner is an all-in-one connector cleaning tool. A complete self-contained unit requiring no additional components to clean fiber optic connectors. Recommended for cleaning FC, SC and ST connectors. To clean a connector, the user opens the shutter by gripping the lever and then sliding the connector end face along the exposed cleaning surface while gripping the lever.



### 946 Adapter Cleaning Wands

Adapter wands are a convenient, economical and disposable way to clean and maintain fiber optic interfaces and bulkhead adapters. Incorporating the same lint-free material as the all-in-one Connector Reel Cleaner, cleaning wands are effective in removing contaminants from hard-to-reach connector end face ferrule alignment sleeves. Ten cleaning wands come in each package.

FOR PRODUCT VIDEOS,  
DEMONSTRATIONS AND MORE VISIT:  
<http://bit.ly/GreenleeCommsYouTube>



## ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION
180XL	03578	VISUAL FAULT LOCATOR
1.25MM-ADAPTER	03579	1.25MM ADAPTER FOR LC AND MU CONNECTORS
560XL	84485	FIBER OPTIC POWER METER
567XL	00025	FIBER OPTIC POWER METER SI, (SOC)
568XL	00026	FIBER OPTIC POWER METER, SOC-HP INGAAS
570XL-FC	84486	850/1300NM LED SOURCE W/FC INTERFACE
570XL-SC	84487	850/1300NM LED SOURCE W/SC INTERFACE
570XL-ST	84488	850/1300NM LED SOURCE W/ST INTERFACE
573XL	00023	650NM LED SOURCE W/ST INTERFACE
577XL AS100	00029	850NM LED SOURCE WITH AS100 LAUNCH
577XL M90	00027	850NM LED SOURCE WITH M90 LAUNCH
580XL-FC	84489	1310/1550NM LASER SOURCE W/FC INTERFACE
580XL-SC	84490	1310/1550NM LASER SOURCE W/SC INTERFACE
580XL-ST	84491	1310/1550NM LASER SOURCE W/ST INTERFACE
5670-FC	84492	MULTIMODE FIBER OPTIC TEST SET W/FC INTERFACE
5670-SC	84493	MULTIMODE FIBER OPTIC TEST SET W/SC INTERFACE
5670-ST	84494	MULTIMODE FIBER OPTIC TEST SET W/ST INTERFACE
5680-FC	84495	SINGLEMODE FIBER OPTIC TEST SET W/FC INTERFACE

CAT NO.	UPC NO.	DESCRIPTION
5680-SC	84496	SINGLEMODE FIBER OPTIC TEST SET W/SC INTERFACE
5680-ST	84497	SINGLEMODE FIBER OPTIC TEST SET W/ST INTERFACE
5890-FC	84498	MULTIMODE AND SINGLEMODE FIBER OPTIC TEST SET W/FC INTERFACE
5890-SC	84499	MULTIMODE AND SINGLEMODE FIBER OPTIC TEST SET W/SC INTERFACE
5890-ST	84500	MULTIMODE AND SINGLEMODE FIBER OPTIC TEST SET W/ST INTERFACE
A APC-108	60572	FC/PC UCI ADAPTER
A AST-108	60573	ST/PC UCI ADAPTER
A ASC-108	60574	SC/PC UCI ADAPTER
A 1062	60575	SC/PC SOC ADAPTER
A T1020	60576	FC/PC SOC ADAPTER
A T1030	60577	ST/PC SOC ADAPTER
A 948	60692	CONNECTOR REEL CLEANER CLEANING SYSTEM
A 946	60571	2.5 MM CLEANING WANDS

A = ACCESSORY

### MA5636 REV 12/18

1390 Aspen Way Vista, CA • 92081  
Latin America Phone : 1.760.510.0558 | EMEA Phone: +44 (0) 1633 627710  
©2018 Greenlee Tools, Inc. • An ISO 9001 Company • Printed in USA

[greenleecomms.com](http://greenleecomms.com)



tel 800.642.2155

