

CS-C1C-D0-1D1WFR

720P Indoor Internet Wi-Fi Camera



Introduction

EZVIZ products have been designed for your entertainment, communication and security. When you install the EZVIZ APP on your smartphone or tablet, EZVIZ devices will be connected to the cloud via their QR code and will immediately be online. With EZVIZ you can talk to your loved ones, watch your child's progress when you are away, keep an eye on your home, interact with your four-legged friends and prevent household accidents.

Main Features



HD 720P



110° Wide-Angle Lens



True Day/Night, auto switch, Infra-Red support up to 10meters(32.8ft)



Two-way audio



Support Micro SD card (Max. 256G)



Support 2.4GHz Wi-Fi (IEEE802.11b, 802.11g,802.11n)

Dimension



Specifications

| | |
|-----------------------------|---|
| Model | CS-C1C-D0-1D1WFR |
| Camera | |
| Image sensor | 1/4" Progressive Scan CMOS |
| Shutter Speed | Self-adaptive shutter |
| Lens | 2.8mm, view angle:92° (Horizontal), 110°(Diagonal) |
| Lens Mount | M12 |
| Day & Night | IR-cut filter with auto-switching |
| DNR | 3D DNR |
| WDR | Digital WDR |
| Compression | |
| Video Compression | H.264 |
| H.264 Type | Main Profile |
| Video Bit Rate | HD; Standard; Basic. Adaptive bit rate. |
| Audio Bit Rate | Self-Adaptive |
| Max. Bitrate | 2M |
| Image | |
| Max. Resolution | 1280 x 720 |
| Frame Rate | Max : 20fps; Self-Adaptive during network transmission |
| Network | |
| Smart Alarm | Motion detection |
| Wi-Fi Pairing | AP paring |
| Protocol | EZVIZ cloud proprietary protocol |
| Interface Protocol | EZVIZ cloud proprietary protocol |
| General Features | Anti-Flicker, Dual-Stream, Heart Beat, Mirror Image, Password Protection, Watermark |
| Interface | |
| Storage | Micro SD card slot (Max. 256G) |
| Power | Micro USB |
| Wi-Fi | |
| Standard | IEEE802.11b, 802.11g, 802.11n Draft |
| Frequency Range | 2.4 GHz ~ 2.4835 GHz |
| Channel Bandwidth | Support 20MHz |
| Security | 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK |
| Transmission Rate | 11b: 11Mbps,11g :54Mbps,11n :72Mbps |
| General | |
| Operating Conditions | 14°F to 113 °F (-10°C ~ 45°C), Humidity 95% or less (non-condensing) |
| Power Supply | DC 5V±10% |
| Power Consumption | MAX. 4.0 W |
| IR Range | MAX. 10meters(32.8ft) |
| Dimensions | 64mm x 64mm x 103mm(2.52 " x 2.52 " x 4.06 ") |
| Packaging Dimensions | 123mm x 79mm x 125.5mm (4.84 " x 3.11 " x 4.94 ") |
| Suttle Weight | 96g (0.21lbs) |