HENRY

HNSH20

TECHNICAL DETAILS ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1" Flow Restriction Options: 2.5, 2.0, 1.75, 1.5 Depth / Width: 23 3/4" Height: 21 1/16" Inlet Connection Size: 1/2" Inlet Connection Type: Copper Compression Installation Type: Wall Mounted Integrated Diverter: N Integrated Spray: N Length: 7 7/8" Pivot: N Primary Material: Brass Safety Warnings: DO NOT USE PEX PIPING ON INLET CONNECTION. COPPER PIPE IS REQUIRED. Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY GOOSENECK WALL MOUNTED 8" SHOWER ROSE, ARM AND FLANGE| HNSH20

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

Henry Gooseneck Wall Mounted 8" Shower Rose, Arm and Flange

CODES & STANDARDS

Code # HNSH20X: Complies with ASME A112.18.1/CSA B125.1, ANSI A117.1 ADA & ASTM E 1621-05. Certified with IAPMO, Cupc, CEC & State of MA

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Brass material is used for components.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.



PRODUCT (NOTES)

DO NOT USE PEX PIPING ON INLET CONNECTION. COPPER PIPE IS REQUIRED.

HENRY

HNSH20

Henry Gooseneck Wall Mounted 8" Shower Rose, Arm and Flange

