

HEATING & AIR CONDITIONING

SINGLE-PACKAGED ROOFTOPS

* THE INDOOR OUTFITTERS

Apex[™] Series Single-Packaged R


Comfort you can count on.

Creating a comfortable environment takes rugged technology that can deliver the performance you demand day after day, season after season. You can count on Coleman[®] for energy-efficient operation that meets your needs quietly and reliably.

Durable, efficient MicroChannel coil

The all-aluminum MicroChannel condenser coil provides outstanding efficiency and reliability thanks

to an advanced coil design. (MicroChannel coils only apply to air conditioning models.)



Reliable operation

The compressor is internally protected against high pressure and temperature to ensure dependable performance in tough conditions.

Greater durability

Durable finish using powder-painted, galvanized steel meets 1,000-hour salt-spray test demands as assurance of a long-lasting, corrosion-resistant cabinet.

Limited maintenance

For years of trouble-free service, the condenser and evaporator fan motor bearings are permanently lubricated to ensure reliable performance.

Solid foundation

Installation goes smooth and easy thanks to full-perimeter base rails that are permanently attached to the unit to save time and materials.

Outstanding warranty

You can depend on Coleman[®] for year-round comfort and long-lasting durability. Built for years of trouble-free service and reliable operation, Apex[™] systems are backed by warranties you can count on.

ooftops

The Coleman[®] Apex[™] Series combines high-efficiency and advanced economizer controls with unprecedented installation flexibility and low installed costs, providing a great solution for commercial-building applications.

- Innovative Simplicity[®] control board for easy setup and programming
- Common, compact design fits in a single footprint
- MagnaDRY[™] models provide cost-effective dehumidification



- Durable MicroChannel condenser coil ensures long-term efficiency (MicroChannel coils only apply to air conditioning models)
- Permanently lubricated condenser and evaporator fan motor bearings
- Complete line of fieldinstalled accessories

The big difference: Simplicity® controls

It's the built-in brain that requires no additional controls. The Simplicity[®] control system is part of each Apex[™] model and, for the building manager, it monitors the entire HVAC system continuously. All alarm and diagnostic data is transmitted directly to an onsite PC. Or, you can monitor the system over the Internet.

- Single-button programming
- Five-minute anti-short cycle delay
- Alarm recall, even after power failures
- Three-minute minimum compressor run time
- Built-in low-voltage protection
- Independent monitoring of all safety switches



| Apex [™] MagnaDRY [™] Gas/Electric Rooftop Packaged Units (ZK) | | | | | | | |
|---|----------------|------|------|----------------------|---------|------|--|
| MODEL | COOLING MBH | SEER | EER | HEATING MBH INPUT | %SSE | LBS. | |
| ZK-03N05 | 35.0 | 13.0 | 11.0 | 50 | - | 575 | |
| ZK-03N11 | 35.0 | 13.0 | 11.0 | 100 | - | 575 | |
| ZK-03D07 | 35.0 | 13.0 | 11.0 | 75 | 81.1 | 575 | |
| ZK-03D13 | 35.0 | 13.0 | 11.0 | 115 | 80.2 | 575 | |
| ZK-04N07 | 46.5 | 13.0 | 11.0 | 75 | - | 585 | |
| ZK-04N13 | 46.5 | 13.0 | 11.0 | 125 | - | 585 | |
| ZK-04D07 | 46.5 | 13.0 | 11.0 | 75 | 81.1 | 585 | |
| ZK-04D13 | 46.5 | 13.0 | 11.0 | 125 | 80.5 | 585 | |
| ZK-05N11 | 60.0 | 13.0 | 11.0 | 100 | - | 590 | |
| ZK-05N13 | 60.0 | 13.0 | 11.0 | 125 | - | 590 | |
| ZK-05D07 | 60.0 | 13.0 | 11.0 | 75 | 81.1 | 590 | |
| ZK-05D13 | 60.0 | 13.0 | 11.0 | 125 | 80.5 | 590 | |
| Apex [™] MagnaDRY [™] Electric/Electric Rooftop Packaged Units (ZK) | | | | | | | |
| MODEL | COOLING MBH | SEER | EER | ELECTRIC HE | AT (kW) | LBS. | |
| ZK-03E | 35.0 | 13.0 | 11.0 | 5, 7, 10, 15 | i, 20 | 575 | |
| ZK-04E | 46.5 | 13.0 | 11.0 | 5, 7, 10, 15 | i, 20 | 585 | |

| ZK-05E | 60.0 13 | 3.0 11.0 | 5, 7, 10, 15, 20, 30 | 590 | | | |
|--|------------|----------|----------------------|------|--|--|--|
| Apex [™] MagnaDRY [™] Cooling Only Rooftop Packaged Units (ZK) | | | | | | | |
| MODEL | COOLING ME | BH SEER | EER | LBS. | | | |
| ZK-03C00 | 35.0 | 13.0 | 11.0 | 575 | | | |
| ZK-04C00 | 46.5 | 13.0 | 11.0 | 585 | | | |

13.0

11.0

590

Apex[™] Gas/Electric Rooftop Packaged Units (ZS)

60.0

ZK-05C00

| MODEL | COOLING MBH | SEER | EER | HEATING MBH INPUT | % SSE | LBS. |
|-----------|----------------|------|------|----------------------|-------|------|
| ZS-03N05 | 36.0 | 13.0 | 11.0 | 50 | _ | 470 |
| ZS-03N11 | 36.0 | 13.0 | 11.0 | 100 | _ | 470 |
| ZS-03D07 | 36.0 | 13.0 | 11.0 | 75 | 81.1 | 470 |
| ZS -03D13 | 36.0 | 13.0 | 11.0 | 115 | 80.2 | 470 |
| ZS-04N07 | 47.5 | 13.0 | 11.0 | 75 | - | 539 |
| ZS-04N13 | 47.5 | 13.0 | 11.0 | 125 | — | 539 |
| ZS-04D07 | 47.5 | 13.0 | 11.0 | 75 | 81.1 | 539 |
| ZS-04D13 | 47.5 | 13.0 | 11.0 | 125 | 80.5 | 539 |
| ZS-05N11 | 57.0 | 13.0 | 10.8 | 100 | — | 567 |
| ZS-05N13 | 57.0 | 13.0 | 10.8 | 125 | — | 567 |
| ZS-05D07 | 57.0 | 13.0 | 10.8 | 75 | 81.1 | 567 |
| ZS-05D13 | 57.0 | 13.0 | 10.8 | 125 | 80.5 | 567 |
| ZS-A6N11 | 68.0 | - | 11.0 | 100 | - | 640 |
| ZS-A6N13 | 68.0 | _ | 11.0 | 125 | - | 640 |
| ZS-A6D07 | 68.0 | - | 11.0 | 75 | 81.1 | 640 |
| ZS-A6D13 | 68.0 | - | 11.0 | 125 | 80.5 | 640 |
| | | | | | | |

Trusted products. Reliable service.

By partnering with one of the most respected and trusted brands in the world, you can rest assured that our knowledgeable professionals will help you choose the perfect comfort system that's right for your application.

| Apex [™] Electric/Electric Rooftop Packaged Units (ZS) | | | | | | | |
|---|-------------|--------------|------|------|------------------|------|--|
| MODEL | | 4BH OLING | | SEER | EER | LBS. | |
| ZS-03E | ć | 36.0 | | 13.0 | 11.0 | 470 | |
| ZS-04E | 4 | 47.5 | | 13.0 | 11.0 | 539 | |
| ZS-05E | ! | 57.0 | | 13.0 | 11.0 | 567 | |
| ZS-A6E | e | 68.0 | | _ | 11.2 | 640 | |
| Apex [™] Cooling Only Rooftop Packaged Units (ZS) | | | | | | | |
| MODEL | COOLING MBH | SEER | EER | El | ECTRIC HEAT (kW) | LBS. | |
| ZS-03C00 | 36.0 | 13.0 | 11 0 | | 5 7 10 15 20 | 470 | |

| ZS-03C00 | 36.0 | 13.0 | 11.0 | 5, 7, 10, 15, 20 | 470 | | |
|---|------|------|------|----------------------|-----|--|--|
| ZS-04C00 | 47.5 | 13.0 | 11.0 | 5, 7, 10, 15, 20 | 539 | | |
| ZS-05C00 | 57.0 | 13.0 | 10.8 | 5, 7, 10, 15, 20, 30 | 567 | | |
| ZS-A6C00 | 68.0 | - | 11.2 | 5, 7, 10, 15, 20, 30 | 640 | | |
| Apex [™] Packaged Heat Pump Units (XA) | | | | | | | |

| MODEL | COOLING MBH | SEER | EER | HSPF | LBS. |
|----------|-------------|------|------|------|------|
| XA-03C00 | 35.0 | 13.0 | 11.0 | 7.7 | 575 |
| XA-03E | 35.0 | 13.0 | 11.0 | 7.7 | 575 |
| XA-04C00 | 46.5 | 13.0 | 10.8 | 7.7 | 585 |
| XA-04E | 46.5 | 13.0 | 10.8 | 7.7 | 585 |
| XA-05C00 | 57.5 | 13.0 | 10.6 | 7.7 | 590 |
| XA-05E | 57.5 | 13.0 | 10.6 | 7.7 | 590 |

All models meet or exceed ASHRAE 90.1-2007 Standards and select models are ENERGY STAR® qualified.

Warrantied for years of comfort

Every Coleman® system is backed by some of the best limited warranties available: Warranties for gas/electric models ZK, ZF: 10-year heat exchanger warranty, 5-year compressor warranty, 1-year parts warranty;

Warranties for electric/electric models ZK, ZF: 5-year electric heat warranty, 5-year compressor warranty, 1-year parts warranty

Warranties for model XA: 5-Year compressor warranty, 1-year parts warranty

Our technicians ensure that the installation and maintenance of your system provides maximum quality, comfort and efficiency for years to come.

When you want it done right the first time, contact your Coleman® Dealer.



