

Philips Signage Solutions Q-Line Display

**48"** Direct LED Backlight Full HD



BDL4830QL

# Intensify your signage experience

# with priceless smart performance

Deliver startlingly clear images in a more eco-friendly way. High on performance and reliability, yet low on power consumption, it is ideal for projects where no compromise is accepted.

### Maximizing the impact of your message

- Full HD LED for brilliant images with incredible contrast
- Manage and control your network remotely via SmartControl

### Innovative solutions for any signage application

- Free and easy-to-use content management with SmartCMS
- Connect and control your content via the cloud with HTML5
- Save and play content with internal memory
- Schedule what you want, when you want with SmartPlayer

# Care about you, your business and your audience

- Show clinical images consistently with D-image
- SmartPower for energy saving



# BDL4830QL/00

# Highlights

#### Full HD LED technology

Picture Quality matters. Regular displays deliver quality, but you expect more. Imagine crisp detail paired with high brightness, incredible contrast and realistic colors for a true to life picture.

### SmartControl



SmartControl lets you remotely control and manage your network of displays via RJ45 and RS232C. Easily fine-tune all display settings including resolution, brightness, contrast and cloning of your settings over your complete network.

#### **SmartCMS**



Free and easy-to-use content management system that works exclusively with Philips Sigage Solutions displays to manage your digital signage content. With SmartCMS you can create and schedule your own content over 24 hours every day. Simply create your network, design your content, schedule your playlist and you are ready to play!

#### Integrated HTML5 browser



Connect and control your content via the cloud with the integrated HTML5 browser. Design your signage content online and connect it with a display or with your complete network. Simply plug in a RJ45 internet cable for network connection, connect the display with the dedicated url-address and you are ready to play your cloud based content.

#### **Internal Memory**

Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content streaming by playing a cached version of the content, ensuring that your media is up even when there is no network connection.

# SmartPlayer

Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display.Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.

#### **Clinical D-image**



D-image helps you to review and diagnose clinical images with consistent and accurate display performance. To achieve reliable clinical interpretations our professional displays are factory calibrated to give optimized greyscale standard display performance. D-image helps you to excel in every aspect of patient care.

#### SmartPower



The backlight intensity can be controlled and pre-set by the system to reduce the power consumption by up to 50%, which saves substantially on energy costs.

#### **Smart**Collection

#### **SmartCollection**

SmartCollection offers you customizable solutions to meet your specific requirements.

Both integrators and solution providers are offered the latest innovations, while the audience can enjoy impactful solutions. When developing smart innovations we focus on Caring, Innovative and Impactful solutions.



📽 Smart**Control** 





Smart**Player** 



# Specifications

#### **Picture/Display**

- Diagonal screen size: 47.6 inch / 120.9 cm
- Panel resolution: 1920x1080p
- Optimum resolution: 1920 x 1080 @ 60 Hz
- Brightness: 350 cd/m<sup>2</sup>
- Contrast ratio (typical): 4000:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing angle (H / V): 178 / 178 degree
- Pixel pitch: 0.549 x 0.549 mm
- Display colors: 16.7 Million
   DICOM: Clinical D image
- DICOM: Clinical D-image

# Supported Display Resolution

## Computer formats

	Compater forme	
	Resolution	Refresh rate
	640 x 480	60, 67, 72, 75Hz
	800 × 600	56, 60, 72, 75Hz
	1024 x 768	60Hz
	1280 x 768	60Hz
	1280 x 800	60Hz
	1360 x 768	60Hz
	1366 x 768	60Hz
	1440 x 900	60Hz
	1600 x 1200	60Hz
	1920 x 1080	60Hz
	1920 x 1200	60Hz
•	Video formats	
	Resolution	Refresh rate
	480i	60Hz
	480p	60Hz
	576p	50Hz
	576i	50Hz
	720p	50, 60Hz
	1080i	50, 60Hz
	1080p	50, 60Hz
	•	

#### Connectivity

- Video input: DVI-D, HDMI, Component (RCA), Composite (RCA), VGA (Analog D-Sub)
- Audio input: 3.5 mm jack, Audio Left/Right (RCA)
- Audio output: Audio Left/Right (RCA), 3.5mm jack
   External control: RJ45, RS232C (in/out) 2.5 mm
- jack, IR (in/out) 3.5 mm jack
- Other connections: USB

#### Convenience

- Memory: Internal memory access, 8GB eMMC
- Screen saving functions: Pixel Shift

- Energy saving functions: Smart Power
- Tiled Matrix: Up to 15 x 15
- Start-up: Wake up on LAN, Switch on delay, Switch on status
- Start-up window: enable / disable Philips logo
- Keyboard control: Lockable, Hidden
  Network controllable: RS232, RJ45, One Wire (HDMI-CEC)
- Signal Loop Through: RS232, IR Loopthrough

#### Dimensions

- Bezel width: 11.9 (TLR) / 14.7 (B) mm
- Set dimensions ( $W \times H \times D$ ):
- 1081.8 x 623.4 x 59.9 mm
- Set dimensions in inch (W x H x D):
- 42.59 x 24.54 x 2.36 inch • VESA Mount: 400 x 400 mm, 200x200 mm, M6
- Product weight: 11.52 kg
- Product weight. 11.52 kg
   Product weight (lb): 25.4

#### **Operating conditions**

- Temperature range (operation): 5 ~ 40 °C
- Temperature range (storage): -20 ~ 60 °C
- Relative humidity: 20 ~ 80 %
- MTBF: 50,000 hour(s)

#### Power

- Consumption (On mode): 115 W (EnergyStar 6.0 test method)
- Mains power: 100 ~ 240 VAC
- Standby power consumption: <0.5W</li>

#### Sound


• Built-in speakers: 2 x 10W RMS

#### **Multimedia Applications**

- USB Playback Video: 3G2, 3GP, ASF, ASX, AVI, DAT, DivX, F4V, FLV, M2TS, M4V, MK3D, MKV, MOV, MP4, MPE, MPEG, MPG, MTS, QT, TRP, TS, TTS, VOB, WEBM, WMV, Xvid
- USB Playback Picture: BMP, GIF, JPEG, JPG
- USB Playback Audio: AAC, AC3, AIF, AIFF, AMR, EC3, M4A, MP3, OGA, OGG, WAV, WMA

#### Accessories

 Included accessories: AC Power Cord, RS232 cable, VGA cable, Remote Control, Batteries for remote control, User manual on CD-ROM, Quick start guide





Issue date 2015-08-20

© 2015 Koninklijke Philips N.V. All Rights reserved.

www.philips.com

Version: 1.2.1

All Rights reserved. Specifications are subject to change without notice.

Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 22321 EAN: 87 12581 73031 4 BDL4830QL/00

#### Miscellaneous

• Warranty: Global: 3 years

BSMI, CB, GOST, CECP, EPA

- On-Screen Display Languages: English, French, German, Italian, Polish, Russian, Spanish, Turkish,
- Simplified Chinese, Traditional Chinese • Regulatory approvals: CE, CCC, UL/cUL, C-Tick,