



For more information on our products, download our 2016 from our website.

GrassProtecta"







(Standard) 1.2kg/m² (Heavy) 2.0kg/m²

GrassProtecta[®] is an improved heavy duty thick polyethylene mesh for reinforcing grassed surfaces prone to wear, rutting and smearing

Applications:

- Grass overspill car parks
- Domestic driveways
- Front lawn and grass verge parking
- Boat and caravan parking
- Golf course buggy path and maintenance vehicle routes
- Emergency vehicle access routes
- Caravan parks
- Light aircraft taxiways

Benefits:

- High level of reinforcement up to 8 tonnes per axle (imposed load)
- Ideal for permanent or temporary applications such as park on grass
- Fast and cost effective installation compared to plastic paving grids
- No excavation or soil removal necessarily required
- Improved traction and grip compared to the standard straight orientated protection meshes

Specifications:

Standard

Roll: 1m x 10m or 2m x 20m

> Thickness: 11mm Colour: Green

- or 2m x 20m Weight: 1200gsm • Weight: 2000gsm
 - Thickness: 14mm

• Roll: 1m x 10m

Colour: Green



Physical: 42 Izone Drive Izone Business Park Rolleston 7675

PO Box 11-303, Sockburn Christchurch 8443 Postal:

www.advancelandscape.co.nz

0800 600 789



0800 600 788

sales@advancelandscape.co.nz

Heavy - ideal for heavy traffic or softer ground



GRASSPROTECTA® PRODUCT SPECIFICATIONS								
PHYSICAL CHARACTERISTICS:		STANDARD 1.2kg/m ²		HEAVY 2kg/m ²				
Structure		Oscillated		Oscillated				
Polymer		HDPE (80% Virgin, 20% Recycled)		HDPE (80% Virgin, 20% Recycled)				
Colour		Green		Green				
UV Stabilised		Yes		Yes				
NOMINAL DIMENSIONS:								
Roll Width		2m	1m	2m	1m			
Roll Length		20m	10m	20m	10m			
Roll Weight		48kg	12kg	80kg	20kg			
Weight per liner metre		2.4kg	1.2kg	4kg	2kg			
Weight per square metre		1.2kg/m ²		2kg/m ²				
Thickness		11mm		14mm				
Mesh Aperture (Diamond:Oval)		3:1 ratio		3:1 ratio				
TECHNICAL CHARACTERIST	ICS:							
Measurement	Method	Results		Results				
Tensile strength (MD)	ISO 10319	12kN/m		16kN/m				
Yield point elongation (MD)	01001001	30%		35%				
Residual thickness @ 500 kPa	ASTM D1621	45%		60%				
Slip risk PTV value	BS7976: 1-3	>40 (low slip)		>40 (low slip)				

GRASSPROTECTA® PINS & PEGS						
Product	U-Pin	Pegs - Black	Pegs - Yellow	Washers - Yellow		
Material	Steel	Plastic	Plastic	Plastic		
Size	170mm x 70mm x 6mm dia.	140mm long	140mm long	58mm diameter		
Outer	50 pack	100 pack	100 pack	100 pack		





Plastic fixing pegs and parking bay markers / washers