



Circuit Protection	Code
Fuse	<b>F</b>
MCB	<b>CR</b>

PDU Feed	Code
Bottom	<b>B</b>
Top	<b>T</b>

Chassis Color	Code
Black	<b>1</b>
White	<b>2</b>
Red	<b>3</b>
Blue	<b>4</b>
Green	<b>5</b>
Orange	<b>6</b>
Yellow	<b>7</b>
Purple	<b>8</b>

Standard color : Black



NEMA L6-30P

30A model :	Circuit Protection
V8C13/2C19-30A/ <b>F</b> _L630/3 <b>B</b> -1	Resettable Fuse x 2
V8C13/2C19-30A/ <b>CR</b> _L630/3 <b>T</b> -1	1-pole MCB x 2

Input Rating : 30Amp, 208V  
 Cordset : 10 feet UL SJT 10 AWG cordset  
 Protection : 16A resettable fuse or 16A hydraulic MCB x 2  
 Circuit A : Output 12A max., C13 #1-4 + C19 #C1  
 Circuit B : Output 12A max., C13 #5-8 + C19 #C2  
 Weight : Net 3.58 lb / Gross 6.31 lb



NEMA L6-20P

20A model :	Circuit Protection
V8C13/2C19-20A/ <b>F</b> _L620/3 <b>B</b> -1	Resettable Fuse x 1
V8C13/2C19-20A/ <b>CR</b> _L620/3 <b>T</b> -1	1-pole MCB x 1

Input Rating : 20Amp, 208V  
 Cordset : 10 feet UL SJT 12 AWG cordset  
 Protection : 20A resettable fuse or 20A hydraulic MCB x 1  
 Circuit : Output 16A max., C13 #1-8 + C19 #C1-C2  
 Weight : Net 2.31 lb / Gross 5.03 lb

Operating Temperature : -5 to 60 °C  
 Storage Temperature : -25 to 65 °C  
 Operating Altitude : 0 to 2,000 m  
 Storage Altitude : 0 to 15,000 m  
 Humidity : 8 to 95% RH, non-condensing

EMC Compliance : FCC Part 15 Subpart Class A  
 Safety Compliance : Tested to UL 62368-1:2014 standard  
 Tested to UL 60730-1:2016 standard  
 Environment Compliance : RoHS3 & REACH

**AUSTIN HUGHES** Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2021 Austin Hughes Electronics Ltd. All rights reserved.

Product Dimension : 2.1 (W) x 2.8 (D) x 23.6 (H) inch  
 Packing dimension ( for 2 PDUs ) : 4.3 (W) x 10.6 (D) x 43.0 (H) inch