Eaton gets IT – in every environment

Healthcare solutions

Protect and connect patients and staff with





Power Strips

Hospital-grade outlets distribute power in patient areas. New UL 2930 models feature a redundant ground connection to protect against electric shock.*



Surge Protectors

Surge protectors safeguard equipment inside and outside patient areas. 120V models include hospitalgrade plugs and outlets.*



Medical-grade **UPS systems**

UPS systems provide battery backup to equipment in patient areas during power outages.



Medical-grade isolation transformers

Isolation transformers with full UL or IEC 60601-1 listing protect sensitive electronic equipment in patient areas



UV charging carts (120V only)

Charge, secure and sanitize up to 32 tablets and laptops (hospital-grade plugs in select models).*



Antibacterial cables

Ethernet, USB and video cables connect equipment where extra protection against bacteria is required.*



Wall-mount enclosures

Secure and organize IT hardware, rack-mount A/V equipment and other devices while preserving space.



TV/monitor wall mounts

Swivel/tilt wall mounts safely and securely accommodate up to 100 in. TVs and monitors.*



Medical-grade hospital cart power supplies

Mobile power solutions keep hospital cart equipment running with up to 350W AC power, both inside and outside patient care vicinities.

*To promote a healthier environment for patients and staff, Safe-IT™ antimicrobial and antibacterial options are available for select models.



SEE REVERSE FOR MORE SOLUTIONS

Eaton gets IT – in every environment



Medical-Grade UPS Systems

Model	Output	IEC Compliance	Runtime (Half/Full Load)	Hospital-Grade AC Outlets ⁽¹⁾	Comm. Ports	AC Input Cord Length	AC Input Inlet
OMNIX350HG	350VA/225W	IEC 60601-1	37/15.5 min.	6 (C13)	USB	15.2 cm	C14
SMX700HG	700VA/450W	IEC 60601-1	36/14.5 min.	6 (C13)	Serial and USB	15.2 cm	C14
SMX700HGL ⁽²⁾	700VA/450W	IEC 60601-1	36/14.5 min.	6 (C13)	Serial and USB	15.2 cm	C14
SMX1200XLHG	1000VA/750W	IEC 60601-1	27.5/11 min. +	6 (C13)	Serial and USB	15.2 cm	C14
SMX1200XLHGL ⁽²⁾	1000VA/750W	IEC 60601-1	27.5/11 min. +	6 (C13)	Serial and USB	15.2 cm	C14

(1) Backup runtimes vary with load, battery condition and other factors. Increase runtimes for "+" models by connecting optional external battery packs. (2) Includes Lithium Iron Phosphate (LiFePO4) battery with 20-30 times the cycle life of traditional batteries.



Medical-Grade Hospital Cart Power Supplies

Model	Wattage	IEC Compliance	Battery	Runtime ⁽¹⁾	Battery Charge	Outlets	Port	Runtime
HCINT150SL	150	EN60601-1-2:2015, 4th Edition	SLA or LiFePhos 12VDC	Up to 6 hours	Equal to discharge time (9-20A)	(1) C13	USB	Yes
HCINT350SNR	300	EN60601-1-2:2015, 4th Edition	SLA 12VDC	Up to 6 hours	Equal to discharge time (9-20A)	(1) C13	USB	Yes

(1) Up to 6 hours typical runtime in standard configuration. Runtime varies depending on battery condition and load.



Medical-Grade Isolation Transformers

Model	Output	Nominal AC Voltage	IEC Compliance	Hospital-Grade AC Outlets	AC Input Inlet
IS300HGDV	300W	115/230V	IEC 60601-1	4 (C13)	C14
IS600HGDV	600W	115/230V	IEC 60601-1	6 (C13)	C14
IS1000HGDV	1000W	115/230V	IEC 60601-1	8 (C13)	C14
IS1800HGDV	1800W	115/230V	IEC 60601-1	8 (C13)	C20



Medical-Grade Ethernet Isolator

RJ45 Ethernet network isolator for patient care vicinity, IEC 60601-1

Connectivity Solutions for Medical Equipment & Hospitals



USB 2.0 Hubs (2 Models)

4- and 7-Port Industrial-Grade USB 2.0 Hubs -15 kV ESD Immunity, Metal Housing, Mountable



USB 3.0 Hubs (3 Models)

4-, 7- and 10-Port Industrial-Grade USB 3.0 SuperSpeed Hubs - 20 kV ESD Immunity, Metal Housing, Mountable



USB-C Hubs (2 Models)

4- and 7-Port Industrial-Grade USB-C Hubs -USB 3.1 Gen 2, 10 Gbps, USBA & USB-C Ports, 15 kV ESD Immunity, 2 kV Surge



B127M-101-H Video Extender

HDMI over Cat6 Extender Kit for Medical Environments, 4K @ 60 Hz, HDR, 4:4:4,PoC, 230 ft., TAA



Managed and Unmanaged Industrial Ethernet Switches (18 Models)

Up to 16 Ports and up to GB speed – DIN Mount, Operating Ranges as wide as -40° to 75°C, Options Include PoE+, Wall Mounting, Ruggedized Housing and GbE SFP Slots



For more information or contact your Eaton representative: