

Overview

The HP LaserJet Pro M404 printer—focus your time where it's most effective–growing your business

Winning in business means working smarter. The HP LaserJet Pro M404 printer is designed to let you focus your time where it's most effective-helping to grow your business and staying ahead of the competition.

Built to keep you—and your business moving forward

Help decrease the amount of paper used in the office by printing on both sides of the page.[12]

Best -in-class security-detect and stop attacks[6]

A suite of embedded security features help protect your printer from being an entry point for attacks.[6]

Simply designed to uncomplicate your day

Set up this printer fast and easily manage device settings to help increase overall printing efficiency.

Sustainability is smart business

Avoid frustrating reprints, wasted supplies, and service calls using Original HP toner cartridges.

Features

Wi Fi-Dual band	Enhanced security
Bluetooth Low-Energy for HP Roam	Energy efficient

[6] Based on HP review of 2019 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://www.hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/printersecurityclaims

[12] 2 sided printing not supported on the M404n

Specifications

Print Resolution Technologies	HP FastRes1200, HP ProRes1200, Economode	
Print quality black (best)	Fine Lines (1200 x 1200 dpi)	
Print speed black (ISO, A4)	Up to 38 ppm (default) ; Up to 40 ppm (HP High Speed)	
Print speed black (ISO, letter)	Up to 40 ppm (default); Up to 42 ppm (HP High Speed)	
Print speed	Prints up to 40/42 ppm (A4/LTR) (HP High Speed)	
Functions	Print	
Duplex printing	Automatic (default)	
Duty cycle (monthly, A4)	Up to 80,000 pages	
Duty cycle (monthly, letter)	Up to 80,000 pages ^[10]	
Printer smart software features	Apple AirPrint™, Mopria certified, Google Cloud Print 2.0, Wi-Fi Direct printing, ROAM enabled for easy printing, HP ePrint, HP Auto-On/Auto-Off Technology, Job Storage with PIN printing, N-up printing, collation	
Energy savings feature technology	HP Auto-On/Auto-Off Technology; Instant-on Technology	
Replacement cartridges	AMS: For distribution and use in North America and Latin America only: HP 58A Black LaserJet Toner Cartridge (~3,000 pages), CF258A; HP 58X Black LaserJet Toner Cartridge (~10,000 pages), CF258X; EMEA: For distribution and use in Europe, Middle East, Russia, CIS, and Africa only: HP 59A Black LaserJet Toner Cartridge (~3,000 pages), CF259A; HP 59X Black LaserJet Toner Cartridge (~10,000 pages), CF259X; APJ: For distribution and use only in Asia Pacific - excluding China (PRC) and India: HP 76A Black LaserJet Toner Cartridge (~3,000 pages), CF276A; HP 76X Black LaserJet Toner Cartridge (~10,000 pages), CF276X ^[3]	
Supplies feature	HP JetIntelligence Cartridge	
Connectivity, standard	1 Hi-Speed USB 2.0; 1 host USB at rear side;Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE) 802.11b/g/n / 2.4 / 5 GHZ Wi-Fi radio	
Network capabilities	Built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X	
Wireless capability	Yes, built-in dual-band Wi-Fi; Authentication via WEP, WPA/WPA2, WPA Enterprise; Encryption via AES or TKIP; WPS; Wi-Fi Direct; Bluetooth Low-Energy	
Mobile printing capability	Apple AirPrint™; Google Cloud Print™; HP ePrint; HP Smart App; Mobile Apps; Mopria™ Certified; ROAM capable for easy printing; Wi-Fi® Direct printing	
Network protocols, supported	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, HP ePrint, Apple AirPrint™, Google Cloud Print 2.0, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download	

Software included	No software solutions are included in the Box, Download software at http://123.hp.com/laserjet or http://hp.com	
Compatible Operating Systems	Windows Client OS (32/64 bit), Win10, Win8.1, Win 8 Basic, Win8 Pro, Win8 Enterprise, Win8 Enterprise N, Win7 Starter Edition SP1, UPD Win7 Ultimate, Mobile OS, iOS, Android, Mac, Apple® macOS Sierra v10.12, Apple® macOS High Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see http://www.hp.com/go/upd	
Sustainable impact specifications	Mercury-free	
Energy star certified	Yes	
Energy efficiency	ENERGY STAR® qualified; EPEAT® Silver; CECP ^[13]	
Blue Angel compliant	Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies	
Display area (imperial)	1.79 x 0.53 in	
Display area (metric)	4.55 x 1.35 cm	
Display	2-line backlit LCD graphic display	
Minimum dimensions (W x D x H)	381 x 357 x 216 mm (Without trays and covers not extended)	
Minimum dimensions (W x D x H)	15 x 14.06 x 8.5 in (Without trays and covers not extended)	
Weight	8.56 kg	
Weight	18.87 lb	
Power consumption	495 watts (active printing), 5.5 watts (ready), 0.5 watts (sleep), 0.5 watts (Auto Off/Wake on LAN, enabled at shipment), 0.05 watts (Auto-off/Manual-on), 0.05 (Manual Off) ^[2]	
Power supply type	Internal (built-in) Power Supply	
What's in the box	HP LaserJet Pro M404dw; Preinstalled HP Black LaserJet Toner Cartridge (59A for EMEA, 58A for AMS, 76A for AP, yield ~3,000 pages); Getting Started Guide; Support Flyer; Warranty Guide; Regulatory Flyer; Power cord; USB cable ^[14]	
Services (Care Pack)	UB9T8E - HP 3y NBD LJ Pro M404 M405 M304 M305 SVC; UB9T9E - HP 4y NBD LJ Pro M404 M405 M304 M305 SVC; UB9U0E - HP 5y NBD LJ Pro M404 M405 M304 M305 SVC; UC0Q4E - HP3y4h9x5 LJ Pro M404 M405 M304 M305 SVC; UC0Q5E - HP4y4h9x5 LJ Pro M404 M405 M304 M305 SVC; UC0Q6E - HP5y4h9x5 LJ Pro M404 M405 M304 M305 SVC; UB9U1E - HP 3yNBDExchg LJPro M404M405M304M305 SVC; UB9U2E - HP 3y RTD LJ Pro M404 M405 M304 M305 SVC; UB9U3PE - HP 1yPWNBD LJPro M404 M405 M304 M305 SVC; UB9U4PE - HP 2yPWNBD LJPro M404 M405 M304 M305 SVC; UC0Q7PE - HP1yPW4h9x5LJPro M404 M405 M304 M305 SVC; UB9U5PE - HP1yPWNBDExchg LJProM404M405M304M305 SVC; UB9U6PE - HP 1yPWRTD LJPro M404 M405 M304 M305 SVC;	

Warranty

One-year Bench/Depot Repair warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (wty code 4E; wty ID A033)

Additional specifications

Accessories	HP LaserJet 550-sheet Feeder Tray D9P29A; HP v222w 16GB Mini USB Drive P0R81AA
Acoustic power emissions (active, printing)	6.7 B(A)
Acoustic power emissions (ready)	2.6 B(A)
Acoustic pressure emissions bystander (active, printing)	54 dB(A)
Acoustic pressure emissions bystander (ready)	15 dB(A)
Automatic paper sensor	No
Bottom margin (A4)	5 mm
Cable included	Yes, 1 USB cable
Compatible Network Operating Systems	Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit, Failover Cluster 2008 R2, Failover Cluster 2012 R2, Terminal server 2008 R2, Remote Desktop server 2012 R2, Citrix Server 6.5, Citrix XenApp & XenDesktop 7.6, Novell iPrint server, Citrix Ready Kit Certification - Upto Citrix Server 7.18 for more information see http://citrixready.citrix.com, Linux- For more information see http://developers.hp.com/hp-linux-imaging-and-printing, Unix- For more information see http://hp.com/go/unixmodelscripts, UPD PCL6 / PS Printer Drivers, Supported for Compatible Network Operating systems please see http://hp.com/go/upd
Control panel	2-line LCD; OK button; Left button; Right button; Cancel button; Back button; Wireless button; Ready LED; Error LED; Wi-Fi LED
Count of cartons per pallet layer	9
Count of layers in pallet	5 (NA), 4 (EMEA, AP)
Country of origin	Made in Philippines
Downloadable software	From http://123.hp.com, HP Easy Start (Guided Software Install for Windows and Mac), From http://hp.com for Windows OS, Fullsolution software and drivers, Basicsolution software and drivers, HP PCL6 XPS Discrete Print Driver, Product Documentation and Support, From http://hp.com for Mac OS, HP Easy Start (Guided Software Install), HP Mac PS Print Driver, HP Easy Admin, For Mobile OS, iOS For more information see http://hp.com/go/businessmobileprinting, Android For more information see http://hp.com/go/businessmobileprinting, From http://hp.com for printer administrators, Printer Administrator Resource Kit (Driver Configuration Utility Driver Deployment Utility Managed Printing Administrator), HP Universal Print Drivers PCL6 GDI & PS GDI for Windows, HP ePrint Software (Mobile Driver for Windows), SAP Print Drivers for more information see http://support.hp.com/usen/document/c05051702, HP Web JetAdmin, HP JetAdvantage Security Manager, HP Roam, HPLIP Linux Printer Driver for more information see http://hplipopensource.com/hplipweb/index.html, Unix Model Script Printer Driver for more information see http://hp.com/go/unixmodelscripts

Driver updates	Latest supported operating systems and Print drivers available at HTTP://www.hp.com/support/ljM404
Duty cycle note	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Electromagnetic compatibility	CISPR 32:2012/EN 55032:2012 - Class B, CISPR 32:2015/EN 55032:2015 - Class B, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015, FCC Title 47 CFR, Part 15 Class B / ICES-003, Issue 6
Envelope Feeder	No
Finished output handling	Sheetfed
First page out black (A4, ready)	As fast as 6.3 sec
First page out black (A4, sleep)	As fast as 8.8 sec
First page out black (letter, ready)	As fast as 6.1 sec
First page out black (letter, sleep)	As fast as 8.6 sec
Fonts and typefaces	84 scalable TrueType fonts
Input capacity	Up to 350 sheets (Tray 1: up to 100 sheets; Tray 2: up to 250 sheets)
Internal Storage	None
Left margin (A4)	4 mm
Mac compatible	Yes
Maximum Memory	256 MB
Maximum dimensions (W \times D \times H)	381 x 634 x 241 mm
Maximum dimensions (W x D x H)	15 x 25 x 9.5 in
Maximum input capacity (sheets)	Up to 900 sheets
Maximum output capacity (sheets)	Up to 150 sheets
Maximum print area	207.4 x 347.1mm
Media size, tray 1	A4, A5, A6, B5 (JIS), B6 (JIS), 16K (195 \times 270 mm, 184 \times 260 mm, 197 \times 273 mm), 10 \times 15 cm, Oficio (216 \times 340 mm), postcards (JIS single, JIS double), envelopes (DL, C5, B5)
Media size, tray 2	A4, A5, A6, B5 (JIS), B6 (JIS), 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm), 10×15 cm, Oficio (216 x 340 mm), postcards (JIS single, JIS double), envelopes (DL, C5, B5)
Media size, tray 3	A4; A5; A6; B5 (JIS); B6 (JIS); 16K (195 \times 270 mm, 184 \times 260 mm, 197 \times 273 mm); 10 \times 15 cm; Oficio (216 \times 340 mm); postcards (JIS single, JIS double)
Media sizes supported	Tray 1, Tray 2: A4; A5; A6; B5 (JIS); B6 (JIS); 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); 10 x 15 cm; Oficio (216 x 340 mm); postcards (JIS single, JIS double); envelopes (DL, C5, B5); Optional Tray 3: A4; A5; A6; B5 (JIS); B6 (JIS); 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); 10 x 15 cm; Oficio (216 x 340 mm); postcards (JIS single, JIS double); Automatic duplexer: A4; B5; 16K (195 x 270 mm, 184 x 260 mm; 197 x 273 mm); Oficio (216 x 340 mm)

Media sizes supported	Tray 1, Tray 2: Letter, legal, executive, Oficio $(8.5 \times 13 \text{ in})$, $4 \times 6 \text{ in}$, $5 \times 8 \text{ in}$, envelopes (No 10, Monarch); Optional Tray 3: Letter, legal, executive, Oficio $(8.5 \times 13 \text{ in})$, $4 \times 6 \text{ in}$, $5 \times 8 \text{ in}$; Automatic duplexer: Letter, legal, executive, Oficio $(8.5 \times 13 \text{ in})$	
Media sizes supported, key	4 x 6 in; Letter; Legal; Envelopes	
Media sizes supported, key	10 x 15 cm; A4; Envelopes	
Media sizes, custom	Tray 1: 3 x 5 to 8.5 x 14 in; Tray 2, optional Tray 3: 3.94 x 5.83 to 8.5 x 14 in	
Media sizes, custom	Tray 1: 76 x 127 to 216 x 356 mm; Tray 2, optional Tray 3: 100 x 148 to 216 x 356 mm	
Media type and capacity, tray 1	Sheets: 100; envelopes: 10	
Media type and capacity, tray 2	Sheets: 250	
Media type and capacity, tray 3	Sheets: 550	
Media types	Paper (plain, EcoFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels	
Media weight (tray 1)	60 to 200 g/m ²	
Media weight (tray 2)	60 to 120 g/m ²	
Media weight (tray 3)	60 to 120 g/m² (optional 550-sheet tray)	
Media weight, supported	Tray 1: 60 to 200 g/m²; Tray 2, Optional 550-sheet Tray 3: 60 to 120 g/m²	
Media weight, supported	Tray 1: 16 to 46.6 lb; Tray 2 and Optional 550-sheet Tray 3: 16 to 32 lb	
	256 MB	
Memory	256 MB	
Memory Minimum System Requirements	256 MB 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com	
•	2 GB available hard disk space, Internet connection, USB port, Internet	
Minimum System Requirements Minimum System Requirements	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS	
Minimum System Requirements Minimum System Requirements for Macintosh	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges	 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range Output capacity	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C Up to 150 sheets	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range Output capacity Package dimensions (W x D x H)	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C Up to 150 sheets 443 x 274 x 464 mm	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range Output capacity Package dimensions (W x D x H) Package dimensions (W x D x H)	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C Up to 150 sheets 443 x 274 x 464 mm 17.44 x 10.78 x 18.26 in	
Minimum System Requirements Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range Output capacity Package dimensions (W x D x H) Package weight	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C Up to 150 sheets 443 x 274 x 464 mm 17.44 x 10.78 x 18.26 in 23.1 lb	
Minimum System Requirements for Macintosh Number of print cartridges Number of users Operating humidity range Operating temperature range Operating temperature range Output capacity Package dimensions (W x D x H) Package weight Package weight Page yield (set-up/inbox	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see microsoft.com 2 GB available hard drive space, Internet connection or USB port, OS hardware requirements see apple.com 1 (black) 3-10 Users 10 to 80% RH 59 to 90.5°F 15 to 32.5°C Up to 150 sheets 443 x 274 x 464 mm 17.44 x 10.78 x 18.26 in 23.1 lb 10.5 kg	

Pallet weight	495.2 kg (NA), 400.7 kg (EMEA, AP)
Pallet weight	1089.4 lb (NA), 881.5 lb (EMEA, AP)
Paper handling input, optional	Optional third 550-sheet tray
Paper handling input, standard	100-sheet multipurpose Tray 1, 250-sheet input Tray 2
Paper handling output, standard	150-sheet output bin
Paper trays, maximum	3
Paper trays, standard	2
Plug and play	Auto Wireless Connect; HP Smart Install
Power	110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, product varies by part number with # Option code identifier)
Print Technology	Laser
Print colors	No
Print languages	HP PCL 6, HP postscript level 3 emulation, PDF, URF, PWG Raster
Print quality black (normal)	Normal (Native: 600×600 dpi, enhanced up to 4800×600 dpi)
Print resolution black (fine lines)	Fine Lines (1200 x 1200 dpi)
Print speed black (Landscape, A5)	Up to 63 ppm
Print speed black (Portrait, A5)	Up to 14 ppm
Print speed duplex (A4)	Up to 31 ipm
Print speed duplex (letter)	Up to 33 ipm
Print speed footnote (A5)	Measured using ISO 24734 Feature Test, A5 Landscape Feed. Speed may vary based on content, PC, media orientation, and media type.
Print technology	Laser
Printer Management	HP Printer Assistant; HP Utility (Mac); HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)
Processor speed	1200 MHz
Quantity per pallet	45 (NA), 36 (EMEA, AP)
RMN number	SHNGC-1800-01
Recommended media weight (duplex)	60 to 120 g/m ²
Recommended media weight (duplex)	16 to 32 lb
Recommended monthly page volume	750 to 4000 ^[11]
Recommended operating humidity range	30 to 70% RH

Recommended operating temperature range	17.5 to 25℃	
Recommended operating temperature range	63.5 to 77°F	
Right margin (A4)	4 mm	
Safety	IEC 60950-1:2005 +A1:2009+A2:2013/EN 60950-1:2006 +A11:2009+A1:2010+A12:2011+A2:2013; IEC 60825-1:2014/EN 60825- 1:2014 (Class 1 Laser/LED Product); IEC 62479: 2010/EN 62479: 2010	
Security management	Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; IPP over TLS; Network: enable/disable network ports and features, unused protocol and service disablement, SNMPv1, SNMPv2, and SNMPv3, community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication, SASL authentication; Firewall and ACL; control panel lock, certificates configuration, UPD PIN printing, Syslog, signed firmware, administrator settings, 802.1x authentication (EAP-TLS, and PEAP), authentication via WEP, WPA/WPA2 Personal, WPA2-enterprise; encryption via AES or TKIP; Encrypted data storage; Secure data erase; Automatic firmware updates; Secure Encrypted Print via optional job storage, Compatible with optional HP JetAdvantage Security Manager, IPPS	
Standard input capacity (envelopes)	Up to 10	
Standard media sizes (duplex)	A4; 16K (195 x 270 mm, 184 x 260 mm, 197 x 273 mm); B5; Oficio	
Standard media sizes (duplex, imperial)	Letter; Legal; Executive; Oficio (8.5 x 13 in)	
Standard output capacity (envelopes)	Up to 10 envelopes	
Storage	Optional Job storage via external rear host USB port (Minimum 16 GB)	
Storage device and direct print support	Wireless direct printing; Optional job storage via external rear host USB port (Minimum 16GB)	
Storage temperature range	-4 to 104°F	
Storage temperature range	-20 to 40°C	
SureSupply supported	Yes	
Target user and print volume	For teams up to 10 users; Prints up to 4,000 pages/month	
Tariff numbers	(AM) 8443321010; (EU) 8443321000; (AP) 84433231	
Top key features	Roam; Fast first page out speeds; Strong Security; Dualband Wi-Fi	
Top margin (A4)	5 mm	
Typical electricity consumption (TEC) footnote	BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.	
Typical electricity consumption (TEC) number	1.10 kWh/Week (Blue Angel); 0.371 kWh/Week (Energy Star 3.0) ^[15]	
UNSPSC code	43212105	

UPC number	(696) 193808294228; (697) 193808294235; (ABO) 195122462444; (ABT) 192018902923; (ABY) 192018902930; (AC8) 193808294242; (ACQ) 192018902947; (B19) 192018902954; (BAZ) 192018902961; (BBU) 192545283175; (BGJ) 192018902978; (BGM) 192545283182	
Warm-up time	As fast as 45 sec	
Waste electrical and electronic weight	8.56 kg	
Web address for additional information	http://www.hp.com/go/support	

OC) 102002201220 (COT) 102002201225 (ADO) 105122162111 (ADT)

- [2] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.
- [3] Toner cartridges designed for distribution and use within a designated region only; will not work outside of designated region.
- [10] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
- [11] HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period
- [13] EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
- [14] In box cartridge yields 3,000 black pages based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see: http://www.hp.com/go/learnaboutsupplies. Pages may vary based on customer printing conditions and usage.
- [15] BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.

Accessories

Paper Handling

★: Recommended

Input Trays

HP LaserJet Pro 550-sheet Feeder Tray

D9P29A ★

Ink/Toner/Paper/Printer Supplies

HP Laser Toner Cartridges and Kits

HP Black and White Laser Toner Printer Cartridges

HP 58A Black Original LaserJet Toner Cartridge	CF258A
HP 58X High Yield Black Original LaserJet Toner Cartridge	CF258X
HP 59A Black Original LaserJet Toner Cartridge	CF259A
HP 59X High Yield Black Original LaserJet Toner Cartridge	CF259X
HP 76A Black Original LaserJet Toner Cartridge	CF276A
HP 76X High Yield Black Original LaserJet Toner Cartridge	CF276X
HP 77A Black Original LaserJet Toner Cartridge	CF277A
HP 77X High Yield Black Original LaserJet Toner Cartridge	CF277X

★: Recommended

HP Paper Designed for Laser Printers

HP Laser Everyday Paper

HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A3/297 x 420 mm	7MV81A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A4/210 x 297 mm	7MV82A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Letter 8.5 x 11 in	4WN08A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Tabloid/11 x 17 in	4WN07A

HP Professional Laser Paper

HP Professional Glossy Laser Paper 120 gsm-250 sht/A3/297 x 420 mm	CG969A
HP Professional Glossy Laser Paper 150 gsm-150 sht/A4/210 x 297 mm	CG965A
HP Professional Laser Glossy FSC Paper 200 gsm-150 sht/A4/210 x 297 mm	7MV83A
HP Professional Laser Glossy FSC Paper 200 gsm-150 sht/Letter/8.5 x 11 in	4WN10A
HP Professional Laser Matte FSC Paper 200 gsm-150 sht/A4/210 x 297 mm	7MV80A
HP Professional Laser Matte FSC Paper 200 gsm-150 sht/Letter/8.5 x 11 in	4WN05A

Solutions

JetAdvantage Printing Solutions

★: Recommended

JetAdvantage Print Management

HP JetAdvantage Insights	HPJETADINSIGHTS
HP Universal Print Driver	HPUNIVPRNTDRV
HP Web Jetadmin	HPWEBJETADMIN

JetAdvantage Mobile Printing

HP Roam for Business	HPROAM
ePRINTit	HP3PEPRINTIT

Disclaimer — Copyright

© Copyright 2020 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Feb 03, 2021 8:52 PM UTC+0000

Contact us to request a quote.

www.archimediasg.com





