IN134



The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN134

The InFocus IN134 XGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

Key Features

- ♦ XGA (1024 x 768) resolution
- TechStation lets you customize your projector with the devices you already use
- Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design















Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless



when not in use, and save even more money over the life of the projector.

Over 1 Billion Colors

BrilliantColor™ DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -- including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).



Quietest Projector in its Class

Make sure students always hear the lessons, not the fans. With only 21dB in eco mode, IN134 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient enclosure, and silent bearings.

Save Energy with Value that Lasts

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP* chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free ProjectorNet 4.1 software from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

Specifications*

Projector	IN134
Resolution – Native	XGA (1024 x 768)
Display Technology	DLP
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Eco Mode	3,200 lumens
Lamp Life	5,500 hours
Lamp Life – Low Power	10,000 hours
Lamp Life – Dynamic Mode	15,000 hours
Lamp Power	220W

Lump New — Exe Mode M5W Color Wheel Migh Speed 6 Segment RYGCWB Number of Calors 107 billion Synch Scan Frequency — Horizontal 315 - 79.6 kHz Synch Scan Frequency Vertical 45 Appect Ratio Compatibility 169, 1600, 2.351, 13, 23, 139, 159, 54 Projection Lans FStop — Maximum 2,8 Lans Type Manual facus Image Size — Maximum 244 in Projection Lans FStop — Maximum 244 in Image Size — Maximum 244 in Projection Offset 155 + 55 W Keyston Correctors 4 40 W Connectors – Pupuls 35 mm audio Composte vicion, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TockStation Connection) Connectors – Outputs 35 mm audio coutout, Monitor out (VGA) Controll RS232, It Remote Audible Noise — Eco Mode 2 1 de A at 0°F / 178°C Included Accessories Power cond, Remote, HDMI Cable, Documentation, User Manual (CD) Disport 1000 @ 60 ML, All DMI 14a 3D formats, DLP Link 3D glasses required Power Consumption — Standty Mode 9 Link A 10°F / 18B°C Power Consumption — Eco Mode <	Projector	IN134
Color Might Speed & Segment RYGCWB Number of Colors 1.07 billion Synch Scan Frequency - Horizontal 31.5" 978 kHz Synch Scan Frequency Vertical 56 120 kHz Aspect Ratio Compatibility 169, 1610, 2351, 11, 21, 3139, 15-9, 54 Projection Lens F-Stop - Minimum 2.53 Len's Type Manual focis Image Size - Minimum 2.44 Image Size - Minimum 2.44 in Projection Order 1.55 + 25 V Keyston Correction 4.40 V Connectors - Inputs 3.5mm audio comput. Monitor out (VGA) Connectors - Outputs 3.5mm audio comput. Monitor out (VGA) Control Accessories 9 Rower Consumption Object of Mode 2.1 disk at 07 + 175 C Included Accessories Power Consumption 3.00 W max Power Consumption - Eco Mode 1.08 M max Power Consumption - Low Power Standby 0.5 W max Power Consumption - Low Power Standby 0.5 W max Power Consumption - Low Power Standby 2.5 W max Power Consumption - Low Power Standby 3.5 m max Power Consumption - Low	Lamp Power – Eco Mode	145W
Number of Colors 1.07 billion Synch Scan Frecuency - Horizontal 31.5 "976 RHz Synch Scan Frecuency - Vertical 56 - 120 kHz Aspect Ratio 4.3 Aspect Ratio Compatibility 169, 1610, 2,351, 11, 21, 139, 15-9, 54 Projection Lens F-Stop - Minimum 2.51 Lors Type Manual focus Image Size - Minimum 2.1 Image Size - Maximum 2.2 in Projection Offset 158 k - 58 V Keystone Correction 4.0V Connectors - Outputs 3.5mm audio, Composite video, VEA, HDM1 14a x3 (with 14a 3D support), USB-A (TechStation Connection) Control of S252, IR Remote 3.5mm audio, Lorny state video, VEA, HDM1 14a x3 (with 14a 3D support), USB-A (TechStation Connection) Control of S252, IR Remote 4.0V Control of S252, IR Remote 4.00 th No.10 to 10 (VA) Control of S252, IR Remote 4.00 th No.10 to 10 (VA) Fortistion of S22, IR Remote 4.10 th A OF / 178°C Included Accessories Power cont. Bernate, IRMI Cable, Documentation, User Manual (CD) 3D Support 1080 pg 60 GNL, All HDM1 14a 3D formats, DLP Link 3D glasses required Power Consumption – Lorn More	Contrast Ratio	28,500:1
Synch Scan Freeuency - Horizontal 31.5 ° 97.6 KHz Synch Scan Freeuency - Vertral 56 - 120 KHz Aspert Ratin 43 Aspert Ratin Compatibility 169,1 151,2 2,51, 11, 21, 139, 159, 54 Projection Lens F-Stop - Maximum 2.53 Lens Type Manual focus Image Size - Maximum 2.2 in Image Size - Maximum 2.44 in Projection Offset 155 + 55 V Keystone Correction 4.07 V Connectors - Ingust 3.5mm audio curput, Monitor out (VGA) Connectors - Dutputs 3.5mm audio curput, Monitor out (VGA) Contral RS232; IR Remote Auchible Noise - Eco Mode < 21 disk at 0°F / 178°C	Color Wheel	High Speed 6 Segment RYGCWB
Synch San Frequency - Vertical 56 - 120 KHz Aspect Ratio 43 Aspect Ratio Compatibility 16.9, 16:10, 2.351, 11, 21, 13.9, 15.9, 54 Projection Lean F-Stop - Minimum 2.41 Projection Lean F-Stop - Minimum 2.93 Lans Type Manual focus Inange Size - Minimum 2.44 in Projection Diffset 115% + 5% KV Keystone Correction 4.40 V Connectors - Inputs 3.5mm audio composite video, VGA, HDM1.4a x3 (with 1.4a 30 support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio cottout, Monitor out (VGA) Connectors - Eco Mode < 21 cl84 at 0°F / 7/8°C	Number of Colors	1.07 billion
Aspect Ratio 4.3 Aspect Ratio Campatibility 16:9, 16:10, 2:35:1, 1:1, 2:1, 13:9, 15:9, 5:4 Projection Lans F-Stop – Minimum 2.53 Linary Syze Manual Focus Image Size – Maximum 22 in Image Size – Maximum 244 in Projection Offset 115% + 5% V Keyston Correction 2 40V Connectors – Inputs 3.5mm audio composite video, VGA, HDMI 1:4a x3 (with 1:4a 3D support), USB A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monifor out (VGA) Control 85232, IR Remote Control 85232, IR Remote Included Accessories Power Consumption Do Support 10800 @ 66 OHZ, All HDMI 1:4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 1.8W max Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 2.70 DW max Power Standard AC 100 to 2400, 50/60	Synch Scan Frequency – Horizontal	31.5 ~ 97.6 KHz
Aspect Ratio Compatibility 16.9, 16:10, 2.351, 11, 2:1, 13.9, 15:9, 5:4 Projection Lens F-Stop – Minimum 2.41 Projection Lens F-Stop – Maximum 2.53 Lens Type Manual focus Image Size – Minimum 2.41 Projection Offset 115% + 5% % Keystone Cornection 2.44 in Connectors – Injusts 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS-322, IR Remote Audible Noise – Eco Mode < 2.1 dBA at 0°F / 178°C	Synch Scan Frequency – Vertical	56 - 120 KHz
Projection Lens F-Stop – Minimum 2.41 Projection Lens F-Stop – Maximum 2.53 Lens Type — Maximum 22 in Image Size – Minimum 224 in Bridge Step – Maximum 244 in Projection Offset 15% + 5% V Keystone Correction 1 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 30 support), USB-A (TechStation Connection) Control 8.232, IR Remote Control 8.232, IR Remote Audible Noise – Eca Mode 2.21 dBA at 0°F / 1.78°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 10800 g 6 GHA, All HDMI 1.4a 3D formats, DLP LInk 30 glasses required Power Consumption 30.00 W max Power Consumption – Standby Mode 1.8W max Power Consumption – Eca Mode 2.00 W max	Aspect Ratio	4:3
Projection Lens F-Stop – Maximum 25 l Lens Type Manual focus Lens Type Manual focus Linage Size – Minimum 22 ln Linage Size – Maximum 24 ln Projection Offset 15% + 5% V Keystone Correction 4 0VV Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Control 8.523.2 ik Remote Audible Noise – Eco Mode < 21 d BA at 0°F / 178°C Included Accessories Power Consumption 9 over correction 30 Support 1080 pg 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.9W max Power Consumption – Low Power Standby 0.9W max Power Consumption – Low Power Standby 0.9W max Power Consumption – Low Power Standby 0.10 to 240V, 50/60 Operating Conditions 41 to 104F at 0 to 10000 ft / 5 to 40°C at 0 to 30.48 m Power Consumption – Low Power Standby English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Kroean, Swedish, Russian, Frininsh, Arabic, Indonesian, Portuguese English, French, German, Span	Aspect Ratio Compatibility	16:9, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Lens Type Manual focus Inage Size – Minimum 22 in Inage Size – Maximum 244 in Projection Offset 115% ~ 5% V Kaystone Correction 40°V Connectors – Inputs 3.5mm audio cutput, Monitor out (VGA) Control 85232. IR Remote Control 85232. IR Remote Included Accessories 9 ever cord. Remote. HDMI Cable, Documentation, User Manual (CD) 3D Support 1080.pg 6 OHz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 1.8W max Power Consumption – Eco Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 2.0W max Power Consumption – Eco Mode 2.0W max Power Consumption – Eco Mode 1.4 to 1047 at 0 to 10000 tr / 5 to 40°C at 0 to 30.0B m Decamentation Languages Ac 100 to 240°C, 50/60 Bocamentation Languages Finglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, Prohish, Turkish, Danish, Arabic, Indonesia	Projection Lens F-Stop – Minimum	2.41
Image Size – Miximum 22 in Image Size – Miximum 244 in Projection Offset 1158 + 5% V Keystone Correction 4 40°V Connectors – Inputs 3.5mm audio cutput, Monitor out (VGA) Connectors – Outputs 3.5mm audio cutput, Monitor out (VGA) Connectors – Outputs 3.5mm audio cutput, Monitor out (VGA) Control 8232, IR Remote Audible Noise – Eco Mode 21 dBA at 0°F / 178°C Included Accessories Power Cond. Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 1.8W max Power Consumption – Standby Mode 1.8W max Power Consumption – Eco Mode 220.0W max Power Consumption – Eco Mode 220.0W max Power Standard A 1 to 104°F at 0 to 10000 ft/ Operating Conditions 41 to 104°F at 0 to 10000 ft/ Sto 40°C at 10 to 3048 m Finish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Fininsh, Ardish, India, Indi	Projection Lens F-Stop – Maximum	2.53
Image Size – Maximum 244 in Projection Offset 1158 + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio cutput Monitor out (VGA) Connectors – Outputs 3.5mm audio output Monitor out (VGA) Control 85231, IR semote Audible Noise – Eco Mode < 21 dBA at 0°F /-178°C	Lens Type	Manual focus
Projection Offset 115% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control R5232; IR Remote Audible Noise – Eco Mode < 21 dBA of Y - / 126°C	Image Size – Minimum	22 in
Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio output, Monitor out (VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control 85232, IR Remote Audib Noise – Eco Mode < 21 dBA at OT F / 178°C	Image Size – Maximum	244 in
Connectors − Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USBA (TechStation Connection) Connectors − Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise − Eco Mode < 21 d8A at 0°F / -178°C Included Accessories power cond, Remote, HDMI Cable, Documentation, User Manual (CD) Dower Consumption 300.00 max Power Consumption − Standby Mode 1.8W max Power Consumption − Eco Mode 2.00 Vm max Power Standard AC 100 to 240V, 50/60 Power Standard AC 100 to 240V, 50/60 Operating Conditions English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Phugarian, Portuguese, Vietnamese, Czech, Romanian, Phugarian, Malay, Hindi, Flijion, Farsi, Japanese, Than Security Features Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Mainimum 1.0 m Throw Distance – Mainimum 1.94.1 Throw Distance – Mainimum 1.94.1 Throw Distance – Mainimum 1.94.2	Projection Offset	115% +- 5% V
Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise - Eco Mode < 21 dBA at OF / -17.8°C	Keystone Correction	± 40°V
Control RS232, IR Remote Audible Noise – Eco Mode 21 dBA at OF / 178°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 10800 @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required Power Consumption 300,0W max Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220,0W max Power Standard Act 100 to 2400, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Operating Conditions 41 English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, Arabic, Indonesian, Portuguese Renu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Throw Altion More Swedish, Musich, Filipino, Farsi, Japanese, Thai Throw Altion 10 m Throw Altion 10 m	Connectors – Inputs	3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)
Audible Noise – Eco Mode < 21 dBA at 0°F / -178°C	Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080 p. @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Plungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TachStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry Pl, EZ Cast Pro Dongle and other HDMI devices Throw Bistance – Minimum 1.0 m Throw Ratio – Maximum 1.94.1 Throw Ratio – Maximum 2.16.1 Zoom Ratio 1.1.4 Shipping Prod	Control	RS232, IR Remote
3D Support 1080p @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 31 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hund, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Aschromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Bistance – Minimum 1.0 m Throw Ratio – Maximum 1.20 m Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.11	Audible Noise – Eco Mode	< 21 dBA at 0°F / -17.8°C
Power Consumption 300.0W max Power Consumption – Standby Mode 18W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 1 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Krean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1.0 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.11 Throw Ratio – Maximum 4.9 × 9.3 x 12.3 in / 12.4 s x 23.6 z x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 12.4 s x 23.6 z x 312.4 mm	Included Accessories	Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)
Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard ACt 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindit, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Throw And Zoom Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Saus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1.0 m Throw Ratio – Minimum 1.9 4:1 Throw Ratio – Maximum 2.16:1 Soom Ratio 1.1:1 Shipping 4.9 x 9.3 x 12.3 in / 12.4 x 2.36.2 x 312.4 mm Product Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	3D Support	1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hilot, Fillipin, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw And Zoom Throw Distance – Minimum 1.0 m Throw Distance – Maximum 1.0 m 1.0 m 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.9 x 9.3 x 12.3 in / 1.2 to 2.2 to 2.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 1.2 to 2.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption	300.0W max
Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Throw And Zoom Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Maximum 1.0 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping 4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 19.5 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.5 in / 19.5 6 x 337.8 x 398.8 mm	Power Consumption – Standby Mode	1.8W max
Power Standard AC 100 to 240V, 50/60 Operating Conditions dt 10/4" at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom 10 m Throw Distance – Minimum 1.0 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.11 Shipping 49 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm Product Dimensions 4.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Low Power Standby	0.5W max
Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom Throw Distance – Maximum 1.0 m 1hrow Ratio – Maximum 1.94.1 1nrow Ratio – Maximum 2.16:1 2oom Ratio 1.1:1 Shipping Product Dimensions 49 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 7.7 × 13.3 × 15.7 in / 195.6 × 3378 × 398.8 mm	Power Consumption – Eco Mode	220.0W max
Operating Conditions5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationKensington lock portThrow and ZoomWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1.0 mThrow Distance – Maximum1.20 mThrow Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions49 × 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Standard	AC 100 to 240V, 50/60
Finnish, Arabic, Indonesian, Portuguese English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Pollish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindir, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Minimum 1.0 m Throw Ratio – Maximum 1.2.0 m Throw Ratio – Maximum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 12.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 1.3.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Operating Conditions	,
Menu LanguagesRussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, asc Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1.0 mThrow Distance – Maximum12.0 mThrow Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Documentation Languages	
TechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1.0 mThrow Distance – Maximum12.0 mThrow Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Menu Languages	Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian,
Throw and Zoom Throw Distance – Minimum 1.0 m Throw Ratio – Maximum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio Maximum 2.16:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Phoduct Weight 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Security Features	Kensington lock port
Throw Distance – Minimum 1.0 m Throw Distance – Maximum 12.0 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	TechStation	
Throw Distance – Maximum 12.0 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw and Zoom	
Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Minimum	1.0 m
Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Maximum	12.0 m
Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Minimum	1.94:1
Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Maximum	2.16:1
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Zoom Ratio	1.1:1
Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Shipping	
Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Dimensions	
Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Weight	
		7.7 x 13.3 x 15.7 in /
	Shipping Weight	

^{*} Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1)
Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
InFocus Standard Replacement Remote (HW-NAVIGATOR-5)

DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

Soft Carry Case for Value Projectors (CA-SOFTVAL-2)

Soft Projector Carry Case (CA-SOFTCASE-VAL3) Soft Projector Carry Case (CA-SOFTCASE-MTG2) SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

 $LiteShow\ 4\ DB+\ Dual\ Band\ Wireless\ Adapter\ (INLITESHOW4DB+)$

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)

Projector Lamp for the SP2080HD and IN130/IN130ST/IN2130 Series (SP-LAMP-101)