

TTER HOME PRODUCT

SOMA COLLECTION SPECIFICATIONS

SATIN NICKEL FINISH





(BHP) ITEM# 20126DC - Passage Set

Grade III tubular passage set. All metal components


Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4" Function: Both levers always free

Strike - Full lip radius corner standard. Other options available Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius

corner face plate standard. Other options available





(BHP) ITEM# 20226DC - Privacy Set

Grade III tubular privacy set. All metal components **Door Prep** - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"

Function - Both sides lever locked or unlocked by center turn-button


inside. Also can be opened by emergency key out side

Strike - Full lip radius corner standard. Other options available

Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner

face plate standard. Other options available





(BHP) ITEM# 20426DC - Push Button Privacy Set

Grade III tubular privacy set. All metal components **Door Prep** - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"


Function - Both sides lever locked by center push button inside. Inside

always open. Also can be opened by emergency key out side Strike - Full lip radius corner standard. Other options available

Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner

face plate standard. Other options available





BHP ITEM# 20326DC - Dummy Lever

Grade III dummy lever. All metal components


Door Prep - Surface mounted with 2 exposed mounting screws. No door prep needed

Door Thickness - greater than 1"

Function: Active lever, for doors where only a pull / push is required.

Door Handing - Non - handed





(BHP) ITEM# 25526DC - Entry Set

Grade III tubular Lever-Lever entry set. All metal components

Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"

Function: Both sides locked or unlocked by key out side or center turn-

button inside


Cylinder - 5 pins, Kwikset® KW 1 keyway

Strike - Full lip radius corner standard. Other options available

Latch - 1/2" throw dead latch, 2 3/8" or 2 3/4" backset adjustable. Radius

corner face plate standard. Other options available





(BHP) ITEM# 20926DC - Trim Lever

Grade III handleset trim lever, works for all BHP offering handlesets.

All metal components

Door Prep - See BHP handleset door prep

Door Thickness - 1 3/8" to 1 3/4"

Function: Lever always free