

Power Cord Kit (6 EA), Locking, C19 TO C20, 0.6M (2FT), Red

AP8712SX340

Call for More Information 0800 2799254



Output	
Cord Length	0.6meters
Maximum Total Current Draw	16
Output Connections	(1) IEC 60320 C19

Input	
Input Connections	IEC 60320 C20
Cord Length	0.6meters
Number of Power Cords	6
Maximum Input Current	16A
Maximum Line Current	16A

Physical	
Maximum Height	300MM, 30.0CM
Maximum Width	60MM, 6.0CM
Maximum Depth	65MM, 6.5CM
Net Weight	1.12KG
Shipping weight	1.12KG
Shipping Height	300MM, 30.0CM
Shipping Width	65MM, 6.5CM
Shipping Depth	60MM, 6.0CM
Color	Red
Units per Pallet	390.0

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Temperature	0 - 75 °C
Operating Relative Humidity	20 - 80 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 75 °C
Storage Relative Humidity	20 - 80 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CCC, CSA, PSE, UL listed, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.