



Overview

Description	Specialized enclosures with integrated cooling, noise dampening, and power distribution for server and network applications in office environments.
Model Name	NetShelter CX 38U in colour Black Intl.
Includes	Casters , Installation guide , Key(s) , Leveling feet , Rack Power Distribution Unit (PDU) , Side Panels
Standard Lead Time	Special Order - Call for Quoted Lead Times
Product Distribution	Albania , Algeria , Andorra , Angola , Armenia , Australia , Austria , Azerbaijan , Bahrain , Belarus , Belgium , Benin , Bosnia And Herzegovina , Botswana , Bulgaria , Burkina Faso , Burundi , Cameroon , Cayman Islands , Central African Republic , Chad , China , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Croatia , Cyprus , Czech Republic , Denmark , Djibouti , Egypt , Equatorial Guinea , Eritrea , Estonia , Ethiopia , Finland , France , Gabon , Gambia , Georgia , Germany , Ghana , Gibraltar , Greece , Guinea , Hong Kong , Hungary , Iceland , Iran (Islamic Republic Of) , Iraq , Ireland , Israel , Italy , Jordan , Kazakhstan , Kenya , Kuwait , Latvia , Lebanon , Lesotho , Liberia , Liechtenstein , Lithuania , Luxembourg , Macedonia , Malawi , Mali , Malta , Mauritania , Moldova, Republic Of , Mongolia , Morocco , Mozambique , Namibia , Netherlands , New Zealand , Niger , Nigeria , Norway , Oman , Pakistan , Poland , Portugal , Romania , Russian Federation , Rwanda , Saudi Arabia , Senegal , Sierra Leone , Slovakia (Slovak Republic) , Slovenia , Somalia , South Africa , Spain , Sudan , Suriname , Sweden , Switzerland , Taiwan , Tajikistan , TANZANIA, UNITED REPUBLIC OF , Togo , Turkey , Turkmenistan , Uganda , Ukraine , United Arab Emirates , Uzbekistan , Western Sahara , Yemen , Zambia , Zimbabwe

Input

Nominal Input Voltage	200V , 208V , 220V , 230V , 240V
Input Frequency	50/60 Hz
Input Connections	IEC-320 C14

Physical

Net Weight	202.5 kg
Maximum Height	1950.0 mm
Maximum Width	750.0 mm
Maximum Depth	1130.0 mm
Shipping Weight	230.0 kg
Shipping Height	2150.0 mm
Shipping Width	800.0 mm
Shipping Depth	1200.0 mm
Minimum Mounting Depth	28.35

Maximum Mounting Depth	34.65
Rack Height	38 U
Color	Black
Units per Pallet	1.0

Conformance

Approvals	EIA 19 Inch , TAA compliance
Standard warranty	2 year (manufacturer's defect)

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs