

Fiber Media Converter Gigabit 1000Mbps MM Fibre LC 550m

**Product ID:** ET91000LC2



The ET91000LC2 1000 Mbps Gigabit Multimode Fiber Media Converter (LC, 550m) lets you extend a Gigabit Ethernet network over multimode fiber, at distances up to 550m (1804 ft).

A cost-effective solution for connecting a Gigabit Ethernet (1000Base-T) network to remote network segments over a (1000Base-LX/SX) fiber backbone, this GbE to MM fiber converter supports full Gigabit speeds for ideal network performance and scalability. Designed to offer a durable and convenient Ethernet-to-fiber solution, the Ethernet to LC Fiber converter features an all-steel chassis, and a simple plug-and-play installation with minimal configuration required.

For added versatility, this fiber media converter supports standalone operation, as well as a replaceable SFP slot.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

### Applications

- Provides connectivity to a user or network segment that is in an isolated area of a large complex or in another building altogether
- Perfect for secure connections required by government agencies where EMI is not acceptable
- Connect traffic control/monitoring systems at extreme distances to the main office
- Extend network connectivity to remote areas of stadiums, auditoriums or other venues
- Converts 1000Base-LX fiber optic signals to 1000Base-T Ethernet over multi mode fiber cable

## Features

- SFP can be removed from the unit, for replacement or swapping to a different specification
- Cost-effective way to extend/bridge networks using fiber cabling
- Advanced features include Link-loss forwarding, remote monitor status, two frame lengths
- Maximum Fiber Cable length of 550m
- Supports full or half-duplex operation
- Easy to use and install
- Jumbo Frame support

---

### Hardware

Warranty	2 Years
PoE	No
WDM	No

---

### Performance

Maximum Data Transfer Rate	2000 Mbps (full duplex mode)
Max Transfer Distance	550 m (1804 ft)
Type	Multi Mode
Wavelength	850nm
Fiber Operating Mode	Half/Full-Duplex
Auto MDIX	Yes
MTBF	65,000 Hours

---


### Connector(s)

Local Unit Connectors	Fiber Optic LC Duplex RJ-45
-----------------------	--------------------------------

---

### Power

Power Source	AC Adapter Included
--------------	---------------------



Input Voltage	100 - 240 AC
Input Current	0.36A
Output Voltage	12V DC
Output Current	1.6 A
Center Tip Polarity	Positive
Plug Type	M
Power Consumption (In Watts)	4

---

#### Environmental

Operating Temperature	0C to 60C (32F to 140F)
Storage Temperature	-10C to 70C (14F to 158F)
Humidity	10~90% RH

---

#### Physical Characteristics

Color	Black
Material	Steel
Product Length	6.3 in [16 cm]
Product Width	3.7 in [95 mm]
Product Height	0.8 in [20 mm]
Weight of Product	14.3 oz [405 g]

---

#### Packaging Information

Package Length	5.4 in [13.8 cm]
Package Width	8.1 in [20.6 cm]
Package Height	3.5 in [89 mm]
Shipping (Package) Weight	27.3 oz [774 g]

---

#### What's in the Box

Included in Package	Fiber Media Converter
---------------------	-----------------------

Universal power adapter: comes ready for NA/EU/UK only when you buy in NA/EU/UK; comes ready for Australia and New Zealand only when you buy in Australia and New Zealand

Grounding Screw

Instruction Manual

---

***\*Product appearance and specifications are subject to change without notice.***

