

# SBPAR3I15K20R2M2-WP

## APC Parallel Maintenance Bypass for 2 UPS (1+1) 3:1 15-20kVA Wallmount



### Purchase

APC  
[SBPAR3I15K20R2M2-WP](#)

### Overview

Model Name	APC Parallel Maintenance Bypass for 2 UPS (1+1) 3:1 15-20kVA Wallmount
Includes	Installation guide
Standard Lead Time	Usually Ships within 4 Weeks
Product Distribution	Andorra , United Arab Emirates , Afghanistan , Albania , Armenia , Angola , Austria , Australia , Azerbaijan , Bosnia And Herzegovina , Bangladesh , Belgium , Burkina Faso , Bulgaria , Bahrain , Burundi , Benin , Brunei Darussalam , Bhutan , Botswana , Belarus , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Central African Republic , Congo , Switzerland , Cote D'Ivoire , Cook Islands , Cameroon , China , Serbia And Montenegro , Cyprus , Czech Republic , Germany , Djibouti , Denmark , Algeria , Estonia , Egypt , Western Sahara , Spain , Ethiopia , Finland , Fiji , France , Gabon , United Kingdom , Georgia , French Guiana , Ghana , Gibraltar , Gambia , Guinea , Guadeloupe , Equatorial Guinea , Greece , Hong Kong , Croatia , Hungary , Indonesia , Ireland , Israel , India , Iraq , Iran (Islamic Republic Of) , Iceland , Italy , Jordan , Kenya , Cambodia , KOREA, REPUBLIC OF , Kuwait , Kazakhstan , Lebanon , Liechtenstein , Sri Lanka , Liberia , Lesotho , Lithuania , Luxembourg , Latvia , Morocco , Moldova, Republic Of , Madagascar , Macedonia , Mali , Myanmar , Martinique , Mauritania , Malta , Mauritius , Malawi , Malaysia , Mozambique , Namibia , Niger , Nigeria , Netherlands , Norway , Nepal , New Zealand , Oman , Papua New Guinea , Philippines , Pakistan , Poland , Portugal , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Sudan , Sweden , Singapore , Slovenia , Slovakia (Slovak Republic) , Sierra Leone , Senegal , Somalia , Turks And Caicos Islands , Chad , Togo , Thailand , Turkmenistan , Tunisia , East Timor , Turkey , Taiwan , TANZANIA, UNITED REPUBLIC OF , Ukraine , Uganda , Uzbekistan , Viet Nam , Yemen , Mayotte , South Africa , Zambia , Zimbabwe

### Output

Nominal Output Voltage	220V
Output Connections	(1) Hard Wire 3-wire (H N + G) (Battery Backup)

### Input

Nominal Input Voltage	400V 3PH
-----------------------	----------

## Physical

Net Weight	100 kg
Maximum Height	1200 mm
Maximum Width	1010 mm
Maximum Depth	800 mm
Shipping Weight	120 kg
Shipping Height	1600 mm
Shipping Width	1200 mm
Shipping Depth	800 mm

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-9000 meters

## Conformance

Approvals	EN 50091-2 , EN/IEC 62040-1-1 , EN/IEC 62040-3 , VFI-SS-111
Standard warranty	1 year repair or replace