

USB 3.0 to Gigabit Ethernet NIC Network Adapter – 10/100/1000 Mbps

Product ID: USB31000NDS



The USB31000NDS USB 3.0 to Gigabit Ethernet Network Adapter adds a single RJ45 Ethernet port to a USB-enabled computer system, with support for Gigabit network connections at full bandwidth when used with a USB 3.0 host connection, unlike USB 2.0 adapters.

This compact USB 3.0 NIC works with 10/100/1000 Mbps networks and offers backward compatibility with USB 2.0/1.x computer systems (speed limited by USB bus), making it an ideal portable replacement LAN adapter or laptop accessory. Support for features such as Jumbo Frames, VLAN tagging and Wake on LAN (WOL), provides versatile Gigabit network performance for home or business use.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility

Applications

- Add Gigabit Ethernet capabilities to a desktop or laptop
- Replace a failed integrated network adapter with an external, USB Ethernet solution to avoid opening the computer case

Features

- Full Gigabit bandwidth support over USB 3.0
- IEEE 802.3, 802.3u and 802.3ab (10BASE-T, 100BASE-TX, and 1000BASE-T) compatible
- USB-Powered



- Crossover Detection & Auto-Correction (Auto MDIX)
- IEEE 802.1Q VLAN Tagging support
- Jumbo Frame support
- Supports Checksum Offload (IPv4, IPv6, TCP, UDP) and Large Send Offload
- Activity and Link LED indicators
- Compact, lightweight design

Hardware		
	Warranty	2 Years
	Ports	1
	Interface	RJ45 (Gigabit Ethernet)
	Bus Type	USB 3.0
	Industry Standards	IEEE802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az
	Chipset ID	ASIX - AX88179A
Performance		
	Maximum Data Transfer Rate	1Gbps (Gigabit Ethernet)
	Max Distance	100 m / 330 ft
	Type and Rate	USB 3.0 - 5 Gbit/s
	Compatible Networks	10/100/1000 Mbps
	Auto MDIX	Yes

Yes

4K max.

Connector(s)

Connector Type(s) RJ-45

Full Duplex Support

Jumbo Frame Support

USB Type-A (9 pin) USB 3.0 (5 Gbps)

Software



OS Compatibility Windows XP, Vista, 7, 8, 8.1, 10, 11

Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019

macOS 10.6 to 10.15, 11.3 and up <i>VLAN tagging is currently

not supported in macOS</i>

Linux Kernel 2.6.25 to 4.11.x <i>LTS Versions only</i>

Special Notes / Requirements

System and Cable Requirements

Host computer system with an available USB 3.0/2.0 port

Indicators

LED Indicators Link (Green)

Activity (Yellow)

Power

Power Source USB-Powered

Environmental

Operating Temperature 0C to 50C (32F to 122F)

Storage Temperature 0C to 70C (32F to 158F)

Humidity 10~90% RH

Physical Characteristics

Color Black

Form Factor Dongle

Material Plastic

Product Length 2.7 in [68 mm]

Product Width 0.9 in [22.6 mm]

Product Height 1.0 in [26 mm]

Weight of Product 0.8 oz [22 g]

Packaging Information

Package Length 6.8 in [17.3 cm]



Package Width	5.5 in [14 cm]

Package Height 1.3 in [32 mm]

Shipping (Package) Weight

3.5 oz [98 g]

What's in the Box

USB 3.0 to Gigabit Ethernet Adapter Included in Package

Driver CD

Instruction Manual

^{*}Product appearance and specifications are subject to change without notice.