

## USB 3.0 to VGA Adapter - On-Board Driver Installation - 1920x1200

**Product ID:** USB32VGAV



This USB 3.0 to VGA video adapter works as an external video card, enabling the USB port on your computer to output video to a VGA display at 1920 x 1200 resolution. The adapter also features on-board driver installation, which means the adapter will work when you connect it, even without a software disc or Internet connection.

For the ultimate in hassle-free installation, this USB video adapter features on-board drivers which prompts for installation as soon as you connect the adapter to your Ultrabook or laptop computer. This means you can maximize portability by never requiring an installation disc or Internet connection to install the device.

Adding a second or third display to your computer can vastly increase your productivity by giving the freedom to access more applications at the same time. This video adapter is intended to support all of your business applications including web browsing, e-mail, spreadsheets and presentations. You can also leave your system video card available for more demanding applications such as gaming or CAD design, while you use the USB monitor for reference material.

Using the high-bandwidth USB 3.0 interface, this adapter enables smoother scrolling through documents, higher refresh rates and an overall enhanced performance over USB 2.0. The adapter is optimized for use with USB 3.0, but for added compatibility this adapter is also backward compatible with USB 2.0 computer systems supporting an 800 x 600 resolution at 60Hz.

The USB32VGAV is backed by a 2-year StarTech.com warranty and free lifetime technical support.

## Certifications, Reports and Compatibility

### Applications

- Install an external video card on a device that does not have a CD-ROM or Internet connection
- Increase productivity by running multiple applications on different displays; check your email on one display while

editing a document on the other

- Add a secondary VGA display to your desktop without taking apart your computer to install a new video card
- View large or multiple spreadsheets across multiple displays

## Features

- Hassle-free setup while you're on the go, with drivers that install automatically without an Internet connection or software disc
- Increase productivity by connecting an additional display using a USB port
- Exceptional external performance with support for video resolutions up to 1920x1200
- USB-powered operation with no external power adapter required
- Versatile connectivity options support for both USB 3.0 and 2.0 computers

---

### Hardware

Warranty	2 Years
AV Input	USB 3.0
AV Output	VGA
USB Pass-Through	No
Memory	8MB
Industry Standards	SuperSpeed USB 3.0, USB 2.0
Chipset ID	Fresco - FL2000DX

---

### Performance

Maximum Analog Resolutions	USB 3.0: 1920x1200 USB 2.0: 800x600
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720  Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600



Wide Screen Supported	Yes
General Specifications	<p>Recommended System Requirements:</p> <p>Core 2.4GHz or higher processor (i5 recommended)</p> <p>4GB of RAM</p> <p>This USB video adapter uses a Fresco family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a DisplayLink or Trigger family chipset.</p>
MTBF	1,138,683 hours

---

#### Connector(s)

Connector A	USB Type-A (9 pin) USB 3.0 (5 Gbps)
Connector B	VGA (15 pin, High Density D-Sub)

---

#### Software

OS Compatibility	<p>Windows Vista, 7, 8, 8.1, 10, 11</p> <p>Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019</p> <p>Linux 2.6.31 to 4.11.x &lt;i&gt;LTS versions only&lt;/i&gt;</p>
Microsoft WHQL Certified	Yes

---

#### Special Notes / Requirements

System and Cable Requirements	<p>System Processor: Quad Core 2.4GHz (i5 recommended)</p> <p>System Memory: 4GB</p>
Note	<p>This USB video adapter uses a Fresco Logic family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, avoid using devices with different family chipsets, such as DisplayLink or Trigger</p> <p>Connect a maximum of 6 USB video adapters on a single computer. Support for multiple adapters will vary depending upon your system resources</p> <p>This USB video adapter is not intended for graphical intensive applications, such as gaming</p>

---

#### Environmental

Operating Temperature	0C to 70C (32F to 158F)
Storage Temperature	-10C to 55C (14F to 131F)



Humidity 40%~50% RH

---

**Physical Characteristics**

Cable Length	5.5 in [14.0 cm]
Product Length	7.7 in [19.5 cm]
Product Width	1.0 in [25.0 mm]
Product Height	0.5 in [12.0 mm]
Weight of Product	0.8 oz [22.0 g]

---

**Packaging Information**

Package Length	8.7 in [22.0 cm]
Package Width	5.0 in [12.8 cm]
Package Height	0.5 in [12.0 mm]
Shipping (Package) Weight	0.8 oz [22.0 g]

---

**What's in the Box**

Included in Package	USB 3.0 to VGA adapter
	Quick install guide

---

***\*Product appearance and specifications are subject to change without notice.***

