



DIGISOL™

SWITCHING SOLUTIONS

DIGISOL L2 Gigabit Dual Stack Intelligent Switches

DG-GS4628HPE-P



Key Features:-

- Energy Efficient with Energy saving feature & Fan less design
- Advanced Security features including RADIUS & TACACS+ Authentication
- Supports Ethernet Ring Protection Switching (ERPS)
- Supports Multicast Features including MVR (Multicast VLAN Register)



Introduction:-

DIGISOL DG-GS4628HPE-P switch is a Layer 2 Gigabit intelligent switch. It supports comprehensive QoS, enhanced VLAN functions (VLAN VPN, Voice VLAN, QinQ, N: 1 VLAN Translation etc), Ethernet Ring Protection Protocol (G.8032), classified bandwidth control, intelligent security control, OAM (Operations, Administration and Maintenance), manageability functions and Triple-Play services. DG-GS4628HPE-P switch also offers green features like IEEE 802.3az (Energy Efficient Ethernet), Fanless design feature, which can dramatically lower power consumption. This switch with full GE ports and 4 SFP uplink ports, integrates advanced management and security functions to provide performance and scalability.

Technical Specifications:-

HARDWARE FEATURES

Ports

- 24x10/100/1000Base-T
- + 4 x 1000Base-SFP

Performance

- Switching Capacity : 56Gbps
- Forwarding Rate : 41.7Mpps
- MAC address : 16K
- Jumbo Frame : 12K

- ACL Table : 2K
- Queues Per Port : 8
- VLAN Table : 4K

Physical

- Dimension (W×H×D) : 440mm x 260mm x 43.6mm
- Power Input : 100~240VAC, 50~60Hz

- Temperature Working : 0°C~50°C, Storage -40°C~70°C
- Relative Humidity : 5%~95%, non-condensing
- PoE : IEEE 802.3af POE (15.4W), IEEE 802.3at POE+ (30W), PoE Budget: 370w



DIGISOL™

SWITCHING SOLUTIONS

Technical Specifications:-

MAIN FEATURES

• Storage & Forwarding

VLAN

- Port-based VLAN
- IEEE802.1Q
- Private VLAN
- Protocol VLAN
- Voice VLAN
- MAC VLAN
- Q-in-Q, Selective QinQ, Flexible QinQ
- VLAN Translation, N:1 VLAN Translation

DHCP

- IPv4/ IPv6 DHCP Client
- IPv4/ IPv6 DHCP Relay Option 82, Option 37/38
- IPv4/ IPv6 DHCP Snooping
- IPv4/ IPv6 DHCP Server

• Reliability

SPANNING TREE PROTOCOL

- 802.1D Spanning Tree
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree
- Root Guard
- BPDU Guard
- BPDU Forwarding

LACP

- 16 groups / 8 ports

L2 Ring Protection

- MRPP
- ITU-T G.8032

- Loopback Detection
- Fast Link

• Security Features

- IP ACL, MAC ACL, MAC-IP ACL, User-Defined ACL
- Time Range ACL
- ACL on VLAN interface
- Storm Control based on packets & bytes
- Port Security, MAC Limit based on VLAN and Port
- Anti-ARP-Spoofing, Anti-ARP-Scan, ARP Binding
- ND Snooping
- Dynamic ARP Inspection (DAI)
- IEEE 802.1x
- Authentication, Authorization, Accounting
- Radius & TACACS+

• Multicast

- IGMP Snooping (V1,v2,v3)
- IGMP Fast Leave
- MLD v1/ v2 Snooping
- MVR

• QOS Features

- 8 Queue Per Port
- Bandwidth Control
- Flow Redirect
- Classification based on
 - ACL (Access Control List)
 - VLAN ID
 - COS
 - TOS

- DSCP
- Policy Based on Port & VLAN
- Remark DSCP, COS/ 802.1p, Precedence, TOS
- SP, WRR, SWRR, DWRR for Scheduling
- Match the IP fragmentation of message

• Maintenance & Operation Management

- TFTP/FTP
- CLI, Telnet, Console
- Web/SSL (IPv4/IPv6)
- SSH (IPv4/IPv6)
- SNMPv1/v2c/v3
- SNMP Trap
- Public & Private MIB interface
- RMON 1,2,3,9
- Ping, Trace Route
- Radius Authentication
- Syslog (IPv4/IPv6)
- SNT/NT/PT (IPv4/IPv6)
- Dual IMG, Multiple Configuration Files
- Port Mirror, CPU Mirror, RSPAN
- VCT, DDM
- OAM
- ULDP (Like Cisco UDLD)
- LLDP/LLDP MED

• Green Energy

- IEEE 802.3az (Energy Efficient Ethernet)
- FAN less and Smart FAN design
- LED Shut-Off

Ordering Information:-

DG-GS4628HPE-P: DIGISOL L2 Gigabit Intelligent Ethernet PoE Switch with 24*10/100/1000Base-T and 4*100/1000Base-SFP ports

*Lifetime Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2017 DIGISOL SYSTEMS LIMITED. All rights reserved.

DIGISOL is a Subsidiary of Smartlink Network Systems Ltd.

DIGISOL SYSTEMS LIMITED
Smartlink House,
Plot No. 5, Off CST Road,
Bandra-Kurla Complex Road,
Santacruz (East), Mumbai - 400 098.

1800-209-3444
www.digisol.com
helpdesk@digisol.com

f@DIGISOLINDIA t@DIGISOL_SNSL