
WorkForce Enterprise WF-C21000 D4TW





Print up to 100,000 pages in mono or 50,000 in colour without changing the supplies. This reliable, low maintenance 4-in-1 device² offers high-speed performance, superior image quality, all with significant sustainability advantages over laser models.

Superior quality at high speeds

The WorkForce Enterprise WF-C21000 delivers superior image quality at print speeds of up to 100ppm and a fast first copy out time (FCOT) of 4.9 seconds. **Super high ink yield**

Print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies. This means there is even less need for user intervention. Through fewer consumables and supplies, it also produces less waste. With ultra-low power consumption, the overall environmental impact of printing is cut dramatically.

Robust, high-end finishing capability

With advanced finishing such as booklet finisher and hole punch options, this device offers advanced finishing capability. It also offers a high paper capacity of up to 5,350 pages, increasing productivity further.

Heat-free technology

Epson Heat-Free Precision Core Technology requires no heat to warm up when it is switched on or awoken from sleep, which significantly reduces energy consumption. This allows Epson's Heat-Free inkjets to deliver an fast FCOT compared to laser technology.

Advanced software solution compatibility

A variety of software solutions can be integrated into existing IT infrastructure to improve efficiency. This includes Epson's new Epson Remote Services (ERS) which offers cloud-based device monitoring and management system that delivers advanced remote diagnostics for Epson business products.

DATASHEET / BROCHURE



















KEY FEATURES

- Faster performance
 Fast FCOT of 4.9 seconds and print speeds of up to 100ppm
- High capacity ink yield
 Users can print up to 100,000 pages in mono or 50,000 in colour without changing the ink supplies¹
- Improved finishing capability
 Robust finishing such as booklet finisher and hole punch options
- Powerful scanning capability
 Thin paper support and improved quality of scanning
- Works with Epson Remote Services
 Cloud based, advanced diagnosis of
 Epson printers and MFPs



PRODUCT SPECIFICATIONS

TECHNOLOGY

PrecisionCore™ Micro TFP printhead Printing Method Nozzle Configuration 8.676 Nozzles Black, 8.676 Nozzles per Color

Minimum Droplet Size 3,5 pl

DURABrite™ Pro Ink Technology Category Office Departmental All-in-One Functions Print, Scan, Copy

PRINT

First Page Out Monochrome 4.9 Seconds, Colour 4.9 Seconds Printing Speed ISO/IEC 24734 100 pages/min Monochrome, 100 pages/min Colour **Duplex Printing Speed** 100 A4 Pages/min Monochrome, 100 A4 Pages/min Colour

ISO/IEC 24734

Printing Speed ISO/IEC 24734 54 pages/min Monochrome, 54 pages/min Colour

Maximum Printing Speed 100 pages/min Monochrome (plain paper 75 g/m²), 100 pages/min Colour (plain paper 75 g/m²)

600 x 2.400 DPI **Printing Resolution** Printing Volume 400.000 pages per month

The maximum number of printed pages per month based on the performance capabilities of

the printer, including ISO rated print speeds and paper handling capabilities.

Recommended Duty Cycle 8.000 - 100.000 pages per month

Colours Black, Cyan, Yellow, Magenta

For detailed information on printing speeds please visit http://www.epson.eu/testing.

SCAN

Double-sided scanning

60 ipm (Monochrome, Single-sided, 300 dpi, ADF); 110 ipm (Monochrome, Double-sided, Scanning Speed

300 dpi, ADF); 60 ipm (Colour, Single-sided, 300 dpi, ADF); 110 ipm (Colour, Double-sided,

300 dpi, ADF);

Optical Resolution 600 DPI x 600 DPI (Horizontal x Vertical) Optical Resolution (ADF) 600 DPI x 600 DPI (Horizontal x Vertical)

Advanced document Scan to Email, Scan to FTP, Scan to USB, Computer (Epson Document Capture Pro), USB

integration Memory Device / Card

Output formats BMP, JPEG, TIFF, multi-TIFF, PDF, PNG

Scanner type Contact image sensor (CIS)

600 DPI x 600 DPI (Horizontal x Vertical) Optical Resolution

Type of fax Walk-up black and white and colour fax capability

Fax Transmission Speed Up to 33.6kbps / Approx. 3 sec/page

CCITU/ITU Group3 fax with Error Correction Mode Error correction mode Fax speed dials (max) 2.000 names and numbers

Up to 550 pages/ 6MB (ITU-T No. 1 chart) Page memory

PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Fax to Folder, Address Book, Fax Fax Functions

Preview, Polling Reception

WorkForce Enterprise WF-C21000 D4TW

WHAT'S IN THE BOX

- Information sheet
- Power cable
- User guide



PRODUCT SPECIFICATIONS

WorkForce Enterprise WF-C21000 D4TW

COPY

Copy Speed Up to 100 ipm Black, Up to 100 ipm Colour

*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)

Copy resolution (dpi) 600 x 1200 Reduction / Enlargement 25 % - 400 % Maximum number of copies 9.999 Maximum Copy Size A3

CONNECTIVITY

IPP, LDP, Port 9100, WSD **Network Printing Protocols**

Network Management ${\sf SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping}$

Protocols

Network Protocol IPv4, IPv6

Interfaces 10 Base-T, Ethernet interface (100 Base-TX / 10 Base-T), Gigabit ethernet interface, Ethernet

> Interface (1000 Base-T/ 100-Base TX/ 10-Base-T), Wireless LAN IEEE 802.11a/b/g/n, Wi-Fi Direct, USB 1.1 Type A, USB 2.0 Type A, USB 3.0 Type B, Near Field Communication (NFC)

WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA PSK (AES) **WLAN Security** Network Protocol TCP/IPv4, TCP/IPv6, TCP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS

PAPER / MEDIA HANDLING

A3, A4, Postcard, A3+, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL Paper Formats

(Envelope), Executive, Letter, Legal, HLT, No. 10 (Envelope), User defined

Automatic Document Feed 150 pages 60 g/m² - 350 g/m² Compatible Paper Weight Duplex Yes (A4/A3, plain paper)

2.350 Sheets Standard, 150 Sheets MP tray, 550 Sheets paper tray Standard Paper input

Output Tray Capacity 550 Sheets Maximum paper input 5.350 Number of paper trays 4

PAPER FEED RASF

Paper Input Name

A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope), Paper Formats

Letter, 20 x 25 cm, HLT, User defined, SRA3 $\,$

Min 55x 330 mm to Max 127x 1.200 mm

60 g/m² - 350 g/m² Compatible paper weight Paper Capacity 1 150 80gsm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED C1

Paper Input Name

Paper Formats A3, A4, A5, B4, B5, Letter, HLT, Executive Min 140x 297 mm to Max 182x 432 mm Custom sizes

Compatible paper weight 60 g/m² - 160 g/m² Paper Capacity 1 550 80gsm

Plain Paper, Recycled Paper, Colour Paper, Letterhead Media type

{SPECGROUPNAMEPAPERFEEDC2-C4} C2-C4

Paper Input Name Paper Formats A3, A4, A5, B4, B5, Letter, HLT

Custom sizes Min 140x 297 mm to Max 182x 432 mm

60 g/m² - 160 g/m² Compatible paper weight

Paper Capacity 1 550 80asm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead

PAPER FEED LCT

Paper Input Name LCT A4, Letter Paper Formats Compatible paper weight 60 g/m² - 160 g/m² Paper Capacity 1 3.000 80asm

Media type Plain Paper, Recycled Paper, Colour Paper, Letterhead



PRODUCT SPECIFICATIONS

PAPER FEED DUPLEX

Paper Input Name Duplex

Compatible paper weight 60 g/m² - 160 g/m²

GENERAL

Energy Use 170 Watt (standalone copying, ISO/IEC 24712 pattern), 1,1 Watt (sleep mode), 76 Watt

(Ready), 0,1 Watt (Power off), TEC 0,4 kWh/week

AC 100 V - 240 V, 50 Hz - 60 Hz Supply Voltage

Product dimensions 674 x 757 x 1.243 mm (Width x Depth x Height)

177.1 ka Product weight

Compatible Operating Mac OS 10.10.x, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X 10.11.x, Mac OS X

10.12.x, Mac OS X 10.13.x, Mac OS X 10.6.8, Windows 10 (32/64 bit), Windows 7 (32/64 bit), Systems

Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2003 R2 x64, Windows Server 2003 SP2, Windows Server 2008 R2, Windows Server 2016, Windows Vista (32/64 bit),

Windows XP SP3, Windows XP SP3 or later (32-bit), Windows Server 2003 SP2 or later, XP

Professional x64 Edition SP2 Sound Power Operation: 7.5 B (A)

Noise Operation: 60 dB (A) 220V, 240V Power supply

ADDITIONAL FEATURES

Features Touchscreen

Type: Color, Touchscreen, Diagonal: 22,7 cm

Media Handling Duplex (A4/A3, plain paper)

Security Functions Limit access function with Epson Web Config, Secure confidential printing with PIN code

release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin

Mode

OTHER FEATURES

Emulations PCL5c, PCL6, PostScript 3, PDF 1.7, ESC/P, ESC/P-R, PCL5e, ESC/Page, ESC/Page-Colour

SUPPLIES

• WorkForce Enterprise Staple Cartridge for Booklet Finisher

• WorkForce Enterprise Staple Cartridge for Staple Finisher

Maintenance box

• WorkForce Enterprise WF-C21000 Magenta Ink

• WorkForce Enterprise WF-C21000 Cyan Ink

INK YIELD DATA

55166

D4TW

50.000 pages*

50.000 pages*

Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

WorkForce Enterprise WF-C21000

• WorkForce Enterprise WF-C21000 Yellow Ink

WorkForce Enterprise WF-C21000 Black Ink

C12C935411

C12C935401 C13T671300

C13T02Y400 50.000 pages

C13T02Y300 50.000 pages C13T02Y200 50.000 pages

C13T02Y100 50.000 pages

OPTIONAL ACCESSORIES

Cassette Lock

C12C933231

• 3000-sheet High Capacity Paper Tray

C12C933041

WorkForce Enterprise Saddle Unit

C12C935801 WorkForce Enterprise Staple Finisher

C12C935501

• WorkForce Enterprise 2/4 Hole Punch Unit

C12C935171 • WorkForce Enterprise Booklet Finisher

C12C935071

• WorkForce Enterprise Finisher Bridge Unit

C12C935101

• Super G3/G3 Fax Board C12C934491



PRECISIONCORE C11CH88401 8715946677040 EAN code

Epson Italia SpA, .: 211 1986212 fax: 210-6828615 info@epson.gr www.epson.gr

Seiko Epson Corporation

1. ¹Approx. page yield with the WF-C20600. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield.

2. ²Fax optional at an additional cost

