

Philips Signage Solutions
OPS accessory

HDbaseT receiver
OPSinsert compatible

SignageSolutions

CRD25

Future Proof Connectivity

With HDBaseT OPS receiver

Making use of leading technology standards, the HDBaseT OPS receiver integrated within the OPSinsert provides you with a powerful combination and a unique all-in-one solution

Innovative solutions for any signage application

- Optional OPS Insert to create an all-in-one solution
- OPS receiver module enables reception of HDbaseT signals



CRD25/00

Highlights

Specifications

Related Products

 Compatible with: BDL4256ET, BDL4260EL, BDL4271VL, BDL4280VL, BDL4660EL, BDL4671VL, BDL4677XH, BDL4678XL, BDL4680VL, BDL4765EL, BDL5551EL, BDL5556ET, BDL5560EL, BDL5571VL, BDL5580VL, BDL5588XH, BDL5588XL

Supported Display Resolution

Computer formats

Resolution	Refresh rate
1280×768	60Hz
1280×800	60Hz
1360×768	60Hz
1366 x 768	60Hz
1440×900	60Hz
$1920 \times 1080p$	60Hz
640 x 480	60, 67, 72, 7

800 x 600
• Video formats

 Resolution
 Refresh rate

 1080i
 50, 60Hz

 1080p
 50, 60Hz

 480i
 60Hz

 480p
 60Hz

576i 50Hz 576p 50Hz 720p 50, 60Hz

Dimensions

• Set dimensions (W x H x D): 141.1 x 23.5 x 105.8 mm

Operating conditions

- Altitude: 0 ~ 3000 m
- Relative humidity: 20 ~ 80 %
- Temperature range (operation): 0 \sim 40 $^{\circ}$ C
- Temperature range (storage): -20 ~ 60 °C
- MTBF: 60,000 hour(s)

Miscellaneous

- Regulatory approvals: CB, CE, C-Tick, FCC, Class B, RoHS, UL/cUL, VCCI
- · Warranty: 3 year warranty

Accessories

Included accessories: Quick start guide, RS232 cable

OPS Insert



Turn your display into an all-in-one digital signage solution and create a display network which is connected, intelligent and secure. Open Pluggable Specification (OPS) is an industry standard slot into which you can add an OPS-standardized media player. This cable free solution gives you the ability to install, use or maintain your hardware whenever you need.

HDbaseT signals




HDbaseT is a connectivity standard over a single CAT5e / 6 cable, converging uncompressed full HD digital video, audio signals.

OPSInsert



56, 60, 72, 75Hz





Issue date 2022-04-21

© 2022 Koninklijke Philips N.V. All Rights reserved.

Version: 3.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 11649 EAN: 87 12581 71116 0

www.philips.com