



The VersaLink[®] C9000 Colour Printer is built on Xerox[®] ConnectKey[®] Technology. For more information, go to **www.ConnectKey.com**.

System Specifications	VersaLink [®] C9000DT	
One-Sided Speed 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 55 ppm (pages per minute) long edge feed (LEF) Up to 40 ppm Up to 32 ppm Up to 27 ppm	
Two-Sided Speed 8.5 x 11 in. / A4 8.5 x 11 in. / A4 SEF 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm / 12 x 18 in / SRA3 / 320 x 450 mm	Up to 55 ppm LEF Up to 40 ppm Up to 21 ppm Up to 19 ppm	
Monthly Duty Cycle ¹	Up to 270,000 pages / month	
Recommended Average Monthly Print Volume ²	Up to 30,000 pages per month	
Hard Drive	320 GB HDD	
Processor	1.6 GHz Dual-Core	
Memory	4 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting Tool, Role Based Permissions, Convenience Authentication Enabled	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan	

Device Specifications				
Electrical Requirements				
North America	Voltage: 110-127V +/-1 Frequency: 50/60 Hz +/			
Europe and Other Geographies	Voltage: 220-240V +/- Frequency: 50/60 Hz +/			
Power Consumption				
Printing ³	For 110V: 2.85 kWh For 220V: 2.82 kWh			
Standby Mode ³	110V: 75.3 Watts or le 220V: 73.8 Watts or le			
Sleep Mode ³	110V: 0.48 watts or less 220V: 0.53 watts or less			
Operating Environment				
Required Temperature Range (Storage)	Below 48° C, and in con	npliance with MN2-810.1	3	
Required Temperature Range (Operating)	50° to 83° F (10° to 28°	50° to 83° F (10° to 28° C) Must be 28° C or below if humidity is at 85 $\%$		
Required Relative Humidity	15% to 85% Must be 62.5% or below at 32°C			
Sound Power Levels	Printing: 6.83 B(A) or less Standby: 3.24 B(A) or less Full System (including finisher)			
	Full System (including finisher) Printing: 7.64 B(A) Standby: 3.38 B(A)			
Sound Pressure Levels	Printing: 58.2 dB or less Standby: 15.1 dB or less			
	Full System (including finisher) Printing: 58.1 dB Standby: 15.3 dB			
Boot Time (from Off to UI Ready)	Less than 60 seconds	Less than 60 seconds		
Warm-up Time (from Sleep to UI Ready)	Less than 16 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
VersaLink® C9000/DT	24.4 in. / 620 mm	28.5 in. / 723 mm	31.9 in. / 809.3 mm	178 lb. / 80.8 kg
Two Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	60.0 lb. / 27.2 kg
Tandem Tray Module	26.3 in. / 668.5 mm	28.5 in. / 723 mm	10.3 in. / 261.2 mm	74.5 lb. / 33.8 kg
High Capacity Feeder	15.3 in. / 389 mm	23.7 in. / 602.9 mm	15.0 in. / 380.01 mm	63.9 lb. / 29.0 kg
Office Finisher	22 in. / 559.8 mm	21.7 in. / 552 mm	39.8 in. / 1012 mm	61.7 lb. / 28.0 Kg
Booklet Maker (Office Finisher)	11.75 in. / 298.5 mm	23.5 in. / 597 mm	42.5 in. / 1080 mm	20.3 lb. / 9.2 Kg
BR Booklet Maker Finisher	30.28 in. / 769.2 mm	28.5 in. / 723 mm	41.5 in. / 1055.1 mm	134.3 lb. / 60.9 Kg
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
VersaLink [®] C9000/DT	32.8 in. / 833 mm	28.2 in. / 717 mm	33.4 in. / 852 mm	209.4 lb. / 95 kg
High Capacity Feeder	20.7 in. / 526 mm	29.8 in. / 756 mm	19.3 in. / 491 mm	74.3 lb. / 33.7 kg
Two Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	72.7 lb. / 33 kg

Tandem Tray Module	32.7 in. / 830 mm	33.5 in. / 850 mm	15.75 in. / 400 mm	86 lb. / 39 kg
Office Finisher	27.2 in. / 690 mm	40.2 in. / 1021 mm	25.7 in. / 654 mm	82 lb. / 37 kg
Booklet Maker Finisher	20 in. / 507 mm	30 in. / 761 mm	17.2 in. / 437 mm	31 lb. / 14 kg
BR Booklet Maker Finisher	30 in. / 764 mm	30.5 in. / 774 mm	47.4 in. / 1203 mm	169.7 lb. / 77 kg
Horizontal Transport for BR Booklet Maker Finisher	21 in. / 533 mm	23.1 in. / 589 mm	12.6 in. / 319 mm	14.3 lb. / 6.5 kg
Certifications				
To view the latest list of certifications	s, go to www.xerox.con	n/OfficeCertifications.		
Print				
First-print-out Time	As fast as 10.5 seconds colour			
	As fast as 10 seconds black			
Print Resolution	Up to 1200 x 2400 d	pi		
Page Description Languages	Adobe [®] PostScript [®] 3 [™] PCL [®] 5c, 6 PDF XPS TIFF JPEG HP-GL			
Colour Management	Embedded spot colour table with the ability to swap out PANTONE [®] approved colour table, Custom spot colour editor, optional Xerox [®] Precise Colour Management System software			
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper			
Print Features	Application Defaults Banner Pages Enable / Disable Bi-directional Real-time Status Booklet Layout Colour Adjustments (lightness, contrast, saturation, colour balance) Colour Correction Draft Mode Finishing (requires finishing) Fit to new paper size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable / Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Store dob Scalen Two-sided Printing (as default) Watermark (predefined and custom)			
Print from USB	Xerox® Earth Smart Driver Settings Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A			

Operating Systems	Windows [®] 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Server 2019 macOS [®] 10.11, 10.12, 10.13 Citrix [®] Redhat [®] Enterprise Linux [®] Fedora Core IBM [®] AIX [®] HP-UX [®] Oracle [®] Solaris SUSE [®] SAP [®] UNIX [®] Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com.	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox [®] Mobile Express Driver [®]	Makes it easy for mobile users to find, use and manage Xerox [®] and non-Xerox [®] devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox [®] and non-Xerox [®] devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox [®] Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office [®] , Ysoft [®] SafeQ [®] , Pharos [®] and others.	
Mobile Solutions and Mobile Device	e Apps	
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.	
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.	
Mopria® Certified	ConnectKey [®] Technology-enabled print devices are Mopria [®] certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android [™]) smartphone, tablet and other mobile devices instantly and easily.	
@PrintByXerox	@PrintByXerox is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.	
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox [®] Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play [™] store.	
Xerox® Workplace Suite and Xerox® Workplace Cloud	 Xerox[®] Workplace Solutions boost productivity and reduce costs with a modular print management and mobility solution. Control and manage your printer fleet while enabling mobile productivity with simplified workflows, convenience and security—for any brand printer, anywhere. Xerox[®] Workplace Solutions offer flexible license options to suit any size business with the ability to scale as you grow. Xerox[®] Workplace Suite: On site, your server Xerox[®] Workplace Cloud: Simple setup, cloud administration To learn more about the Xerox[®] Workplace Suite and Xerox[®] Workplace Cloud, visit www.xerox.com/Mobility. 	

Software Solutions	
Xerox [®] ConnectKey [®] Apps (Found at the Xerox [®] App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, Serverless ConnectKey Apps to the device.
Security	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of external programme falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL
Accounting	
Xerox® Standard Accounting / Netv	ork Accounting (Standard)
Tracking	Print usage
Accounting	Xerox® Standard Accounting ToolUp to 9,999 User AccountsUp to 500 General accountsNetwork Accounting (Job Based Accounting)Up to 60,000 User IDs; Up to 60,000 Account IDsUp to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server.
Accounting Options – Network Acco	unting (Allows central server to manage all accounting)
	 Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device print usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account
Paper Handling	
Bypass Tray	
Capacity ⁴	100 sheets
Sizes	Custom sizes: 3.5 x 3.9 in. to 12.6 x 19 in./88.9 x 98.4 mm to 320 x 482.6 mm Banners: 3.5 x 3.9 in. to 12.6 x 52 in./88.9 x 98.4 mm to 320 x 1320.8 mm
Weights	Simplex: 18 lb. bond to 130 lb. cover/64 to 350 gsm Duplex: 18 lb. bond to 110 lb. cover/64 to 300 gsm

Types	BondPlain PaperCardstockCustomEnvelopesExtra Heavyweight CardstockExtra Heavyweight Glossy CardstockGlossy CardstockHole PunchedLabelsHeavyweight Glossy CardstockLabelsHeavyweight Glossy CardstockLetterheadLightweight CardstockLightweight Glossy CardstockPre-PrintedPostcardsRecycled	
Tray 1 and 2		
Capacity ⁴	520 sheets each	
Sizes	Tray 1: 3.9 x 5.8 in. to 11.7 x 17 in./100 x 148 mm to 297 x 431.8 mm Tray 2: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm	
Weights	18 lb. bond to 110 lb. cover/64 to 300 gsm	
Types	BondPlain PaperCardstockCustomGlossy CardstockHole PunchedLabelsHeavyweight CardstockHeavyweight Glossy CardstockLightweight CardstockLightweight CardstockReryPrintedRecycled	
Two Tray Module		
Capacity ⁴	1,040 sheets	
Sizes	Custom sizes: 3.9 x 5.8 in. to 12.6 x 18 in./100 x 148 mm to 320 x 457.2 mm	
Weights	18 lb. bond to 110 lb. cover/64 to 300 gsm	
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
Tandem Tray Module		
Capacity ⁴	2,000 sheets	
	8.5 x 11 in., 7.25 x 10.5 in./A4, B5	
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5	

Types	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Labels Heavyweight Cardstock Heavyweight Glossy Cardstock Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Pre-Printed Recycled	
High Capacity Feeder		
Capacity ⁴	2,000 sheets	
Sizes	8.5 x 11 in., 7.25 x 10.5 in./A4, B5	
Weights	18 lb. bond to 95 lb. cover/64 to 216 gsm	
Types	Bond Plain Paper Cardstock Custom Glossy Cardstock Hole Punched Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Recycled	
Envelope Tray – Replaces Tray 1 (O	ptional)	
Capacity ⁴	Up to 50 envelopes	
Sizes	#10 commercial, Monarch, DL, C4, C5, C6 Custom sizes: 3.5 x 3.85 in. to 9.5 x 13.1 in./90 x 98 mm to 241 x 332 mm	
Total Capacity		
VersaLink [®] C9000/DT Capacity ⁴	1,140 sheets	
Maximum Capacity ⁴	5,140 sheets	
Finishing		
Output Trays		
Catch Tray	500 sheets (without center tray) 2x 250 sheets (with center tray when offset is off) 2x 125 sheets (with center tray when offset is on)	
Office Finisher (Optional)		
Capacity ⁴	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker) Offset available for collated sets of standard size paper (8.5 x 11 in. / A4 to 11 x 17 in. / A3)	
Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover/60 to 220 gsm	
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm	

Hole Punch (Optional) North America: Europe:	Up to 65 lb cover (200 gsm) 2/3 hole punch 2/4 hole punch	
Booklet Maker for Office Finish	ner (Score/Crease, Saddle-stitch Staple) (Optional)	
Capacity ⁴	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)	
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF	
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm	
Score / Crease	1-15 sheets / unstapled / 60-105 gsm only	
Optional BR Booklet Maker Fir	nisher (Requires Horizontal Transport Kit)	
Capacity ⁴	Offsetting Top Tray: 500 sheets of 8.5 x 11 in./A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in./11 x 17 in./A4/A3 unstapled or 200 stapled sets of 8.5 x 11 in./A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in./A3	
Sizes	4 x 6 in. to 11 x 17 in./A6 to A3 for stacking 7.25 x 10.5 in. to 11 x 17 in./B5 to A3 for stapling	
Weights	16 bond to 110 lb. cover/60 to 300 gsm (coated and uncoated)	
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb. / 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported	
Hole Punch North America Europe	2/3 hole punch 2/4 hole punch 4 hole "Swedish" punch (optional)	
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported	
Device Management		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour [®] / AirPrint [™] Most protocols not in use can be disabled	
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS	
Xerox [®] CentreWare [®] Web		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
Xerox® Embedded Web Server – Integrated Device Web Page		
Device Status	 Tray status/contents Consumables status Billing/Usage Quick Links Online Support 	
Print Queue Viewing	Job print queue management—view and delete	
	Print-ready files (PS, PCL, PDF, XPS, JPEG, TXT, PRN, TIF)	

Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]		
Remote Services	-		
Xerox [®] MeterAssistant [®] Service	Automates the process of collecting and submitting meter Xerox [®] device usage. Eliminates the need for time-consume that meter reads are submitted to Xerox on time.		
Xerox [®] SuppliesAssistant [®] Service	Automatically orders supplies for Xerox [®] output devices t need to manually manage supplies inventory.	pased on actual usage, eliminating the	
MaintenanceAssistant Service	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.		
What's In The Box			
	 VersaLink[®] C9000 Colour Printer Starter Capacity Print Cartridge: One of each (Cyan, Ma Black: 18,000 print capacity⁵ Drum Cartridge – One of each (Cyan, Magenta, Yellow, Quick Use Guide Install Guide Software and Documentation CD (with Drivers, Warran Recycle Disposal Guide) Power Cord 	and Black 190,000 print capacity) ⁶	
Supplies and Accessories	Quantity	Part Number	
Supplies			
Standard Capacity Toner Cartridges	Cyan: 12,300 standard pages ⁵ Magenta: 12,300 standard pages ⁵ Yellow: 12,300 standard pages ⁵ Black: 18,900 standard pages ⁵	106R04070 106R04071 106R04072 106R04073	
High Capacity Toner Cartridges	Cyan: 26,500 standard pages ⁵ Magenta: 26,500 standard pages ⁵ Yellow: 26,500 standard pages ⁵ Black: 31,400 standard pages ⁵	106R04082 106R04083 106R04084 106R04085	
Drum Cartridge	Cyan: 190,000 standard pages6101R00602Magenta: 190,000 standard pages6Yellow: 190,000 standard pages6Black: 190,000 standard pages6Herein Standard pages6		
	Yellow: 190,000 standard pages ⁶		
Waste Cartridge	Yellow: 190,000 standard pages ⁶	108R01504	
Waste Cartridge IBT Cleaner	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶	108R01504 104R00256	
-	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶ 47,000 standard pages ⁶		
IBT Cleaner	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶ 47,000 standard pages ⁶ 160,000 standard pages ⁶	104R00256	
IBT Cleaner Transfer Roller	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶ 47,000 standard pages ⁶ 160,000 standard pages ⁶ 200,000 standard pages ⁶	104R00256 116R00015	
IBT Cleaner Transfer Roller Tray 1-4 Feed Rollers	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶ 47,000 standard pages ⁶ 160,000 standard pages ⁶ 200,000 standard pages ⁶ 300,000 standard pages ⁶	104R00256 116R00015 109R00790	
IBT Cleaner Transfer Roller Tray 1-4 Feed Rollers Tray 5 (MPT) Feed Rollers	Yellow: 190,000 standard pages ⁶ Black: 190,000 standard pages ⁶ 47,000 standard pages ⁶ 160,000 standard pages ⁶ 200,000 standard pages ⁶ 300,000 standard pages ⁶ 100,000 standard pages ⁶	104R00256 116R00015 109R00790 116R00016	

Staple Cartridges for BR Finisher and Office Finisher (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R12964
Staple Cartridges for BR Booklet Maker (1 cartridge per carton)	5,000 staples (5,000 each cartridge)	008R13177
Accessories / Options		
Xerox® Precise Colour Management System Software		097504974
Two Tray Module		097504969
Tandem Tray Module		097504970
High Capacity Feeder		097S04845
Envelope Tray (Replaces Tray 1)		497K17880
Office Finisher Gap Filler (required)		097S04848 497K17370
2/3 Hole Punch for Office Finisher		497K03860
2/4 Hole Punch for Office Finisher		497K03870
Booklet Maker for Office Finisher		497K03852
BR Booklet Maker Finisher with 2/3 Hole Punch		097504981
BR Booklet Maker Finisher with 2/4 Hole Punch		097504982
Horizontal Transport for BR Finisher (required with BR Booklet Maker Finisher)		497K17440
Swedish 4 Hole Punch for BR Finisher		497K14370
Wireless Network Adapter Kit		497K16750
Xerox Precise Colour Management System		097504974

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
 ² Expected regular monthly throughput.
 ³ Power states defined per ENERGY STAR® Programme requirements for Imaging Equipment.
 ⁴ Paper capacities are based on 20 lb. 75 gsm stock; capacities will vary with different weight stocks.
 ⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: http://www.office.xerox.com/Latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox[®] Green World Alliance[®] collection/reuse/recycling programme. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

