

Fujitsu recommends Windows.

# Data Sheet

## FUJITSU ESPRIMO E420 D

### Desktop PC

Combines Business-Class Performance with Manageability

The FUJITSU ESPRIMO E420 D delivers high-quality computing for your office applications and projects at a very attractive price point. You can choose cost-optimized fixed configurations for immediate delivery. Alternatively, you can use customization options to meet your specific hardware needs, while staying within your budget. DASH Out-of-Band manageability keeps administration costs to a minimum.

#### High performance and best price/performance ratio

Cost-effective system for price-conscious customers

- 4th generation Intel® Core™ processor family

#### Flexibility

Freedom of choice with tailored systems, perfect fit for specific requirements

- Flexible logistic concept - optional customizing program

#### Reliability

High-quality and functional stability

- Development and production in Europe

#### Lifecycle

Hardware continuity for long-term projects

- Managed lifecycle up to 12 months

#### Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

- Power supply with 85% efficiency



# Components

<b>Processor</b>	Intel® Core™ i7-4790 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 4600) * Intel® Core™ i5-4690 processor (4 Cores / 4 Threads, 3.50 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 4600) * Intel® Core™ i5-4590 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.7 GHz, 6 MB, Intel® HD Graphics 4600) * Intel® Core™ i5-4460 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.4 GHz, 6 MB, Intel® HD Graphics 4600) Intel® Core™ i3-4170 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 4400) Intel® Core™ i3-4160 processor (2 Cores / 4 Threads, 3.60 GHz, 3 MB, Intel® HD Graphics 4400) Intel® Pentium® processor G3460 (2 Cores / 2 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G3450 (2 Cores / 2 Threads, 3.40 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G3260 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G3250 (2 Cores / 2 Threads, 3.20 GHz, 3 MB, Intel® HD Graphics) Intel® Celeron® processor G1840 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics)
	*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
<b>Operating systems</b>	
<b>Operating system</b>	Windows 8.1 Pro Windows 8.1 Windows 7 Professional 64-bit Windows 7 Professional 32-bit
<b>Operating system compatible</b>	openSUSE Linux
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM 8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1,600 MHz, PC3-12800, DIMM
<b>Hard disk drives (internal)</b>	HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch HDD SATA III, 7,200 rpm, 250 GB, 3.5-inch HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch
<b>Hard disk notes</b>	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
<b>Hard disk drives (internal)</b>	SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch SSHD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch SSD SATA III, 128 GB, 2.5-inch, SED SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch
<b>Graphics</b>	NVIDIA® GeForce® GTX 745 2 GB LP, 2 GB NVIDIA® GeForce® GT630 DisplayPort 2GB LP, 2 GB NVIDIA® GeForce® 605 DisplayPort 1GB LP, 1 GB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DVI-I to VGA Adapter DP to DVI-D (single link) Adapter Cable
<b>Drives (optional)</b>	BD Triple Writer SATA slim (tray) DVD-ROM DVD Super Multi MultiCard Reader 24in1 USB 2.0 3.5"

**Interface add on cards/components  
(optional)**

WLAN 802.11 a/g/n (2x2), (dedicated regions only, not for Indonesia)
USB 3.0 PCIe x1
Dual serial card PCIe x1

## Base unit

Base unit	ESPRIMO E420 D
<b>Mainboard</b>	
Mainboard type	D3230-C
Formfactor	µATX
Chipset	Intel® H81
Processor socket	LGA 1150
Processor quantity maximum	1
Memory slots	2 DIMM (DDR3)
Supported capacity RAM (max.)	16 GB
Memory frequency	1,600 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
LAN	10/100/1,000 MBit/s Realtek RTL8111EP
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	High Definition Audio, 5.1 surround sound
<b>I/O controller on board</b>	
Serial ATA total	3
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI
<b>Interfaces</b>	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	6
USB 3.0 total	2
USB front	2x 2.0
USB rear	2x 2.0/ 2x 3.0
USB internal	2x 2.0
VGA	1
DVI	1 (DVI-D)
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1

**Input device / components**

	Optical USB wheel mouse
<b>Input devices (optional)</b>	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

**Drive bays**

<b>Drive bays total</b>	3
<b>3.5-inch internal bays</b>	1
<b>3.5-inch external bays</b>	1
<b>5.25-inch external bays</b>	1
<b>Drive bay notes</b>	3,5" bay can be used for 2,5" drives; optional external bay as internal 3,5";

**Slots**

<b>PCI-Express 2.0 x16</b>	1 x (210 mm / 8.27 inch) Low profile
<b>PCI-Express x1</b>	2 x (210 mm / 8.27 inch) Low profile

**Graphics on board**

<b>Graphics brand name</b>	Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor)
<b>Shared video memory</b>	up to 1,782 MB
<b>TFT resolution (VGA)</b>	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
<b>TFT resolution (DVI)</b>	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
<b>Graphics features</b>	Dual display support DirectX® 11.1 HDCP support Open CL® 1.2 OpenGL® 4.0
<b>Graphics notes</b>	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85% 0-Watt mode with hard-off switch
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	280 W
<b>Power factor correction/active power</b>	active
<b>Monitor outlet</b>	No

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption 0-Watt mode with hard-off switch
<b>Link to Energy White Paper</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=3183da7b-8ca3-4dae-8f6a-ee73a9460a66">http://docs.ts.fujitsu.com/dl.aspx?id=3183da7b-8ca3-4dae-8f6a-ee73a9460a66</a>

**Heat dissipation**

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

**Noise emission**

Related Processors for noise	Intel® Core™ i7 4770
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	Bystander position
Standard noise operation mode: CPU 50% load	3.6 B / 22 dB(A) Bystander; 25 dB(A) Operator position
Standard noise operation mode: HDD load	3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position
Standard noise operation mode: Idle mode	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position
Standard noise operation mode: ODD load	4.6 B / 31 dB(A) Bystander; 36 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position

**Dimensions / Weight / Environmental**

Dimensions (W x D x H)	330 x 405 x 104 mm 13.0 x 15.95 x 4.1 inch
Operating position	horizontal / vertical (optional, feet needed)
Weight	9 kg
Weight (lbs)	20.22 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)
Product	ESPRIMO E420 D
Model	DTL2
Germany	TÜV GS
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	<a href="http://globalsp.ts.fujitsu.com/sites/certificates">http://globalsp.ts.fujitsu.com/sites/certificates</a>

**Additional Software**

Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

**Manageability**

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) DASH Out-of-Band management supporting real time inventory, remote on/ off, text console redirection
--------------------------	--

**Manageability**

Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
---------------------	--

**Security**

Physical Security	Kensington Lock support Eye for padlock
System and BIOS Security	Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)

**Miscellaneous****Packaging information**

Packaging dimension (mm)	467 x 265 x 540 mm
Packaging dimension (inch)	18.39 x 10.43 x 21.26 inch
Max. quantity / pallet	28
Material - Weight (g) Carton	1180 g
Material - Weight (lbs) Carton	2.6 lbs
Material - Weight (g) EPS / PS	180 g
Material - Weight (lbs) EPS / PS	0.4 lbs
Material - Weight (g) PE	60 g
Material - Weight (lbs) PE	0.13 lbs
Packaging notes	printed user documentation is bleached in chlorine free process

**Warranty**

Warranty period	1 year
Service level	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 1 year material warranty)
Warranty Terms & Conditions	<a href="http://support.ts.fujitsu.com/warranty">http://support.ts.fujitsu.com/warranty</a>
<b>Product Support Services - the perfect extension</b>	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	<a href="http://www.fujitsu.com/fts/services/support">http://www.fujitsu.com/fts/services/support</a>

## Recommended Accessories

**Mouse M440 ECO**

Fujitsu Mouse M440 ECO is made from 100% bio material and has a completely PVC free cable. The elegant M440 ECO works on nearly every surface and follows all your hand movements smoothly and precisely. It features two main buttons and as well as a scroll wheel providing comfortable computing to both right and left-handed users.

Order Code:  
S26381-K450-L200

**SOUNDSYSTEM DS E2000 Air**

The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting.

Order Code:  
S26391-F7128-L600

**UC&C USB Headset Stereo H650e**

The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.

Order Code:  
S26391-F7139-L10

**Busylight UC Lync**

Boost communication and productivity in the office with the Busylight. The genius of this device is that it both advertises your present working state and promotes the use of Lync, making your office more efficient. Perfect for the work environment in open-plan offices, the Busylight makes users feel comfortable with Lync's features and eases the transition from traditional office internal telephone systems.

Order Code:  
S26391-F7139-L30

**HS E2000 Communicator Headset**

The Fujitsu HS E2000 Communicator headset allows you to use your personal computer for Voice over IP (VoIP) in stereo audio quality. This premium headset is designed to provide superb audio quality and comfort for the telephony, internet chat, speech recognition, video conferencing and multimedia applications.

Order Code:  
S26391-F7139-L5

**Keyboard KBPC PX ECO**

Fujitsu's KBPC PX ECO keyboard is the perfect contribution to Green IT. The keyboard is made out of 45% renewable raw material and comes with a PVC free USB cable. In addition, the KBPC PX ECO offers first class comfort and ergonomics. It attracts attention with its impressive modern design and useful extras.

S26381-K341-L1\*\* (\*\*: country specific variation)

## More information

### Fujitsu OPTIMIZATION Services

In addition to FUJITSU ESPRIMO E420 D, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about FUJITSU ESPRIMO E420 D, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2015 Fujitsu Technology Solutions GmbH

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

### Contact

FUJITSU Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2015-06-29 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
© 2015 Fujitsu Technology Solutions GmbH