





EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

PEX2PECP2

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant



2 Port PCI Express / PCI-e Parallel Adapter Card – IEEE 1284 with Low Profile Bracket

StarTech ID: PEX2PECP2



The PEX2PECP2 2 Port PCI Express Parallel Adapter Card - EPP/ECP/SPP/PS2 parallel card adds two IEEE 1284 parallel ports to your PC, with support for parallel data communication at speeds of up to 1.5 Mbps.

This high performance 2 Port PCI Express parallel card adds 2 DB25 parallel ports, perfect for connecting printers, scanners, memory card readers, bar code scanners and more. With the added convenience of plug-and-play capability, installing the parallel adapter card is hassle-free. The PCIe Parallel card also includes both standard and half-height/low profile mounting brackets for compatibility with almost any system form factor.

Backed by a StarTech.com Lifetime Warranty and free lifetime technical support.

Applications

 Connects any parallel peripheral including printers, scanners, CD-R/RWs, Zip® drives, and memory card readers

Features

- Supports Standard Parallel Port(SPP), Enhanced Parallel Port(EPP), Enhanced Capability Port(ECP) and PS/2
- Data transfer rate up to 1.5 Mbps
- Standard and low-profile brackets included



Technical Specifications

Warranty Lifetime

Ports 2

Bus Type PCI Express

Card Type Standard Profile (LP bracket incl.)

Port Style Integrated on Card

Chipset ID ASIX/MosChip - MCS9865 Connector Type(s) 1 - PCI Express x1 Male

External Ports 2 - DB-25 (25 pin; D-Sub) Female

Maximum Data Transfer Rate 1.5 Mbps

OS Compatibility Windows® 8 (32/64), 7 (32/64), Vista(32/64), XP(32/64), 2000

Windows® Sever 2008 R2, 2003 (32/64)

Linux

Product Length 121 mm [4.8 in]
Product Width 19 mm [0.7 in]
Product Height 86 mm [3.4 in]
Product Weight 51 g [1.8 oz]

Humidity 5~85% RH, Non-condensing
Operating Temperature 0°C to 40°C (32°F to 122°F)
Storage Temperature -20°C to 60°C (-4°F to 140°F)

Shipping (Package) Weight 0.2 kg [0.4 lb]

Included in Package 1 - 2 Port PCle Parallel Card

Included in Package 2 - Low Profile Brackets

Included in Package 1 - Driver CD

Included in Package 1 - Instruction Manual





Certifications, Reports and Compatibility



















EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

PEX2PECP2

ΕN

This Datasheet is presented by the manufacturer

DE

Dieses Datenblatt wird vom Hersteller bereitgestellt

FR

Cette fiche technique est présentée par le fabricant